



Designation: D5765 – 05

# Standard Practice for Solvent Extraction of Total Petroleum Hydrocarbons from Soils and Sediments Using Closed Vessel Microwave Heating<sup>1</sup>

This standard is issued under the fixed designation D5765; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This practice covers the solvent extraction of total petroleum hydrocarbon (TPH) from soils and sediments, using closed vessel microwave heating, for subsequent determination by gravimetric or gas chromatographic techniques.

1.2 This practice is recommended only for solid samples that can pass through a ten mesh screen (approximately 2-mm openings).

1.3 The solvent extract obtained by this practice may be analyzed for total or specific nonvolatile and semivolatile petroleum hydrocarbons but may require sample clean-up procedures prior to specific compound analysis.

1.4 This practice is limited to solvents that are recommended for use in microwave solvent extraction systems.

1.5 The values stated in pounds per square inch (psi) are to be regarded as the standard. The SI units given in parentheses are for information only.

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* Specific hazard statements are given in Section 8.

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>2</sup>

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee D19 on Water and is the direct responsibility of Subcommittee D19.07 on Sediments, Geomorphology, and Open-Channel Flow.

Current edition approved Aug. 15, 2005. Published August 2005. Originally approved in 1995. Last previous edition approved in 2001 as D5765 – 95 (2001). DOI: 10.1520/D5765-05.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

D3694 Practices for Preparation of Sample Containers and for Preservation of Organic Constituents

D3856 Guide for Good Laboratory Practices in Laboratories Engaged in Sampling and Analysis of Water

D3974 Practices for Extraction of Trace Elements from Sediments

D3976 Practice for Preparation of Sediment Samples for Chemical Analysis

D5368 Test Methods for Gravimetric Determination of Total Solvent Extractable Content (TSEC) of Solid Waste Samples

### 2.2 Federal Standard:

Code of Federal Regulations, Title 21, Part 1030, and Title 47, Part 18<sup>3</sup>

## 3. Summary of Practice

3.1 The chemical portion of this practice involves solvent extraction to dissociate petroleum hydrocarbons from the matrix.

3.2 The sample is extracted with acetone/hexane in a sealed microwave transparent vessel using microwave heating to an internal temperature of 150°C.

3.3 This practice provides a sample suitable for analysis by gas chromatography or gravimetric measurements.

## 4. Significance and Use

4.1 Solvent extraction of soils and sediments can provide information on the availability of petroleum hydrocarbons to leaching, water quality changes, or other site conditions.

4.2 Rapid heating, in combination with temperatures in excess of the atmospheric boiling point of acetone/hexane, reduces sample preparation or extraction times.

<sup>3</sup> Available from the U.S. Government Printing Office, Washington, DC.