
**Data interchange on 120 mm and 80 mm
Optical Disk using +R DL Format —
Capacity: 8,55 and 2,66 Gbytes per Side
(Recording speed 2,4x)**

*Échange de données sur disque optique de 120 mm et 80 mm utilisant
le format +R DL. Capacité: 8,55 Go et 2,66 Go par face (vitesse
d'enregistrement 2,4x)*

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[ISO/IEC 25434:2006](https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006)

[https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-
dc79382c4f4c/iso-iec-25434-2006](https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 25434:2006](https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006)

<https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006>

© ISO/IEC 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Section 1 - General	1
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 Conformance	4
4.1 Optical Disk	4
4.2 Generating system.....	4
4.3 Receiving system.....	4
4.4 Compatibility statement	4
5 Conventions and notations	4
5.1 Representation of numbers	4
5.2 Names	5
6 Abbreviations and acronyms	5
7 General description of the optical disk	6
8 General Requirements.....	7
8.1 Environments	7
8.1.1 Test environment.....	7
8.1.2 Operating environment	7
8.1.3 Storage environment.....	7
8.1.4 Transportation.....	7
8.2 Safety requirements	7
8.3 Flammability	8
9 Reference Drive.....	8
9.1 Optical system	8
9.2 Optical beam	9
9.3 Read channel 1.....	9
9.4 Disk clamping.....	9
9.5 Rotation of the disk	10
9.6 Wobble channel (Read channel 2)	10
9.7 Tracking channel (Read channel 2)	11
9.8 Reference servo systems	11
9.8.1 Normalized servo transfer function	11
9.8.2 Reference Servo for Axial Tracking	11
9.8.3 Reference Servo for Radial Tracking.....	12
Section 2 - Dimensional, mechanical and physical characteristics of the disk	14
10 Dimensional characteristics	14
10.1 Reference Planes	15
10.2 Overall dimensions.....	15
10.3 First transition area	15
10.4 Second transition area	16
10.5 Clamping Zone	16
10.6 Third transition area	16
10.7 Information Zone.....	16
10.7.1 Sub-division of the Information Zone	17
10.7.2 Track mode.....	18
10.8 Rim area.....	18
10.9 Remark on tolerances	18

11	Mechanical characteristics	18
11.1	Mass	18
11.2	Moment of inertia	18
11.3	Dynamic imbalance.....	18
11.4	Axial runout	18
11.5	Radial runout	19
12	Optical characteristics in the Information Zone	19
12.1	Index of refraction	19
12.2	Thickness of the substrate.....	19
12.3	Reflectivity	19
12.4	Birefringence	19
12.5	Angular deviation	20
Section 3 - Format of information.....		21
13	Data format	21
13.1	Data Frames.....	21
13.1.1	Identification Data (ID)	21
13.1.2	ID Error Detection Code (IED).....	23
13.1.3	RSV	23
13.1.4	Error Detection Code (EDC).....	23
13.2	Scrambled Frames	23
13.3	ECC Blocks	24
13.4	Recording Frames.....	25
13.5	Modulation and NRZI conversion.....	26
13.6	Physical Sectors	27
13.7	Layout of a Recording Unit (RUN).....	28
13.7.1	Recording Unit position	29
13.8	d.c. component suppression control.....	29
14	Track format.....	30
14.1	Track shape	30
14.2	Track path	30
14.3	Track pitch	31
14.4	Track layout	31
14.4.1	ADIP information	31
14.4.2	Physical format information in ADIP	35
Section 4 - Format of the Information Zone		43
15	General description of the Information Zone	43
16	Layout of the Information Zone of a Single-session disk.....	44
16.1	Usage of the Data Zone	45
16.1.1	Additional Testing Zone on Layer 1 (optional).....	46
16.2	Physical Sector Numbers (PSNs).....	47
17	Inner Drive Areas	48
17.1	Initial Zone / Final Zone	49
17.2	Inner Disk Test Zones	49
17.3	Count Zone Run-in / Dummy Zone	49
17.4	Inner Disk Count Zones	49
17.5	Inner Disk Administration Zone.....	50
17.6	Table of Contents (TOC) Zone	50
17.6.1	Table of Contents Blocks	51
17.6.2	Recorded Area Indicators	53
18	Lead-in Zone	55
18.1	Guard Zone 1	56
18.2	Reserved Zone 1	56
18.3	Reserved Zone 2	56
18.4	Inner Disk Identification Zone.....	56
18.5	Reserved Zone 3	56

18.6	Reference Code Zone	56
18.7	Buffer Zone 1	56
18.8	Control Data Zone	56
18.8.1	Physical format information	57
18.8.2	Disk manufacturing information	59
18.8.3	Content provider information	59
18.9	Buffer Zone 2	59
19	Data Zone	59
20	Middle Zones	60
20.1	Buffer Zones 3	61
20.2	Reserved Zones	61
20.3	Guard Zones 2	61
21	Outer Drive Areas	61
21.1	Outer Disk Administration Zones	62
21.2	Outer Disk Count Zones	62
21.3	Dummy Zone / Count Zone Run-in	63
21.4	Outer Disk Test Zone	63
21.5	Guard Zones 3	63
22	Lead-out Zone	63
22.1	Lead-out Zone at finalization	63
22.2	Lead-out Zone at closing of first Session	64
23	Multi-session Layout	65
23.1	Intro	66
23.1.1	Buffer Zone A	66
23.1.2	Inner Session Identification Zone	66
23.1.3	Session Control Data Zone	66
23.1.4	Buffer Zone B	66
23.2	Data Zone	66
23.3	Closure	66
23.3.1	Buffer Zone C	66
23.3.2	Outer Session Identification Zone	66
24	Sequential recording in Fragments	67
24.1	Opening a Session	67
24.1.1	Incomplete Fragment	67
24.1.2	Reserved Fragments	67
24.1.3	Recording User Data in Fragments	68
24.1.4	Closing a Fragment	68
24.2	Closing a Session	69
24.2.1	Lead-in/Intro Zone	69
24.2.2	Closure Zone	70
24.3	Finalizing the disk	70
25	Assignment of Logical Sector Numbers (LSNs)	70
26	Disk Control Blocks	70
26.1	General format of Disk Control Blocks	70
26.2	Format of the Session DCB (SDCB)	72
26.2.1	Session Items	74
Section 5 - Characteristics of the groove		76
27	General	76
28	Method of testing	76
28.1	Environment	76
28.2	Reference Drive	76
28.2.1	Optics and mechanics	76
28.2.2	Read power	77
28.2.3	Read channels	77

28.2.4	Tracking	77
28.3	Definition of signals	77
29	Characteristics of the groove signals	78
29.1	Phase depth	78
29.2	Push-pull signal	78
29.3	Track Cross signal	78
29.4	Normalized wobble signal	78
29.5	Characteristics of the wobble	79
Section 6 - Characteristics of the recording layer		79
30	Method of testing	79
30.1	Environment	79
30.2	Reference Drive	79
30.2.1	Optics and mechanics	79
30.2.2	Read power	79
30.2.3	Read channels	80
30.2.4	Tracking	80
30.2.5	Scanning velocity	80
30.3	Write conditions	80
30.3.1	Write pulse waveform	80
30.3.2	Write power	80
30.3.3	Write power dependency on wavelength	81
30.3.4	Write power window	81
30.3.5	Write power shift for layer L1 due to recording on layer L0	82
30.4	Measurement conditions	82
31	Characteristics of the recorded signals	82
31.1	Channel bit length	82
31.2	Definition of signals	82
31.2.1	High frequency signals (HF)	82
31.2.2	Modulated amplitude	83
31.2.3	Signal asymmetry	83
31.2.4	Normalized Slicing Level jump	83
31.2.5	Jitter	84
31.2.6	Track Cross signal	84
31.3	Read stability	84
32	Additional testing conditions	84
32.1	Test environment	84
32.1.1	Optics	84
32.2	Definition of signals	85
32.2.1	Modulated amplitude	85
32.2.2	Signal asymmetry	85
32.2.3	Jitter	85
32.2.4	Track Cross signal	85
32.2.5	Differential phase tracking error signal	85
32.2.6	Tangential push-pull signal	86
33	Quality of the recording layer	87
33.1	Defects	87
33.2	Data errors	87
Section 7 - Characteristics of user data		88
34	Method of testing	88
34.1	Environment	88
34.2	Reference Drive	88
34.2.1	Optics and mechanics	88
34.2.2	Read power	88
34.2.3	Read channels	88
34.2.4	Error correction	88
34.2.5	Tracking	89

ITC STANDARD PREVIEW
 (standards.itech.ai)
 ISO/IEC 25434:2006
<https://standards.itech.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006>

35	Minimum quality of a Recording Unit	89
35.1	Tracking	89
35.2	User-written data.....	89
Annex A (informative)	80 mm +R DL disk	91
Annex B (normative)	Structure for Extended format information in the Data Zone	95
Annex C (normative)	Measurement of light reflectivity.....	98
Annex D (normative)	Measurement of birefringence	100
Annex E (normative)	Measuring conditions for operation signals	102
Annex F (normative)	Measurement of the differential phase tracking error.....	105
Annex G (normative)	The write pulse wave form for testing	109
Annex H (normative)	8-to-16 Modulation	112
Annex I (normative)	Optimum Power Control and Recording Conditions	120
Annex J (informative)	Running OPC	123
Annex K (informative)	Wavelength dependency	124
Annex L (informative)	Measurement of the groove wobble amplitude.....	129
Annex M (informative)	Light fastness of the disk	131
Annex N (informative)	Transportation.....	132
Annex O (informative)	Video Content Protection System.....	133
Annex P (informative)	How to use the Physical format information in ADIP	134
Annex Q (informative)	Values to be Implemented in Existing and Future Specifications	136

[ISO/IEC 25434:2006](https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006)

<https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 25434 was prepared by ECMA TC 31 (as ECMA-364) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

ITEH STANDARD PREVIEW

(standards.iteh.ai)

ISO/IEC 25434:2006

<https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006>

Introduction

Ecma Technical Committee TC 31 was established in 1984 for the standardization of Optical Disks and Optical Disk Cartridges (ODC). Since its establishment, the Committee has made major contributions to ISO/IEC toward the development of International Standards for 80 mm, 90 mm, 120 mm, 300 mm, and 356 mm media. Numerous standards have been developed by TC 31 and published by Ecma, almost all of which have also been adopted by ISO/IEC under the fast-track procedure as International Standards.

In July 2004 a group of Companies proposed to TC 31 to develop a standard for 120 mm dual layer recordable optical disks using the WORM recording technology and based on the DVD – Read-Only standard (ECMA-267), the +RW format (ECMA-337) and the +R format (ECMA-349). TC 31 adopted this project and started the work that has resulted in this Standard.

This International Standard specifies two Types of recordable optical disks, one (Type S9) making use of recording on only a single side of the disk and yielding a nominal capacity of 8,55 or 2,66 Gbytes per disk and the other (Type D18) making use of recording on both sides of the disk and yielding a nominal capacity of 17,1 or 5,32 Gbytes per disk.

This International Standard, taken together with a standard for volume and file structure, such as for instance developed in Ecma Technical Committee TC 15, provides the requirements for information interchange between systems.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 25434:2006](https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006)

<https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 25434:2006

<https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006>

Data interchange on 120 mm and 80 mm Optical Disk using +R DL Format — Capacity: 8,55 and 2,66 Gbytes per Side (Recording speed 2,4x)

Section 1 — General

1 Scope

This International Standard specifies the mechanical, physical and optical characteristics of 120 mm recordable optical disks with capacities of 8,55 Gbytes and 17,1 Gbytes. It specifies the quality of the recorded and unrecorded signals, the format of the data and the recording method, thereby allowing for information interchange by means of such disks. The data can be written once and read many times using a non-reversible method. These disks are identified as +R DL.

The +R DL system also allows 80 mm disks with capacities of 2,66 Gbytes and 5,32 Gbytes. These disks have the same characteristics as the 120 mm disks, except for some parameters related to the smaller dimensions. All parameters unique for the 80 mm disks are specified in Annex A.

This Standard specifies

- two related but different Types of this disk (see Clause 7);
- the conditions for conformance; <https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f4c/iso-iec-25434-2006>
- the environments in which the disk is to be tested, operated and stored;
- the mechanical, physical and dimensional characteristics of the disk, so as to provide mechanical interchange between data processing systems;
- the format of the information on the disk, including the physical disposition of the tracks and sectors, the error correcting codes and the coding method;
- the characteristics of the signals recorded on the disk, thus enabling data processing systems to read the data from the disk.

This International Standard provides for the interchange of disks between optical disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 4873:1991, *Information technology — ISO 8-bit code for information interchange — Structure and rules for implementation*

ISO/IEC 16448:2002, *Information technology — 120 mm DVD — Read-only disk*

ISO/IEC 25434:2006(E)

ISO/IEC 16449:2002, *Information technology — 80 mm DVD — Read-only disk*

ISO/IEC 17341:2005, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +RW format -- Capacity: 4,7 Gbytes and 1,46 Gbytes per side (recording speed up to 4X)*

ISO/IEC 17344:2005, *Information technology — Data interchange on 120 mm and 80 mm optical disk using +R format -- Capacity: 4,7 and 1,46 Gbytes per side (recording speed up to 8X)*

ECMA-287 (2002), *Safety of Electronic Equipment*

Unauthorized copying and/or redistribution of video data that is recorded in the DVD+R/+RW Video Format can be prevented by applying the Video Content Protection System as referred to in Annex O.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

channel bit

elements by which the binary values ZERO and ONE are represented by marks and spaces on the disk

3.2

clamping zone

The annular part of the disk within which the clamping force is applied by the clamping device

3.3

Digital Sum Value

DSV

arithmetic sum obtained from a bit stream by allocating the decimal value +1 to bits set to ONE and the decimal value -1 to bits set to ZERO

3.4

Disk Reference Plane

plane defined by the perfectly flat annular surface of an ideal spindle onto which the clamping Zone of the disk is clamped, and which is normal to the axis of rotation

3.5

dummy substrate

layer which may be transparent or not, provided for the mechanical support of the disk and, in some cases, of the recording layer as well

3.6

entrance surface

surface of the disk onto which the optical beam first impinges

3.7

field

subdivision of a sector

3.8

groove

trench-like feature of the disk, applied before the recording of any information, and used to define the track location

NOTE The groove is located nearer to the entrance surface than the so-called land in between the grooves. The recording is made on the groove.

3.9**interleaving**

process of reallocating the physical sequence of units of data so as to render the data more immune to burst errors

3.10**mark**

non-reversible feature of the recording layer which may take the form of less reflective area, a pit, or any other type or form that can be sensed by the optical system

NOTE The pattern of marks and spaces represents the data on the disk.

3.11**Multi-session disk**

disk containing more than one set of Lead-in/Intro, Data, and Lead-out/Closure Zones

3.12**Physical Sector**

smallest addressable part of a track in the Information Zone of a disk that can be accessed independently of other addressable parts of the zone

3.13**recording layer**

layer of the disk on which data is written during manufacture and / or use

3.14**Reed-Solomon code (RS)**

error detection and / or correction code

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.15**reference velocity**

linear velocity that results in the nominal channel bit rate of 26,156 25 Mbit/s

ISO/IEC 25434:2006

<https://standards.iteh.ai/catalog/standards/sist/ef7d817a-b3ea-4cfd-84ac-dc79382c4f1e/iso-iec-25434-2006>

3.16**single-session disk**

disk containing a Lead-in Zone, one Data Zone and a Lead-out Zone

3.17**session**

continuous part of the Information Zone of the disk consisting of a Lead-in or Intro Zone, a Data Zone and a Lead-out or Closure Zone

3.18**space**

feature of the recording layer represented by any area between two marks which can be sensed by the optical system

NOTE The pattern of marks and spaces represents the data on the disk.

3.19**spacer**

transparent layer of the disk, provided for achieving an accurate separation of the pair of recording layers which are accessed by the optical beam through the same entrance surface

3.20**substrate**

transparent layer of the disk, provided for mechanical support of the recording layer, through which the optical beam accesses the recording layer

3.21

track

360° turn of a continuous spiral

3.22

track pitch

distance between adjacent track centrelines, measured in a radial direction

3.23

Video Content Protection System

VCPS

method to prevent unauthorized copying and/or redistribution of video data that is recorded in the DVD+R/+RW Video Format

3.24

wobble

continuous sinusoidal deviation of the track from the average centreline

NOTE Location information is included as phase modulated data in the wobble.

3.25

zone

annular area of the disk

4 Conformance

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4.1 Optical Disk

A claim of conformance with this Standard shall specify the Type implemented. An optical disk shall be in conformance with this Standard if it meets all mandatory requirements specified for its Type.

4.2 Generating system

A generating system shall be in conformance with this Standard if the optical disk it generates is in accordance with 2.1.

4.3 Receiving system

A receiving system shall be in conformance with this Standard if it is able to handle both Types of optical disk according to 2.1.

4.4 Compatibility statement

A claim of conformance by a Generating or Receiving system with this Standard shall include a statement listing any other standards supported. This statement shall specify the numbers of the standards, the optical disk types supported (where appropriate) and whether support includes reading only or both reading and writing.

5 Conventions and notations

5.1 Representation of numbers

A measured value may be rounded off to the least significant digit of the corresponding specified value. For instance, it implies that a specified value of 1,26 with a positive tolerance of + 0,01 and a negative tolerance of - 0,02 allows a range of measured values from 1,235 to 1,274.

Numbers in decimal notations are represented by the digits 0 to 9.

Numbers in hexadecimal notation are represented by the hexadecimal digits 0 to 9 and A to F in parentheses.

The setting of bits is denoted by ZERO and ONE.

Numbers in binary notations and bit patterns are represented by strings of digits 0 and 1, with the most significant bit shown to the left. In a pattern of n bits, bit b_{n-1} shall be the most significant bit (msb) and bit b_0 shall be the least significant bit (lsb). Bit b_{n-1} shall be recorded first.

Negative values of numbers in binary notation are given as Two's complement.

In each data field, the data is recorded so that the most significant byte (MSB), identified as Byte 0, shall be recorded first and the least significant byte (LSB) last.

In a field of $8n$ bits, bit $b_{(8n-1)}$ shall be the most significant bit (msb) and bit b_0 the least significant bit (lsb). Bit $b_{(8n-1)}$ shall be recorded first.

5.2 Names

The names of entities, e.g. specific tracks, fields, etc., are given with an initial capital.

6 Abbreviations and acronyms

a.c.	alternating current	NRZ	Non Return to Zero
ADIP	Address in Pre-groove	NRZI	Non Return to Zero Inverted
ASM	Asymmetry	NSL	Normalized Slicing Level
BP	Byte Position	NWPW	Normalized Write Power Window
BPF	Band Pass Filter	OPC	Optimum Power Control
CAV	Constant Angular Velocity	OTP	Opposite Track Path
CLD	Constant Linear Density	PAA	Physical Address in ADIP
CLV	Constant Linear Velocity	PBS	Polarizing Beam Splitter
cm	current mark	PI	Parity of Inner-code
d.c.	direct current	PLL	Phase Locked Loop
DCB	Disk Control Block	PO	Parity of Outer-code
DCC	d.c. component suppression Control	PP	Push-Pull
DSV	Digital Sum Value	pp	peak-to-peak
ECC	Error Correction Code	ps	previous space
EDC	Error Detection Code	PSN	Physical Sector Number
EI	Extended Information	PTP	Parallel Track Path
HF	High Frequency	RIN	Relative Intensity Noise
ID	Identification Data	RPM	Revolutions per Minute
IED	ID Error Detection code	RS	Reed-Solomon code
LPF	Low Pass filter	RSV	Reserved
LSB	Least Significant Byte		(in use by specific applications)
lsb	Least Significant Bit	RUN	Recording UNit
LSN	Logical Sector Number	SDCB	Session DCB
MSB	Most Significant Byte	SNR	Signal to Noise Ratio
msb	Most Significant Bit	SYNC	Synchronization code
NA	Numerical Aperture	TOC	Table of Contents