# INTERNATIONAL STANDARD

Second edition 2008-05-15

# Motorcycles — Measurement methods for moments of inertia

Motocycles — Méthodes de mesure des moments d'inertie

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 9129:2008</u> https://standards.iteh.ai/catalog/standards/sist/fafbdd28-dc4a-4343-9385-33451656a5b8/iso-9129-2008



Reference number ISO 9129:2008(E)

#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

### iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 9129:2008</u> https://standards.iteh.ai/catalog/standards/sist/fafbdd28-dc4a-4343-9385-33451656a5b8/iso-9129-2008



#### COPYRIGHT PROTECTED DOCUMENT

#### © ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

### Contents

Fore	word	iv
Intro	duction	v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Measurement conditions	2
5	Measuring instruments	2
6 6.1 6.2 6.3 6.4	Measuring procedure Measurement of location of centre of gravity Roll moment of inertia about x-axis (physical pendulum principle) Pitch moment of inertia about y-axis (physical pendulum principle) Yaw moment of inertia about z-axis (bifilar pendulum principle)	
7	Test results	16
Anne	ex A (normative) Format for measurement results	17

# (standards.iteh.ai)

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 9129 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 22, *Motorcycles*.

This second edition cancels and replaces the first edition (ISO 9129:1988), which has been technically revised. (standards.iteh.ai)

### Introduction

The stability of a motorcycle is a very important element of its active safety. The motorcycle/rider combination and the environment in which this combination is used form a unique closed-loop system. However, the evaluation of motorcycle/rider combination stability is extremely complex because of interaction of the intrinsic motorcycle stability, the influence of the position of the rider and his response to continuously changing conditions.

In the evaluation of motorcycle stability, the determination of the kinetic characteristics of the motorcycle/rider combination is considered an important part of the design parameters of the vehicle itself.

The test procedure described in this International Standard deals with one aspect of the kinetic characteristics: the determination of the moments of inertia of the motorcycle and of the motorcycle/rider combination.

### iTeh STANDARD PREVIEW (standards.iteh.ai)

## iTeh STANDARD PREVIEW (standards.iteh.ai)

### Motorcycles — Measurement methods for moments of inertia

#### 1 Scope

This International Standard specifies a measuring method for determining the moments of inertia of the motorcycle and of the motorcycle/rider combination. It applies to two-wheeled motorcycles.

Other measuring methods can be used if it is demonstrated that the results are equivalent.

Measurement results obtained exclusively by the method described in this International Standard (see Annex A) cannot be used for an evaluation of vehicle stability because they deal with only one aspect of this very complex phenomenon.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies results.

ISO 3779, Road vehicles — Vehicle identification number (VIN) — Content and structure

<u>ISO 9129:2008</u>

ISO 9130, Motorcycles Measurement method for Ibcation of Centre of gravity 5-33451656a5b8/iso-9129-2008

49 CFR Part 572 Subpart B [Code of Federal Regulations, issued by the National Highway Traffic Administration (NHTSA)]

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1

#### motorcycle-fixed axis system (x, y, z)

right-hand orthogonal axis system fixed in the motorcycle, such that when the motorcycle is moving in a straight line on a level road, the x-axis is substantially horizontal, points forwards and is in the longitudinal plane of symmetry of the motorcycle, the y-axis points to the rider's left side and the z-axis points upwards

NOTE 1 This coordinate system performs translation motion and rotational motion together with the motorcycle.

NOTE 2 Assuming that the motorcycle is fixed to a platform, the coordinate system is also applied to the platform.

#### 3.2

#### earth-fixed axis system (X, Y, Z)

right-hand orthogonal axis system fixed on the Earth, such that the X-axis and the Y-axis are in a horizontal plane and the Z-axis points upwards

#### 4 Measurement conditions

- 4.1 Measurement conditions for a motorcycle shall be as follows:
- a) the motorcycle shall be quite clean and free from mud and deformation, and shall operate normally;
- b) the fuel shall be filled up to the top level specified in the operation manual;
- c) lubricating oil and cooling water, for water-cooled engines, shall be filled up to the level specified in the operation manual;
- d) tyre pressure shall be as specified in the operation manual;
- e) tools shall be provided at the regular storage positions;
- f) front and rear suspension systems shall be fixed at a static position;
- g) the front wheel shall be positioned along the x-axis.

If the conditions are to be modified depending on the object of measurement, the modified conditions shall be recorded in the measurement results (see Annex A).

- **4.2** Measurement conditions when a rider is on the motorcycle shall be as follows:
- a) measurement conditions of the motorcycle shall be as specified in 4.1; VIEW
- b) a test dummy as specified in 49 CFR Part 572 Subpart B (or equivalent), with a mass of 73,4 kg, or an equivalent human being, shall be used as the rider,
- c) the rider shall be positioned as follows: ISO 9129:2008 https://standards.iteh.ai/catalog/standards/sist/fafbdd28-dc4a-4343-9385-
  - 1) positioned on the vertical centre surface of the motorcycle; 2008
  - 2) sitting on the seat, holding the handle bar by both hands, with both feet placed on the foot rests;
  - with an angle of posture formed by the line connecting the point S (indicating the centre of rotation of the torso and the arms of the rider) and point H (indicating the centre of rotation of the torso and femoral regions of the rider) and the x-axis;
  - 4) at a seating position that is the distance between the front axle and the point H along the x-axis.

However, if the conditions are to be modified depending on the object of measurement, the modified conditions shall be recorded in the measurement results (see Annex A).

#### **5** Measuring instruments

Measuring instruments to measure the moments of inertia shall be as follows or shall have equivalent functions and accuracy:

- a) a precision square level that can measure up to 0,1 mm/1 m ( $\approx 20^{\circ}$ );
- b) a steel tape measure with a tolerance of  $\pm [0,3+0,1(L-1)]$  mm at the length of L m;
- c) weighing stands with enough accuracy to weigh the object up to 0,1 kg;
- d) a stop watch that can measure up to 0,01 s, used for measuring the oscillation time;

- e) a platform with the highest possible rigidity, and of light weight;
- a knife edge, where the roundness at the edge shall be below 1 mm in radius, and an edge angle below 90 degrees is recommended;

NOTE The roundness at the edge is the form of the edge finished sharply when rounded with the load.

g) weights, to incline the platform.

#### 6 Measuring procedure

#### 6.1 Measurement of location of centre of gravity

Calculate the mass and location of centre of gravity of the platform, motorcycle, and the platform with the motorcycle placed on it, in accordance with ISO 9130.

#### 6.2 Roll moment of inertia about x-axis (physical pendulum principle)

#### 6.2.1 Roll moment of inertia about AB-axis for empty platform

Inertia moment about the AB-axis for the empty platform shall be measured in the procedure described below (see Figure 1).

- a) Place the knife edges A and B on the stay so that they can freely oscillate around the AB-axis.
- b) Oscillate the platform gently around the AB-axis. It is desirable to keep total oscillating angle below 5°.
- c) Make sure that the platform oscillates in<u>a</u>stable(way and measure the time required for the platform to oscillate 50 times; by statstop it watchta Repeat this process. 3 times; and obtain the average value of 3 average cycle times. The result shall be the period 29-2008
- d) Calculate the inertia moment of the platform about the AB-axis, *I*<sub>xp</sub>, expressed in kgm<sup>2</sup>, using Equation (1):

$$I_{\rm xp} = \left(\frac{T_{\rm xp}}{2\pi}\right)^2 \sqrt{c_{\rm p}^2 + y_{\rm p}^2} m_{\rm p}g \tag{1}$$

where

- $T_{\rm xp}$  is the period for the platform to oscillate around the AB-axis, in s;
- $c_{\rm p}$  is the distance along the z-axis from the knife edge to the centre of gravity of the platform, in m;
- $y_{\rm p}$  is the distance along the y-axis from the knife edge to the centre of gravity of the platform, in m;
- $m_{\rm p}$  is the mass of the platform, in kg;
- g is acceleration due to gravity (9,81 m/s<sup>2</sup>).



#### Key

 $c_{\rm p}$   $\,$  distance along the z-axis from the knife edge to the centre of gravity of the platform

 $m_{\rm p}~{\rm mass}~{\rm of}~{\rm platform}$ 

 $y_{\rm p}$  distance along the y-axis from the knife edge to the centre of gravity of the platform

# Figure 1 — Measurement procedure for roll moment of inertia of empty platform (procedure with physical pendulum principle)

#### 6.2.2 Roll moment of inertia of motorcycle about x-axis

Roll moment of inertia of the motorcycle about the x-axis shall be measured in the procedure described below (see Figure 2).

- NOTE This measurement applies to both the empty motorcycle and the motorcycle with a rider.
- a) Place the motorcycle on the platform and fix it so that it cannot move. The lateral inclination angle of the motorcycle to the platform shall be 0° ± 0,5°.
- b) Place the knife edges A and B on the stay so that they can freely oscillate around the AB-axis.
- c) Oscillate the motorcycle/platform combination gently around the AB-axis. It is desirable to keep total oscillating angle below 5°.
- d) Make sure that the platform oscillates in a stable way and measure the time required for the platform to oscillate 50 times by a stop watch. Repeat this process 3 times and obtain the average value of 3 average cycle times. The result shall be the period.
- e) Calculate the inertia moment of the motorcycle about the x-axis, *I*<sub>xm</sub>, expressed in kgm<sup>2</sup>, using Equation (2):

$$I_{\rm xm} = \left(\frac{T_{\rm xT}}{2\pi}\right)^2 \sqrt{c_{\rm T}^2 + y_{\rm T}^2} m_{\rm T}g - I_{\rm xp} - m_{\rm m} \left(c_{\rm m}^2 + y_{\rm m}^2\right)$$
**iTeh STANDARD PREVIEW**
(2)

where

### (standards.iteh.ai)

- $T_{xT}$  is the period for the platform with the motorcycle on it to oscillate around the AB-axis, in s; <u>ISO 9129:2008</u>
- c<sub>T</sub> is the idistance along the alz axis drom is the dknife edge 3 to 3 the centre of gravity of the motor cycle/platform combination anomiso-9129-2008
- y<sub>T</sub> is the distance along the y-axis from the knife edge to the centre of gravity of the motorcycle/platform combination, in m;
- $m_{\rm T}$  is the mass of motorcycle/platform combination, in kg;
- $I_{xp}$  is the inertia moment of the platform about the AB-axis, in kgm<sup>2</sup> [see Equation (1)];
- g is acceleration due to gravity (9,81m/s<sup>2</sup>);
- $m_{\rm m}$  is the mass of motorcycle, in kg;

2

- $c_{\rm m}$  is the distance along the z-axis from the knife edge to the centre of gravity of the motorcycle, in m;
- $y_{\rm m}$  is the distance along the y-axis from the knife edge to the centre of gravity of the motorcycle, in m.