

# ETSI EN 302 969 V1.2.1 (2014-11)



## Reconfigurable Radio Systems (RRS); Radio Reconfiguration related Requirements for Mobile Devices

*iTeh STANDARDS PREVIEW  
(standards.iteh.ai)  
Full standard available at: <https://standards.iteh.ai/catalog/standards/sr/58848cd-005d-48cd-833f-bb5b7189217c/etsi-en-302-969-v1-2-2014-11>*

---

Reference

REN/RRS-0210

---

Keywords

CRS, mobile, SDR

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope .....	6
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	6
3 Definitions and abbreviations.....	6
3.1 Definitions.....	6
3.2 Abbreviations .....	8
4 Requirement Organization and Methodology .....	8
4.1 Requirement Organization.....	8
4.2 Requirement Format.....	9
4.3 Requirement Formulation.....	10
5 Working assumptions .....	10
5.1 Assumptions .....	10
5.1.1 Mobile Device Reconfiguration Classes.....	10
6 Functional Requirements.....	13
6.1 Requirements on RAT Link Support and Management .....	13
6.1.1 R-FUNC-RAT-01 Function for MDRC-1 to MDRC-7.....	13
6.1.2 R-FUNC-RAT-02 Function for MDRC-1 to MDRC-7.....	13
6.1.3 R-FUNC-RAT-03 Function for MDRC-1 to MDRC-7.....	13
6.1.4 R-FUNC-RAT-04 Function for MDRC-1 to MDRC-7.....	14
6.1.5 R-FUNC-RAT-05 Function for MDRC-1 to MDRC-7.....	14
6.1.6 R-FUNC-RAT-06 Function for MDRC-1 to MDRC-7.....	14
6.2 Radio Application Requirements .....	14
6.2.1 R-FUNC-RA-01 Radio Applications Support for MDRC-1 to MDRC-7 .....	14
6.2.2 R-FUNC-RA-02 Composition for MDRC-1 to MDRC-7 .....	14
6.2.3 R-FUNC-RA-03 Concurrency for MDRC-1 to MDRC-7.....	14
6.2.4 R-FUNC-RA-04 Data for MDRC-1 to MDRC-7 .....	14
6.2.5 R-FUNC-RA-05 Context Information for MDRC-1 to MDRC-7 .....	14
6.2.6 R-FUNC-RA-06 Pipelining for MDRC-2 to MDRC-7 .....	15
6.3 Radio Application Functional Block Requirements .....	15
6.3.1 R-FUNC-FB-01 Implementation for MDRC-2 to MDRC-7 .....	15
6.3.2 R-FUNC-FB-02 Execution for MDRC-2 to MDRC-7 .....	15
6.3.3 R-FUNC-FB-03 Side Effects for MDRC-2 to MDRC-7 .....	16
6.3.4 R-FUNC-FB-04 Shared Data for MDRC-2 to MDRC-7 .....	16
6.3.5 R-FUNC-FB-05 Concurrency for MDRC-2 to MDRC-7 .....	16
6.3.6 R-FUNC-FB-06 Extendability for MDRC-2 to MDRC-7 .....	16
6.4 Mobile Device Reconfiguration Requirements .....	16
6.4.1 R-FUNC-MDR-01 Platform-specific Executable Code for MDRC-2, MDRC-3 or MDRC-4.....	16
6.4.2 R-FUNC-MDR-02 Platform-independent Source Code or IR for MDRC-5, MDRC-6 or MDRC-7.....	17
6.4.3 R-FUNC-MDR-03 Radio Configuration of Platform MDRC-1 to MDRC-7.....	17
6.4.4 R-FUNC-MDR-04 Radio Programming for MDRC-1 to MDRC-7 .....	17
6.4.5 R-FUNC-MDR-05 Dynamic Execution for MDRC-4, and MDRC-7 .....	17
6.4.6 R-FUNC-MDR-06 Independency on Memory Model for MDRC-1 to MDRC-7 .....	17
6.4.7 R-FUNC-MDR-07 Code for MDRC-2 to MDRC-7.....	17
6.4.8 R-FUNC-MDR-08 IR Format for MDRC-5 to MDRC-7.....	18
6.4.9 R-FUNC-MDR-09 Timing Constraints for MDRC-1 to MDRC-7 .....	18
6.4.10 R-FUNC-MDR-10 Platform Independency for MDRC-5 to MDRC-7 .....	18
6.4.11 R-FUNC-MDR-11 Radio Application for MDRC-5 to MDRC-7 .....	18
6.4.12 R-FUNC-MDR-12 Function Granularity for MDRC-1 to MDRC-7 .....	18

6.4.13	R-FUNC-MDR-13 Radio Virtual Machine for MDRC-2 to MDRC-7 .....	18
6.4.14	R-FUNC-MDR-14 RadioVirtual Machine Structure for MDRC-2 to MDRC-7 .....	18
6.4.15	R-FUNC-MDR-15 Selection of Radio Virtual Machine Protection Class for MDRC-2 to MDRC-7 .....	18
6.5	Radio Frequency(RF) Transceiver Requirements .....	20
6.5.1	R-FUNC-RFT-01 RF Configuration for MDRC-1 to MDRC-7 .....	20
6.5.2	R-FUNC-RFT-02 Extendibility for multiple-antenna system for MDRC-1 to MDRC-7 .....	20
6.5.3	R-FUNC-RFT-03 Capability of multiple frequency bands for MDRC-1 to MDRC-7 .....	20
6.5.4	R-FUNC-RFT-04 Reconfigurability of RF Transceiver for MDRC-1 to MDRC-7 .....	20
6.5.5	R-FUNC-RFT-05 Interoperability of radio resources for MDRC-2 to MDRC-7 .....	20
6.5.6	R-FUNC-RFT-06 Testability of radio equipment for MDRC-1 to MDRC-7 .....	20
6.5.7	R-FUNC-RFT-07 Unified representation of control information for MDRC-1 to MDRC-7 .....	20
6.5.8	R-FUNC-RFT-08 Unified representation of data payload for MDRC-1 to MDRC-7 .....	21
6.5.9	R-FUNC-RFT-09 Selection of RF Protection Class for MDRC-1 to MDRC-7 .....	21
History	.....	22

**iTeh STANDARD PREVIEW**  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/58838bcd-d05d-48cd-833f-bb5b7189217c/etsi-en-302-969-v1.2.1-2014-11>

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Reconfigurable Radio Systems (RRS).

National transposition dates	
Date of adoption of this EN:	10 November 2014
Date of latest announcement of this EN (doa):	28 February 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2015
Date of withdrawal of any conflicting National Standard (dow):	31 August 2015

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**may not**", "**need**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](https://standards.iteh.ai/catalog/standards/sist/58838bcd-005-48cd-3731-b5b7189217c1/etsi-en-302-969-v1.2.1-2014-11) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The scope of the present document is to define the high level system requirements for reconfigurable Mobile Devices enabling the provision of Radio Applications. The work will be based on the Use Cases defined in TR 103 062 [i.1] and TR 102 944 [i.2].

---

# 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

Not applicable.

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 103 062: "Reconfigurable Radio Systems (RRS); Use Cases and Scenarios for Software Defined Radio (SDR) Reference Architecture for Mobile Device".
- [i.2] ETSI TR 102 944: "Reconfigurable Radio Systems (RRS); Use Cases for Baseband Interfaces for Unified Radio Applications of Mobile Device".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**Functional Block (FB):** function needed for real-time implementation of Radio Application(s)

NOTE 1: A functional block includes not only the modem functions in Layer1 (L1), Layer2 (L2), and Layer 3 (L3) but also all the control functions that should be processed in real-time for implementing given Radio Application(s).

NOTE 2: Functional blocks are categorized into *standard functional blocks* and *user defined functional blocks*. In more details:

- 1) *Standard functional blocks* can be shared by many Radio Applications. For example, Forward Error Correction (FEC), Fast Fourier Transform (FFT)/Inverse Fast Fourier Transform (IFFT), (de)interleaver, Turbo coding, Viterbi coding, Multiple Input Multiple Output (MIMO), Beamforming, etc are the typical category of standard functional block.

- 2) *User defined functional blocks* include those functional blocks that are dependent upon a specific Radio Application. They are used to support special function(s) required in a specific Radio Application or to support a special algorithm used for performance improvement. In addition, a user defined functional block can be used as a baseband controller functional block which controls the functional blocks operating in baseband processor in real-time and to control some context information processed in real-time.

NOTE 3: Each functional block has its unique name, Input, Output and properties.

**network coding:** technique in which transmitted data is encoded and decoded to improve network performance

**Radio Application (RA):** software which enforces the generation of the transmit RF signals or the decoding of the receive RF signals

NOTE 1: The Software is executed on a particular radio platform or an RVM as part of the radio platform.

NOTE 2: Radio applications might have different forms of representation. They are represented as:

- source codes including Radio Library calls of Radio Library native implementation and Radio HAL calls;
- Intermediate Representations (IRs) including Radio Library calls of Radio Library native implementation and radio HAL calls;
- Executable codes for a particular radio platform.

**radio library:** library of Standard Functional Blocks (SFB) that is provided by a platform vendor in a form of platform-specific executable code

NOTE 1: SFBs implement reference codes of functions which are typical for radio signal processing. They are not atomic and their source codes are typed and visible for Radio Application developers.

NOTE 2: An SFB is implemented through a Radio Hardware Abstraction Layer (HAL) when the SFB is implemented on dedicated HW accelerators. Radio HAL is part of ROS.

**Radio Virtual Machine (RVM):** abstract machine supporting reactive and concurrent executions

NOTE: A Radio Virtual Machine may be implemented as a controlled execution environment which allows the selection of a trade-off between flexibility of base band code development and required (re-)certification efforts.

**reconfigurable mobile device:** Mobile Device with radio communication capabilities providing support for radio reconfiguration

NOTE: Reconfigurable Mobile Devices include but are not limited to: Smartphones, Feature Phones, Tablets, Laptops.

**resources:** Hardware Resources that a Radio Application needs in active state

NOTE 1: Resources are provided by the reconfigurable Mobile Device (MD), to be used by the Radio Applications when they are active. Radio Applications provide their Resource needs (e.g. using operational states) so that the multiradio computer may judge whether these Resources are available, in order to ensure non-conflicting operation with other Radio Applications. Resources may or may not be shared in the reconfigurable MD.

NOTE 2: Resources may include processors, accelerators, memory, Radio Frequency circuitry, etc.

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASIC	Application Specific Integrated Circuit
BER	Bit Error Rate
CAT	Category
CR	Cognitive Radio
DoA	Direction of Arrival
FB	Functional Block
FEC	Forward Error Correction
FFT	Fast Fourier Transform
HAL	Hardware Abstraction Layer
IR	Intermediate Representation
LTE	Long Term Evolution
MAC	Media Access Control
MD	Mobile Device
MDRC	Mobile Device Reconfiguration Class
MIMO	Multi-Input Multi-Output
MU-MIMO	Multi User- Multi-Input Multi-Output
PER	Packet Error Rate
PMI	Precoding Matrix Indicator
RA	Radio Application
RAT	Radio Access Technology
RF	Radio Frequency
RI	Rank Indicator
ROS	Radio Operating System
RRS	Reconfigurable Radio Systems
RSSI	Received Signal Strength Indication
RVM	Radio Virtual Machine
Rx	Receive
SDR	Software Defined Radio
SFB	Standard Functional Block
SINR	Signal to Interference-plus-Noise Ratio
SU-MIMO	Single User- Multi-Input Multi-Output
Tx	Transmit
UDFB	User Defined Functional Block
WiFi	Wireless Fidelity

PRE-STANDARD PREVIEW  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/58838bcd-d05d-48cd-81e2-bb5b789177c/etsi-en-302-969-v1.2.1-2014-11>

---

## 4 Requirement Organization and Methodology

This clause is containing the description of how the requirements are organized and the related format.

### 4.1 Requirement Organization

As shown in Figure 1, all requirements described in the present document belong to one single category (the functional requirements category). Requirements are, in turn, organized into groups.






Figure 1: Overall requirements structure

## 4.2 Requirement Format

A letter code system is defined which makes a unique identification of each requirement R-<CAT>-<GROUP>-<XX>. Each requirement is constructed as follows:

- R-: Standard requirement prefix
- <CAT>

Code	Category
FUNC	Functional aspects

- <GROUP>: Requirement group identifier. A letter code will be used for this identifier. The three first letters will give the identifier of the group.
- <XX>: Requirement identifier within requirement group; range 01 => 99.

EXAMPLE: R-FUNC-QOS-01.

## 4.3 Requirement Formulation

A requirement is formulated in such a way that it is uniquely defined. It is built as follows:

Title: <Title Description>

- Description: the description of a requirement will be formulated using one of the following terms:
  - "shall" is used to express mandatory requirements (i.e. provisions that have to be followed)
  - "should" is used to express recommendations (provisions that an implementation is expected to follow unless there is a strong reason for not doing so)
  - "May" is used to express permissible actions (provisions that an implementation is able to follow or not follow)

## 5 Working assumptions

### 5.1 Assumptions

#### 5.1.1 Mobile Device Reconfiguration Classes

As it is expected that the reconfiguration capabilities of a Mobile Device will evolve over time, Mobile Device Reconfiguration Classes (MDRC) are introduced. As shown in Figure 2, 7 different classes of reconfigurable MD are introduced (MDRC-0 corresponds to a non-reconfigurable device).

No reconfiguration	MDRC-0	
No resource share (fixed hardware)	MDRC-1	
Pre-defined static resources	MDRC-2	MDRC-5
Static resource requirements	MDRC-3	MDRC-6
Dynamic resource requirements	MDRC-4	MDRC-7
	Platform-specific executable code	Platform-independent source code or IR

**Figure 2: Definition of MDRCs according to reconfiguration capabilities**

A reconfigurable MD belongs to a defined class according to the reconfiguration capabilities, which are determined by the type of Resource requirements and the form of the Radio Application Package. Reconfigurable MD classes are defined as follows (see also Figure 2):

- 1) MDRC-0: No MD reconfiguration is possible

MDRC-0 represents legacy radio implementations and do not allow for MD reconfiguration (except for bug fixing and release-updates through firmware updates) or exploitation of Cognitive Radio (CR) features. MDRC-0 represents legacy radio implementations and does not allow for MD reconfiguration.