



SLOVENSKI STANDARD

SIST-TP ISO/TR 1281-1:2009

01-junij-2009

Rolling bearings - Explanatory notes on ISO 281 - Part 1: Basic dynamic load rating and basic rating life

Wälzlager - Erläuternde Anmerkungen zur ISO 281 - Teil 1: Dynamische Tragzahlen und nominelle Lebensdauer

Roulements - Notes explicatives sur l'ISO 281 - Partie 1: Charges dynamiques de base et durée nominale de base

Ta slovenski standard je istoveten z: ISO/TR 1281-1:2008

ICS:

21.100.20 Kotalni ležaji Rolling bearings

SIST-TP ISO/TR 1281-1:2009

en,fr

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TP ISO/TR 1281-1:2009](https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0cd489ec/sist-tp-iso-tr-1281-1-2009)

<https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0cd489ec/sist-tp-iso-tr-1281-1-2009>

TECHNICAL REPORT

**ISO/TR
1281-1**

First edition
2008-12-01

Rolling bearings — Explanatory notes on ISO 281 —

Part 1: Basic dynamic load rating and basic rating life

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Roulements — Notes explicatives sur l'ISO 281 —
Partie 1: Charges dynamiques de base et durée nominale de base*

SIST-TP ISO/TR 1281-1:2009

<https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0cd489ec/sist-tp-iso-tr-1281-1-2009>



Reference number
ISO/TR 1281-1:2008(E)

© ISO 2008

ISO/TR 1281-1:2008(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TP ISO/TR 1281-1:2009](https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0cd489ec/sist-tp-iso-tr-1281-1-2009)

<https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0cd489ec/sist-tp-iso-tr-1281-1-2009>

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Symbols	1
4 Basic dynamic load rating	3
4.1 Basic dynamic radial load rating, C_r , for radial ball bearings	4
4.2 Basic dynamic axial load rating, C_a , for single row thrust ball bearings	7
4.3 Basic dynamic axial load rating, C_a , for thrust ball bearings with two or more rows of balls	9
4.4 Basic dynamic radial load rating, C_r , for radial roller bearings.....	10
4.5 Basic dynamic axial load rating, C_a , for single row thrust roller bearings	12
4.6 Basic dynamic axial load rating, C_a , for thrust roller bearings with two or more rows of rollers	13
5 Dynamic equivalent load.....	15
5.1 Expressions for dynamic equivalent load	15
5.2 Factors X , Y , and e	27
6 Basic rating life	38
7 Life adjustment factor for reliability	39
Bibliography	40

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In exceptional circumstances, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example), it may decide by a simple majority vote of its participating members to publish a Technical Report. A Technical Report is entirely informative in nature and does not have to be reviewed until the data it provides are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TR 1281-1 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*, Subcommittee SC 8, *Load ratings and life*.

<https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0c1489ec/sist-tp-iso-tr-1281-1-2009>

This first edition of ISO/TR 1281-1, together with the first edition of ISO/TR 1281-2, cancels and replaces the first edition of ISO/TR 8646:1985, which has been technically revised.

ISO/TR 1281 consists of the following parts, under the general title *Rolling bearings — Explanatory notes on ISO 281*:

- *Part 1: Basic dynamic load rating and basic rating life*
- *Part 2: Modified rating life calculation, based on a systems approach of fatigue stresses*

Introduction

ISO/R281:1962

A first discussion on an international level of the question of standardizing calculation methods for load ratings of rolling bearings took place at the 1934 conference of the International Federation of the National Standardizing Associations (ISA). When ISA held its last conference in 1939, no progress had been made. However, in its 1945 report on the state of rolling bearing standardization, the ISA 4 Secretariat included proposals for definition of concepts fundamental to load rating and life calculation standards. This report was distributed in 1949 as document ISO/TC 4 (Secretariat-1)1, and the definitions it contained are in essence those given in ISO 281:2007 for the concepts “life” and “basic dynamic load rating” (now divided into “basic dynamic radial load rating” and “basic dynamic axial load rating”).

In 1946, on the initiative of the Anti-Friction Bearing Manufacturers Association (AFBMA), New York, discussions of load rating and life calculation standards started between industries in the USA and Sweden. Chiefly on the basis of the results appearing in Reference [1], an AFBMA standard, *Method of evaluating load ratings of annular ball bearings*, was worked out and published in 1949. On the same basis, the member body for Sweden presented, in February 1950, a first proposal to ISO, “Load rating of ball bearings” [doc. ISO/TC 4/SC 1 (Sweden-1)1].

In view of the results of both further research and a modification to the AFBMA standard in 1950, as well as interest in roller bearing rating standards, in 1951, the member body for Sweden submitted a modified proposal for rating of ball bearings [doc. ISO/TC 4/SC 1 (Sweden-6)20] as well as a proposal for rating of roller bearings [doc. ISO/TC 4/SC 1 (Sweden-7)21].

Load rating and life calculation methods were then studied by ISO/TC 4, ISO/TC 4/SC 1 and ISO/TC 4/WG 3 at 11 different meetings from 1951 to 1959. Reference [2] was then of considerable use, serving as a major basis for the sections regarding roller bearing rating.

The framework for the Recommendation was settled at a TC 4/WG 3 meeting in 1956. At the time, deliberations on the draft for revision of AFBMA standards were concluded in the USA and ASA B3 approved the revised standard. It was proposed to the meeting by the USA and discussed in detail, together with the Secretariat's proposal. At the meeting, a WG 3 proposal was prepared which adopted many parts of the USA proposal.

In 1957, a Draft Proposal (document TC 4 N145) based on the WG proposal was issued. At the WG 3 meeting the next year, this Draft Proposal was investigated in detail, and at the subsequent TC 4 meeting, the adoption of TC 4 N145, with some minor amendments, was concluded. Then, Draft ISO Recommendation No. 278 (as TC 4 N188) was issued in 1959, and ISO/R281 accepted by ISO Council in 1962.

ISO 281/1:1977

In 1964, the member body for Sweden suggested that, in view of the development of imposed bearing steels, the time had come to review ISO/R281 and submitted a proposal [ISO/TC 4/WG 3 (Sweden-1)9]. However, at this time, WG 3 was not in favour of a revision.

In 1969, on the other hand, TC 4 followed a suggestion by the member body for Japan (doc. TC 4 N627) and reconstituted its WG 3, giving it the task of revising ISO/R281. The AFBMA load rating working group had at this time started revision work. The member body for the USA submitted the Draft AFBMA standard, *Load ratings and fatigue life for ball bearings* [ISO/TC 4/WG 3 (USA-1)11], for consideration in 1970 and *Load ratings and fatigue life for roller bearings* [ISO/TC 4/WG 3 (USA-3)19] in 1971.

In 1972, TC 4/WG 3 was reorganized and became TC 4/SC 8. This proposal was investigated in detail at five meetings from 1971 to 1974. The third and final Draft Proposal (doc. TC 4/SC 8 N23), with some amendments, was circulated as a Draft International Standard in 1976 and became ISO 281-1:1977.

ISO/TR 1281-1:2008(E)

The major part of ISO 281-1:1977 constituted a re-publication of ISO/R281, the substance of which had been only very slightly modified. However, based mainly on American investigations during the 1960s, a new clause was added, dealing with adjustment of rating life for reliability other than 90 % and for material and operating conditions.

Furthermore, supplementary background information regarding the derivation of mathematical expressions and factors given in ISO 281-1:1977 was published, first as ISO 281-2, *Explanatory notes*, in 1979; however, TC 4/SC 8 and TC 4 later decided to publish it as ISO/TR 8646:1985.

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[SIST-TP ISO/TR 1281-1:2009](https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0cd489ec/sist-tp-iso-tr-1281-1-2009)

<https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0cd489ec/sist-tp-iso-tr-1281-1-2009>

Rolling bearings — Explanatory notes on ISO 281 —

Part 1: Basic dynamic load rating and basic rating life

1 Scope

This part of ISO/TR 1281 gives supplementary background information regarding the derivation of mathematical expressions and factors given in ISO 281:2007.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 281:2007, *Rolling bearings — Dynamic load ratings and rating life*

3 Symbols

<https://standards.iteh.ai/catalog/standards/sist/c3a5703f-86bc-45f7-8fc5-1d6d0cd489ec/sist-tp-iso-tr-1281-1-2009>

		Clause
A	constant of proportionality	7
A_1	constant of proportionality determined experimentally	4
B_1	constant of proportionality determined experimentally	4
C_1	basic dynamic radial load rating of a rotating ring	4, 5
C_2	basic dynamic radial load rating of a stationary ring	4, 5
C_a	basic dynamic axial load rating for thrust ball or roller bearing	4, 6
C_{a1}	basic dynamic axial load rating of the rotating ring of an entire thrust ball or roller bearing	4
C_{a2}	basic dynamic axial load rating of the stationary ring of an entire thrust ball or roller bearing	4
C_{ak}	basic dynamic axial load rating as a row k of an entire thrust ball or roller bearing	4
C_{a1k}	basic dynamic axial load rating as a row k of the rotating ring of thrust ball or roller bearing	4
C_{a2k}	basic dynamic axial load rating as a row k of the stationary ring of thrust ball or roller bearing	4
C_e	basic dynamic load rating for outer ring	5
C_i	basic dynamic load rating for inner ring	5
C_r	basic dynamic radial load rating for radial ball or roller bearing	4, 5, 6

ISO/TR 1281-1:2008(E)

D_{pw}	pitch diameter of ball or roller set	4
D_w	ball diameter	4, 5
D_{we}	mean roller diameter	4
E_o	modulus of elasticity	4
F_a	axial load	5
F_r	radial load	4, 5
J_1	factor relating mean equivalent load on a rotating ring to Q_{max}	4, 5
J_2	factor relating mean equivalent load on a stationary ring to Q_{max}	4, 5
J_a	axial load integral	5
J_r	radial load integral	4, 5
L	bearing life	7
L_{10}	basic rating life	6, 7
L_{we}	effective contact length of roller	4
L_{wek}	L_{we} per row k	4
N	number of stress applications to a point on the raceway	4
P_a	dynamic equivalent axial load for thrust bearing	5, 6
P_r	dynamic equivalent radial load for radial bearing	5, 6
P_{r1}	dynamic equivalent radial load for the rotating ring	5
P_{r2}	dynamic equivalent radial load for the stationary ring	5
Q	normal force between a rolling element and the raceways	4, 6
Q_C	rolling element load for the basic dynamic load rating of the bearing	4, 6
Q_{C1}	rolling element load for the basic dynamic load rating of a ring rotating relative to the applied load	4, 5
Q_{C2}	rolling element load for the basic dynamic load rating of a ring stationary relative to the applied load	4, 5
Q_{max}	maximum rolling element load	4, 5
S	probability of survival, reliability	4, 7
V	volume representative of the stress concentration	4
V_f	rotation factor	5
X	radial load factor for radial bearing	5
X_a	radial load factor for thrust bearing	5
Y	axial load factor for radial bearing	5
Y_a	axial load factor for thrust bearing	5
Z	number of balls or rollers per row	4, 5
Z_k	number of balls or rollers per row k	4
a	semimajor axis of the projected contact ellipse	4
a_1	life adjustment factor for reliability	7
b	semiminor axis of the projected contact ellipse	4
c	exponent determined experimentally	4, 6
c_c	compression constant	5

e	measure of life scatter, i.e. Weibull slope determined experimentally	4, 5, 6, 7
f_c	factor which depends on the geometry of the bearing components, the accuracy to which the various components are made, and the material	4
h	exponent determined experimentally	4, 6
i	number of rows of balls or rollers	4
l	circumference of the raceway	4
r	cross-sectional raceway groove radius	5
r_e	cross-sectional raceway groove radius of outer ring or housing washer	4
r_i	cross-sectional raceway groove radius of inner ring or shaft washer	4
t	auxiliary parameter	4
v	$J_2(0,5)/J_1(0,5)$	5
z_0	depth of the maximum orthogonal subsurface shear stress	4
α	nominal contact angle	4, 5
α'	actual contact angle	5
γ	$D_w \cos \alpha / D_{pw}$ for ball bearings with $\alpha \neq 90^\circ$ D_w / D_{pw} for ball bearings with $\alpha = 90^\circ$ $D_{we} \cos \alpha / D_{pw}$ for roller bearings with $\alpha \neq 90^\circ$ D_{we} / D_{pw} for roller bearings with $\alpha = 90^\circ$	4
ε	parameter indicating the width of the loaded zone in the bearing	5
η	reduction factor	4, 5
λ	reduction factor	4
μ	factor introduced by Hertz	4
ν	factor introduced by Hertz, or adjustment factor for exponent variation	4
σ_{\max}	maximum contact stress	4
$\Sigma \rho$	curvature sum	4
τ_0	maximum orthogonal subsurface shear stress	4
φ_0	one half of the loaded arc	5

4 Basic dynamic load rating

The background to basic dynamic load ratings of rolling bearings according to ISO 281 appears in References [1] and [2].

The expressions for calculation of basic dynamic load ratings of rolling bearings develop from a power correlation that can be written as follows:

$$\ln \frac{1}{S} \propto \frac{\tau_0^c N^e V}{z_0^h} \quad (1)$$

where

S is the probability of survival;

τ_0 is the maximum orthogonal subsurface shear stress;

ISO/TR 1281-1:2008(E)

- N is the number of stress applications to a point on the raceway;
- V is the volume representative of the stress concentration;
- z_0 is the depth of the maximum orthogonal subsurface shear stress;
- c, h are experimentally determined exponents;
- e is the measure of life scatter, i.e. the Weibull slope determined experimentally.

For “point” contact conditions (ball bearings) it is assumed that the volume, V , representative of the stress concentration in Correlation (1) is proportional to the major axis of the projected contact ellipse, $2a$, the circumference of the raceway, l , and the depth, z_0 , of the maximum orthogonal subsurface shear stress, τ_0 :

$$V \propto a z_0 l \quad (2)$$

Substituting Correlation (2) into Correlation (1):

$$\ln \frac{1}{S} \propto \frac{\tau_0^c N^e a l}{z_0^{h-1}} \quad (3)$$

“Line” contact was considered in References [1] and [2] to be approached under conditions where the major axis of the calculated Hertz contact ellipse is 1,5 times the effective roller contact length:

$$2a = 1,5 L_{we} \quad (4)$$

In addition, b/a should be small enough to permit the introduction of the limit value of ab^2 as b/a approaches 0:

$$ab^2 = \frac{2}{\pi} \frac{3Q}{E_0 \sum \rho} \quad (5)$$

(for variable definitions, see 4.1).

4.1 Basic dynamic radial load rating, C_r , for radial ball bearings

From the theory of Hertz, the maximum orthogonal subsurface shear stress, τ_0 , and the depth, z_0 , can be expressed in terms of a radial load F_r , i.e. a maximum rolling element load, Q_{\max} , or a maximum contact stress, σ_{\max} , and dimensions for the contact area between a rolling element and the raceways. The relationships are:

$$\tau_0 = T \sigma_{\max}$$

$$z_0 = \zeta b$$

$$T = \frac{(2t-1)^{1/2}}{2t(t+1)}$$

$$\zeta = \frac{1}{(t+1)(2t-1)^{1/2}}$$

$$a = \mu \left(\frac{3Q}{E_0 \sum \rho} \right)^{1/3}$$

$$b = v \left(\frac{3Q}{E_0 \Sigma \rho} \right)^{1/3}$$

where

σ_{\max} is the maximum contact stress;

t is the auxiliary parameter;

a is the semimajor axis of the projected contact ellipse;

b is the semiminor axis of the projected contact ellipse;

Q is the normal force between a rolling element and the raceways;

E_0 is the modulus of elasticity;

$\Sigma \rho$ is the curvature sum;

μ, v are factors introduced by Hertz.

Consequently, for a given rolling bearing, τ_0 , a , l and z_0 can be expressed in terms of bearing geometry, load and revolutions. Correlation (3) is changed to an equation by inserting a constant of proportionality. Inserting a specific number of revolutions (e.g. 10^6) and a specific reliability (e.g. 0.9), the equation is solved for a rolling element load for basic dynamic load rating which is designated to point contact rolling bearings introducing a constant of proportionality, A_1 :

$$Q_C = \frac{1,3}{4^{(2c+h-2)/(c-h+2)}} \frac{0,5^{3e/(c-h+2)}}{D_w^{(2c+h-5)/(c-h+2)} Z^{-3e/(c-h+2)}} \left(\frac{2r}{2r-D_w} \right)^{0,41} (1 \mp \gamma)^{(1,59c+1,41h-5,82)/(c-h+2)} (1 \pm \gamma)^{3e/(c-h+2)} \times \left(\frac{\gamma}{\cos \alpha} \right)^{3/(c-h+2)} \quad (6)$$

where

Q_C is the rolling element load for the basic dynamic load rating of the bearing;

D_w is the ball diameter;

γ is $D_w \cos \alpha / D_{pw}$;

in which

D_{pw} is the pitch diameter of the ball set,

α is the nominal contact angle;

Z is the number of balls per row.

The basic dynamic radial load rating, C_1 , of a rotating ring is given by:

$$C_1 = Q_{C_1} Z \cos \alpha \frac{J_r}{J_1} = 0,407 Q_{C_1} Z \cos \alpha \quad (7)$$