



SLOVENSKI STANDARD
SIST-TS ISO/TS 19129:2009
01-september-2009

Geografske informacije - Sestava podob, gridnih in vektorskih podatkovnih slojev

Geographic information - Imagery, gridded and coverage data framework

Information Géographique - Structure de données pour les images, les matrices et les mosaïques

(standards.iteh.ai)

Ta slovenski standard je istoveten z: ISO/TS 19129:2009

<https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009>

ICS:

35.240.70	Uporabniške rešitve IT v znanosti	IT applications in science
-----------	-----------------------------------	----------------------------

SIST-TS ISO/TS 19129:2009

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST-TS ISO/TS 19129:2009

<https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009>

TECHNICAL SPECIFICATION

ISO/TS 19129

First edition
2009-04-01

Geographic information — Imagery, gridded and coverage data framework

*Information Géographique — Structure de données pour les images, les
matrices et les mosaïques*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TS ISO/TS 19129:2009](https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009)

<https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009>



Reference number
ISO/TS 19129:2009(E)

© ISO 2009

ISO/TS 19129:2009(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ISO/TS 19129:2009](https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009)

<https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009>

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Terms and definitions.....	1
4.1 Terms	1
4.2 Abbreviated terms	7
4.3 Notation	7
5 Background for the framework	8
5.1 Legacy concepts and terminology.....	8
5.2 Separation of carrier and content	8
5.3 Content model.....	9
6 General feature model as applied to imagery and gridded data.....	10
6.1 Coverages as features.....	10
6.2 Additional feature relationships.....	10
7 Framework.....	10
7.1 Framework structure	10
7.2 Elements of the framework structure.....	12
7.3 Encoding level.....	15
7.4 Imagery and gridded data portrayal.....	16
7.5 Feature relationship for LUTs.....	16
8 Spatial referencing of imagery, gridded and coverage data	17
9 Imagery, gridded and coverage data structure	17
9.1 IGCD structure and metadata	17
9.2 Framework structure classes	19
10 Templates	20
10.1 Application schema for imagery and gridded data	20
10.2 Grid coverages.....	21
10.3 Continuous quadrilateral grid coverage.....	23
10.4 Riemann hyperspatial multidimensional grid coverage	24
10.5 TIN coverage	27
10.6 Discrete point coverage	28
10.7 Discrete surface grid coverage	29
11 Tiling.....	31
11.1 Tiled grids.....	31
11.2 Tile densities	31
11.3 Tiling scheme	32
Annex A (normative) Abstract test suite.....	33
Annex B (informative) Use cases.....	35
Annex C (informative) Portrayal of imagery and gridded data	36
Bibliography	37

ISO/TS 19129:2009(E)**Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 19129 was prepared by Technical Committee ISO/TC 211, *Geographic information/Geomatics*.

Introduction

Gridded data, including imagery, is a major form of geographic information. Over the past two decades many, largely incompatible, standards have been developed that are widely used for the interchange of geographic imagery and gridded data. These include standards developed by ISO, as well as those developed by other organizations. With so many different imagery and gridded data standards, each standard aimed at different but overlapping information communities, there is a considerable legacy problem. Working with data encoded using different formats is often difficult because all of the necessary information for interworking has not been recorded using some of these standards. It is not possible to develop a new comprehensive standard to replace what exists or to simply endorse one existing standard (or industrial specification) to “solve” the interworking problem, because very large volumes of data exist in the various formats already in use. The Technical Report ISO/TR 19121:2000 identified the existing work on imagery and gridded data that had been ongoing in ISO and external technical organizations. What is required is a structure that allows for the specification of the content in a manner independent of and compatible with the various different encoding standards.

The area of imagery, gridded and coverage data is one of the most challenging within the field of geographic information. The data appears to be simple; however, there is significant structural complexity. While most data is organized in simple grids, there are many different traversal methods for grids and structures that support the distribution of attributes over a space. Sensor information and associated georeferencing are an important aspect of imagery, gridded and coverage geographic information.

This Technical Specification endeavours to address the harmonization of the broad legacy of existing imagery and gridded data. The approach specified is *not* to build a very flexible standard that encompasses everything with a broad array of options, since that does not create compatibility. One can be fooled into thinking things are standardized, because two data sets use incompatible subsets of the same set of general standards. All that would be accomplished would be to give an ISO label to the existing diversity and incompatibility. Compatibility is required for the underlying structure and primary elements of information content, regardless of how that information content is expressed. The purpose of this Technical Specification is to provide a framework within which interworking can occur. The approach used is to define a set of a few common information content structures for geographic imagery, gridded data and certain types of coverage data, which can be expressed using different encoding mechanisms and different interchange standards. The compatibility results from the common underlying content models that are expressed as a *generic set of UML patterns for application schemas*.

This Technical Specification recognizes that there are many overlapping imagery and gridded data specifications in wide use that differ significantly in how the information content is structured for encoding and in what choices of information form the content model. Different types of encoding may be appropriate in different situations. However, differences in content are difficult to reconcile. The existing different encoding standards do not necessarily conflict because they represent different ways of providing the same information in different contexts. Differences in content are also permitted for different situations, but the content definition must be the same in similar situations for interchange to be achieved without loss of information.

Most of the existing specifications for imagery and gridded data used in industry specify how content is to be expressed, rather than the content itself. They relate content to encoding, encapsulation and transfer of data. Those content descriptions that do appear to vary from one specification to another may not be in conflict or incompatible but reflect different real world situations that require different treatments.

This Technical Specification combines a number of well-defined content structures in accordance with ISO 19123, the International Standard for coverage geometry and functions together with metadata, spatial referencing and other aspects of imagery, gridded and coverage data into a framework. This will foster a convergence at the content model level for existing imagery, gridded and coverage data while allowing for backward compatibility with the identified suite of existing standards.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST-TS ISO/TS 19129:2009

<https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009>

Geographic information — Imagery, gridded and coverage data framework

1 Scope

This Technical Specification defines the framework for imagery, gridded and coverage data. This framework defines a content model for the content type imagery and for other specific content types that can be represented as coverage data. These content models are represented as a set of generic UML patterns for application schemas.

2 Conformance

Any application schema or profile claiming conformance with this Technical Specification shall pass the requirements described in the abstract test suite, presented in Annex A.

The abstract test suite indicates what is required for an application schema to comply with the framework established in this Technical Specification.

ITeCh STANDARD PREVIEW
(standards.iteh.ai)

3 Normative references

[SIST-TS ISO/TS 19129:2009](https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-19129-2009)

<https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-19129-2009>

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19107, *Geographic information — Spatial schema*

ISO 19109:2005, *Geographic information — Rules for application schema*

ISO 19115, *Geographic information — Metadata*

ISO 19115-2, *Geographic information — Metadata — Part 2: Extensions for imagery and gridded data*

ISO 19118, *Geographic information — Encoding*

ISO 19123, *Geographic information — Schema for coverage geometry and functions*

4 Terms and definitions

4.1 Terms

For the purposes of this document, the following terms and definitions apply.

4.1.1

application schema

conceptual schema for data required by one or more applications

[ISO 19101:2002]

ISO/TS 19129:2009(E)

4.1.2

content model

information view of an **application schema**

NOTE The term “information view” comes from the ISO Reference Model for Open Distributed Processing (RM-ODP), as specified in 19101-2.

4.1.3

continuous coverage

coverage that returns different values for the same **feature** attribute at different **direct positions** within a single spatial object, temporal object, or **spatiotemporal object** in its **domain**

[ISO 19123:2005]

NOTE Although the **spatiotemporal domain** of a continuous coverage is ordinarily bounded in terms of its spatial extent, it can be subdivided into an infinite number of **direct positions**.

4.1.4

coordinate

one of a sequence of n -numbers designating the position of a **point** in n -dimensional space

[ISO 19111:2007]

NOTE In a **coordinate reference system**, the numbers must be qualified by units.

4.1.5

coordinate reference system

coordinate system that is related to an object by a datum

[ISO 19111:2007]

NOTE For geodetic and vertical datums it will be related to the Earth.

4.1.6

coverage

feature that acts as a **function** to return values from its **range** for any **direct position** within its spatial, temporal or **spatiotemporal domain**

[ISO 19123:2005]

EXAMPLE Examples include a **raster** image, polygon overlay, or digital elevation **matrix**.

4.1.7

data compaction

reduction of the number of data elements, bandwidth, cost, and time for the generation, transmission, and storage of data without loss of information by eliminating unnecessary redundancy, removing irrelevancy, or using special coding

[ANSI T1.523-2001]

NOTE 1 Whereas data compaction reduces the amount of data used to represent a given amount of information, **data compression** does not.

NOTE 2 Data compaction can be done through aggregation of like values in adjacent **grid** cells, tiling schemes or other means of eliminating information that is not relevant.

4.1.8**data compression**

reducing either the amount of storage space required to store a given amount of data, or the length of message required to transfer a given amount of information

NOTE 1 Adapted from ANSI T1.523-2001.

NOTE 2 Data compression is probabilistic in nature based on particular instances of **imagery**, **gridded** or **coverage data** and is related to **encoding** and is outside the scope of this Technical Specification.

4.1.9**data interchange**

delivery, receipt and interpretation of data

[ISO 19118:2005]

4.1.10**dataset**

identifiable collection of data

[ISO 19115:2003]

4.1.11**direct position**

position described by a single set of **coordinates** within a **coordinate reference system**

[ISO 19107:2003]

4.1.12**discrete coverage**

coverage that returns the same **feature** attribute values for every **direct position** within any single spatial object, temporal object, or **spatiotemporal object** in its **domain**

[ISO 19123:2005]

NOTE The **spatiotemporal domain** of a discrete coverage consists of a finite set of geometric objects.

4.1.13**domain**

well-defined set

[ISO/TS 19103:32005]

NOTE Domains are used to define the domain set and **range** set of attributes, operators and **functions**.

4.1.14**encoding**

conversion of data into a series of codes

[ISO 19118:2005]

4.1.15**encoding rule**

identifiable collection of conversion rules that define the **encoding** for a particular data structure

[ISO 19118:2005]

ISO/TS 19129:2009(E)

4.1.16**feature**

abstraction of real world phenomena

[ISO 19101:2002]

NOTE A feature may occur as a type or an instance. Feature type or feature instance should be used when only one is meant.

4.1.17**framework**

relationship between the elements of the **content model** and the separate **encoding** and portrayal mechanisms

4.1.18**function**

rule that associates each element from a **domain** (source, or domain of the function) to a unique element in another domain (target, co-domain, or **range**)

[ISO 19107:2003]

4.1.19**geographic information**

information concerning phenomena implicitly or explicitly associated with a location relative to the Earth

[ISO 19101:2002]

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4.1.20**grid**

network composed of two or more sets of curves in which the members of each set intersect the members of the other sets in an algorithmic way

[SIST-TS ISO/TS 19129:2009](https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009)
<https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009>

[ISO 19123:2005]

NOTE The curves partition a space into grid cells.

4.1.21**grid coordinates**

sequence of two or more numbers specifying a position with respect to its location on a **grid**

[ISO 19115-2:2009]

4.1.22**grid point**

point located at the intersection of two or more curves in a **grid**

[ISO 19123:2005]

4.1.23**gridded data**

data whose attribute values are associated with positions on a **grid coordinate** system

[ISO 19115-2:2009]

4.1.24**imagery**

representation of phenomena as images produced by electronic and/or optical techniques

NOTE The term imagery is often used colloquially with various meanings in different contexts. It is often used to describe any set of **gridded**, **point** set or other form of **coverage data** that can be portrayed. This is not a very useful concept because virtually any set of data can be portrayed in some manner. A more precise meaning is given in ISO/TS 19101-2.

[ISO/TS 19101-2:2008]

4.1.25**matrix**

rectangular array of numbers

NOTE A matrix is a mathematical term.

4.1.26**metadata**

data about data

[ISO 19115:2003]

4.1.27**pixel**

smallest element of a digital image to which attributes are assigned

NOTE 1 This term originated as a contraction of "picture element".

NOTE 2 Related to the concept of a **grid** cell.

[ISO/TS 19101-2:2008] <https://standards.iteh.ai/catalog/standards/sist/0d65ab48-1045-4357-bf13-610d24e1b077/sist-ts-iso-ts-19129-2009>

4.1.28**point**

0-dimensional geometric primitive, representing a position

[ISO 19107:2003]

NOTE The boundary of a point is the empty set.

4.1.29**point coverage**

coverage that has a **domain** composed of **points**

[ISO 19123:2005]

4.1.30**quality**

totality of characteristics of a product that bear on its ability to satisfy stated and implied needs

[ISO 19101:2002]

4.1.31**range**

⟨coverage⟩ set of **feature** attribute values associated by a **function** with the elements of the **domain** of a **coverage**

[ISO 19123:2005]