



SLOVENSKI STANDARD
SIST EN 301 908-2 V7.1.1:2016

01-marec-2016

**Celična omrežja IMT - Harmonizirani EN, ki zajema bistvene zahteve člena 3.2
direktive R&TTE - 2. del: CDMA z neposrednim razprševanjem ("Direct Spread")
(UTRA FDD) (UE)**

IMT cellular networks - Harmonized EN covering the essential requirements of article 3.2
of the R&TTE Directive - Part 2: CDMA Direct Spread (UTRA FDD) User Equipment
(UE)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 908-2 V7.1.1:2016](https://standards.iteh.ai/catalog/standards/sist/45e8b58b-5ee8-4849-85b4-12c7262794ea/sist-en-301-908-2-v7-1-1-2016)

[https://standards.iteh.ai/catalog/standards/sist/45e8b58b-5ee8-4849-85b4-](https://standards.iteh.ai/catalog/standards/sist/45e8b58b-5ee8-4849-85b4-12c7262794ea/sist-en-301-908-2-v7-1-1-2016)

[12c7262794ea/sist-en-301-908-2-v7-1-1-2016](https://standards.iteh.ai/catalog/standards/sist/45e8b58b-5ee8-4849-85b4-12c7262794ea/sist-en-301-908-2-v7-1-1-2016)

Ta slovenski standard je istoveten z: EN 301 908-2 V7.1.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.070.99	Druge mobilne storitve	Other mobile services

SIST EN 301 908-2 V7.1.1:2016 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-2 V7.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/45e8b58b-5ee8-4849-85b4-12c7262794ea/sist-en-301-908-2-v7-1-1-2016>

ETSI EN 301 908-2 V7.1.1 (2015-12)



**IMT cellular networks;
Harmonised EN covering the essential requirements
of article 3.2 of the R&TTE Directive;
Part 2: CDMA Direct Spread (UTRA FDD)
User Equipment (UE)**

SIST EN 301 908-2 V7.1.1:2016
<https://standards.etsi.org/standards-search/4849-85b4-12c7262794ea/sist-en-301-908-2-v7-1-1-2016>

Reference

REN/MSG-TFES-011-02

Keywords

3G, 3GPP, cellular, digital, IMT, mobile, radio,
regulation, UMTS, UTRA, WCDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-2 V7.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/45e8b58b-5ee8-4849-85b4-12c726279421/EN-301-908-2-v7-1-1-2016>

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	7
1 Scope	8
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols.....	11
3.3 Abbreviations	12
4 Technical requirements specifications	13
4.1 Environmental profile.....	13
4.2 Conformance requirements	13
4.2.1 Introduction.....	13
4.2.2 Transmitter maximum output power.....	14
4.2.2.1 Transmitter maximum output power	14
4.2.2.1.1 Definition.....	14
4.2.2.1.2 Limits	14
4.2.2.1.3 Conformance	14
4.2.2.2 Transmitter maximum output power for DC-HSUPA	14
4.2.2.2.1 Definition for DC-HSUPA	14
4.2.2.2.2 Limits for DC-HSUPA	15
4.2.2.2.3 Conformance	15
4.2.2.3 Transmitter maximum output power for UL-OLTD	15
4.2.2.3.1 Definition for UL-OLTD	15
4.2.2.3.2 Limits for UL-OLTD	15
4.2.2.3.3 Conformance	15
4.2.3 Transmitter spectrum emission mask.....	16
4.2.3.1 Transmitter spectrum emission mask	16
4.2.3.1.1 Definition.....	16
4.2.3.1.2 Limits	16
4.2.3.1.3 Conformance	16
4.2.3.2 Transmitter spectrum emission mask for DC-HSUPA	16
4.2.3.2.1 Definition for DC-HSUPA	16
4.2.3.2.2 Limits for DC-HSUPA	16
4.2.3.2.3 Conformance	17
4.2.3.3 Transmitter spectrum emission mask for UL-OLTD	17
4.2.3.3.1 Definition for UL-OLTD	17
4.2.3.3.2 Limits for UL-OLTD	17
4.2.3.3.3 Conformance	17
4.2.3.4 Transmitter spectrum emission mask for UL-CLTD Activation state 1	18
4.2.3.4.1 Definition for UL-CLTD Activation state 1	18
4.2.3.4.2 Limits for UL-CLTD Activation state 1	18
4.2.3.4.3 Conformance	18
4.2.4 Transmitter spurious emissions.....	18
4.2.4.1 Transmitter spurious emissions	18
4.2.4.1.1 Definition.....	18
4.2.4.1.2 Limits	18
4.2.4.1.3 Conformance	20
4.2.4.2 Transmitter spurious emissions for DC-HSUPA	20
4.2.4.2.1 Definition for DC-HSUPA	20
4.2.4.2.2 Limits for DC-HSUPA	20

4.2.4.2.3	Conformance	22
4.2.5	Transmitter minimum output power	23
4.2.5.1	Transmitter minimum output power.....	23
4.2.5.1.1	Definition.....	23
4.2.5.1.2	Limits	23
4.2.5.1.3	Conformance	23
4.2.5.2	Transmitter minimum output power for DC-HSUPA	23
4.2.5.2.1	Definition for DC-HSUPA	23
4.2.5.2.2	Limits for DC-HSUPA	23
4.2.5.2.3	Conformance	23
4.2.5.3	Transmitter minimum output power for UL CLTD Activation state 1	23
4.2.5.3.1	Definition for UL CLTD Activation state 1	23
4.2.5.3.2	Limits for UL CLTD Activation state 1	23
4.2.5.3.3	Conformance	23
4.2.6	Receiver Adjacent Channel Selectivity (ACS)	23
4.2.6.1	Definition	23
4.2.6.2	Limits	24
4.2.6.3	Conformance.....	24
4.2.7	Receiver blocking characteristics	24
4.2.7.1	Definition	24
4.2.7.2	Limits	24
4.2.7.3	Conformance.....	26
4.2.8	Receiver spurious response.....	26
4.2.8.1	Definition	26
4.2.8.2	Limits	26
4.2.8.3	Conformance.....	26
4.2.9	Receiver intermodulation characteristics	26
4.2.9.1	Definition	26
4.2.9.2	Limits	26
4.2.9.3	Conformance.....	27
4.2.10	Receiver spurious emissions	27
4.2.10.1	Definition	27
4.2.10.2	Limits	27
4.2.10.3	Conformance.....	28
4.2.11	Out-of-synchronization handling of output power.....	28
4.2.11.1	Definition	28
4.2.11.2	Limits	28
4.2.11.3	Conformance.....	30
4.2.12	Transmitter Adjacent Channel Leakage power Ratio (ACLR).....	30
4.2.12.1	Transmitter adjacent channel leakage power ratio (ACLR).....	30
4.2.12.1.1	Definition.....	30
4.2.12.1.2	Limits	30
4.2.12.1.3	Conformance	30
4.2.12.2	Adjacent channel leakage power ratio for DC-HSUPA	30
4.2.12.2.1	Definition for DC-HSUPA	30
4.2.12.2.2	Limits for DC-HSUPA	30
4.2.12.2.3	Conformance	30
4.2.12.3	Adjacent channel leakage power ratio for UL OLTD	31
4.2.12.3.1	Definition for UL OLTD	31
4.2.12.3.2	Limits for UL OLTD	31
4.2.12.3.3	Conformance	31
4.2.12.4	Adjacent channel leakage power ratio for UL CLTD Activation state 1	31
4.2.12.4.1	Definition for UL CLTD Activation state 1	31
4.2.12.4.2	Limits for UL CLTD Activation state 1	31
4.2.12.4.3	Conformance	31
5	Testing for compliance with technical requirements.....	32
5.1	Environmental conditions for testing	32
5.2	Interpretation of the measurement results	32
5.3	Essential radio test suites.....	33
5.3.1	Transmitter maximum output power.....	33
5.3.1.1	Method of test	33

5.3.1.1.1	UTRA	33
5.3.1.1.1A	DC-HSUPA	34
5.3.1.1.1B	UL OLTD	34
5.3.1.2	Test requirements	35
5.3.2	Transmitter spectrum emission mask	35
5.3.2.1	Method of test	35
5.3.2.1.1	UEs not supporting HSDPA and/or E-DCH	35
5.3.2.1.1A	UEs supporting HSDPA and/or E-DCH	36
5.3.2.1.1B	DC-HSUPA	36
5.3.2.1.1C	UL OLTD	36
5.3.2.1.1D	UL CLTD Activation state 1	37
5.3.2.2	Test requirements	38
5.3.3	Transmitter spurious emissions	38
5.3.3.1	Method of test	38
5.3.3.1.1	UTRA	38
5.3.3.1.1A	DC-HSUPA	38
5.3.3.2	Test requirements	39
5.3.4	Transmitter minimum output power	39
5.3.4.1	Method of test	39
5.3.4.1.1	UTRA	39
5.3.4.1.1A	DC-HSUPA	39
5.3.4.1.1B	UL CLTD Activation state 1	40
5.3.4.2	Test requirements	40
5.3.5	Receiver Adjacent Channel Selectivity (ACS)	40
5.3.5.1	Method of test	40
5.3.5.1.1	Initial conditions	40
5.3.5.1.2	Procedure	41
5.3.5.2	Test requirements	41
5.3.6	Receiver blocking characteristics	41
5.3.6.1	Method of test	41
5.3.6.1.1	Initial requirements	41
5.3.6.1.2	Procedure	41
5.3.6.2	Test requirements	41
5.3.7	Receiver spurious response	42
5.3.7.1	Method of test	42
5.3.7.1.1	Initial conditions	42
5.3.7.1.2	Procedure	42
5.3.7.2	Test requirements	42
5.3.8	Receiver Intermodulation characteristics	42
5.3.8.1	Method of test	42
5.3.8.1.1	Initial conditions	42
5.3.8.1.2	Procedure	43
5.3.8.2	Test requirements	43
5.3.9	Receiver spurious emissions	43
5.3.9.1	Method of test	43
5.3.9.1.1	Initial conditions	43
5.3.9.1.2	Procedure	43
5.3.9.2	Test requirements	43
5.3.10	Out-of-synchronization handling of output power	43
5.3.10.1	Method of test	43
5.3.10.1.1	Initial conditions	43
5.3.10.1.2	Procedure	44
5.3.10.2	Test requirements	44
5.3.11	Transmitter adjacent channel leakage power ratio	44
5.3.11.1	Method of test	44
5.3.11.1.1	UEs not supporting HSDPA and/or E-DCH	44
5.3.11.1.1A	UEs supporting HSDPA and/or E-DCH	45
5.3.11.1.1B	DC-HSUPA	45
5.3.11.1.1C	UL OLTD	45
5.3.11.1.1D	UL CLTD Activation state 1	46
5.3.11.2	Test requirements	47

Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT)	48
Annex B (normative):	Environmental profile	50
B.1	General	50
B.1.1	Introduction	50
B.1.2	Temperature	50
B.1.3	Voltage	50
B.1.4	Test environment.....	50
Annex C:	Void	51
Annex D (informative):	Bibliography	52
History	53

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 908-2 V7.1.1:2016

<https://standards.iteh.ai/catalog/standards/sist/45e8b58b-5ee8-4849-85b4-12c7262794ea/sist-en-301-908-2-v7-1-1-2016>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to mandates M/284 and M/406 issued from the European Commission under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.10].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonised Standard under the Directive 1999/5/EC [i.2].

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.11].

iTEK STANDARD PREVIEW
(standards.iteh.ai)

National transposition dates	
Date of adoption of this EN:	SIST EN 301 908-2 V7.1.1:2016 21 December 2015
Date of latest announcement of this EN (doa):	https://standards.iteh.ai/catalog/standards/sist/45e8b58b-5ee8-4849-85b4-12c7202794ea/sist-en-301-908-2-v7-1-1-2016 31 March 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2016
Date of withdrawal of any conflicting National Standard (dow):	30 September 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in ETSI EG 201 399 [i.3].

1 Scope

The present document applies to the following radio equipment type:

- User Equipment for IMT-2000 CDMA Direct Spread (UTRA FDD).

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1-1.

Table 1-1: UTRA FDD operating bands

UTRA FDD Band	Direction of transmission	UTRA FDD operating bands
I	Transmit	1 920 MHz to 1 980 MHz
	Receive	2 110 MHz to 2 170 MHz
III	Transmit	1 710 MHz to 1 785 MHz
	Receive	1 805 MHz to 1 880 MHz
VII	Transmit	2 500 MHz to 2 570 MHz
	Receive	2 620 MHz to 2 690 MHz
VIII	Transmit	880 MHz to 915 MHz
	Receive	925 MHz to 960 MHz
XV	Transmit	1 900 MHz to 1 920 MHz
	Receive	2 600 MHz to 2 620 MHz
XVI	Transmit	2 010 MHz to 2 025 MHz
	Receive	2 585 MHz to 2 600 MHz
XX	Transmit	832 MHz to 862 MHz
	Receive	791 MHz to 821 MHz
XXII	Transmit	3 410 MHz to 3 490 MHz
	Receive	3 510 MHz to 3 590 MHz

ITeH STANDARD PREVIEW

The present document covers requirements for UTRA FDD User Equipment from 3GPP Releases 99, 4, 5, 6, 7, 8, 9, 10, and 11 defined in ETSI TS 125 101 [5]. This includes the requirements for UE operating bands from 3GPP Release 12 defined in ETSI TS 125 101 [i.12]. In addition, the present document covers requirements for UTRA FDD User Equipment in the operating bands specified in ETSI TS 102 735 [i.4].

NOTE 1: For Band XX:

- for user equipment designed to be mobile or nomadic, the requirements in the present document measured at the antenna port also show conformity to the corresponding requirement defined as TRP (Total Radiated Power), as described in Commission Decision 2010/267/EU [i.7], ECC Decision (09)03 [i.8] and CEPT Report 30 [i.9];
- for user equipment designed to be fixed or installed, the present document does not address the requirements described in Commission Decision 2010/267/EU [i.7], ECC Decision (09)03 [i.8] and CEPT Report 30 [i.9].

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive) article 3.2, which states that "radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.2] may apply to equipment within the scope of the present document.

NOTE 2: A list of such ENs is included on the web site <http://www.newapproach.org/>.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] ETSI TS 134 121-1 (V12.1.0) (10-2015): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) conformance specification; Radio transmission and reception (FDD); Part 1: Conformance specification (3GPP TS 34.121-1 version 12.1.0 Release 12)".
- [3] ETSI TS 134 108 (V12.1.0) (10-2015): "Universal Mobile Telecommunications System (UMTS); LTE; Common test environments for User Equipment (UE); Conformance testing (3GPP TS 34.108 version 12.1.0 Release 12)".
- [4] ETSI TS 134 109 (V12.0.0) (09-2014): "Universal Mobile Telecommunications System (UMTS); Terminal logical test interface; Special conformance testing functions (3GPP TS 34.109 version 12.0.0 Release 12)".
- [5] ETSI TS 125 101 (V11.11.0) (01-2015): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) radio transmission and reception (FDD) (3GPP TS 25.101 version 11.11.0 Release 11)".
- [6] IEC 60068-2-1 (03-2007): "Environmental testing - Part 2-1: Tests - Test A: Cold".
- [7] IEC 60068-2-2 (07-2007): "Environmental testing - Part 2-2: Tests - Test B: Dry heat".
- [8] ETSI TS 125 214 (V11.12.0) (07-2015): "Universal Mobile Telecommunications System (UMTS); Physical layer procedures (FDD) (3GPP TS 25.214 version 11.12.0 Release 11)".
- [9] ETSI TS 145 004 (V11.0.0) (10-2012): "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 11.0.0 Release 11)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).

- [i.3] ETSI EG 201 399 (V2.2.1) (08-2010): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.4] ETSI TS 102 735 (V7.1.0): "Universal Mobile Telecommunications System (UMTS); Band-specific requirements for UMTS Frequency Division Duplex (FDD) operation in the bands 1 900 MHz to 1 920 MHz paired with 2 600 MHz to 2 620 MHz and 2 010 MHz to 2 025 MHz paired with 2 585 MHz to 2 600 MHz".
- [i.5] Void.
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] Commission Decision 2010/267/EU of 6 May 2010 on harmonised technical conditions of use in the 790-862 MHz frequency band for terrestrial systems capable of providing electronic communications services in the European Union.
- [i.8] ECC Decision (09)03 of 30 October 2009 on harmonised conditions for mobile/fixed communications networks (MFCN) operating in the band 790 - 862 MHz.
- [i.9] CEPT Report 30 of 30 October 2009 to the European Commission in response to the Mandate on "The identification of common and minimal (least restrictive) technical conditions for 790 - 862 MHz for the digital dividend in the European Union".
- [i.10] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.11] ETSI EN 301 908-1 (V7.1.1) (03-2015): "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 1: Introduction and common requirements".
- [i.12] ETSI TS 125 101 (V12.9.0) (10-2015): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) radio transmission and reception (FDD) (3GPP TS 25.101 version 12.9.0 Release 12)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

chip rate: rate of "chips" (modulated symbols after spreading) per second

NOTE: The UTRA FDD chip rate is 3,84 Mchip/s.

data rate: rate of the user information, which is transmitted over the Air Interface

EXAMPLE: Output rate of the voice codec.

enhanced performance receiver type 1 for DCH: receiver with performance requirements which are optional for the UE and utilize receiver diversity during DCH reception

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

maximum output power: measure of the maximum power the UE can transmit (i.e. the actual power as would be measured assuming no measurement error) in a bandwidth of at least $(1 + \alpha)$ times the chip rate of the radio access mode

NOTE: The period of measurement is assumed to be at least one timeslot.

mean power: power (transmitted or received) in a bandwidth of at least $(1 + \alpha)$ times the chip rate of the radio access mode, when applied to a WCDMA modulated signal

NOTE: The period of measurement is assumed to be at least one timeslot unless otherwise stated.

node B: logical node responsible for radio transmission/reception in one or more cells to/from the User Equipment

nominal maximum output power: nominal power defined by the UE power class

operating band: frequency range that is defined with a specific set of technical requirements, in which UTRA FDD operates

NOTE: Operating bands for UTRA are designated with Roman numerals, while the corresponding operating bands for E-UTRA are designated with Arabic numerals.

power spectral density: function of power versus frequency and when integrated across a given bandwidth, the function represents the mean power in such a bandwidth

NOTE 1: When the mean power is normalized to (divided by) the chip-rate it represents the mean energy per chip. Some signals are directly defined in terms of energy per chip, (DPCH_Ec, Ec, OCNS_Ec and S-CCPCH_Ec) and others defined in terms of PSD (I_o , I_{oc} , I_{or} and \hat{I}_{or}). There also exist quantities that are a ratio of energy per chip to PSD (DPCH_Ec/ I_{or} , E_c/I_{or} , etc.). This is the common practice of relating energy magnitudes in communication systems.

NOTE 2: It can be seen that if both energy magnitudes in the ratio are divided by time, the ratio is converted from an energy ratio to a power ratio, which is more useful from a measurement point of view. It follows that an energy per chip of X dBm/3,84 MHz can be expressed as a mean power per chip of X dBm. Similarly, a signal PSD of Y dBm/3,84 MHz can be expressed as a signal power of Y dBm.

NOTE 3: The units of Power Spectral Density (PSD) are extensively used in the present document.

RRC filtered mean power: mean power as measured through a root raised cosine filter with roll-off factor α and a bandwidth equal to the chip rate of the radio access mode

NOTE: The RRC filtered mean power of a perfectly modulated WCDMA signal is 0,246 dB lower than the mean power of the same signal.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

α	Roll-off factor of the root raised cosine filter, $\alpha = 0,22$
DPCH_Ec	Average energy per PN chip for DPCH
E_c	Average energy per PN chip
F_{uw}	Frequency of unwanted signal

NOTE: This is specified in bracket in terms of an absolute frequency(s) or a frequency offset from the assigned channel frequency.

I_o	The total received power spectral density, including signal and interference, as measured at the UE antenna connector
I_{oc}	Power spectral density (integrated in a noise bandwidth equal to the chip rate and normalized to the chip rate) of a band limited white noise source (simulating interference from cells, which are not defined in a test procedure) as measured at the UE antenna connector
I_{or}	Total transmit power spectral density (integrated in a bandwidth of $(1 + \alpha)$ times the chip rate and normalized to the chip rate) of the downlink signal at the Node B antenna connector
\hat{I}_{or}	Received power spectral density (integrated in a bandwidth of $(1 + \alpha)$ times the chip rate and normalized to the chip rate) of the downlink signal as measured at the UE antenna connector
β_c	Gain factor for DPCCCH
β_d	Gain factor for DPDCH

β_{hs}	Gain factor for HS-DPCCH
β_{ec}	Gain factor for E-DPCCH
β_{ed}	Gain factor for E-DPDCH

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

<REFSENS>	Reference sensitivity
AC	Access Channel
ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
BER	Bit Error Ratio
CA	Carrier Aggregation
CDMA	Code Division Multiple Access
CLTD	Closed Loop Transmit Diversity
CW	Continuous Wave

NOTE: Unmodulated signal.

DB-DC-HSDPA	Dual Band Dual Cell HSDPA
DCH	Dedicated Channel

NOTE: Which is mapped into Dedicated Physical Channel.

DC-HSUPA	Dual Cell HSUPA
DL	Downlink
DPCCH	Dedicated Physical Control Channel
DPCH	Dedicated Physical Channel
DPDCH	Dedicated Physical Data Channel
E-DCH	Enhanced Dedicated Channel
E-DPCCH	Enhanced DPCCH
E-DPDCH	Enhanced DPDCH
EMC	ElectroMagnetic Compatibility
ERM	Electromagnetic compatibility and Radio spectrum Matters
EUT	Equipment Under Test
FDD	Frequency Division Duplex
FRC	Fixed Reference Channel
GMSK	Gaussian Minimum Shift Keying
GSM	Global System for Mobile
HSDPA	High Speed Downlink Packet Access
HS-DPCCH	High Speed DPCCH
HSUPA	High Speed Uplink Packet Access
IMT	International Mobile Telecommunications
LTE	Long Term Evolution
MPR	Maximum Power Reduction
MSG	Mobile Standards Group
OCNS	Orthogonal Channel Noise Simulator

NOTE: A mechanism used to simulate the users or control signals on the other orthogonal channels of a downlink.

OLTD	Open Loop Transmit Diversity
PCH	Paging Channel
PN	PseudoNoise
PSD	Power Spectral Density
QPSK	Quadrature Phase Shift Keying
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
RRC	Root Raised Cosine

SS System Simulator

NOTE: See ETSI TS 134 121-1 [2].

TFES Task Force for European Standards for IMT
 TH Temperature High
 TH/VH High extreme Temperature/High extreme Voltage
 TH/VL High extreme Temperature/Low extreme Voltage
 TL Temperature Low
 TL/VH Low extreme Temperature/High extreme Voltage
 TL/VL Low extreme Temperature/Low extreme Voltage
 TPC Transmit Power Control
 TRP Total Radiated Power
 UARFCN UTRA Absolute Radio Frequency Channel Number
 UE User Equipment
 UL UpLink
 UMTS Universal Mobile Telecommunications System
 UTRA Universal Terrestrial Radio Access
 VH Higher extreme Voltage
 VL Lower extreme Voltage
 WCDMA Wideband Code Division Multiple Access

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

For guidance on how a supplier can declare the environmental profile see annex B.

4.2 Conformance requirements

The requirements in the present document are based on the assumption that the operating band (i.e. band I, III, VII, VIII, XV, XVI, XX and XXII) is shared between systems of the IMT family (for band III and VIII also GSM) or systems having compatible characteristics.

4.2.1 Introduction

To meet the essential requirement under article 3.2 of the Directive 1999/5/EC [i.2] (R&TTE Directive) for IMT User Equipment (UE) eight essential parameters in addition to those in ETSI EN 301 908-1 [i.11] have been identified. Table 4.2.1-1 provides a cross reference between these eight essential parameters and the corresponding eleven technical requirements for equipment within the scope of the present document.

Table 4.2.1-1: Cross references

Essential parameter	Corresponding technical requirements
Spectrum emissions mask	4.2.3 Transmitter Spectrum emissions mask
	4.2.12 Transmitter adjacent channel leakage power ratio
Conducted spurious emissions in active mode	4.2.4 Transmitter spurious emissions
Accuracy of maximum output power	4.2.2 Transmitter maximum output power
Prevention of harmful interference through control of power	4.2.5 Transmitter minimum output power
Conducted spurious emission in idle mode	4.2.10 Receiver spurious emissions
Impact of interference on receiver performance	4.2.7 Receiver Blocking characteristics
	4.2.8 Receiver spurious response
	4.2.9 Receiver Intermodulation characteristics
Receiver adjacent channel selectivity	4.2.6 Receiver Adjacent Channel Selectivity (ACS)
Control and Monitoring functions	4.2.11 Out of synchronization handling of output power