



**Satellite Earth Stations and Systems (SES);
Harmonised EN for Earth Stations on
Mobile Platforms (ESOMP) transmitting towards
satellites in non-geostationary
orbit in the 27,5 GHz to 29,1 GHz and 29,5 GHz to 30,0 GHz
frequency bands covering the essential requirements
of article 3.2 of the R&TTE Directive**

PREVIEW
https://standards.etsi.org/standards-search/4983-147e-4983-a3af-8780-09e110000000/4983-147e-4983-a3af-8780-09e110000000-v1.1.1-2015-07

Reference

DEN/SES-00364

Keywords

antenna, earth station, mobile, non-GSO,
regulation, satellite

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	7
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	13
3.3 Abbreviations	13
4 Technical requirements specifications	14
4.1 General	14
4.1.1 Environmental profile	14
4.1.2 Operational configurations	14
4.1.3 Determination of geographic location of the ESOMP	14
4.1.4 EIRP _{Aggregate} for networks of ESOMPs.....	15
4.1.5 Presentation of equipment for testing purposes.....	15
4.1.6 Choice of model for testing	15
4.1.7 Mechanical and electrical design	15
4.1.7.1 General	15
4.1.7.2 Marking (equipment identification)	15
4.1.7.3 Equipment identification	15
4.2 Conformance requirements	16
4.2.1 Off-axis spurious radiation	16
4.2.1.1 Justification	16
4.2.1.2 Specification.....	16
4.2.1.3 Conformance tests.....	17
4.2.2 On-axis spurious radiation.....	17
4.2.2.1 Justification	17
4.2.2.2 Specification.....	17
4.2.2.2.1 "Carrier-on" radio state.....	17
4.2.2.2.2 "Carrier-off" and "Emissions disabled" radio states	17
4.2.2.3 Conformance tests.....	17
4.2.3 epdf Limits.....	18
4.2.3.1 Justification	18
4.2.3.2 Specification.....	18
4.2.3.3 Conformance tests.....	18
4.2.4 Uplink Power Control Specification	18
4.2.5 Carrier suppression	18
4.2.5.1 Justification	18
4.2.5.2 Specification.....	18
4.2.5.3 Conformance tests.....	18
4.2.6 Antenna pointing and polarization alignment	18
4.2.6.1 Antenna pointing accuracy.....	18
4.2.6.1.1 Purpose	18
4.2.6.1.2 Pointing accuracy specification	18
4.2.6.1.3 On-axis cross polarization isolation specification	19
4.2.6.1.4 Conformance tests	19
4.2.6.2 Antenna Pointing Error Detection.....	19
4.2.6.2.1 Purpose	19
4.2.6.2.2 Pointing error detection specification.....	19

4.2.6.2.3	Polarization angle alignment specification	19
4.2.6.2.4	Conformance tests	20
4.2.7	Cessation of emissions	20
4.2.7.1	Justification	20
4.2.7.2	Specification.....	20
4.2.7.2.1	Specification 1: Mode of cessation of emissions	20
4.2.7.2.2	Specification 2: Conditions under which the ESOMP shall cease emissions	20
4.2.7.2.3	Specification 3: Cessation of emissions	21
4.2.7.2.4	Specification 4: Fault conditions	21
4.2.7.3	Conformance tests	21
4.2.8	Identification of the ESOMP	21
4.2.8.1	Justification	21
4.2.8.2	Specification.....	21
4.2.8.3	Conformance tests	21
4.2.9	Control and Monitoring Functions (CMFs)	22
4.2.9.1	ESOMP States.....	22
4.2.9.1.1	General	22
4.2.9.1.2	CMF state diagram	23
4.2.9.2	Processor monitoring	24
4.2.9.2.1	Justification	24
4.2.9.2.2	Specification	24
4.2.9.2.3	Conformance tests	24
4.2.9.3	Transmit subsystem monitoring	25
4.2.9.3.1	Justification	25
4.2.9.3.2	Specification	25
4.2.9.3.3	Conformance tests	25
4.2.9.4	Power-on/Reset	25
4.2.9.4.1	Justification	25
4.2.9.4.2	Specification	25
4.2.9.4.3	Conformance tests	25
4.2.9.5	Control Channel (CC) and Response Channel (RC)	25
4.2.9.5.1	Justification	25
4.2.9.5.2	Specification	25
4.2.9.5.3	Conformance tests	26
4.2.9.6	Network control commands	26
4.2.9.6.1	Justification	26
4.2.9.6.2	Specification.....	26
4.2.9.6.3	Conformance tests	27
4.2.9.7	Initial burst transmission	27
4.2.9.7.1	Justification	27
4.2.9.7.2	Specification	27
4.2.9.7.3	Conformance tests	27
4.2.9.8	Inhibition of transmissions	27
4.2.9.8.1	Justification	27
4.2.9.8.2	Specification	27
4.2.9.8.3	Conformance tests	27
5	Testing for compliance with technical requirements.....	28
5.1	Environmental conditions for testing	28
5.2	Essential radio test suites.....	28
6	Test methods for all aspects of the ESOMP	28
6.1	General	28
6.1.1	General requirements	28
6.1.2	Interpretation of measurement results	28
6.1.3	Measuring receiver	29
6.2	Off-axis spurious radiation	30
6.2.1	General.....	30
6.2.2	Test method	30
6.2.2.1	General	30
6.2.2.2	Multi-carrier operation	31
6.2.3	Measurements up to 1 000 MHz	31

6.2.3.1	Test site	31
6.2.3.2	Measuring receivers	31
6.2.3.3	Procedure	31
6.2.4	Measurements above 1 000 MHz	32
6.2.4.1	General	32
6.2.4.2	Identification of the significant frequencies of spurious radiation	32
6.2.4.2.1	Test site.....	32
6.2.4.2.2	Procedure.....	32
6.2.4.3	Measurement of radiated power levels of identified spurious radiation.....	32
6.2.4.3.1	Test site.....	32
6.2.4.3.2	Procedure.....	33
6.2.4.4	Measurement of conducted spurious radiation at the antenna flange.....	34
6.2.4.4.1	Test site.....	34
6.2.4.4.2	Procedure.....	34
6.3	On-axis spurious radiation.....	35
6.3.1	Test method	35
6.3.1.1	General	35
6.3.1.2	Test site	35
6.3.1.3	Method of measurement.....	35
6.3.1.3.1	General	35
6.3.1.3.2	Method of measurement at the antenna flange	35
6.3.1.3.3	Method of measurement for an EUT with antenna.....	37
6.4	epfd limits.....	38
6.5	Carrier suppression.....	38
6.5.1	Test method	38
6.6	Antenna pointing	38
6.6.1	General.....	38
6.6.2	Test method	38
6.7	Polarization angle alignment capability.....	39
6.7.1	General.....	39
6.7.2	Test method	39
6.8	Cessation of emissions of the ESOMP.....	39
6.8.1	General.....	39
6.8.2	Test Method.....	39
6.8.2.1	Required documentation	39
6.8.2.2	Cessation of emissions from the "Transmission enabled" state	39
6.8.2.3	Cessation of emission from the "Transmission disabled" state	40
6.8.2.4	Cessation of emission from the "Initial Phase" state.....	40
6.8.2.4.1	EUTs transmitting initial bursts.....	40
6.8.2.4.2	EUTs not transmitting initial bursts.....	40
6.8.2.5	"Single action" means of cessation of emissions.....	41
6.8.2.6	Fault conditions.....	41
6.9	Identification of ESOMP.....	42
6.9.1	Test arrangement	42
6.9.2	Test method	42
6.10	Control and monitoring functions	42
6.10.1	General.....	42
6.10.2	Test arrangement	42
6.10.3	Processor monitoring- Test method.....	42
6.10.4	Transmit subsystem monitoring-Test method.....	42
6.10.5	Power-on/Reset-Test method.....	43
6.10.6	Control Channel and Response Channel -Test method.....	43
6.10.7	Network Control commands-Test method.....	44
6.10.8	Initial burst transmission-Test method.....	45
6.10.9	Inhibition of transmission-Test method	45
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	47
Annex B (informative):	Linear Polarization Alignment Error Calculation	49
Annex C (normative):	Radiated measurement.....	50

C.1	Test sites and general arrangements for measurements involving the use of radiated fields	50
C.1.1	General	50
C.1.2	Anechoic Chamber	50
C.1.3	Anechoic Chamber with a conductive ground plane	51
C.1.4	Open Area Test Site (OATS)	52
C.1.5	Minimum requirements for test sites for measurements above 18 GHz.....	53
C.1.6	Test antenna.....	53
C.1.7	Substitution antenna	54
C.1.8	Measuring antenna	54
C.2	Guidance on the use of radiation test sites	54
C.2.1	General	54
C.2.2	Verification of the test site	54
C.2.3	Preparation of the EUT.....	54
C.2.4	Power supplies to the EUT	54
C.2.5	Range length.....	55
C.2.6	Site preparation	55
C.3	Coupling of signals.....	56
C.3.1	General	56
C.4	Standard test methods.....	56
C.4.1	General	56
C.4.2	Calibrated setup.....	56
C.4.3	Substitution method.....	56
Annex D (normative):	Conducted measurements	58
Annex E (informative):	General Requirements for RF Cables.....	59
Annex F (informative):	RF Waveguides	60
Annex G (informative):	Bibliography.....	61
History		62

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document has been produced by ETSI in response to mandate M/284 issued from the European Commission issued under Directive 98/34/EC [i.1] as amended by Directive 98/48/EC [i.5].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonised Standard under the Directive 1999/5/EC [i.2].

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

For non EEA countries the present document may be used for regulatory (type approval) purposes.

National transposition dates	
Date of adoption of this EN:	6 July 2015
Date of latest announcement of this EN (doa):	31 October 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2016
Date of withdrawal of any conflicting National Standard (dow):	30 April 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in ETSI EG 201 399 [i.3].

The present document is largely based on ETSI EN 303 978 [i.7], for ESOMPs operating with GSO satellites.

The present document may also be applicable to the frequency bands 30,0 GHz to 31,0 GHz (Earth-to-space) and 20,2 GHz to 21,2 GHz (space-to-Earth) subject to national regulation.

Annex A (normative) provides HS Requirements and conformance Test specifications Table (HS-RTT).

Annex B (informative) provides information on Linear Polarization Alignment Error Calculation.

Annex C (normative) provides specifications concerning radiated measurements.

Annex D (normative) provides specifications concerning conducted measurements.

Annex E (informative) provides general information concerning RF cables.

Annex F (informative) provides information concerning RF waveguides.

Annex G (informative) Bibliography covers other supplementary information.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/340f7383-147e-4983-a3af-dfb8017669e7/etsi-en-303-979-v1.1.1-2015-07>

1 Scope

The present document applies to Earth Stations on Mobile Platforms (ESOMP), which have the following characteristics.




Figure 1: ESOMP System Overview

- The ESOMP is designed for both mobile and stationary operation.
- The ESOMP operates on various mobile platforms such as trains, maritime vessels, aircraft and other vehicles and, therefore, may be subject to occasional disturbances and interruptions in the satellite link.
- The ESOMP is operating as part of a satellite network (e.g. star, mesh or point-to-point) used for the distribution and/or exchange of information.
- The ESOMP is comprised of all the equipment, electrical and mechanical, from the antenna itself to the interface with other communications equipment on a mobile platform (usually referred to as the terrestrial interface).
- The ESOMP comprises of one or more emitters and the system overview given in figure 1 should be interpreted accordingly.
- The transmit and receive frequencies are shown in table 1.

Table 1: Frequency bands

	Frequency Bands/frequencies
Transmit (Earth-to-space)	27,5 GHz to 29,1 GHz and 29,5 GHz to 30,0 GHz
Receive (space-to-Earth)	17,30 GHz to 20,20 GHz

- The ESOMP transmits within the frequency range from 27,5 GHz to 29,1 GHz and 29,5 GHz to 30,0 GHz, which is a band allocated to the Fixed Satellite Services (FSS) (Earth-to-space) among other services. National regulations will specify the bands available for the operation of the ESOMP. Such regulations may designate some parts of the frequency range 27,5 GHz to 29,1 GHz to terrestrial services such as the Fixed Service. However, the operation of the ESOMP may be permitted under national regulations in the 29,50 GHz to 30,00 GHz band since this band is allocated on a primary basis to the Fixed-Satellite Service.
- The ESOMP receives in one or more frequencies within the range from 17,30 GHz to 20,20 GHz (FSS).
- The ESOMP uses linear or circular polarization.
- The ESOMP operates through non-geostationary satellites.
- The ESOMP is designed for unattended operation.

- The ESOMP is controlled and monitored by a Network Control Facility (NCF). This function may be performed centrally (e.g. for a network of ESOMPs with a central hub) or it could be performed within the ESOMP for autonomous control. The NCF is outside the scope of the present document.
- The ESOMP operating in the 27,5 GHz to 28,6 GHz and 29,5 GHz to 30 GHz bands: epfd limits given in Article 22 of the ITU Radio Regulations [i.6] apply for the ESOMPs operating with the NGSO system for the protection of the GSO networks (see No 22.5D of the ITU RR).
- ESOMP operating in the 28,6 GHz to 29,1 GHz band: No 9.11A of the ITU RR applies to the NGSO network of the ESOMP, meaning that the NGSO will be required to coordinate with earlier filed GSO networks or NGSO systems (See No. 5.523A of the ITU RR).

The present document applies to the ESOMP with its ancillary equipment and its various telecommunication ports, and when operated within the boundary limits of the operational environmental profile as declared by the applicant and when installed as required by the applicant's declaration or in the user documentation.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive) article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

NOTE 1: Operational requirements are defined by national administrations and by relevant ECC Decisions.

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of Article 3 of the Directive 1999/5/EC [i.2] (R&TTE Directive) may apply to equipment within the scope of the present document.

NOTE 2: A list of such ENs is included on the web site <http://www.newapproach.org/>.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [2] ETSI TR 102 273 (all parts) (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [3] ANSI C63.5 (2006): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".
- [4] CISPR 16-1-1 Ed.3.0 (2010): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".
- [5] CISPR 16-1-4 Ed.3.0 (2010): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Antennas and test sites for radiated disturbance measurements".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the Radio & Telecommunication Terminal Equipment Directive 1999/5/EC (R&TTE) and a first guide on the impact of the Radio Equipment Directive 2014/53/EU (RED) on Harmonized Standards".
- [i.4] ETSI TS 103 052: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [i.5] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.6] ITU Radio Regulations (edition 2012).
- [i.7] ETSI EN 303 978 (V1.1.2): "Satellite Earth Stations and Systems (SES); Harmonized EN for Earth Stations on Mobile Platforms (ESOMP) transmitting towards satellites in geostationary orbit in the 27,5 GHz to 30,0 GHz frequency bands covering the essential requirements of article 3.2 of the R&TTE Directive".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 1999/5/EC [i.2] and the following apply:

ancillary equipment: equipment used in connection with an ESOMP

NOTE: Equipment is considered as ancillary if the three following conditions are met:

- the equipment is intended for use in conjunction with the ESOMP to provide additional operational and/or control features (e.g. to extend control to another position or location); and
- the equipment cannot be used on a stand alone basis, to provide user functions independently of the ESOMP; and
- the absence of the equipment does not inhibit the operation of the ESOMP.

antenna controller: equipment used to maintain antenna stabilization and tracking accuracy based on inputs from the Control and Monitoring Function

applicant: manufacturer or his authorized representative within the European Community or the person responsible for placing the apparatus on the market

carrier-off radio state: radio state in which the ESOMP may transmit and does not transmit any carrier

NOTE 1: The phrase "the ESOMP may transmit" means that all the conditions for transmission are satisfied (e.g. in a state where transmissions are permitted, no failure detected, and the ESOMP is correctly pointed towards the satellite).

NOTE 2: The existence of a "Carrier-off" radio state depends on the system of transmission used. For ESOMPs designed for continuous transmission mode there may be no "Carrier-off" state.

carrier-on radio state: radio state in which the ESOMP may transmit and transmits a carrier

Control Channel (CC): channel or channels by which ESOMPs receive control information from the NCF

EIRP_{Aggregate}: the sum of the EIRP (Watts) within the nominated bandwidth of the ESOMP network

EIRP_{max}: maximum EIRP capability of the ESOMP as declared by the applicant

emissions disabled radio state: radio state in which the ESOMP shall not emit

NOTE: Examples of cases where the ESOMP is in this radio state: before system monitoring pass, before the control channel is received, when a failure is detected, when an ESOMP is commanded to disable, and when the ESOMP is in a location requiring cessation of emissions.

equivalent power flux density: as defined in the ITU Radio Regulations footnote 22.5C.1, the sum of the power flux-densities produced at a geostationary-satellite system receive station on the Earth's surface or in the geostationary orbit, as appropriate, by all the transmit stations within a non-geostationary-satellite system, taking into account the off-axis discrimination of a reference receiving antenna assumed to be pointing in its nominal direction

external control channel: control channel which is either:

- (i) carried by the ESOMP network via the same or another satellite, but not within the internal protocol of the ESOMP system; or
- (ii) carried by any other radio communication system

external response channel: response channel which is either:

- (i) carried by the ESOMP network via the same or another satellite, but not within the internal protocol of the ESOMP system; or
- (ii) carried by any other radio communication system

integral antenna: antenna which may not be removed during the tests according to the applicant's statement

internal control channel: control channel which is carried by the ESOMP network via the same satellite as used for transmission of user data and within the internal protocol structure of the ESOMP system

internal response channel: response channel which is carried by the ESOMP network via the same satellite as used for transmission of user data and within the internal protocol structure of the ESOMP system

mobile platform: any non-stationary platform such as a train, a vessel, an aircraft or other vehicles

Network Control Facility (NCF): set of functional entities that, at system level, monitor and control the correct operation of the ESOMP and, if appropriate, all of the ESOMPs in a network

nominated bandwidth: bandwidth of the ESOMP radio frequency transmission nominated by the applicant

NOTE 1: The nominated bandwidth is centred on the transmit frequency and does not exceed 5 times the occupied bandwidth.

NOTE 2: The nominated bandwidth is wide enough to encompass all spectral elements of the transmission which have a level greater than the specified spurious radiation limits. The nominated bandwidth is wide enough to take account of the transmit carrier frequency stability. This definition is chosen to allow flexibility regarding adjacent channel interference levels which will be taken into account by operational procedures depending on the exact transponder carrier assignment situation.

occupied bandwidth (Bo):

- for a digital modulation scheme: the width of the signal spectrum 10 dB below the maximum in-band density;
- for an analogue modulation scheme: the width of a frequency band such that, below the lower and above the upper frequency limits, the mean power emitted is equal to 0,5 % of the total mean power of the emission

off-axis angle: angle between the direction of the axis of the antenna main beam and the considered direction

removable antenna: antenna which may be removed during the tests according to the applicant's statement

Response Channel (RC): channel by which ESOMP transmit monitoring information to the NCF

spurious radiation: any radiation outside the nominated bandwidth

transmission disabled state: radio state in which the ESOMP is not authorized to transmit by the NCF

transmission enabled state: radio state in which the ESOMP is authorized to transmit by the NCF

3.2 Symbols

For the purposes of the present document, the following symbols apply:

dBi	ratio of an antenna gain to the gain of an isotropic antenna, expressed in decibels
dBW	ratio of a power to 1 watt, expressed in decibels
dBpW	ratio of a power to 1 picowatt, expressed in decibels
dB μ V/m	ratio of an electric field to 1 μ V/m, expressed in decibels ($20 \cdot \log(\text{electric field} / 1 \mu\text{V/m})$)

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BDC	Block Down Converter
Bo	occupied Bandwidth
BUC	Block Up Converter
CC	Control Channel
CCF	Control Channel reception Failure
CCR	Control Channel correctly Received
CENR	Cessation of Emissions Not Required
CEPT	Conférence Européenne des Postes et Télécommunications (European Conference of Postal and Telecommunications)
CER	Cessation of Emissions Required
CISPR	Comité International Spécial des Perturbations Radioélectriques (International Special Committee on Radio Interference)
CMF	Control and Monitoring Functions
DC	Direct Current
ECC	Electronic Communications Committee (of CEPT)
EEA	European Economic Area
EIA	Electronic Industries Alliance
EIRP	Equivalent Isotropically Radiated Power
EMC	Electro-Magnetic Compatibility
epfd	equivalent power flux-density
epfd \uparrow	Uplink equivalent power flux-density
ESOMP	Earth Station On Mobile Platform
EUT	Equipment Under Test
FEC	Forward Error Correction
FSS	Fixed Satellite Service
GSO	Geostationary Satellite Orbit
HPA	High Power Amplifier
IEC	International Electrotechnical Commission
IPR	Intellectual Property Rights
LNA	Low Noise Amplifier