
**Textile machinery and accessories —
Beams for winding —**

Part 4:

**Test methods and quality classification of
flanges for weaver's beams, warper's
beams and sectional beams**

iTeh STANDARD PREVIEW

(standards.iteh.ai)

Matériel pour l'industrie textile — Ensembles pour enroulement —

*Partie 4: Méthodes d'essai et classes de qualité pour les joues
d'ensembles de tissage, d'ourdissiers et sectionnelles*

ISO 8116-4:2008

<https://standards.iteh.ai/catalog/standards/sist/4cda75dd-4a40-4703-90a1-66a6e5f1cedc/iso-8116-4-2008>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 8116-4:2008

<https://standards.iteh.ai/catalog/standards/sist/4cda75dd-4a40-4703-90a1-66a6e5f1cedc/iso-8116-4-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 8116-4 was prepared by Technical Committee ISO/TC 72, *Textile machinery and accessories*, Subcommittee SC 3, *Machinery for fabric manufacturing including preparatory machinery and accessories*.

This third edition cancels and replaces the second edition (ISO 8116-4:1995), which has been technically revised.

ISO 8116 consists of the following parts, under the general title *Textile machinery and accessories — Beams for winding*:

- ISO 8116-4:2008**
<https://standards.iteh.ai/catalog/standards/sist/4cda75dd-4a40-4703-90a1-66a6e5f1cedc/iso-8116-4-2008>
- *Part 1: General vocabulary*
 - *Part 2: Warper's beams*
 - *Part 3: Weaver's beams*
 - *Part 4: Test methods and quality classification of flanges for weaver's beams, warper's beams and sectional beams*
 - *Part 5: Sectional beams for warp knitting machines*
 - *Part 6: Beams for ribbon weaving and ribbon knitting*
 - *Part 7: Beams for dyeing slivers, rovings and yarns*
 - *Part 8: Definitions of run-out tolerances and methods of measurement*
 - *Part 9: Dyeing beams for textile fabrics*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 8116-4:2008

<https://standards.iteh.ai/catalog/standards/sist/4cda75dd-4a40-4703-90a1-66a6e5f1cedc/iso-8116-4-2008>

Textile machinery and accessories — Beams for winding —

Part 4:

Test methods and quality classification of flanges for weaver's beams, warper's beams and sectional beams

1 Scope

This part of ISO 8116 specifies the test procedure for flanges for weaver's beams, warper's beams and sectional beams and the quality classes in this respect.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8116-1, *Textile machinery and accessories — Beams for winding — Part 1: General vocabulary*

ISO 8116-2:2008, *Textile machinery and accessories — Beams for winding — Part 2: Warper's beams*

ISO 8116-3, *Textile machinery and accessories — Beams for winding — Part 3: Weaver's beams*

ISO 8116-5:2008, *Textile machinery and accessories — Beams for winding — Part 5: Sectional beams for warp knitting machines*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8116-1 and the following apply.

3.1

quality class

classification of beam flanges according to their deformation behaviour under load

3.2

maximum test load

F_{\max}

maximum value of load applied to the beam flange during testing according to its quality class

4 Quality classification

Beam flanges are classified according to four quality classes. The designation of the quality classes is Q1, Q2, Q3 or Q4.

Depending on the quality class, the beam flanges are loaded with different ultimate loads. These limit values are given in Clause 6.

For examples of application by quality class, see Annex A.

5 Test methods

5.1 Principle

The beam flange is subjected to a test load and the resulting deformation is measured.

For weaver's beams, the test load is applied to the flange via a beam barrel. For warper's beams and sectional beams, the load is applied to the beam flange via a pressure plate. A pressure ring with a defined inner diameter is used as an anvil.

The permanent deformation and the plastic deformation of the flange shall not exceed the defined limit values when the maximum load is applied.

5.2 Apparatus

5.2.1 Press device, with indications for the application of the test load.

5.2.2 Three dial gauges, for determination of deformation of the flange with an accuracy of 0,01 mm.

5.2.3 Measurement device, for joint installation of the three dial gauges on the bearing device, in an angle of 120° each.

5.2.4 Steel pressure ring.

5.2.5 Beam barrel, for load application (for weaver's beams).

5.2.6 Pressure plate, for load application (for warper's beams and sectional beams).


5.3 Testing configuration

ISO 8116-4:2008

<https://standards.iteh.ai/catalog/standards/sist/4cda75dd-4a40-4703-90a1-30da393e31e8>

For measurement of flange deformation, three dial gauges are installed on the bearing device by means of the measurement device. These are used to measure the relative path between the outer diameter of the beam barrel d_2 and the circle diameter $d_1 - 20$ mm. The dial gauges are staggered by 120°. The testing configuration for weaver's beams is given in Figure 1. The testing configurations for warper's beams are given in Figure 2 and Figure 3. The testing configuration for sectional beams is given in Figure 4.

Dimensions in millimetres



Key

- | | |
|---|--|
| 1 dial gauge (schematic representation) | d_1 outer diameter of weaver's beam flange |
| 2 beam barrel | d_2 outer diameter of weaver's beam barrel |
| 3 threaded ring | D_i inner diameter of pressure ring |
| 4 weaver's beam | |
| 5 steel pressure ring | |


iTeh STANDARD PREVIEW

Figure 1 — Testing configuration for weaver's beam

ISO 8116-4:2008

<https://standards.iteh.ai/catalog/standards/sist/4cda75dd-4a40-4703-90a1-66a6e5f1cedc/iso-8116-4-2008>

Dimensions in millimetres




Key

- | | |
|---|--|
| 1 dial gauge (schematic representation) | d_1 outer diameter of warper's beam flange |
| 2 pressure plate | d_2 outer diameter of warper's beam barrel |
| 3 warper's beam | D_i inner diameter of pressure ring |
| 4 steel pressure ring | |
| 5 warper's beam barrel (not required for pressure test) | |

Figure 2 — Testing configuration for warper's beam flange with shaft (Type A) and cylindrical hole (Type B)

The diameter of the pressure plate for load application for warper's beams of Type A and Type B is defined as $d_2 - 20$ mm (see Figure 2).



Key

- | | | | |
|---|---|-------|--|
| 1 | dial gauge (schematic representation) | d_1 | outer diameter of warper's beam flange |
| 2 | pressure plate | d_2 | outer diameter of warper's beam barrel |
| 3 | warper's beam flange | D_1 | inner diameter of pressure ring |
| 4 | steel pressure ring | | |
| 5 | warper's beam barrel (not required for pressure test) | | |

iTeh STANDARD PREVIEW
(standards.iteh.ai)


ISO 8116-4:2008

<https://standards.iteh.ai/catalog/standards/sist/4cda75dd-4a40-4703-90a1-66a6e5f1cedc/iso-8116-4-2008>

Figure 3 — Testing configuration for warper's beam flange with tooth cone — Type C

The diameter of the pressure plate for load application for warper's beams with tooth cone (Type C) is defined using d_5 in accordance with ISO 8116-2:2008, Table 2.

Dimensions in millimetres

**Key**

- | | |
|--|--|
| 1 dial gauge (schematic representation) | d_1 outer diameter of sectional beam flange |
| 2 pressure plate | d_2 outer diameter of sectional beam barrel |
| 3 sectional beam flange | d_3 bore diameter of flange (see also ISO 8116-5:2008, Figure 1) |
| 4 steel pressure ring | D_i inner diameter of pressure ring |
| 5 sectional beam barrel (not required for pressure test) | |

Figure 4 — Testing configuration for sectional beams

The diameter of the pressure plate for load application for sectional beams of knitting machines is defined using $d_3 + 40$ mm.

5.4 Performance

The measurement device is installed as described in 5.3. The beam flange, the pressure ring and the pressure plate, if required, are aligned centrally below the press loading pad.

Stepwise loading of the flange shall occur in steps to be chosen usefully.

The load applied and the deformation are determined at the test area for each loading step. The value of the total deformation is calculated from the average of the three measurement values. After each load step, unloading of the flange is optional.

After unloading, the values indicated are read with the dial gauge. The values for the plastic deformation are calculated from the average of the three measurement values.

Then loading is applied with the next higher load value.

This procedure is repeated until the defined maximum test load of the corresponding quality class as given in Equation (2) and Table 1 is reached.

The beam flange corresponds to the quality class if the value measured for the total deformation and the value measured for the plastic deformation are below the values obtained when using Equation (3) and Equation (4).