



SLOVENSKI STANDARD
SIST ISO 1224-1:2008

01-julij-2008

BUXca Yý U
SIST ISO 1224:2001

?cHUb]`YýU]!'BUHUb b]`YýU]`nU]bgHfi a YbHY!'%rXY.'Ni bUb`Y`a YfYžhc`YfUbWV]b
_UfU_hYf]gh]_Y`nU`YýU`Y`n`a Yf] b]a]`a YfUa]

Rolling bearings - Instrument precision bearings - Part 1: Boundary dimensions, tolerances and characteristics of metric series bearings

ITEH STANDARD PREVIEW
(standards.iteh.ai)

Wälzlager - Präzisionslager für Instrumente - Teil 1: Grenzmaße und Toleranzen für Lager einer metrischen Reihe

[SIST ISO 1224-1:2008](https://standards.iteh.ai/catalog/standards/sist/4632c7ba-5a22-4ef5-98f5-)

<https://standards.iteh.ai/catalog/standards/sist/4632c7ba-5a22-4ef5-98f5->

Roulements - Roulements de précision pour instruments - Partie 1: Dimensions d'encombrement, tolérances et caractéristiques, séries métriques

Ta slovenski standard je istoveten z: ISO 1224-1:2007

ICS:

21.100.20 Kotalni ležaji Rolling bearings

SIST ISO 1224-1:2008 **en,fr**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 1224-1:2008

<https://standards.iteh.ai/catalog/standards/sist/4632c7ba-5a22-4ef5-98f5-672ef35aa1a6/sist-iso-1224-1-2008>

**Rolling bearings — Instrument precision
bearings —**

Part 1:

**Boundary dimensions, tolerances and
characteristics of metric series bearings**

iTeh STANDARD PREVIEW
Roulements — Roulements de précision pour instruments —
(standards.iteh.ai) *Partie 1: Dimensions d'encombrement, tolérances et caractéristiques,*
séries métriques

SIST ISO 1224-1:2008

<https://standards.iteh.ai/catalog/standards/sist/4632c7ba-5a22-4ef5-98f5-672ef35aa1a6/sist-iso-1224-1-2008>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 1224-1:2008

<https://standards.iteh.ai/catalog/standards/sist/4632c7ba-5a22-4ef5-98f5-672ef35aa1a6/sist-iso-1224-1-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Symbols	2
5 Characteristics	4
6 Bearing types	4
7 Boundary dimensions	5
8 Tolerances	7
8.1 Tolerance class 5A	7
8.2 Tolerance class 4A	8
9 Radial internal clearance	9
10 Bore and outside diameter classification	9
11 Torque test conditions	9
11.1 General.....	9
11.2 Test conditions	9
11.3 Correlation of test results on different types of test equipment	10
12 Limitations of bearing yield rates	10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 1224-1 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*.

This first edition of ISO 1224-1, together with ISO 1224-2, cancels and replaces ISO 1224:1984, which has been technically revised.

ISO 1224 consists of the following parts, under the general title *Rolling bearings — Instrument precision bearings*:

- SIST ISO 1224-1:2008
<https://standards.iteh.ai/catalog/standards/sist/4632c7ba-5a22-4e05-985-672e35aa1a6/sist-iso-1224-1-2008>
- *Part 1: Boundary dimensions, tolerances and characteristics of metric series bearings*
 - *Part 2: Boundary dimensions, tolerances and characteristics of inch series bearings*

Rolling bearings — Instrument precision bearings —

Part 1: Boundary dimensions, tolerances and characteristics of metric series bearings

1 Scope

This part of ISO 1224 specifies the characteristics that define instrument precision rolling bearings, metric series, their types, boundary dimensions, tolerances and internal clearance, classifications used for selective assembly, torque definitions and test condition, and limitations of bearing yield rates.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15, *Rolling bearings — Radial bearings — Boundary dimensions, general plan*

ISO 582, *Rolling bearings — Chamfer dimensions — Maximum values*

ISO 1132-1, *Rolling bearings — Tolerances — Part 1: Terms and definitions*

ISO 5593:1997, *Rolling bearings — Vocabulary*

ISO 15241, *Rolling bearings — Symbols for quantities*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1132-1, ISO 5593 and the following apply.

3.1

perpendicularity of inner ring bore with respect to the face

⟨basically cylindrical surface⟩ total variation of the relative position, in a radial direction parallel with the plane tangential to the reference face of the inner ring, of points on the same generatrix of the bore at a distance from the side faces of the ring equal to 1,2 times the largest axial single chamfer dimension

3.2

axial runout of outer ring flange back face of assembled bearing

⟨radial groove ball bearing⟩ difference between the largest and the smallest of the axial distances between the back face of the outer ring flange, in different angular positions of this ring, at a radial distance from the outer ring axis equal to half the mean diameter of the flange back face, and a point in a fixed position relative to the inner ring

NOTE For a measurement to be valid, the inner and outer ring raceways shall be in contact with all the balls.

3.3 torque quality

torque quality of an instrument ball bearing is a function of average and maximum torques

NOTE Maximum torque is most frequently specified for slow speed (near zero) applications and for limited arcs of travel. Where considerable rotation is involved, average torque may be the criterion.

3.4 maximum torque

maximum value of torque recorded during any test cycle

3.5 average torque

arithmetic mean value of the torque readings obtained during the test cycle

3.6 test load

specified axial load coincident with the axis of rotation of the bearing

4 Symbols

For the purposes of this document, the symbols given in ISO 15241 and the following apply.

The symbols (except those for tolerances) shown in Figure 1 and the values given in the Tables 1 to 6 denote nominal dimensions unless specified otherwise.

B	inner ring width
C	outer ring width
C_1	outer ring flange width
D	outside diameter of bearing
D_1	outside diameter of outer ring flange
d	bore diameter
K_{ea}	radial runout of outer ring of assembled bearing
K_{ia}	radial runout of inner ring of assembled bearing
r	chamfer dimension (except where r_1 is applicable)
$r_{s \min}$	smallest single chamfer dimension of r
$r_{s \max}$	largest single chamfer dimension of r
r_1	chamfer dimension of front face of angular contact ball bearing inner and outer rings
$r_{1s \min}$	smallest single chamfer dimension of r_1
S_D	perpendicularity of outer ring outside surface with respect to the face ¹⁾
S_d	perpendicularity of inner ring face with respect to the bore ¹⁾
S_{dr}	perpendicularity of inner ring bore with respect to the face ¹⁾

S_{ea}	axial runout of outer ring of assembled bearing ¹⁾
S_{ea1}	axial runout of outer ring flange back face of assembled bearing ¹⁾
S_{ia}	axial runout of inner ring of assembled bearing ¹⁾
V_{Bs}	variation of inner ring width
V_{Cs}	variation of outer ring width
V_{C1s}	variation of outer ring flange width
V_{Dmp}	variation of mean outside diameter
V_{Dsp}	variation of outside diameter in a single plane
V_{dmp}	variation of mean bore diameter
V_{dsp}	variation of bore diameter in a single plane
Δ_{Bs}	deviation of a single inner ring width
Δ_{Cs}	deviation of a single outer ring width
Δ_{C1s}	deviation of a single outer ring flange width
Δ_{Dmp}	deviation of mean outside diameter in a single plane
Δ_{Ds}	deviation of a single outside diameter
Δ_{D1s}	deviation of a single outside diameter of outer ring flange
Δ_{dmp}	deviation of mean bore diameter in a single plane
Δ_{ds}	deviation of a single bore diameter

1) For angular contact ball bearings, the back face is the reference face.