



SLOVENSKI STANDARD
oSIST prEN 303 258 V1.0.6:2018
01-marec-2018

Industrijske brezžične komunikacije (WIA) - Oprema, ki deluje v frekvenčnem območju od 5725 MHz do 5875 MHz z močnostnimi nivoji do največ 400 mW - Harmonizirani standard za dostop do radijskega spektra

Wireless Industrial Applications (WIA) - Equipment operating in the 5 725 MHz to 5 875 MHz frequency range with power levels ranging up to 400 mW - Harmonised Standard for access to radio spectrum

Ta slovenski standard je istoveten z: ETSI EN 303 258 V1.0.6 (2018-01)

ICS:

33.060.01	Radijske komunikacije na splošno	Radiocommunications in general
-----------	----------------------------------	--------------------------------

oSIST prEN 303 258 V1.0.6:2018	en
---------------------------------------	-----------

Draft ETSI EN 303 258 V1.0.6 (2018-01)



**Wireless Industrial Applications (WIA);
Equipment operating in the 5 725 MHz to 5 875 MHz
frequency range with power levels ranging up to 400 mW;
Harmonised Standard for access to radio spectrum**

Reference

DEN/ERM-TG41-003

Keywords

harmonised standard, radio, regulation, spread spectrum, SRD, testing, transmission

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
Introduction	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	11
3.3 Abbreviations	12
4 Technical requirements specifications	13
4.1 Environmental profile.....	13
4.2 Conformance requirements	13
4.2.1 RF output power and Adaptive Power Control.....	13
4.2.1.1 Definitions.....	13
4.2.1.1.1 RF Output Power	13
4.2.1.1.2 Adaptive Power Control	13
4.2.1.2 Limits	13
4.2.1.2.1 General requirements.....	13
4.2.1.2.2 Limits for RF output power and APC range.....	13
4.2.1.3 Conformance	13
4.2.2 Occupied channel bandwidth.....	14
4.2.2.1 Definition	14
4.2.2.2 Limits	14
4.2.2.3 Conformance	14
4.2.3 Transmitter unwanted emissions in the spurious domain	14
4.2.3.1 Definition	14
4.2.3.2 Limits	14
4.2.3.3 Conformance	14
4.2.4 Receiver spurious emissions	15
4.2.4.1 Definition	15
4.2.4.2 Limits	15
4.2.4.3 Conformance	15
4.2.5 Receiver Blocking	15
4.2.5.1 Applicability.....	15
4.2.5.2 Definition	15
4.2.5.3 Performance Criteria	15
4.2.5.4 Limits	16
4.2.5.5 Conformance.....	16
4.2.6 Dynamic Frequency Selection	16
4.2.6.1 General DFS operation.....	16
4.2.6.1.1 Applicability	16
4.2.6.1.2 General requirements.....	16
4.2.6.1.3 Applicable frequency range.....	16
4.2.6.1.4 DFS operational modes	16
4.2.6.1.5 DFS operation.....	17
4.2.6.1.6 Point to point or multipoint links.....	17
4.2.6.2 DFS technical requirements specifications	18
4.2.6.2.1 Applicability	18
4.2.6.2.2 In-Service Monitoring	18
4.2.6.2.3 Channel Shutdown.....	18
4.2.6.2.4 Non-Occupancy Period	19

4.2.7	Adaptive Channel Access Mechanism.....	19
4.2.7.1	Overview.....	19
4.2.7.1.1	General requirements.....	19
4.2.7.1.2	Applicability.....	20
4.2.7.1.3	Applicable frequency range.....	20
4.2.7.2	Principle for Detect and Avoid (DAA).....	20
4.2.7.3	DAA technical requirements specifications except ITS and TTT.....	20
4.2.7.3.1	Minimum Tx-off time.....	20
4.2.7.3.2	DAA minimum listening time.....	20
4.2.7.3.3	Maximum transmitter on-time.....	21
4.2.7.4	DAA technical requirements specifications for ITS.....	22
4.2.7.4.1	General.....	22
4.2.7.4.2	Applicable frequency range.....	22
4.2.7.4.3	ITS Channel Availability Check time.....	22
4.2.7.4.4	<i>ITS Maximum TX_{on}-time</i>	22
4.2.7.4.5	<i>ITS Minimum TX_{off}-time</i>	23
4.2.7.4.6	<i>ITS DAA latency</i>	23
4.2.7.4.7	<i>ITS DAA Probability</i>	23
4.2.7.4.8	<i>ITS Non-Occupancy Period</i>	24
4.2.7.4.9	<i>ITS DAA threshold</i>	24
4.2.7.5	DAA technical requirements specifications for TTT, general conditions and applicable frequency range.....	24
4.2.7.6	DAA using TTT signal detection.....	25
4.2.7.6.1	General.....	25
4.2.7.6.2	DAA threshold for TTT.....	25
4.2.7.6.3	TTT Channel Availability Check.....	25
4.2.7.6.4	<i>TTT Non-Occupancy Period</i>	26
4.2.7.6.5	<i>TTT DAA Latency</i>	26
4.2.7.6.6	<i>TTT In-Service Monitoring</i>	26
4.2.7.7	Declaration of DAA parameters except ITS and TTT.....	26
4.2.7.7.1	General.....	26
4.2.7.7.2	Limits.....	27
4.2.7.7.3	Conformance.....	27
4.2.8	User Access Restrictions.....	27
4.2.8.1	Definition.....	27
4.2.8.2	Requirement.....	27
4.2.9	Geo-localization capability.....	27
4.2.9.1	Applicability.....	27
4.2.9.2	Definition.....	28
4.2.9.3	Requirements.....	28
4.2.9.4	Conformance.....	28
4.2.10	TTT Detection and Avoidance using a Geolocation Database.....	28
4.2.10.1	Applicability.....	28
4.2.10.2	Definition.....	28
4.2.10.3	Requirements.....	28
4.2.10.4	Conformance.....	29
5	Testing for compliance with technical requirements.....	29
5.1	Environmental conditions for testing.....	29
5.1.1	General requirements.....	29
5.1.2	Normal and extreme test conditions.....	29
5.1.3	Test sequences and traffic load.....	29
5.1.3.1	General test transmission sequences.....	29
5.1.3.2	Test transmission sequences for DFS tests.....	30
5.1.4	Test channels.....	30
5.1.5	Antennas.....	30
5.1.5.1	Integrated and dedicated antennas.....	30
5.1.5.2	Transmit operating modes.....	31
5.1.5.2.1	Operating mode 1 (single antenna).....	31
5.1.5.2.2	Operating mode 2 (multiple antennas, no beamforming).....	31
5.1.5.2.3	Operating mode 3 (multiple antennas, with beamforming).....	31
5.2	Interpretation of the measurement results.....	31

5.3	Conformance tests	32
5.3.1	Product information	32
5.3.2	RF output power and Adaptive Power Control	33
5.3.2.1	Test conditions	33
5.3.2.2	Test method	33
5.3.2.2.1	Conducted measurement	33
5.3.2.2.2	Radiated measurement	35
5.3.3	Occupied Channel Bandwidth	35
5.3.3.1	Test conditions	35
5.3.3.2	Test method	36
5.3.3.2.1	Conducted measurement	36
5.3.3.2.2	Radiated measurement	36
5.3.4	Transmitter unwanted emissions outside the 5,8 GHz WIA band	37
5.3.4.1	Test conditions	37
5.3.4.2	Test method	37
5.3.4.2.1	Conducted measurement	37
5.3.4.2.2	Radiated measurement	39
5.3.5	Receiver spurious emissions	39
5.3.5.1	Test conditions	39
5.3.5.2	Test method	40
5.3.5.2.1	Conducted measurement	40
5.3.5.2.2	Radiated measurement	42
5.3.6	Receiver Blocking	42
5.3.6.1	Test frequencies	42
5.3.6.2	Test conditions	42
5.3.6.3	Test Method	42
5.3.6.3.1	Conducted measurements	42
5.3.6.3.2	Radiated measurements	43
5.3.7	Dynamic Frequency Selection	44
5.3.7.1	Test conditions	44
5.3.7.1.1	General requirements	44
5.3.7.1.2	Selection of radar test signals	44
5.3.7.1.3	Test set-ups	44
5.3.7.2	Test method	46
5.3.7.2.1	Conducted measurement	46
5.3.7.2.2	Radiated measurement	48
5.3.8	Adaptivity (channel access mechanism) except for ITS and TTT	48
5.3.8.1	Test conditions	48
5.3.8.2	Test method	48
5.3.8.2.1	Conducted measurements	48
5.3.8.2.2	Generic test procedure for measuring channel/frequency usage	50
5.3.8.2.3	Radiated measurements	50
5.3.9	Adaptivity (channel access mechanism) for ITS	51
5.3.9.1	General requirements	51
5.3.9.2	ITS test signal	51
5.3.9.3	Initial start-up test	51
5.3.9.3.1	Start-up procedure	51
5.3.9.3.2	Test without an ITS victim test signal during the <i>ITS Channel Availability Check time</i> , $T_{ITS_check_time}$	51
5.3.9.3.3	Test with an ITS victim test signal during the <i>ITS Channel Availability Check time</i> , $T_{ITS_check_time}$	52
5.3.9.4	Test of $ITS_Maximum_TX_{on}$ and $ITS_minimum_TX_{off}$	53
5.3.9.5	ITS in-service DAA test with continuous ITS test signal	53
5.3.9.6	ITS in-service DAA test with ITS test signal switched off after detection	54
5.3.10	Adaptivity (channel access mechanism) for TTT	55
5.3.10.1	General	55
5.3.10.2	TTT test signal	55
5.3.10.3	Initial start-up test	56
5.3.10.3.1	Start-up procedure	56
5.3.10.3.2	Test without a TTT victim test signal during the <i>TTT Channel Availability Check time</i> , $T_{TTT_check_time}$	56
5.3.10.3.3	Test with a TTT victim test signal during the <i>TTT Channel Availability Check time</i>	56

5.3.10.4	TTT in-service DAA test with continuous TTT test signal.....	57
5.3.10.5	TTT in-service DAA test with TTT test signal switched off after detection.....	58
5.3.10.6	TTT DAA using a Geolocation Database	59
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	60
Annex B (normative):	Test sites and arrangements for radiated measurements.....	62
B.1	General requirements	62
B.2	Radiation test sites.....	62
B.2.1	Open Area Test Site	62
B.2.2	Semi Anechoic Room.....	63
B.2.3	Fully Anechoic Room	64
B.2.4	Measurement Distance	65
B.3	Antennas.....	66
B.3.1	General requirements	66
B.3.2	Measurement antenna.....	66
B.3.3	Substitution antenna	66
B.4	Test fixture	66
B.4.1	General requirements	66
B.4.2	Description of the test fixture.....	67
B.4.3	Using the test fixture for relative measurements	67
B.5	Guidance on the use of radiation test sites	67
B.5.1	General requirements	67
B.5.2	Power supplies for the battery powered UUT	67
B.5.3	Site preparation	68
B.6	Coupling of signals.....	68
B.6.1	General requirements	68
B.6.2	Data Signals.....	68
B.7	Interference Signal used for Adaptivity Tests	69
Annex C (normative):	Procedures for radiated measurements.....	70
C.1	General requirements	70
C.2	Radiated measurements in an OATS or SAR.....	70
C.3	Radiated measurements in a FAR	71
C.4	Substitution measurement	71
C.5	Guidance for testing technical requirements	71
C.5.1	Conformance tests and corresponding test sites	71
C.5.2	Guidance for testing Adaptivity (Channel Access Mechanism).....	71
C.5.2.1	General requirements.....	71
C.5.2.2	Measurement Set-up	72
C.5.2.3	Calibration of the measurement Set-up.....	72
C.5.2.4	Test method	72
Annex D (normative):	DFS parameters	73
D.1	Test signals.....	73
Annex E (informative):	Bibliography.....	76
Annex F (informative):	Change History	77
History		78