



TECHNICAL SPECIFICATION

**Integrated broadband cable
telecommunication networks (CABLE);
Testing; Conformance test specifications
for MAP-E technology;
Part 2: Test Suite Structure and Test Purposes (TSS&TP)**

ETSI STANDARD PREVIEW
https://standards.its.europecable.org/standards/38a0db5f-1d4f-400f-acc4-07ca10000000/etsi-ts-103-239-2-v1.1.1-14

Reference

DTS/CABLE-00012-2

Keywords

IP, IPv6, transition, TSS&TP

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	5
3 Abbreviations	5
4 Test Suite Structure	6
5 Test Purposes (TP)	6
5.1 TPs for BR.....	7
5.1.1 Basic Function	7
5.1.2 Address Structure.....	8
5.1.3 Session Control.....	9
5.1.4 Anycast Addressing	10
5.1.5 MSS Clamping.....	10
5.1.6 Fragmentation	11
5.2 TPs for CPE.....	11
5.2.1 Gateway Assignment	11
5.2.2 Basic Function	12
5.2.3 Address Structure.....	13
5.2.4 Fragmentaton	13
5.2.5 MSS Clamping.....	14
5.2.6 Session Control.....	14
Annex A (informative): Bibliography.....	15
History	16

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Integrated broadband cable telecommunication networks (CABLE).

This present document produced for the transition technologies accommodates an urgent need in the industry to define requirements that enable seamless transition of Cable Networks to IPv6. Considering the depletion of IPv4 addresses, transition to IPv6 is required in order to enable continued growth of the customer base connected to Cable Networks and ensure service continuity for existing and new customers. High-quality connectivity to all kinds of IP-based services and networks is essential in today's business and private life.

A plethora of transition technologies have been proposed in IETF, other standardization organizations and by manufacturers of IP technology to allow coexistence of IPv4 and IPv6 hosts, access and core networks as well as services. Each of these technology options is specified, implemented and deployed in various forms and stages. The present document is based on the requirements of ETSI TS 101 569-1 [1].

The present document is part 2 of a multi-part deliverable covering the conformance test specification for MAP-E technology, as identified below:

- Part 1: "Protocol Implementation Conformance Statement (PICS) proforma";
- Part 2: "Test Suite Structure and Test Purposes (TSS&TP)";**
- Part 3: "Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**may not**", "**need**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document provides the Test Suite Structure and Test Purposes (TSS&TP) descriptions for the IPv6 transition technology MAP-E to validate its implementation within a cable communications networks.

The tests are in reference to ETSI TS 101 569-1 [1], the ETSI specification for IPv6 transition technology.

The ISO standards for the methodology of conformance testing (ISO/IEC 9646-1 [i.1] and ISO/IEC 9646-2 [i.2]) as well as the ETSI rules for conformance testing (ETSI ETS 300 406 [i.3]) are used as a basis for the test methodology.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 101 569-1: "Integrated Broadband Cable Telecommunication Networks (CABLE); Cable Network Transition to IPv6 Part 1; IPv6 Transition Requirements".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ISO/IEC 9646-1 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework-- Part 1: General concepts".
- [i.2] ISO/IEC 9646-2 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 2: Abstract Test Suite specification".
- [i.3] ETSI ETS 300 406 (1995): "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
-

3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATS	Abstract Test Suite
B4	(MAP-E) Basic Bridging BroadBand element
CPE	Customer Premises Equipment
DF bit	Don't Fragment flag (in IPv4 header)
DHCP	Dynamic Host Configuration Protocol
DMR	Default Mapping Rule
DNS	Domain Name System
GW	GateWay
HTML	HyperText Markup Language

ICMP	Internet Control Message Protocol
IP	Internet Protocol
IPv4	IP version 4
IPv6	IP version 6
IUT	Implementation Under Test
LAN	Local Area Network
MAP	Mapping of Address and Port
MAP-E	Mapping of Address and Port Encapsulation mode
MSS	Maximum Segment Size
MTS	Methods for Testing and Specification
MTU	Maximum Transmission Unit
NAT	Network Address Translation/Network Address Translator
PD	Prefix Delegation
PICS	Protocol Implementation Conformance Statement
RA	Router Advertisement
TC	Test Case
TCP	Transmission Control Protocol
TP	Test Purpose

4 Test Suite Structure

The identifier of the TP is built according to table 1 as recommended in the MTS methodologies.

Table 1: TP naming convention for MAP-E

TP/<root>/<gr>/<sgr>/<x>/<nn>		
<root> = root	MAP-E	Mapping of Address and Port – Encapsulation Mode
<gr> = group	BR	Border Relay
<sgr> = sub-group	CPE	Customer Premise Equipment
	GWA	GatewayAssignment
	BF	Basic Function
	AS	Address Structure
	SC	Session Control
	AA	Anycast Addressing
	MSSC	Maximum Segment Size Clamping
	FRAG	Packet Fragmentation
<x> = type of testing	BV	Valid Behaviour tests
<nn> = sequential number		01 to 99
NOTE 1: A sub-group may not apply for all groups.		

5 Test Purposes (TP)

This clause proposes a TP proforma which is used in the present document. The fields of this proforma as used in the present document are explained in table 2.

Table 2: TP proforma field description

TP Header	
TP ID	The TP ID is a unique identifier according to the TP naming conventions in tables *
Test objective	Short description of test purpose objective according to the requirements from the base standard.
Reference	The reference indicates the clauses of the reference standard specifications in which the conformance requirement is expressed.
TP Behaviour	
Initial conditions (optional)	The initial conditions define in which initial state the IUT has to be to apply the actual TP. In the corresponding "Test Case" (TC), when the execution of the initial condition does not succeed, it leads to the assignment of an Inconclusive verdict.
Expected behaviour (TP body)	Definition of the events, which are parts of the TP objective, and the IUT are expected to perform in order to conform to the base specification. In the corresponding TC, " Pass" or "Fail" verdicts can be assigned there.

5.1 TPs for BR

5.1.1 Basic Function

TP Id	TP/MAP-E/BR/BF/BV/01
Test objective	Check that the IUT supports the functionality of MAP-E base NAT mapping
Reference	[1]: clause 6.7.10.7 Feature: Packet Encapsulation
Initial conditions	
with { the IUT being properly provisioned and the interfaces are connected & functional }	
Expected behaviour	
ensure that { when { the IUT receives multiple IPv6 packets containing IPv6 transport header containing source address indicating B4 IPv6 address containing destination address indicating IUT GW IPv6 address containing IPv4 payload containing source address indicating a private IPv4 address containing destination address indicating a public IPv4 address from multiple B4 devices } then { the IUT does a basic NAT mapping for each public IPv6 B4 address sourced and the IUT forwards packets to the destination with different IPv4 public addresses } }	

5.1.2 Address Structure

TP Id	TP/MAP-E/BR/AS/BV/01
Test objective	Check that the IUT supports the functionality of unknown destination response
Reference	[1]: clause 6.7.10.7 Feature: Packet Encapsulation
Initial conditions	
with { the IUT is properly provisioned the interfaces are connected & functional }	
Expected behaviour	
<p>ensure that {</p> <p> when {</p> <p> the IUT receives multiple IPv6 packets containing IPv6 transport header containing source address indicating CPE IPv6 address containing destination address indicating IUT GW IPv6 address containing IPv4 payload containing source address indicating a private IPv4 address containing destination address indicating a public IPv4 address from a single CPE and, the IPv4 destination is unknown by the IUT</p> <p> } then {</p> <p> the IUT responds by sending an ICMPv6 destination unreachable message (Type 1, Code 5) indicating the source address failed ingress/egress policy</p> <p> }</p> <p>}</p>	

TP Id	TP/MAP-E/BR/AS/BV/02
Test objective	Check that the IUT supports dropping of packets using private IPv4 destination addresses
Reference	[1]: clause 6.7.10.7 Feature: Packet Encapsulation
Initial conditions	
with { the IUT is properly provisioned the interfaces are connected & functional }	
Expected behaviour	
<p>ensure that {</p> <p> when {</p> <p> the IUT receives multiple IPv6 packets containing IPv6 transport header containing source address indicating CPE IPv6 address containing destination address indicating IUT GW IPv6 address containing IPv4 payload containing source address indicating a private IPv4 address containing destination address indicating a private IPv4 address from a single CPE</p> <p> } then {</p> <p> the IUT drops the packets</p> <p> }</p> <p>}</p>	

TP Id	TP/MAP-E/BR/AS/BV/03
Test objective	Check that the IUT supports dropping of packets using broadcast IPv4 destination addresses
Reference	[1]: clause 6.7.10.7 Feature: Packet Encapsulation
Initial conditions	
with { the IUT is properly provisioned the interfaces are connected & functional }	
Expected behaviour	
ensure that { when { the IUT receives multiple IPv6 packets containing IPv6 transport header containing source address indicating CPE IPv6 address containing destination address indicating IUT GW IPv6 address containing IPv4 payload containing source address indicating a private IPv4 address containing destination address indicating a broadcast destination address from a single CPE then { the IUT drops the packets } }	

5.1.3 Session Control

TP Id	TP/MAP-E/BR/SC/BV/01
Test objective	Check that the IUT supports session control within port ranges
Reference	[1]: clause 6.7.9.14 Feature: MAP-E Inbound Session control
Initial conditions	
with { the IUT is properly provisioned the interfaces are connected & functional the IUT is configured for a specific port range }	
Expected behaviour	
ensure that { when { the IUT receives multiple IPv6 packets containing IPv6 transport header containing source address indicating CPE IPv6 address containing destination address indicating IUT GW IPv6 address containing IPv4 payload containing source address indicating a private IPv4 address containing destination address indicating a public IPv4 address from a single CPE device then { the IUT port maps to range configured and the IUT forwards the packet correctly } }	