



**Intelligent Transport Systems (ITS);
Radiocommunications equipment operating
in the 5 855 MHz to 5 925 MHz frequency band;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

RELEASEREFERENCE: 4158-be5-7ab81067a3344f121-721d-
<https://standards.iteh.eu/standard/etsi-en-302-571-v2.1.1-2017-02>

Reference

REN/ERM-TG37-024

Keywordsharmonised standard, ITS, radio, regulation,
transport**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD
(Standards.iteh.org)
Full standard:
<http://standards.etsi.org/catalog/standards/sistech/302-571-v2.1.1-2017-02>

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions.....	10
3.2 Symbols.....	10
3.3 Abbreviations	11
4 Technical requirements specifications	11
4.1 Environmental profile.....	11
4.2 Conformance requirements	12
4.2.1 Transmitter frequency stability	12
4.2.1.1 Definition	12
4.2.1.2 Limits	12
4.2.1.3 Conformance	12
4.2.2 RF output power	13
4.2.2.1 Definition	13
4.2.2.2 Limits	13
4.2.2.3 Conformance	13
4.2.3 Power spectral density	13
4.2.3.1 Definition	13
4.2.3.2 Limits	13
4.2.3.3 Conformance	13
4.2.4 Transmit power control	13
4.2.4.1 Definition	13
4.2.4.2 Limits	13
4.2.4.3 Conformance	13
4.2.5 Transmitter unwanted emissions	13
4.2.5.1 Transmitter unwanted emissions outside the 5 GHz ITS frequency band	13
4.2.5.1.1 Definition.....	13
4.2.5.1.2 Limits	14
4.2.5.1.3 Conformance	14
4.2.5.2 Transmitter spectrum mask within the 5 GHz ITS frequency band for 10 MHz channels	15
4.2.5.2.1 Definition.....	15
4.2.5.2.2 Limits	15
4.2.5.2.3 Conformance	15
4.2.6 Receiver spurious emissions	15
4.2.6.1 Definition	15
4.2.6.2 Limits	15
4.2.6.3 Conformance	15
4.2.7 Receiver selectivity.....	16
4.2.7.1 Definition	16
4.2.7.2 Limits	16
4.2.7.3 Conformance	16
4.2.8 Receiver sensitivity.....	16
4.2.8.1 Definition	16
4.2.8.2 Limits	17
4.2.8.3 Conformance	17
4.2.9 Interference mitigation for CEN DSRC and HDR DSRC in the frequency band 5 795 MHz to 5 815 MHz	17
4.2.9.1 Definition	17

4.2.9.2	Limits	17
4.2.9.3	Conformance	17
4.2.10	Decentralized congestion control.....	18
4.2.10.1	Definition	18
4.2.10.2	Limits	18
4.2.10.3	Conformance	18
5	Testing for compliance with technical requirements.....	19
5.1	Environmental conditions for testing	19
5.2	Interpretation of measurement results	19
5.3	Radio test suites.....	19
5.3.1	Product information	19
5.3.2	Transmitter frequency stability	20
5.3.2.1	Test purpose	20
5.3.2.2	Test applicability.....	20
5.3.2.3	Test description	20
5.3.2.3.1	Initial conditions.....	20
5.3.2.3.2	Conducted measurement.....	20
5.3.2.3.3	Radiated measurement.....	21
5.3.2.4	Test requirements	21
5.3.3	RF output power, power spectral density and transmit power control.....	21
5.3.3.1	Test purpose	21
5.3.3.2	Test applicability.....	21
5.3.3.3	Test description	21
5.3.3.3.1	Initial conditions.....	21
5.3.3.3.2	Conducted measurement.....	21
5.3.3.3.3	Radiated measurement.....	23
5.3.3.4	Test requirements	23
5.3.4	Transmitter unwanted emissions outside the 5 GHz ITS frequency band	24
5.3.4.1	Test purpose	24
5.3.4.2	Test applicability.....	24
5.3.4.3	Test description	24
5.3.4.3.1	Initial conditions.....	24
5.3.4.3.2	Conducted measurement.....	24
5.3.4.3.3	Radiated measurement.....	25
5.3.4.4	Test requirements	25
5.3.5	Transmitter spectrum mask within the 5 GHz ITS frequency band for 10 MHz channel spacing.....	25
5.3.5.1	Test Purpose.....	25
5.3.5.2	Test applicability.....	25
5.3.5.3	Test description	26
5.3.5.3.1	Initial conditions.....	26
5.3.5.3.2	Conducted measurement.....	26
5.3.5.3.3	Radiated measurement.....	26
5.3.5.4	Test requirements	26
5.3.6	Receiver spurious emissions	27
5.3.6.1	Test Purpose.....	27
5.3.6.2	Test applicability.....	27
5.3.6.3	Test description	27
5.3.6.3.1	Initial conditions.....	27
5.3.6.3.2	Conducted measurement.....	27
5.3.6.3.3	Radiated measurement.....	28
5.3.6.4	Test requirement	28
5.3.7	Receiver selectivity.....	28
5.3.7.1	Test purpose	28
5.3.7.2	Test applicability.....	28
5.3.7.3	Test description	28
5.3.7.3.1	Initial conditions.....	28
5.3.7.3.2	Conducted measurement.....	29
5.3.7.3.3	Radiated measurement.....	29
5.3.7.4	Test requirement	30
5.3.8	Receiver sensitivity.....	30
5.3.8.1	Test purpose	30

5.3.8.2	Test applicability	30
5.3.8.3	Test description	30
5.3.8.3.1	Initial conditions	30
5.3.8.3.2	Conducted measurement	30
5.3.8.3.3	Radiated measurement	31
5.3.8.4	Test requirement	31
5.3.9	CEN DSRC and HDR DSRC protection	31
5.3.9.1	Test Purpose	31
5.3.9.2	Test applicability	31
5.3.9.3	Test description	31
5.3.9.3.1	Initial conditions	31
5.3.9.3.2	Measurement of RF output power, unwanted emissions, and transmit duty cycle in coexistence mode	31
5.3.9.4	Test requirements	32
5.3.10	CEN DSRC and HDR DSRC detection	32
5.3.10.1	Test Purpose	32
5.3.10.2	Initial conditions	32
5.3.10.3	Test of detecting CEN DSRC and HDR DSRC transmissions	32
5.3.10.3.1	Test purpose	32
5.3.10.3.2	Test applicability	32
5.3.10.3.3	Test description	32
5.3.10.3.4	Test requirements	34
5.3.11	Decentralized congestion control	34
5.3.11.1	Test purpose	34
5.3.11.2	Test applicability	34
5.3.11.3	Test description	34
5.3.11.3.1	Initial conditions	34
5.3.11.3.2	Conducted measurement	34
5.3.11.3.3	Radiated measurement	35
5.3.11.4	Test requirement	35
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	36
Annex B (normative):	Test sites and arrangements for radiated measurements	37
B.1	Test sites	37
B.1.1	Open air test sites	37
B.1.2	Anechoic chamber	38
B.1.2.1	General	38
B.1.2.2	Description	38
B.1.2.3	Influence of parasitic reflections	38
B.1.2.4	Calibration and mode of use	38
B.2	Test antenna	39
B.3	Substitution antenna	40
Annex C (normative):	General description of measurement	41
C.1	Introduction	41
C.2	Conducted measurements	41
C.3	Radiated measurements	41
C.4	Substitution measurement	42
Annex D (informative):	Guidance on declaring the environmental profile	44
D.1	Recommended environmental profile	44
D.2	Temperatures	44
D.2.1	Introduction	44
D.2.2	Normal environmental conditions	44

D.2.3	Extreme environmental conditions.....	44
D.3	Test power source.....	45
D.3.1	Introduction	45
D.3.2	Normal test power source.....	45
D.3.2.1	AC mains voltage	45
D.3.2.2	Regulated lead-acid battery power sources used on vehicles.....	45
D.3.2.3	Other power sources	45
D.3.3	Extreme test source voltages	45
D.3.3.1	AC mains voltage	45
D.3.3.2	Regulated lead-acid battery power sources used on vehicles.....	45
D.3.3.3	Power sources using other types of batteries	45
D.3.3.4	Other power sources	46
D.3.4	Procedure for equipment designed for continuous transmission	46
D.3.5	Procedure for equipment designed for intermittent transmission	46
Annex E (informative):	Bibliography	47
Annex F (informative):	Change History	48
History		49

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sistbe9a4621-721d-4158-be57-ab81067a33e/etsi-en-302-571-v2.1.1-2017-02>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.5] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.4].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	6 February 2017
Date of latest announcement of this EN (doa):	31 May 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2017
Date of withdrawal of any conflicting National Standard (dow):	30 November 2018

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies technical characteristics and methods of measurement for radio transmitters and receivers operating in the frequency range 5 855 MHz to 5 925 MHz. The spectrum usage conditions are set out in ECC Decision (08)01 [i.1] for the frequency range 5 875 MHz to 5 925 MHz (with 5 905 MHz to 5 925 MHz considered as a future ITS extension) and in ECC Recommendation (08)01 [i.2] for the frequency range 5 855 MHz to 5 875 MHz. The Commission Decision 2008/671/EC [i.3] mandates a harmonised use of the frequency band 5 875 MHz to 5 905 MHz dedicated to safety-related applications of ITS throughout the member states of the European Union. Table 1 outlines the 5 GHz ITS frequency band segmentation.

Table 1: 5 GHz ITS frequency band segmentation

Frequency range	Usage	Regulation
5 855 MHz to 5 875 MHz	ITS non-safety applications	ECC Recommendation (08)01 [i.2]
5 875 MHz to 5 905 MHz	ITS road safety	Commission Decision 2008/671/EC [i.3], ECC Decision (08)01 [i.1]
5 905 MHz to 5 925 MHz	Future ITS applications	ECC Decision (08)01 [i.1]

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.4] under the conditions identified in annex A.

Interference mitigation techniques in the present document are provided to protect road tolling applications using CEN DSRC or HDR DSRC.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 792 (V1.2.1) (06-2015): "Intelligent Transport Systems (ITS); Mitigation techniques to avoid interference between European CEN Dedicated Short Range Communication (CEN DSRC) equipment and Intelligent Transport Systems (ITS) operating in the 5 GHz frequency range".
- [2] ETSI EN 302 637-2 (V1.3.2) (11-2014): "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Specification of Cooperative Awareness Basic Service".
- [3] Void.
- [4] CISPR 16 (parts 1-1 (2015), 1-4 (2010) and 1-5 (2014)): "Specifications for radio disturbance and immunity measuring apparatus and methods; Part 1: Radio disturbance and immunity measuring apparatus".
- [5] CEN EN 12253:2004: "Road transport and traffic telematics - Dedicated short-range communication - Physical layer using microwave at 5,8 GHz".

- [6] ETSI ES 200 674-1 (V2.4.1) (05-2013): "Intelligent Transport Systems (ITS); Road Transport and Traffic Telematics (RTTT); Dedicated Short Range Communications (DSRC); Part 1: Technical characteristics and test methods for High Data Rate (HDR) data transmission equipment operating in the 5,8 GHz Industrial, Scientific and Medical (ISM) band".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ECC Decision (08)01: "ECC Decision of 14 March 2008 on the harmonised use of the 5875-5925 frequency band for Intelligent Transport Systems (ITS)", approved 14 March 2008 and amended 3 July 2015.
- [i.2] ECC Recommendation (08)01:"Use of band 5855-5875 MHz for Intelligent Transport Systems (ITS)", approved 21 February 2008 and amended 3 July 2015.
- [i.3] Commission Decision 2008/671/EC of 5 August on the harmonised use of radio spectrum in the 5875-5905 MHz frequency band for safety related application of Intelligent Transport Systems (ITS).
- [i.4] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.5] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.8] ETSI TS 103 175 (V1.1.1) (06-2015): "Intelligent Transport Systems (ITS); Cross Layer DCC Management Entity for operation in the ITS G5A and ITS G5B medium".
- [i.9] IEEE 802.11™-2012: "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in Directive 2014/53/EU [i.4] and the following apply:

5 GHz ITS frequency band: frequency bands 5 855 MHz to 5 875 MHz (ITS-G5B), 5 875 MHz to 5 905 MHz (ITS-G5A) and 5 905 MHz to 5 925 MHz (ITS-G5D)

channel busy ratio (CBR): time-dependent value between zero and one representing the fraction of time that a single radio channel is busy with transmissions

dedicated antenna: removable antenna supplied and tested with the radio equipment, designed as an indispensable part of the equipment

NOTE: The dedicated antenna has been designed or developed for one or more specific types of equipment. It is the combination of dedicated antenna and radio equipment that is expected to be compliant with the regulations.

duty cycle: defined as the ratio, expressed as a percentage of the transmitter total "on" time on one carrier frequency, relative to 1 second period

integral antenna: antenna designed as a fixed part of the equipment, without the use of an external connector and as such which cannot be disconnected from the equipment by the user

NOTE: An integral antenna may be fitted internally or externally.

protected zone: area defined where mitigation mechanisms are applied to protect CEN DSRC and HDR DSRC road tolls

radiated measurements: measurements which involve the absolute measurement of a radiated field

vehicle: all kinds of land mobile vehicle

EXAMPLE: Road vehicle and rail vehicle.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

dB	decibel
dB_i	antenna gain relative to isotropic radiator in decibel
dB_c	decibel relative to carrier power
E	electrical field strength
f	frequency
f_c	nominal centre frequency
G	antenna gain
P_H	highest power level
P_L	lowest power level
P_M	lowest TPC power level
P_T	transmit power level
R	distance
T_{busy}	period of time the channel is busy
T_{CBR}	period of time
T_{max}	maximum temperature
T_{min}	minimum temperature
T_{off}	time between two transmissions

T_{on}	duration of a transmission
V_{max}	maximum voltage
V_{min}	minimum voltage
$V_{nominal}$	nominal voltage
Ω	ohm
μs	microsecond

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AC	Alternative Current
BPSK	Binary Phase Shift Keying
CAM	Cooperative Awareness Message
CBR	Channel Busy Ratio
CEN	Comité Européen de Normalisation (European Committee for Standardization)
CISPR	Comité International Spécial des Perturbations Radioélectriques (International Special Committee on Radio Interference)
DC	Direct Current
DCC	Decentralized Congestion Control
DSRC	Dedicated Short Range Communication (CEN DRSC = tolling at 5,8 GHz)
DUT	Device Under Test
e.i.r.p.	equivalent isotropically radiated power
e.r.p.	effective radiated power
EC	European Commission
ECC	Electronic Communication Committee
EFTA	European Free Trade Association
EMC	ElectroMagnetic Compatibility
EN	European Norm
EU	European Union
HDR	High Data Rate
ITS	Intelligent Transport Systems
LP	Linear Polarized
OOB	Out-Of-Band
PD	mean Power Density
PER	Packet Error Rate
ppm	parts per million = 10^{-6}
PSD	Power Spectral Density
QAM	Quadrature Amplitude Modulation
QPSK	Quadrature Phase Shift Keying
RF	Radio Frequency
RMS	Root Mean Square
TPC	Transmit Power Control
VSWR	Voltage Standing Wave Ratio

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile.

Recommended environmental profile parameters are summarized in annex D.

4.2 Conformance requirements

4.2.1 Transmitter frequency stability

4.2.1.1 Definition

The equipment is required to operate on the applicable specific carrier centre frequencies that correspond to the nominal carrier frequencies, f_c , as defined in Table 2.

Table 2: Nominal carrier frequency allocations

Carrier centre frequency f_c (MHz)	Maximum channel bandwidth (MHz)
5 860	10
5 870	10
5 880	10
5 890	10
5 900	10
5 910	10
5 920	10

The frequency channels together with the channel names contained in the three different frequency bands are depicted in Figure 1.




Figure 1: An overview of the three different frequency bands

4.2.1.2 Limits

The actual carrier centre frequency for any given channel given in Table 2 shall be maintained within the range $f_c \pm 20$ ppm.

4.2.1.3 Conformance

Conformance tests as defined in clause 5.3.2 shall be carried out.