



Technical Specification

**Intelligent Transport Systems (ITS);  
Testing;  
Conformance test specifications for  
Decentralized Environmental Notification Messages (DENM);  
Part 1: Test requirements and Protocol Implementation  
Conformance Statement (PICS) proforma**

STANDARDS PREVIEW  
(Standard ID: 201405-102-869-1-v1.3.1-  
https://standards.iso.org/standards/catalog/36675/scad-  
a0f4-46a1-9744-2461-201405-102-869-1-v1.3.1-)

---

Reference

RTS/ITS-00149

---

Keywords

ITS, PICS, testing

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaircor/ETSI\\_support.asp](http://portal.etsi.org/chaircor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

|  |          |
|--|----------|
| Intellectual Property Rights .....                                 | 4        |
| Foreword.....  | 4        |
| 1 Scope .....  | 5        |
| 2 References .....   | 5        |
| 2.1 Normative references .....                                     | 5        |
| 2.2 Informative references.....                                    | 5        |
| 3 Definitions and abbreviations.....                               | 5        |
| 3.1 Definitions.....   | 5        |
| 3.2 Abbreviations .....  | 5        |
| 4 Conformance requirement concerning PICS.....                     | 6        |
| <b>Annex A (normative): DENM PICS Proforma .....</b>               | <b>7</b> |
| A.1 Guidance for completing the ICS proforma .....                 | 7        |
| A.1.1 Purposes and structure.....                                  | 7        |
| A.1.2 Abbreviations and conventions .....                          | 7        |
| A.1.3 Instructions for completing the ICS proforma.....            | 9        |
| A.2 Identification of the implementation .....                     | 9        |
| A.2.1 Date of the statement .....                                  | 9        |
| A.2.2 Implementation Under Test (IUT) identification .....         | 9        |
| A.2.3 System Under Test (SUT) identification .....                 | 10       |
| A.2.4 Product supplier.....  | 10       |
| A.2.5 Client (if different from product supplier).....             | 10       |
| A.2.6 ICS contact person.....                                      | 11       |
| A.3 Identification of the protocol.....                            | 12       |
| A.4 Global statement of conformance.....                           | 12       |
| A.5 Tables .....   | 12       |
| A.5.1 ITS Station role .....                                       | 12       |
| A.5.1.1 Functions .....  | 12       |
| A.5.2 DEN Causes .....   | 13       |
| A.5.3 DENM Message .....   | 15       |
| A.5.3.1 ItsPduHeader element.....                                  | 15       |
| A.5.3.2 DecentralizedEnvironmentalNotificationMessage element..... | 16       |
| A.5.3.2.1 ManagementContainer element.....                         | 16       |
| A.5.3.2.1.1 ManagementContainer sub-elements.....                  | 16       |
| A.5.3.2.2 SituationContainer element .....                         | 16       |
| A.5.3.2.2.1 SituationContainer sub-elements .....                  | 16       |
| A.5.3.2.3 LocationContainer element .....                          | 17       |
| A.5.3.2.4 AlacarteContainer element.....                           | 17       |
| A.5.3.2.4.1 AlacarteContainer sub element.....                     | 17       |
| A.5.4 Protocol parameters.....                                     | 18       |
| A.5.4.1 Timing requirements.....                                   | 18       |
| History .....  | 19       |

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document is part 1 of a multi-part deliverable covering Conformance test specification for Decentralized Environmental Notification Messages (DENM) as identified below:

- Part 1: "Test requirements and Protocol Implementation Conformance Statement (PICS) proforma";**
- Part 2: "Test Suite Structure and Test Purposes (TSS & TP)";
- Part 3: "Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".

**ETSI STANDARD PREVIEW**  
(standard.iteh.ai)  
Full standard available at: <https://standards.iteh.ai/catalog/standards/sist/52475cad-a0f4-46a1-9744-e24cf433082d/etsi-ts-102-869-1-v1.3.1-2014-05>

---

# 1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for Conformance test specification for Decentralized Environmental Notification Messages (DENM) as defined in EN 302 637-3 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [3].

---

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 302 637-3 (V1.2.0): "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 3: Specifications of Decentralized Environmental Notification Basic Service".
- [2] ISO/IEC 9646-1 (1994): "Information technology -- Open Systems Interconnection - Conformance testing methodology and framework -- Part 1: General concepts".
- [3] ISO/IEC 9646-7 (1995): "Information technology -- Open Systems Interconnection - Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".

### 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 302 637-3 [1], ISO/IEC 9646-1 [2] and ISO/IEC 9646-7 [3] apply.

### 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in EN 302 637-3 [1] and the following apply:

|     |  |
|-----|--|
| CAN | Controller Area Network                  |
| DE  | Data Element                             |
| DEN | Decentralized Environmental Notification |

|      |   |
|------|---|
| DENM | DEN Message                                   |
| ICS  | Implementation Conformance Statement          |
| ITS  | Intelligent Transportation Systems            |
| IUT  | Implementation Under Test                     |
| PICS | Protocol Implementation Conformance Statement |
| SUT  | System Under Test                             |

---

## 4 Conformance requirement concerning PICS

If it claims to conform to the present document, the actual PICS proforma to be filled in by a supplier shall be technically equivalent to the text of the PICS proforma given in annex A, and shall preserve the numbering, naming and ordering of the proforma items.

An ICS which conforms to the present document shall be a conforming PICS proforma completed in accordance with the instructions for completion given in clause A.1.

**ITeH STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/3fd75cad-20f4-46a1-9744-e24cf433082d/etsi-ts-102-869-1-v1.3.1-2014-05>

---

## Annex A (normative): DENM PICS Proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the DENM PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed DENM PICS.

---

### A.1 Guidance for completing the ICS proforma

#### A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in EN 302 637-3 [1] may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into clauses for the following categories of information:

- guidance for completing the ICS proforma;
- identification of the implementation;
- identification of the EN 302 637-3 [1];
- global statement of conformance;
- PICS proforma tables.

#### A.1.2 Abbreviations and conventions

The ICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [3].

##### Item column

The item column contains a number which identifies the item in the table.

##### Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

## Status column

The following notations, defined in ISO/IEC 9646-7 [3], are used for the status column:

|     |   |
|-----|---|
| m   | mandatory - the capability is required to be supported.   |
| o   | optional - the capability may be supported or not.  |
| n/a | not applicable - in the given context, it is impossible to use the capability.  |
| x   | prohibited (excluded) - there is a requirement not to use this capability in the given context.   |
| o.i | qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table.                   |
| ci  | conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table. |
| i   | irrelevant (out-of-scope) - capability outside the scope of the reference specification. No answer is requested from the supplier.  |

NOTE 1: This use of "i" status is not to be confused with the suffix "i" to the "o" and "c" statuses above.

## Reference column

The reference column makes reference to EN 302 637-3 [1], except where explicitly stated otherwise.

## Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [3], are used for the support column:

|               |   |
|---------------|---|
| Y or y        | supported by the implementation.  |
| N or n        | not supported by the implementation.  |
| N/A, n/a or - | no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status). |

NOTE 2: As stated in ISO/IEC 9646-7 [3], support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

## Values allowed column

The values allowed column contains the type, the list, the range, or the length of values allowed. The following notations are used:

|   |  |
|---|--|
| - range of values:<br>example:                        | <min value> .. <max value><br>5 .. 20  |
| - list of values:<br>example:<br>example:<br>example: | <value1>, <value2>, ..., <valueN><br>2, 4, 6, 8, 9<br>'1101'B, '1011'B, '1111'B<br>'0A'H, '34'H, '2F'H |
| - list of named values:<br>example:                   | <name1>(<val1>), <name2>(<val2>), ..., <nameN>(<valN>)<br>reject(1), accept(2)                         |
| - length:<br>example:                                 | size (<min size> .. <max size>)<br>size (1 .. 8)   |



## Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

## References to items

For each possible item answer (answer in the support column) within the ICS proforma a unique reference exists, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are discriminated by letters (a, b, etc.), respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table 5 of annex A.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table 6 of annex A.

## Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

## A.1.3 Instructions for completing the ICS proforma

The supplier of the implementation shall complete the ICS proforma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in clause A.1.2.

If necessary, the supplier may provide additional comments in space at the bottom of the tables or separately.

More detailed instructions are given at the beginning of the different clauses of the ICS proforma.

---

## A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the ICS should be named as the contact person.

### A.2.1 Date of the statement

.....

### A.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....