

ETSI EN 301 649 V2.3.1 (2015-03)



Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS)

ITeH STANDARDS PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1a11-2015-03-7024-420a-9e4a-60ebf46acd93/etsi-en-301-649-v2.3.1-2015-03>

Reference

REN/DECT-00305

Keywords

access, data, DECT, DPRS, frame relay, IMT-2000, internet, interoperability, interworking, IP, IPv6, LAN, mobility, multimedia, packet mode, profile, radio, synchronization, TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	15
Foreword.....	15
Modal verbs terminology.....	15
1 Scope	16
2 References	16
2.1 Normative references	16
2.2 Informative references.....	18
3 Definitions, symbols and abbreviations	19
3.1 Definitions.....	19
3.2 Symbols.....	20
3.3 Abbreviations	21
4 Description of services	24
4.1 The DECT Packet Radio Service (DPRS).....	24
4.1.1 Service objectives	24
4.1.2 Characteristics of the DECT packet data service.....	25
4.1.3 Performance Objectives	25
4.1.4 DPRS U-plane Services	26
4.1.5 DPRS operation modes (Classes)	27
4.1.6 DPRS System Categories.....	27
4.2 Protocol architecture.....	28
4.2.1 Reference configuration for Internet Protocol and LANs.....	29
4.2.1.1 Reference configuration for Internet Protocol.....	29
4.2.1.2 Reference configuration for IEEE 802.9 [13].....	30
4.3 Service and feature definitions	30
4.3.1 PHL service definitions	30
4.3.2 MAC service definitions	31
4.3.3 DLC service definitions	33
4.3.4 NWK feature definitions.....	34
4.3.5 Application service definitions	36
4.3.6 Distributed Communication.....	36
4.3.7 Management Entity.....	36
4.3.8 Call Control (CC) and Mobility Management (MM) Service Class.....	37
4.3.9 U-plane Service and Interworking type	37
4.3.10 DPRS System Categories.....	37
4.4 General Class/Service/Interworking support.....	38
4.5 System categories	38
4.5.1 Mapping between DPRS categories and features/services	38
4.5.2 Supported data rates for equipment declaring compliance to a data category	40
4.5.3 Indication of compliance with a data category	42
5 PHL requirements	43
5.1 Physical Layer services	43
5.2 Modulation schemes.....	43
5.3 PHL service to procedure mapping	44
5.4 PHL layer procedures.....	44
5.4.1 General radio requirements.....	44
5.4.2 Minimum Normal Transmit Power (NTP).....	44
5.4.3 Radio receiver sensitivity.....	45
5.4.4 Z-field	45
5.4.5 Sliding collision detection	45
5.4.6 Physical channel availability.....	45
5.4.7 Synchronization window	45
5.4.8 Power management.....	45
5.4.9 Fast hopping radio	45
6 MAC layer requirements	45

6.1	MAC services	45
6.2	MAC service to procedure mapping	47
7	DLC-layer requirements	52
7.1	DLC services	52
7.2	DLC feature to procedure mapping	52
8	NWK layer requirements	53
8.1	NWK features	54
8.2	NWK feature to procedure mapping	55
8.3	Application features	59
8.4	Application feature to procedure mapping	59
8.5	Distributed Communications	60
8.5.1	Distributed Communications features	60
8.6	Distributed Communications feature to procedure mapping	60
9	Management Entity Requirements	60
9.1	Introduction	60
9.1.1	Management Entity (ME) operation modes	60
9.1.2	Management Entity (ME) mode to procedures mapping	61
9.2	Description of the DPRS operation principles	62
9.2.1	General	62
9.2.2	Service class 1	62
9.2.3	Service class 2	62
9.2.4	Service class 3	62
9.2.5	Service class 4	63
9.3	Resource and physical connection management for Class 1 and Class 2 systems	63
9.3.1	Requirements applicable to the Fixed Part (FP)	63
9.3.1.1	Conditions for resumption and management procedures	63
9.3.1.1.1	General	63
9.3.1.1.2	ME procedures for FT initiated connection resumption	63
9.3.1.2	Connection Suspension conditions	65
9.3.1.2.1	General	65
9.3.1.2.2	Connection suspension due to no data activity	65
9.3.1.2.3	Connection suspension due to violation of the minimum number of bearers (MAC Bandwidth command)	65
9.3.1.2.4	Connection suspension by loss of all received bearers	65
9.3.1.2.5	Activation of Fast Scan mode and/or high duty cycle paging detection after Connection suspension	66
9.3.1.3	Conditions for Bandwidth modification	66
9.3.1.3.1	General	66
9.3.2	Requirements applicable to the Portable Part (PP)	66
9.3.2.1	Conditions for connection resumption	66
9.3.2.1.1	Procedure for PT initiated Connection resumption	66
9.3.2.1.2	"RFP-busy-for-data" flag	67
9.3.2.1.3	Waiting time for collision avoidance after deactivation of "RFP-busy-for-data" flag	67
9.3.2.1.4	Bandwidth after resumption	67
9.3.2.1.5	Resumption rejection by the FT	67
9.3.2.2	Conditions for Connection Suspension	67
9.3.2.2.1	General	67
9.3.2.2.2	Connection suspension due to no data activity	67
9.3.2.2.3	Connection suspension due to violation of the minimum number of bearers (MAC Bandwidth command)	68
9.3.2.2.4	Connection suspension by loss of all received bearers	68
9.3.2.2.5	Activation of fast scan mode after Connection suspension	68
9.3.2.3	Conditions for Bandwidth modification	68
9.3.2.3.1	General	68
9.3.2.3.2	Rules for the bandwidth request by the PP	68
9.4	Logical Connection and virtual call management	69
9.4.1	Requirements for class 1 devices	69
9.4.2	Requirements for class 2 devices	69
9.4.2.1	General Description	69
9.4.2.2	Normal procedures of virtual call setup and release	69

9.4.2.2.1	Identification of the call as a DPRS call	69
9.4.2.2.2	Bandwidth attributes of the call	69
9.4.2.2.3	Creation of DLC link and MAC logical connection	70
9.4.2.2.4	Temporary states during the setup procedure	70
9.4.2.3	Abnormal release of Virtual Calls	70
9.4.2.4	Release of Logical Connection	70
9.4.2.5	The handshake (stay alive) procedure	70
9.4.3	Requirements for class 3 devices	71
9.4.3.1	General Description	71
9.4.3.1.1	Identification of the call as a DPRS call	71
9.4.3.1.2	Connection attributes	71
9.4.4	Requirements for class 4 devices	71
9.4.4.1	General Description	71
9.4.4.1.1	Identification of the call as a DPRS call	72
9.5	Resource and physical connection management for Class 3 and Class 4 devices	72
9.5.1	Simplified Class 3 connection management	72
9.5.2	Suspend management (Tx side)	72
9.5.3	Suspend management (Rx side)	72
9.5.4	Resume management	72
9.5.5	Stay alive (timer control)	72
9.5.6	Stay alive (periodic resume)	72
9.5.7	Simplified Class 4 connection management	73
10	MAC layer procedures	73
10.1	General	73
10.1.1	Frame and multiframe structure	73
10.1.2	Bit mappings	73
10.1.2.1	Multiple bitmappings rule	73
10.1.3	Void	73
10.1.4	Scrambling	73
10.1.5	Error control	73
10.1.6	Void	73
10.1.7	Void	73
10.1.8	RFP idle receiver scan sequence	74
10.1.9	PT receiver scan sequence	74
10.1.10	PT states and state transitions	74
10.1.10.1	PT states and state transitions for PTs not supporting fast setup	74
10.1.10.2	PT states and state transitions for PTs supporting fast setup	74
10.1.10.2.1	Fast setup control information provided by the FT	75
10.1.10.2.2	PT states and state transitions when PT and FT supports complete setup detection	75
10.1.10.2.3	PT states and state transitions when PT and FT supports Selective setup detection only	76
10.1.10.2.4	Fast setup control information provided using MAC paging	76
10.1.11	Identities	77
10.2	Non continuous broadcast	77
10.2.1	Request for specific Q channel information	77
10.2.2	Request for a new dummy	77
10.3	Downlink broadcast	77
10.3.1	N_T messages	77
10.3.2	Q_T messages	77
10.3.2.1	Q_T - static system information	77
10.3.2.2	Q_T - FP capabilities	78
10.3.2.2.1	Standard FP Capabilities	78
10.3.2.2.2	Extended FP Capabilities	79
10.3.2.2.3	Extended FP Capabilities part 2	79
10.3.2.3	Q_T - SARI list contents	80
10.3.2.4	Multiframe number	80
10.4	Paging broadcast	80
10.4.1	Paging message formats	80
10.4.1.1	Long or full page message format	81
10.4.1.2	Short page message format	81
10.4.1.3	Zero length page message format	82
10.4.1.4	MAC resume and control page message format	82

10.4.1.5	MAC layer information in zero and short length paging messages.....	83
10.4.1.5.1	RFP status.....	83
10.4.2	MAC layer information messages procedures.....	84
10.4.2.1	Blind slot information for circuit mode service.....	84
10.4.2.2	Bearer handover/replacement information.....	84
10.4.2.3	Other bearer position.....	84
10.4.2.4	Recommended other bearer position.....	84
10.4.2.5	Dummy or C/L bearer position.....	84
10.4.2.6	C/L bearer position.....	84
10.4.2.7	RFP-status and Modulation Types.....	85
10.4.2.8	Blind slot information for packet mode service.....	85
10.4.3	Paging Procedures.....	85
10.4.3.1	LCE Paging.....	85
10.4.3.2	MAC Paging.....	85
10.4.3.2.1	Support of MAC Paging commands for resume and paging detection control.....	85
10.4.3.2.2	Support of MAC Paging codes for control of fast setup.....	86
10.4.4	Paging detection.....	86
10.4.4.1	Normal duty cycle.....	86
10.4.4.2	High duty cycle.....	86
10.4.4.3	Low duty cycle.....	86
10.5	Logical Connection Setup.....	86
10.6	Logical Connection Release.....	87
10.7	Connection Modification.....	87
10.7.1	Connection Modification to change bandwidth.....	87
10.7.1.1	Bandwidth negotiation.....	87
10.7.1.1.1	Bandwidth negotiation with A-field messages.....	88
10.7.1.1.2	Bandwidth negotiation with B-field messages.....	88
10.7.1.1.3	Order and sequence of operations.....	89
10.7.1.2	Bandwidth modification.....	89
10.7.1.2.1	Order and sequence of operations.....	90
10.7.1.3	Suspend.....	90
10.7.1.4	Resume.....	94
10.7.1.5	Bandwidth modification rejection and error handling.....	94
10.7.1.5.1	Error handling.....	95
10.7.2	Connection modification to change service type, slot type, modulation type or adaptive code rate..	95
10.7.2.1	Connection modification to change MAC service type.....	95
10.7.2.2	Connection modification to change slot type.....	95
10.7.2.3	Connection modification to change the modulation scheme and adaptive code rate.....	96
10.7.2.4	ATTRIBUTES_T.req/cfm.....	96
10.8	Physical Connection Setup.....	97
10.8.1	Single bearer physical connection setup.....	97
10.8.2	Multibearer Physical Connection setup.....	98
10.9	Physical Connection Release.....	98
10.10	Bearer Setup.....	98
10.10.1	Duplex bearer setup procedures.....	98
10.10.1.1	MAC control messages.....	98
10.10.1.2	PT initiated initial duplex bearer setup (pilot bearer).....	99
10.10.1.2.1	Prerequisites.....	100
10.10.1.2.2	Usage of channel list procedures.....	100
10.10.1.2.3	Detailed procedure description.....	100
10.10.1.3	FT initiated initial duplex bearer setup (pilot bearer).....	102
10.10.1.3.1	Prerequisites.....	102
10.10.1.3.2	Usage of channel list procedures.....	102
10.10.1.3.3	Detailed procedure description.....	102
10.10.1.4	PT initiated additional duplex bearer setup.....	104
10.10.1.4.1	Use of the procedure and Master side.....	105
10.10.1.4.2	Prerequisites.....	105
10.10.1.4.3	Usage of channel list procedures.....	105
10.10.1.4.4	Detailed procedure description.....	107
10.10.1.5	FT initiated additional duplex bearer setup.....	109
10.10.2	Double simplex bearer setup.....	109
10.10.2.1	MAC control messages.....	110

10.10.2.2	Upstream double simplex bearer setup	111
10.10.2.2.1	Use of the procedure and T-side.....	111
10.10.2.2.2	Prerequisites	111
10.10.2.2.3	Channel selection and usage of channel list procedures	111
10.10.2.2.4	Detailed procedure description.....	112
10.10.2.3	Downstream double simplex bearer setup.....	113
10.10.2.3.1	Use of the procedure and T-side.....	114
10.10.2.3.2	Prerequisites	114
10.10.2.3.3	Channel selection and usage of channel list procedures	114
10.10.2.3.4	Detailed procedure description.....	114
10.11	Bearer Release procedures	116
10.11.1	Unacknowledged release	117
10.11.2	Crossed release (duplex bearers only)	117
10.11.3	Acknowledged release	117
10.11.4	Fast release.....	118
10.11.5	Definition of the procedure to use and the Master side for the different release cases	118
10.11.5.1	Suspend cases.....	118
10.11.5.1.1	FT initiated suspend	118
10.11.5.1.2	PT initiated suspend	119
10.11.5.2	Bandwidth modification cases	119
10.11.5.2.1	Reversal of asymmetric connection: from asymmetric downlink to uplink	119
10.11.5.2.2	Reversal of asymmetric connection: from asymmetric uplink to downlink	119
10.11.5.2.3	Modification from asymmetric downlink to symmetric	119
10.11.5.2.4	Modification from asymmetric uplink to symmetric	119
10.11.5.2.5	Modification from symmetric to asymmetric downlink (with release of duplex bearers)....	120
10.11.5.2.6	Modification from symmetric to asymmetric uplink (with release of duplex bearers).....	120
10.11.6	Listen for setup control codes in Release message.....	120
10.12	Advanced connection handover	120
10.13	I channel operation	120
10.13.1	Protected I channel error_detect mode.....	121
10.13.2	Protected I channel error_correct mode.....	121
10.13.2.1	Unilateral jump	121
10.13.2.2	Bearer reset	121
10.13.3	Connectionless SI _P mode.....	121
10.14	C channel operation.....	122
10.14.1	C _S channel.....	122
10.14.2	C _F channel.....	122
10.14.2.1	Priority schema of the C _F channel	122
10.15	Encryption	123
10.15.1	Encryption process - initialization and synchronization	123
10.15.2	Encryption mode control	124
10.15.2.1	M _T message	125
10.15.2.2	PT procedure for enabling encryption.....	125
10.15.2.3	PT procedure for disabling encryption.....	125
10.15.3	Handover encryption process.....	125
10.16	Quality control.....	125
10.16.1	RFPI handshake	125
10.16.2	PT frequency correction.....	125
10.16.3	Bearer quality report	125
10.16.3.1	Bearer quality report for asymmetric bearers.....	126
10.16.4	Bearer and connection control	126
10.16.5	A-CRC handshake	127
10.17	Physical channel selection.....	127
10.18	Bearer replacement.....	128
10.19	Bearer handover request.....	128
10.20	G _F channel	128
10.20.1	G _F channel data	128
10.20.1.1	G _F channel transmission.....	128
10.20.1.2	G _F channel reception	128
10.21	Time multiplexers.....	128
10.21.1	A-field Multiplexer	128
10.21.1.1	Tail Multiplexer (T-MUX).....	128

10.21.1.2	A-tail identifications.....	128
10.21.2	B-field control Multiplexer (E/U-MUX)	129
10.21.2.1	B-field control Multiplexer (E/U-MUX), basic modes	129
10.21.2.1.1	U-type Multiplexer	129
10.21.2.1.2	E-type Multiplexer, all MAC control	129
10.21.2.1.3	E/U-Mux priority schema	129
10.21.2.1.4	B-field identifications (basic)	129
10.21.2.2	B-field control Multiplexer (E/U-MUX), C _F modes	129
10.21.2.2.1	E-type Multiplexer, all modes	129
10.21.2.2.2	E/U-Mux priority schema	129
10.21.2.2.3	B-field identifications (C _F)	129
10.21.2.3	B-field control Multiplexer (E/U-MUX), E+U modes	130
10.21.2.3.1	E+U-type Multiplexer	130
10.21.2.3.2	E/U-Mux priority schema	130
10.21.2.3.3	B-field identifications (E+U type)	130
10.22	I _{PF} channel	130
10.22.1	I _{PF} channel general	130
10.22.2	I _{PF} channel advanced procedures	130
10.22.3	I _{PF} channel error_correct procedures	131
10.22.4	SI _{PF} channel	131
10.23	A-field (M _T) procedures	131
10.23.1	General.....	131
10.23.2	PT initiated A-field advanced bearer setup.....	131
10.23.2.1	M _T access request message	131
10.23.2.2	M _T Attributes_T.req/cfm message	132
10.23.3	A-field connection/bearer release	133
10.23.3.1	M _T message	133
10.23.4	A-field bearer handover request.....	133
10.23.4.1	M _T message	133
10.23.5	A-field connection handover request.....	134
10.23.5.1	M _T message	134
11	DLC layer procedures	134
11.1	LU10 Enhanced Frame RELay service (EFREL)	134
11.1.1	Window size	135
11.1.2	U-plane transmission class 2.....	135
11.1.2.1	Sending side procedures.....	135
11.1.2.2	Receiving side procedure	135
11.1.3	SDU transmission and delivery mode.....	136
11.2	FU 10 framing (FU10a, FU10b, FU10c).....	136
11.2.1	FU10a	136
11.2.2	FU10b	136
11.2.3	FU10c	136
11.2.3.1	Insertion of FU10c frames in FU10a frames of the opposite link	137
11.3	Class A operation	137
11.3.1	Class A link establishment.....	137
11.3.1.1	Lower Layer Management Entity (LLME) establishment of a MAC connection.....	137
11.3.2	Class A acknowledged information transfer	139
11.3.3	Class A link release.....	139
11.3.4	Class A link re-establishment	139
11.4	Class U operation	140
11.4.1	Class U use of LLN for unacknowledged information transfer	140
11.4.2	Class U link establishment.....	140
11.4.3	Class U unacknowledged information transfer	140
11.4.4	Class U unacknowledged release.....	140
11.5	Lc frame delimiting and sequencing service	140
11.5.1	C _S channel fragmentation and recombination	140
11.5.2	C _F channel fragmentation and recombination	140
11.5.3	Selection of logical channels (C _S and C _F)	140
11.6	Broadcast Lb service	141
11.6.1	Normal broadcast.....	141
11.6.2	Expedited broadcast.....	142

11.7	Connection handover.....	142
11.7.1	Class A connection handover.....	142
11.7.1.1	Voluntary handover.....	143
11.7.1.2	Associated procedure	143
11.7.1.2.1	LLME connection handover management.....	143
11.7.1.3	Exceptional case.....	143
11.7.1.3.1	Receipt of a request for link release	143
11.8	Connection modification	143
11.9	Encryption switching.....	145
11.9.1	Associated procedure.....	145
11.9.1.1	Providing Encryption key to the MAC layer.....	145
11.9.2	Exceptional cases.....	145
11.9.2.1	Encryption fails	145
11.9.2.2	Connection handover of ciphered connections.....	145
11.10	Connectionless point-to-multipoint transmission	145
12	NWK layer procedures.....	146
12.1	PT initiated virtual call request.....	146
12.2	FT initiated virtual call request.....	147
12.3	Terminal capability indication.....	148
12.4	Internal call keypad	151
12.5	Call Resources/Parameters negotiation	151
12.5.1	General requirements.....	151
12.5.2	Allowable values on initiating side.....	152
12.5.3	Negotiation process.....	155
12.5.4	Allowable values in the answer	156
12.5.5	Default values for class 2 on initiating side	160
12.5.6	Exceptional cases.....	162
12.5.7	IP address allocation (IP IWU only).....	162
12.6	Service Change procedures	162
12.6.1	Service change - Bandwidth Change (including symmetry type indicator).....	162
12.6.1.1	Associated procedures.....	165
12.6.1.1.1	Timer F/P < CC_service > management	165
12.6.1.2	Exceptional cases	165
12.6.1.2.1	Service change request is rejected	165
12.6.1.3	Examples.....	165
12.6.2	Service change - slot type change	166
12.6.2.1	Associated procedures.....	166
12.6.2.2	Exceptional cases	166
12.6.2.3	Examples.....	166
12.6.3	Service change - MAC service change	166
12.6.3.1	Associated procedures.....	166
12.6.3.2	Exceptional cases	166
12.6.3.3	Examples.....	166
12.6.4	Service change - modulation schema change	166
12.6.4.1	Associated procedures.....	167
12.6.4.2	Exceptional cases	167
12.6.4.3	Examples.....	167
12.6.5	Service change - DPRS Management Class and other Call-attributes change.....	167
12.6.5.1	Associated procedures.....	167
12.6.5.2	Exceptional cases	167
12.6.5.3	Examples.....	167
12.6.6	Service change - MAC Packet lifetime, DLC Window size, DLC Transit delay and C _F channel attributes change	167
12.6.6.1	Associated procedures.....	168
12.6.6.2	Exceptional cases	168
12.6.6.3	Examples.....	168
12.7	Service change - IWU-attributes change	168
12.7.1	IWU-attributes change - General	168
12.7.1.1	Associated procedures.....	169
12.7.1.2	Exceptional cases	169
12.7.1.3	Examples.....	169

12.7.2	Interworking type change	169
12.7.3	IP address change (IP IWU)	169
12.7.4	Maximum SDU size change	169
12.8	Dynamic Parameters Allocation.....	170
12.8.1	General requirements.....	170
12.8.2	Sent IE and Default IE Dynamic Parameter Allocation.....	170
12.8.2.1	Sent-IE mechanism	170
12.8.2.2	Default-IE mechanisms	170
12.8.2.3	Support of these mechanisms	171
12.8.2.4	Simultaneous use of both mechanisms (one from each side).....	171
12.8.3	Transport of the <<SETUP CAPABILITY>> IE (when used).....	172
12.8.4	Service and parameter settings support indication (PT or FT).....	172
12.8.5	Application media protocol support indication (PT and FT)	176
12.8.6	Allowed and mandatory values for DPRS Class 2 PT and FT devices.....	178
12.8.7	Allowed values for DPRS Class 3 and 4 devices (PT or FT)	180
12.8.8	Transport with {MM-INFO-SUGGEST} message (FT to PT).....	182
12.8.9	Transport with {CLMS-FIXED} message (FT to PT).....	182
12.8.10	Class 2 Default Dynamic Parameters Allocation for PT and FT devices	182
12.9	Cipher-switching initiated by PT.....	183
12.10	Temporary Identity Assign.....	184
12.10.1	Associated procedures	184
12.10.1.1	Timer F-< MM_ident.1 > management.....	184
12.10.2	Exceptional cases.....	185
12.10.2.1	PT rejects the identity assignment.....	185
12.11	Indirect FT initiated link establishment.....	185
12.11.1	Indirect FT initiated link establishment for devices supporting complete MAC control procedures (DPRS-M.5).....	185
12.11.1.1	Initial setup paging.....	185
12.11.1.1.1	Assumptions for Short paging format or for Full format with IPUI.....	185
12.11.1.1.2	Coding for Full paging format with TPUI.....	185
12.11.1.1.3	Message in case of short format.....	186
12.11.1.1.4	Message in case of full format with TPUI.....	187
12.11.1.1.5	Message in case of full format with IPUI.....	188
12.11.1.2	DPRS Resume paging.....	188
12.11.1.2.1	Assumptions for Short paging format.....	188
12.11.1.2.2	Coding for Full paging format with TPUI.....	188
12.11.1.2.3	Message in case of short format	189
12.11.1.2.4	Message in case of full format with TPUI.....	190
12.11.1.2.5	LCE Resume Procedure description.....	191
12.11.2	Indirect FT initiated link establishment for devices supporting simplified A-field MAC control procedures (DPRS-M.30)	191
12.11.2.1	Initial setup paging.....	191
12.11.2.1.1	Assumptions for Short paging format or for Full format with IPUI.....	191
12.11.2.1.2	Coding for Full paging format with TPUI.....	191
12.11.2.1.3	Message in case of short format	192
12.11.2.1.4	Message in case of full format with TPUI.....	192
12.11.2.2	DPRS Resume paging.....	193
12.11.2.2.1	Assumptions for Short paging format.....	193
12.11.2.2.2	Coding for Full paging format with TPUI.....	193
12.11.2.2.3	Message in case of short format	193
12.11.2.2.4	Message in case of full format with TPUI.....	194
12.11.2.2.5	LCE Resume Procedure description.....	195
12.12	Fast paging	195
12.13	Collective and Group Ringing.....	195
12.14	Direct FT initiated link establishment	196
12.14.1	Exceptional case	197
12.14.1.1	Link establishment failure.....	197
12.15	Void.....	198
12.16	Broadcast attributes management.....	198
12.16.1	Higher Layer capabilities.....	198
12.16.2	Extended Higher Layer capabilities.....	198
12.16.3	Extended Higher Layer capabilities part 2.....	199

12.17	U-plane handling	199
12.18	Management of MM procedures	200
12.19	Management - PMID	200
12.20	Length of NWK layer messages	200
12.21	Identities	201
13	Distributed Communications.....	201
13.1	Void.....	201
13.2	General Requirements	201
13.2.1	DCDL-net	201
13.2.2	Subscription	201
13.2.3	Communication.....	201
13.3	Procedure description	201
13.3.1	HyP Identities	201
13.3.2	Membership Access Rights Allocation.....	201
13.3.3	Re-initialization of membership access rights	201
13.3.4	Members Data Transfer	202
13.3.5	Presence/Absence Indication	202
13.3.6	Bandwidth management	202
13.3.7	Direct Link Establishment	202
13.3.8	Indirect Link Establishment	202
13.3.9	MASTER management.....	202
13.3.9.1	MASTER assign	202
13.3.9.2	MASTER Change	202
13.3.9.3	DCDL-net System bearer management.....	203
13.3.10	Common Subscription Database management.....	203
13.3.11	Handover issues	203
13.4	Elements of Messages/Information Elements.....	203
13.5	Usage of PPs or FPs in DCDL-net	203
Annex A (normative):	Operating parameters	204
A.1	ME operating parameters	204
A.1.1	Constants (applicable to class 1 and class 2 devices).....	204
A.1.2	Equations.....	204
A.1.2.1	Waiting time for collision avoidance (WtA).....	204
A.1.2.1.1	Description	204
A.1.2.1.2	Formula	204
A.1.2.2	Waiting time for congestion avoidance (WtB)	204
A.1.2.2.1	Description	204
A.1.2.2.2	Formula	205
A.1.3	Variable parameters (class 2 systems only).....	205
A.1.3.1	Parameters set by the FP (class 2 systems only).....	205
A.1.3.2	Negotiable parameters between FP and PP (class 2 systems only).....	206
A.1.3.2.1	Conditions of negotiation.....	206
A.1.3.2.1.1	Negotiation of T909	206
A.1.3.2.1.2	Negotiation of T911	206
A.1.4	Configuration capabilities for class 1 devices	207
A.2	Default coding of <<IWU-ATTRIBUTES>>, <<CALL-ATTRIBUTES >>, <<CONNECTION-ATTRIBUTES >>, <<WINDOW SIZE >>, <<TRANSIT DELAY >> and <<SETUP-CAPABILITY >> information elements for DPRS Basic Services.....	210
A.2.1	Default setup attributes for basic service "light data service, with Class 4 DPRS management" (code "1001"B).....	210
A.2.2	Default setup attributes for basic service "light data service with Class 3 DPRS management" (code "1010"B).....	213
Annex B (normative):	Interworking conventions for the Frame Relay (FREL) service	215
B.1	Scope of this annex.....	215
B.1.1	Typical configuration for the Frame Relay service	215
B.2	Specific codings for mobility class 2	216
B.2.1	IWU-ATTRIBUTES information element coding	216

B.2.1.1	Profile subtype attributes (octet group 6) of IWU-ATTRIBUTES information element.....	217
B.2.1.1.1	IEEE 802.3/Ethernet	217
B.2.1.1.2	IEEE 802.5 (Token-Ring)	217
B.2.1.1.3	Internet Protocol (IP).....	218
B.2.1.1.3.1	Dynamic IP address allocation	218
B.2.1.1.4	DPRS Generic media encapsulation	219
B.2.1.1.4.1	Description of the different fields:.....	219
B.2.1.1.4.2	Optional control octets	220
B.2.1.1.4.3	D-GMEP Protocol identifier codes.....	222
B.2.2	IWU attributes implemented	222
B.3	Generic Frame Relay service interworking conventions.....	223
B.3.1	DLC U-plane service.....	223
B.3.2	Transmission bit order.....	223
B.3.3	Support of SDU size.....	223
B.3.4	SI _P connectionless downlink	223
B.4	IEEE 802.3/Ethernet.....	223
B.4.1	Typical configuration	223
B.4.1.1	Examples of implementation of the external transport network	223
B.4.2	Specific interworking conventions	224
B.4.2.1	Use of the connectionless downlink SI _P service	225
B.4.2.2	Special conventions for mobility class 1 systems	225
B.5	IEEE 802.5 (token ring)	225
B.5.1	Typical configuration	225
B.5.1.1	Examples of implementation of the external transport network	226
B.5.2	Specific interworking conventions	226
B.5.2.1	Special conventions for mobility class 1 systems	226
B.5.2.2	Use of the connectionless downlink SI _P service	226
B.6	Internet protocol	227
B.6.1	Typical configuration	227
B.6.1.1	Examples of implementation of the external transport network	227
B.6.2	Specific interworking conventions	227
B.6.2.1	Special conventions for mobility class 1 systems	227
B.7	Point-to-Point Protocol.....	227
B.7.1	Typical configuration	227
B.7.1.1	Examples of implementation of the external transport network	228
B.7.2	Specific interworking conventions.....	228
B.7.2.1	Special conventions for mobility class 1 systems	228
B.8	Interworking conventions for DPRS Generic Media Encapsulation transport mechanism	228
B.8.1	General	228
B.8.2	Interworking Requirements	229
B.8.2.1	U-plane format and protocol elements.....	229
B.8.2.1.1	Description of the protocol elements of the U-plane header	230
B.8.2.2	SDU handling and interface to DLC.....	230
B.8.2.2.1	Transmitter side procedure.....	230
B.8.2.2.2	Receiver side procedure	231
B.8.3	Application protocols	232
B.8.3.1	General.....	232
B.8.3.2	List of protocols with specific description in the present document.....	232
B.8.3.3	HTTP limited set nr.1	233
B.8.3.4	HTTP limited set nr.2 (Common HTTP profile)	234
B.8.3.5	HTTP limited set nr.3 (Extended HTTP profile)	234
B.8.3.6	Electronic mail (Limited set nr. 1).....	234
B.8.4	Interworking to external networks.....	235
B.8.4.1	Generic Multiprotocol Interworking to External IP Networks	235
B.8.4.2	Multi-context Interworking to an application proxy.....	236
B.8.4.3	Simplified single-context Interworking to External Networks (or to an application proxy).....	236
Annex C (normative):	Interworking conventions for character-oriented services	238

C.1	Scope	238
C.1.1	Scenario A	240
C.1.2	Scenario B	240
C.2	Specific coding for mobility class 2	241
C.2.1	IWU-Attribute coding	241
C.2.2	Default-values	243
C.2.3	Negotiation of the V.24-parameters	244
C.3	Generic interworking conventions	244
C.3.1	PAD functionality.....	244
C.3.1.1	Character formatting	244
C.3.2	Support of SDU size.....	245
C.3.3	LU10 SDU delivery mode.....	245
C.4	V.24 circuits	245
C.4.1	General	245
C.4.2	Encapsulation	246
C.4.2.1	Description.....	246
C.4.2.2	Framing.....	246
C.4.2.3	Coding of encapsulation	246
C.4.2.3.1	DCE-emulation side interpretation.....	247
C.4.2.3.2	DTE-emulation side interpretation.....	247
C.4.2.4	SDU Structure.....	247
C.4.3	Interworking procedures and conventions.....	248
C.4.3.1	General.....	248
C.4.3.1.1	Data forwarding conditions	248
C.4.3.1.2	Dataflow Control.....	248
C.4.3.1.2.1	Software dataflow control	248
C.4.3.1.2.2	Hardware dataflow control	248
C.4.3.1.3	Transmission of U-plane data procedure.....	248
C.4.3.1.4	Receive of U-plane data procedure	248
C.4.3.1.5	V.24 signalling	249
C.4.3.1.6	Configuration a V.24 interface during a Connection	249
C.4.3.2	Fall back procedure.....	249
C.4.3.3	Procedure at the DCE-emulation side IWU.....	249
C.4.3.3.1	DTE-initiated VC establishment.....	249
C.4.3.3.2	DCE-initiated VC establishment	249
C.4.3.3.3	V.24 call release	249
C.4.3.4	Procedure at the DTE-emulation side IWU	250
C.4.3.4.1	DCE-initiated VC establishment	250
C.4.3.4.2	DTE-initiated VC establishment	250
C.4.3.4.3	V.24 call release	250
C.5	Definition of User Control Information Elements.....	250
C.5.1	Mandatory UIEs	250
C.5.2	Optional UIEs.....	250
C.5.3	Information Element Identifier.....	251
Annex D (normative): Support of double and long slot.....		252
D.1	Double and long slot support (2-level modulation).....	252
D.1.1	General	252
D.1.2	Requirements.....	252
D.1.2.1	Frame structure and slot numbering.....	252
D.1.2.2	Multibearer connections	252
D.1.2.3	Modulation schemes	252
D.1.2.4	Void	252
D.1.2.5	Bit MAPs	252
D.1.2.6	C-MUX	252
D.1.2.7	Scrambling.....	252
D.1.2.8	CRC	252
D.1.2.9	B-field type identification.....	253
D.1.2.10	Fixed Part capabilities.....	253