



# SLOVENSKI STANDARD

## SIST EN 301 649 V2.3.1:2015

01-oktober-2015

---

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Paketna radijska storitev DECT (DPRS)**

Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS)

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Ta slovenski standard je istoveten z: **EN 301 649 V2.3.1**  
SIST EN 301 649 V2.3.1:2015  
<https://standards.iteh.ai/catalog/standards/sist/e261d1a3-ddd5-4240-b25d-a1aacc053523/sist-en-301-649-v2-3-1-2015>

---

**ICS:**

33.070.30	Digitalne izboljšane brezvrvične telekomunikacije (DECT)	Digital Enhanced Cordless Telecommunications (DECT)
-----------	----------------------------------------------------------	-----------------------------------------------------

**SIST EN 301 649 V2.3.1:2015**

**en,fr,de**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 649 V2.3.1:2015](https://standards.iteh.ai/catalog/standards/sist/e261dfa3-ddd3-4240-b25d-a1aacc053523/sist-en-301-649-v2-3-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/e261dfa3-ddd3-4240-b25d-a1aacc053523/sist-en-301-649-v2-3-1-2015>

# ETSI EN 301 649 V2.3.1 (2015-03)



## Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS) (standards.iteh.ai)

[SIST EN 301 649 V2.3.1:2015](https://standards.iteh.ai/catalog/standards/sist/e261dfa3-ddd3-4240-b25d-a1aacc053523/sist-en-301-649-v2-3-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/e261dfa3-ddd3-4240-b25d-a1aacc053523/sist-en-301-649-v2-3-1-2015>

---

**Reference**

REN/DECT-00305

---

**Keywords**

access, data, DECT, DPRS, frame relay,  
IMT-2000, internet, interoperability, interworking,  
IP, IPv6, LAN, mobility, multimedia, packet mode,  
profile, radio, synchronization, TDD, TDMA

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 649 V2.3.1:2015

<https://standards.iteh.ai/catalog/standards/sist/e261dfa3-ddd3-4240-b25d-a1aacc05392284-301-649-v2-3-1-2015>

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	15
Foreword.....	15
Modal verbs terminology.....	15
1 Scope .....	16
2 References .....	16
2.1 Normative references .....	16
2.2 Informative references.....	18
3 Definitions, symbols and abbreviations .....	19
3.1 Definitions.....	19
3.2 Symbols.....	20
3.3 Abbreviations .....	21
4 Description of services .....	24
4.1 The DECT Packet Radio Service (DPRS).....	24
4.1.1 Service objectives .....	24
4.1.2 Characteristics of the DECT packet data service.....	25
4.1.3 Performance Objectives .....	25
4.1.4 DPRS U-plane Services .....	26
4.1.5 DPRS operation modes (Classes) .....	27
4.1.6 DPRS System Categories.....	27
4.2 Protocol architecture.....	28
4.2.1 Reference configuration for Internet Protocol and LANs .....	29
4.2.1.1 Reference configuration for Internet Protocol.....	29
4.2.1.2 Reference configuration for IEEE 802.3 [13] .....	30
4.3 Service and feature definitions .....	30
4.3.1 PHL service definitions .....	30
4.3.2 MAC service definitions .....	31
4.3.3 DLC service definitions .....	33
4.3.4 NWK feature definitions.....	34
4.3.5 Application service definitions .....	36
4.3.6 Distributed Communication.....	36
4.3.7 Management Entity.....	36
4.3.8 Call Control (CC) and Mobility Management (MM) Service Class .....	37
4.3.9 U-plane Service and Interworking type .....	37
4.3.10 DPRS System Categories.....	37
4.4 General Class/Service/Interworking support.....	38
4.5 System categories .....	38
4.5.1 Mapping between DPRS categories and features/services .....	38
4.5.2 Supported data rates for equipment declaring compliance to a data category .....	40
4.5.3 Indication of compliance with a data category .....	42
5 PHL requirements .....	43
5.1 Physical Layer services .....	43
5.2 Modulation schemes.....	43
5.3 PHL service to procedure mapping .....	44
5.4 PHL layer procedures.....	44
5.4.1 General radio requirements.....	44
5.4.2 Minimum Normal Transmit Power (NTP).....	44
5.4.3 Radio receiver sensitivity.....	45
5.4.4 Z-field .....	45
5.4.5 Sliding collision detection .....	45
5.4.6 Physical channel availability.....	45
5.4.7 Synchronization window .....	45
5.4.8 Power management.....	45
5.4.9 Fast hopping radio .....	45
6 MAC layer requirements .....	45

6.1	MAC services .....	45
6.2	MAC service to procedure mapping .....	47
7	DLC-layer requirements .....	52
7.1	DLC services .....	52
7.2	DLC feature to procedure mapping .....	52
8	NWK layer requirements .....	53
8.1	NWK features .....	54
8.2	NWK feature to procedure mapping .....	55
8.3	Application features .....	59
8.4	Application feature to procedure mapping .....	59
8.5	Distributed Communications .....	60
8.5.1	Distributed Communications features .....	60
8.6	Distributed Communications feature to procedure mapping .....	60
9	Management Entity Requirements .....	60
9.1	Introduction .....	60
9.1.1	Management Entity (ME) operation modes .....	60
9.1.2	Management Entity (ME) mode to procedures mapping .....	61
9.2	Description of the DPRS operation principles .....	62
9.2.1	General .....	62
9.2.2	Service class 1 .....	62
9.2.3	Service class 2 .....	62
9.2.4	Service class 3 .....	62
9.2.5	Service class 4 .....	63
9.3	Resource and physical connection management for Class 1 and Class 2 systems .....	63
9.3.1	Requirements applicable to the Fixed Part (FP) .....	63
9.3.1.1	Conditions for resumption and management procedures .....	63
9.3.1.1.1	General .....	63
9.3.1.1.2	ME procedures for FT initiated connection resumption .....	63
9.3.1.2	Connection Suspension conditions .....	65
9.3.1.2.1	General .....	65
9.3.1.2.2	Connection suspension due to no data activity .....	65
9.3.1.2.3	Connection suspension due to violation of the minimum number of bearers (MAC Bandwidth command) .....	65
9.3.1.2.4	Connection suspension by loss of all received bearers .....	65
9.3.1.2.5	Activation of Fast Scan mode and/or high duty cycle paging detection after Connection suspension .....	66
9.3.1.3	Conditions for Bandwidth modification .....	66
9.3.1.3.1	General .....	66
9.3.2	Requirements applicable to the Portable Part (PP) .....	66
9.3.2.1	Conditions for connection resumption .....	66
9.3.2.1.1	Procedure for PT initiated Connection resumption .....	66
9.3.2.1.2	"RFP-busy-for-data" flag .....	67
9.3.2.1.3	Waiting time for collision avoidance after deactivation of "RFP-busy-for-data" flag .....	67
9.3.2.1.4	Bandwidth after resumption .....	67
9.3.2.1.5	Resumption rejection by the FT .....	67
9.3.2.2	Conditions for Connection Suspension .....	67
9.3.2.2.1	General .....	67
9.3.2.2.2	Connection suspension due to no data activity .....	67
9.3.2.2.3	Connection suspension due to violation of the minimum number of bearers (MAC Bandwidth command) .....	68
9.3.2.2.4	Connection suspension by loss of all received bearers .....	68
9.3.2.2.5	Activation of fast scan mode after Connection suspension .....	68
9.3.2.3	Conditions for Bandwidth modification .....	68
9.3.2.3.1	General .....	68
9.3.2.3.2	Rules for the bandwidth request by the PP .....	68
9.4	Logical Connection and virtual call management .....	69
9.4.1	Requirements for class 1 devices .....	69
9.4.2	Requirements for class 2 devices .....	69
9.4.2.1	General Description .....	69
9.4.2.2	Normal procedures of virtual call setup and release .....	69

9.4.2.2.1	Identification of the call as a DPRS call .....	69
9.4.2.2.2	Bandwidth attributes of the call .....	69
9.4.2.2.3	Creation of DLC link and MAC logical connection .....	70
9.4.2.2.4	Temporary states during the setup procedure .....	70
9.4.2.3	Abnormal release of Virtual Calls .....	70
9.4.2.4	Release of Logical Connection .....	70
9.4.2.5	The handshake (stay alive) procedure .....	70
9.4.3	Requirements for class 3 devices .....	71
9.4.3.1	General Description .....	71
9.4.3.1.1	Identification of the call as a DPRS call .....	71
9.4.3.1.2	Connection attributes .....	71
9.4.4	Requirements for class 4 devices .....	71
9.4.4.1	General Description .....	71
9.4.4.1.1	Identification of the call as a DPRS call .....	72
9.5	Resource and physical connection management for Class 3 and Class 4 devices .....	72
9.5.1	Simplified Class 3 connection management .....	72
9.5.2	Suspend management (Tx side) .....	72
9.5.3	Suspend management (Rx side) .....	72
9.5.4	Resume management .....	72
9.5.5	Stay alive (timer control) .....	72
9.5.6	Stay alive (periodic resume) .....	72
9.5.7	Simplified Class 4 connection management .....	73
10	MAC layer procedures .....	73
10.1	General .....	73
10.1.1	Frame and multiframe structure .....	73
10.1.2	Bit mappings .....	73
10.1.2.1	Multiple bitmappings rule .....	73
10.1.3	Void .....	73
10.1.4	Scrambling .....	73
10.1.5	Error control .....	73
10.1.6	Void .....	73
10.1.7	Void .....	73
10.1.8	RFP idle receiver scan sequence .....	74
10.1.9	PT receiver scan sequence .....	74
10.1.10	PT states and state transitions .....	74
10.1.10.1	PT states and state transitions for PTs not supporting fast setup .....	74
10.1.10.2	PT states and state transitions for PTs supporting fast setup .....	74
10.1.10.2.1	Fast setup control information provided by the FT .....	75
10.1.10.2.2	PT states and state transitions when PT and FT supports complete setup detection .....	75
10.1.10.2.3	PT states and state transitions when PT and FT supports Selective setup detection only .....	76
10.1.10.2.4	Fast setup control information provided using MAC paging .....	76
10.1.11	Identities .....	77
10.2	Non continuous broadcast .....	77
10.2.1	Request for specific Q channel information .....	77
10.2.2	Request for a new dummy .....	77
10.3	Downlink broadcast .....	77
10.3.1	$N_T$ messages .....	77
10.3.2	$Q_T$ messages .....	77
10.3.2.1	$Q_T$ - static system information .....	77
10.3.2.2	$Q_T$ - FP capabilities .....	78
10.3.2.2.1	Standard FP Capabilities .....	78
10.3.2.2.2	Extended FP Capabilities .....	79
10.3.2.2.3	Extended FP Capabilities part 2 .....	79
10.3.2.3	$Q_T$ - SARI list contents .....	80
10.3.2.4	Multiframe number .....	80
10.4	Paging broadcast .....	80
10.4.1	Paging message formats .....	80
10.4.1.1	Long or full page message format .....	81
10.4.1.2	Short page message format .....	81
10.4.1.3	Zero length page message format .....	82
10.4.1.4	MAC resume and control page message format .....	82

10.4.1.5	MAC layer information in zero and short length paging messages.....	83
10.4.1.5.1	RFP status.....	83
10.4.2	MAC layer information messages procedures.....	84
10.4.2.1	Blind slot information for circuit mode service.....	84
10.4.2.2	Bearer handover/replacement information.....	84
10.4.2.3	Other bearer position.....	84
10.4.2.4	Recommended other bearer position.....	84
10.4.2.5	Dummy or C/L bearer position.....	84
10.4.2.6	C/L bearer position.....	84
10.4.2.7	RFP-status and Modulation Types.....	85
10.4.2.8	Blind slot information for packet mode service.....	85
10.4.3	Paging Procedures.....	85
10.4.3.1	LCE Paging.....	85
10.4.3.2	MAC Paging.....	85
10.4.3.2.1	Support of MAC Paging commands for resume and paging detection control.....	85
10.4.3.2.2	Support of MAC Paging codes for control of fast setup.....	86
10.4.4	Paging detection.....	86
10.4.4.1	Normal duty cycle.....	86
10.4.4.2	High duty cycle.....	86
10.4.4.3	Low duty cycle.....	86
10.5	Logical Connection Setup.....	86
10.6	Logical Connection Release.....	87
10.7	Connection Modification.....	87
10.7.1	Connection Modification to change bandwidth.....	87
10.7.1.1	Bandwidth negotiation.....	87
10.7.1.1.1	Bandwidth negotiation with A-field messages.....	88
10.7.1.1.2	Bandwidth negotiation with B-field messages.....	88
10.7.1.1.3	Order and sequence of operations.....	89
10.7.1.2	Bandwidth modification.....	89
10.7.1.2.1	Order and sequence of operations.....	90
10.7.1.3	Suspend.....	90
10.7.1.4	Resume.....	94
10.7.1.5	Bandwidth modification rejection and error handling.....	94
10.7.1.5.1	Error handling.....	95
10.7.2	Connection modification to change service type, slot type, modulation type or adaptive code rate..	95
10.7.2.1	Connection modification to change MAC service type.....	95
10.7.2.2	Connection modification to change slot type.....	95
10.7.2.3	Connection modification to change the modulation scheme and adaptive code rate.....	96
10.7.2.4	ATTRIBUTES_T.req/cfm.....	96
10.8	Physical Connection Setup.....	97
10.8.1	Single bearer physical connection setup.....	97
10.8.2	Multibearer Physical Connection setup.....	98
10.9	Physical Connection Release.....	98
10.10	Bearer Setup.....	98
10.10.1	Duplex bearer setup procedures.....	98
10.10.1.1	MAC control messages.....	98
10.10.1.2	PT initiated initial duplex bearer setup (pilot bearer).....	99
10.10.1.2.1	Prerequisites.....	100
10.10.1.2.2	Usage of channel list procedures.....	100
10.10.1.2.3	Detailed procedure description.....	100
10.10.1.3	FT initiated initial duplex bearer setup (pilot bearer).....	102
10.10.1.3.1	Prerequisites.....	102
10.10.1.3.2	Usage of channel list procedures.....	102
10.10.1.3.3	Detailed procedure description.....	102
10.10.1.4	PT initiated additional duplex bearer setup.....	104
10.10.1.4.1	Use of the procedure and Master side.....	105
10.10.1.4.2	Prerequisites.....	105
10.10.1.4.3	Usage of channel list procedures.....	105
10.10.1.4.4	Detailed procedure description.....	107
10.10.1.5	FT initiated additional duplex bearer setup.....	109
10.10.2	Double simplex bearer setup.....	109
10.10.2.1	MAC control messages.....	110



10.10.2.2	Upstream double simplex bearer setup .....	111
10.10.2.2.1	Use of the procedure and T-side.....	111
10.10.2.2.2	Prerequisites .....	111
10.10.2.2.3	Channel selection and usage of channel list procedures .....	111
10.10.2.2.4	Detailed procedure description.....	112
10.10.2.3	Downstream double simplex bearer setup.....	113
10.10.2.3.1	Use of the procedure and T-side.....	114
10.10.2.3.2	Prerequisites .....	114
10.10.2.3.3	Channel selection and usage of channel list procedures .....	114
10.10.2.3.4	Detailed procedure description.....	114
10.11	Bearer Release procedures .....	116
10.11.1	Unacknowledged release .....	117
10.11.2	Crossed release (duplex bearers only) .....	117
10.11.3	Acknowledged release .....	117
10.11.4	Fast release.....	118
10.11.5	Definition of the procedure to use and the Master side for the different release cases .....	118
10.11.5.1	Suspend cases.....	118
10.11.5.1.1	FT initiated suspend .....	118
10.11.5.1.2	PT initiated suspend .....	119
10.11.5.2	Bandwidth modification cases .....	119
10.11.5.2.1	Reversal of asymmetric connection: from asymmetric downlink to uplink .....	119
10.11.5.2.2	Reversal of asymmetric connection: from asymmetric uplink to downlink .....	119
10.11.5.2.3	Modification from asymmetric downlink to symmetric .....	119
10.11.5.2.4	Modification from asymmetric uplink to symmetric .....	119
10.11.5.2.5	Modification from symmetric to asymmetric downlink (with release of duplex bearers)....	120
10.11.5.2.6	Modification from symmetric to asymmetric uplink (with release of duplex bearers).....	120
10.11.6	Listen for setup control codes in Release message .....	120
10.12	Advanced connection handover .....	120
10.13	I channel operation .....	120
10.13.1	Protected I channel error_detect mode.....	121
10.13.2	Protected I channel error_correct mode.....	121
10.13.2.1	Unilateral jump .....	121
10.13.2.2	Bearer release .....	121
10.13.3	Connectionless SI <sub>P</sub> mode.....	121
10.14	C channel operation.....	122
10.14.1	C <sub>S</sub> channel.....	122
10.14.2	C <sub>F</sub> channel.....	122
10.14.2.1	Priority schema of the C <sub>F</sub> channel.....	122
10.15	Encryption .....	123
10.15.1	Encryption process - initialization and synchronization .....	123
10.15.2	Encryption mode control .....	124
10.15.2.1	M <sub>T</sub> message .....	125
10.15.2.2	PT procedure for enabling encryption.....	125
10.15.2.3	PT procedure for disabling encryption.....	125
10.15.3	Handover encryption process.....	125
10.16	Quality control.....	125
10.16.1	RFPI handshake .....	125
10.16.2	PT frequency correction.....	125
10.16.3	Bearer quality report .....	125
10.16.3.1	Bearer quality report for asymmetric bearers.....	126
10.16.4	Bearer and connection control .....	126
10.16.5	A-CRC handshake .....	127
10.17	Physical channel selection.....	127
10.18	Bearer replacement.....	128
10.19	Bearer handover request.....	128
10.20	G <sub>F</sub> channel .....	128
10.20.1	G <sub>F</sub> channel data.....	128
10.20.1.1	G <sub>F</sub> channel transmission.....	128
10.20.1.2	G <sub>F</sub> channel reception .....	128
10.21	Time multiplexers.....	128
10.21.1	A-field Multiplexer .....	128
10.21.1.1	Tail Multiplexer (T-MUX).....	128

10.21.1.2	A-tail identifications.....	128
10.21.2	B-field control Multiplexer (E/U-MUX) .....	129
10.21.2.1	B-field control Multiplexer (E/U-MUX), basic modes .....	129
10.21.2.1.1	U-type Multiplexer .....	129
10.21.2.1.2	E-type Multiplexer, all MAC control .....	129
10.21.2.1.3	E/U-Mux priority schema .....	129
10.21.2.1.4	B-field identifications (basic) .....	129
10.21.2.2	B-field control Multiplexer (E/U-MUX), C <sub>F</sub> modes .....	129
10.21.2.2.1	E-type Multiplexer, all modes .....	129
10.21.2.2.2	E/U-Mux priority schema .....	129
10.21.2.2.3	B-field identifications (C <sub>F</sub> ) .....	129
10.21.2.3	B-field control Multiplexer (E/U-MUX), E+U modes .....	130
10.21.2.3.1	E+U-type Multiplexer .....	130
10.21.2.3.2	E/U-Mux priority schema .....	130
10.21.2.3.3	B-field identifications (E+U type) .....	130
10.22	I <sub>PF</sub> channel .....	130
10.22.1	I <sub>PF</sub> channel general .....	130
10.22.2	I <sub>PF</sub> channel advanced procedures .....	130
10.22.3	I <sub>PF</sub> channel error_correct procedures .....	131
10.22.4	SI <sub>PF</sub> channel .....	131
10.23	A-field (M <sub>T</sub> ) procedures .....	131
10.23.1	General.....	131
10.23.2	PT initiated A-field advanced bearer setup.....	131
10.23.2.1	M <sub>T</sub> access request message .....	131
10.23.2.2	M <sub>T</sub> Attributes_T.req/cfm message .....	132
10.23.3	A-field connection/bearer release .....	133
10.23.3.1	M <sub>T</sub> message .....	133
10.23.4	A-field bearer handover request.....	133
10.23.4.1	M <sub>T</sub> message .....	133
10.23.5	A-field connection handover request .....	134
10.23.5.1	M <sub>T</sub> message .....	134
11	DLC layer procedures .....	134
11.1	LU10 Enhanced Frame RELay service (EFREL) .....	134
11.1.1	Window size .....	135
11.1.2	U-plane transmission class 2.....	135
11.1.2.1	Sending side procedures.....	135
11.1.2.2	Receiving side procedure .....	135
11.1.3	SDU transmission and delivery mode.....	136
11.2	FU 10 framing (FU10a, FU10b, FU10c).....	136
11.2.1	FU10a .....	136
11.2.2	FU10b .....	136
11.2.3	FU10c .....	136
11.2.3.1	Insertion of FU10c frames in FU10a frames of the opposite link .....	137
11.3	Class A operation .....	137
11.3.1	Class A link establishment.....	137
11.3.1.1	Lower Layer Management Entity (LLME) establishment of a MAC connection.....	137
11.3.2	Class A acknowledged information transfer .....	139
11.3.3	Class A link release.....	139
11.3.4	Class A link re-establishment .....	139
11.4	Class U operation .....	140
11.4.1	Class U use of LLN for unacknowledged information transfer .....	140
11.4.2	Class U link establishment.....	140
11.4.3	Class U unacknowledged information transfer .....	140
11.4.4	Class U unacknowledged release.....	140
11.5	Lc frame delimiting and sequencing service .....	140
11.5.1	C <sub>S</sub> channel fragmentation and recombination .....	140
11.5.2	C <sub>F</sub> channel fragmentation and recombination .....	140
11.5.3	Selection of logical channels (C <sub>S</sub> and C <sub>F</sub> ) .....	140
11.6	Broadcast Lb service .....	141
11.6.1	Normal broadcast.....	141
11.6.2	Expedited broadcast.....	142

SIST EN 301 649 V2.3.1:2015

<https://standards.iteh.ai/catalog/standards/sist/c261dd3-ddd3-4240-b25d-afaecc053525/sist-en-301-649-v2-3-1-2015>

11.7	Connection handover.....	142
11.7.1	Class A connection handover.....	142
11.7.1.1	Voluntary handover.....	143
11.7.1.2	Associated procedure .....	143
11.7.1.2.1	LLME connection handover management.....	143
11.7.1.3	Exceptional case.....	143
11.7.1.3.1	Receipt of a request for link release .....	143
11.8	Connection modification .....	143
11.9	Encryption switching.....	145
11.9.1	Associated procedure.....	145
11.9.1.1	Providing Encryption key to the MAC layer.....	145
11.9.2	Exceptional cases.....	145
11.9.2.1	Encryption fails .....	145
11.9.2.2	Connection handover of ciphered connections.....	145
11.10	Connectionless point-to-multipoint transmission .....	145
12	NWK layer procedures.....	146
12.1	PT initiated virtual call request.....	146
12.2	FT initiated virtual call request.....	147
12.3	Terminal capability indication.....	148
12.4	Internal call keypad .....	151
12.5	Call Resources/Parameters negotiation .....	151
12.5.1	General requirements.....	151
12.5.2	Allowable values on initiating side.....	152
12.5.3	Negotiation process.....	155
12.5.4	Allowable values in the answer .....	156
12.5.5	Default values for class 2 on initiating side .....	160
12.5.6	Exceptional cases.....	162
12.5.7	IP address allocation (IP IWU only).....	162
12.6	Service Change procedures .....	162
12.6.1	Service change - Bandwidth Change (including symmetry type indicator).....	162
12.6.1.1	Associated procedures.....	165
12.6.1.1.1	Timer F/P < CC_service > management .....	165
12.6.1.2	Exceptional cases .....	165
12.6.1.2.1	Service change request is rejected .....	165
12.6.1.3	Examples.....	165
12.6.2	Service change - slot type change.....	166
12.6.2.1	Associated procedures.....	166
12.6.2.2	Exceptional cases .....	166
12.6.2.3	Examples .....	166
12.6.3	Service change - MAC service change .....	166
12.6.3.1	Associated procedures.....	166
12.6.3.2	Exceptional cases .....	166
12.6.3.3	Examples.....	166
12.6.4	Service change - modulation schema change .....	166
12.6.4.1	Associated procedures.....	167
12.6.4.2	Exceptional cases .....	167
12.6.4.3	Examples.....	167
12.6.5	Service change - DPRS Management Class and other Call-attributes change.....	167
12.6.5.1	Associated procedures.....	167
12.6.5.2	Exceptional cases .....	167
12.6.5.3	Examples.....	167
12.6.6	Service change - MAC Packet lifetime, DLC Window size, DLC Transit delay and C <sub>F</sub> channel attributes change .....	167
12.6.6.1	Associated procedures.....	168
12.6.6.2	Exceptional cases .....	168
12.6.6.3	Examples.....	168
12.7	Service change - IWU-attributes change .....	168
12.7.1	IWU-attributes change - General .....	168
12.7.1.1	Associated procedures.....	169
12.7.1.2	Exceptional cases .....	169
12.7.1.3	Examples.....	169

12.7.2	Interworking type change .....	169
12.7.3	IP address change (IP IWU) .....	169
12.7.4	Maximum SDU size change .....	169
12.8	Dynamic Parameters Allocation.....	170
12.8.1	General requirements.....	170
12.8.2	Sent IE and Default IE Dynamic Parameter Allocation.....	170
12.8.2.1	Sent-IE mechanism .....	170
12.8.2.2	Default-IE mechanisms .....	170
12.8.2.3	Support of these mechanisms .....	171
12.8.2.4	Simultaneous use of both mechanisms (one from each side).....	171
12.8.3	Transport of the <<SETUP CAPABILITY>> IE (when used).....	172
12.8.4	Service and parameter settings support indication (PT or FT).....	172
12.8.5	Application media protocol support indication (PT and FT) .....	176
12.8.6	Allowed and mandatory values for DPRS Class 2 PT and FT devices.....	178
12.8.7	Allowed values for DPRS Class 3 and 4 devices (PT or FT) .....	180
12.8.8	Transport with {MM-INFO-SUGGEST} message (FT to PT).....	182
12.8.9	Transport with {CLMS-FIXED} message (FT to PT).....	182
12.8.10	Class 2 Default Dynamic Parameters Allocation for PT and FT devices .....	182
12.9	Cipher-switching initiated by PT.....	183
12.10	Temporary Identity Assign.....	184
12.10.1	Associated procedures .....	184
12.10.1.1	Timer F-< MM_ident.1 > management.....	184
12.10.2	Exceptional cases.....	185
12.10.2.1	PT rejects the identity assignment.....	185
12.11	Indirect FT initiated link establishment.....	185
12.11.1	Indirect FT initiated link establishment for devices supporting complete MAC control procedures (DPRS-M.5).....	185
12.11.1.1	Initial setup paging.....	185
12.11.1.1.1	Assumptions for Short paging format or for Full format with IPUI.....	185
12.11.1.1.2	Coding for Full paging format with TPUI.....	185
12.11.1.1.3	Message in case of short format .....	186
12.11.1.1.4	Message in case of full format with TPUI.....	187
12.11.1.1.5	Message in case of full format with IPUI.....	188
12.11.1.2	DPRS Resume paging.....	188
12.11.1.2.1	Assumptions for Short paging format.....	188
12.11.1.2.2	Coding for Full paging format with TPUI.....	188
12.11.1.2.3	Message in case of short format .....	189
12.11.1.2.4	Message in case of full format with TPUI.....	190
12.11.1.2.5	LCE Resume Procedure description.....	191
12.11.2	Indirect FT initiated link establishment for devices supporting simplified A-field MAC control procedures (DPRS-M.30) .....	191
12.11.2.1	Initial setup paging.....	191
12.11.2.1.1	Assumptions for Short paging format or for Full format with IPUI.....	191
12.11.2.1.2	Coding for Full paging format with TPUI.....	191
12.11.2.1.3	Message in case of short format .....	192
12.11.2.1.4	Message in case of full format with TPUI.....	192
12.11.2.2	DPRS Resume paging.....	193
12.11.2.2.1	Assumptions for Short paging format.....	193
12.11.2.2.2	Coding for Full paging format with TPUI.....	193
12.11.2.2.3	Message in case of short format .....	193
12.11.2.2.4	Message in case of full format with TPUI.....	194
12.11.2.2.5	LCE Resume Procedure description.....	195
12.12	Fast paging .....	195
12.13	Collective and Group Ringing.....	195
12.14	Direct FT initiated link establishment .....	196
12.14.1	Exceptional case .....	197
12.14.1.1	Link establishment failure.....	197
12.15	Void.....	198
12.16	Broadcast attributes management.....	198
12.16.1	Higher Layer capabilities.....	198
12.16.2	Extended Higher Layer capabilities.....	198
12.16.3	Extended Higher Layer capabilities part 2.....	199

12.17	U-plane handling .....	199
12.18	Management of MM procedures .....	200
12.19	Management - PMID .....	200
12.20	Length of NWK layer messages .....	200
12.21	Identities .....	201
13	Distributed Communications.....	201
13.1	Void.....	201
13.2	General Requirements .....	201
13.2.1	DCDL-net .....	201
13.2.2	Subscription .....	201
13.2.3	Communication.....	201
13.3	Procedure description .....	201
13.3.1	HyP Identities .....	201
13.3.2	Membership Access Rights Allocation.....	201
13.3.3	Re-initialization of membership access rights .....	201
13.3.4	Members Data Transfer .....	202
13.3.5	Presence/Absence Indication .....	202
13.3.6	Bandwidth management .....	202
13.3.7	Direct Link Establishment .....	202
13.3.8	Indirect Link Establishment .....	202
13.3.9	MASTER management.....	202
13.3.9.1	MASTER assign .....	202
13.3.9.2	MASTER Change .....	202
13.3.9.3	DCDL-net System bearer management.....	203
13.3.10	Common Subscription Database management.....	203
13.3.11	Handover issues.....	203
13.4	Elements of Messages/Information Elements .....	203
13.5	Usage of PPs or FPs in DCDL-net.....	203
<b>Annex A (normative): Operating parameters .....</b>		<b>204</b>
A.1	ME operating parameters .....	204
A.1.1	Constants (applicable to class 1 and class 2 devices) .....	204
A.1.2	Equations.....	204
A.1.2.1	Waiting time for collision avoidance (WtA).....	204
A.1.2.1.1	Description .....	204
A.1.2.1.2	Formula .....	204
A.1.2.2	Waiting time for congestion avoidance (WtB) .....	204
A.1.2.2.1	Description .....	204
A.1.2.2.2	Formula .....	205
A.1.3	Variable parameters (class 2 systems only).....	205
A.1.3.1	Parameters set by the FP (class 2 systems only).....	205
A.1.3.2	Negotiable parameters between FP and PP (class 2 systems only).....	206
A.1.3.2.1	Conditions of negotiation.....	206
A.1.3.2.1.1	Negotiation of T909 .....	206
A.1.3.2.1.2	Negotiation of T911 .....	206
A.1.4	Configuration capabilities for class 1 devices .....	207
A.2	Default coding of <<IWU-ATTRIBUTES>>, << CALL-ATTRIBUTES >>, << CONNECTION-ATTRIBUTES >>, << WINDOW SIZE >>, << TRANSIT DELAY >> and << SETUP-CAPABILITY >> information elements for DPRS Basic Services.....	210
A.2.1	Default setup attributes for basic service "light data service, with Class 4 DPRS management" (code "1001"B).....	210
A.2.2	Default setup attributes for basic service "light data service with Class 3 DPRS management" (code "1010"B).....	213
<b>Annex B (normative): Interworking conventions for the Frame Relay (FREL) service .....</b>		<b>215</b>
B.1	Scope of this annex.....	215
B.1.1	Typical configuration for the Frame Relay service .....	215
B.2	Specific codings for mobility class 2 .....	216
B.2.1	IWU-ATTRIBUTES information element coding .....	216

B.2.1.1	Profile subtype attributes (octet group 6) of IWU-ATTRIBUTES information element.....	217
B.2.1.1.1	IEEE 802.3/Ethernet .....	217
B.2.1.1.2	IEEE 802.5 (Token-Ring) .....	217
B.2.1.1.3	Internet Protocol (IP).....	218
B.2.1.1.3.1	Dynamic IP address allocation .....	218
B.2.1.1.4	DPRS Generic media encapsulation .....	219
B.2.1.1.4.1	Description of the different fields:.....	219
B.2.1.1.4.2	Optional control octets .....	220
B.2.1.1.4.3	D-GMEP Protocol identifier codes.....	222
B.2.2	IWU attributes implemented .....	222
B.3	Generic Frame Relay service interworking conventions.....	223
B.3.1	DLC U-plane service.....	223
B.3.2	Transmission bit order.....	223
B.3.3	Support of SDU size.....	223
B.3.4	SI <sub>P</sub> connectionless downlink .....	223
B.4	IEEE 802.3/Ethernet.....	223
B.4.1	Typical configuration .....	223
B.4.1.1	Examples of implementation of the external transport network .....	223
B.4.2	Specific interworking conventions .....	224
B.4.2.1	Use of the connectionless downlink SI <sub>P</sub> service .....	225
B.4.2.2	Special conventions for mobility class 1 systems .....	225
B.5	IEEE 802.5 (token ring) .....	225
B.5.1	Typical configuration .....	225
B.5.1.1	Examples of implementation of the external transport network .....	226
B.5.2	Specific interworking conventions .....	226
B.5.2.1	Special conventions for mobility class 1 systems .....	226
B.5.2.2	Use of the connectionless downlink SI <sub>P</sub> service .....	226
B.6	Internet protocol .....	227
B.6.1	Typical configuration .....	227
B.6.1.1	Examples of implementation of the external transport network .....	227
B.6.2	Specific interworking conventions .....	227
B.6.2.1	Special conventions for mobility class 1 systems .....	227
B.7	Point-to-Point Protocol.....	227
B.7.1	Typical configuration .....	227
B.7.1.1	Examples of implementation of the external transport network .....	228
B.7.2	Specific interworking conventions .....	228
B.7.2.1	Special conventions for mobility class 1 systems .....	228
B.8	Interworking conventions for DPRS Generic Media Encapsulation transport mechanism .....	228
B.8.1	General .....	228
B.8.2	Interworking Requirements .....	229
B.8.2.1	U-plane format and protocol elements.....	229
B.8.2.1.1	Description of the protocol elements of the U-plane header .....	230
B.8.2.2	SDU handling and interface to DLC.....	230
B.8.2.2.1	Transmitter side procedure.....	230
B.8.2.2.2	Receiver side procedure .....	231
B.8.3	Application protocols .....	232
B.8.3.1	General.....	232
B.8.3.2	List of protocols with specific description in the present document.....	232
B.8.3.3	HTTP limited set nr.1 .....	233
B.8.3.4	HTTP limited set nr.2 (Common HTTP profile) .....	234
B.8.3.5	HTTP limited set nr.3 (Extended HTTP profile) .....	234
B.8.3.6	Electronic mail (Limited set nr. 1).....	234
B.8.4	Interworking to external networks.....	235
B.8.4.1	Generic Multiprotocol Interworking to External IP Networks .....	235
B.8.4.2	Multi-context Interworking to an application proxy.....	236
B.8.4.3	Simplified single-context Interworking to External Networks (or to an application proxy).....	236
<b>Annex C (normative):</b>	<b>Interworking conventions for character-oriented services .....</b>	<b>238</b>

C.1	Scope .....	238
C.1.1	Scenario A .....	240
C.1.2	Scenario B .....	240
C.2	Specific coding for mobility class 2 .....	241
C.2.1	IWU-Attribute coding .....	241
C.2.2	Default-values .....	243
C.2.3	Negotiation of the V.24-parameters .....	244
C.3	Generic interworking conventions .....	244
C.3.1	PAD functionality.....	244
C.3.1.1	Character formatting .....	244
C.3.2	Support of SDU size.....	245
C.3.3	LU10 SDU delivery mode.....	245
C.4	V.24 circuits .....	245
C.4.1	General .....	245
C.4.2	Encapsulation .....	246
C.4.2.1	Description.....	246
C.4.2.2	Framing.....	246
C.4.2.3	Coding of encapsulation .....	246
C.4.2.3.1	DCE-emulation side interpretation.....	247
C.4.2.3.2	DTE-emulation side interpretation.....	247
C.4.2.4	SDU Structure.....	247
C.4.3	Interworking procedures and conventions.....	248
C.4.3.1	General.....	248
C.4.3.1.1	Data forwarding conditions.....	248
C.4.3.1.2	Dataflow Control.....	248
C.4.3.1.2.1	Software dataflow control .....	248
C.4.3.1.2.2	Hardware dataflow control .....	248
C.4.3.1.3	Transmission of U-plane data procedure.....	248
C.4.3.1.4	Receive of U-plane data procedure .....	248
C.4.3.1.5	V.24 signalling .....	249
C.4.3.1.6	Configuration at a V.24 interface during a Connection .....	249
C.4.3.2	Fall back procedure.....	249
C.4.3.3	Procedure at the DCE-emulation side IWU .....	249
C.4.3.3.1	DTE-initiated VC establishment .....	249
C.4.3.3.2	DCE-initiated VC establishment .....	249
C.4.3.3.3	V.24 call release .....	249
C.4.3.4	Procedure at the DTE-emulation side IWU .....	250
C.4.3.4.1	DCE-initiated VC establishment .....	250
C.4.3.4.2	DTE-initiated VC establishment .....	250
C.4.3.4.3	V.24 call release .....	250
C.5	Definition of User Control Information Elements.....	250
C.5.1	Mandatory UIEs .....	250
C.5.2	Optional UIEs.....	250
C.5.3	Information Element Identifier.....	251
<b>Annex D (normative): Support of double and long slot.....</b>		<b>252</b>
D.1	Double and long slot support (2-level modulation).....	252
D.1.1	General .....	252
D.1.2	Requirements.....	252
D.1.2.1	Frame structure and slot numbering.....	252
D.1.2.2	Multibearer connections .....	252
D.1.2.3	Modulation schemes .....	252
D.1.2.4	Void .....	252
D.1.2.5	Bit MAPs .....	252
D.1.2.6	C-MUX .....	252
D.1.2.7	Scrambling .....	252
D.1.2.8	CRC .....	252
D.1.2.9	B-field type identification.....	253
D.1.2.10	Fixed Part capabilities.....	253