

Draft **ETSI EN 301 649** V2.3.0 (2014-11)



**Digital Enhanced Cordless Telecommunications (DECT);
DECT Packet Radio Service (DPRS)**

*ITeH STANDARDS PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1a03-7024-420a-9e4a-60ebf46acd93/etsi-en-301-649-v2.3.0>*

ReferenceREN/DECT-00305

Keywords

access, data, DECT, DPRS, frame relay,
IMT-2000, internet, interoperability, interworking,
IP, IPv6, LAN, mobility, multimedia, packet mode,
profile, radio, synchronization, TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	15
Foreword.....	15
Modal verbs terminology.....	15
1 Scope	16
2 References	16
2.1 Normative references	17
2.2 Informative references.....	18
3 Definitions, symbols and abbreviations	19
3.1 Definitions.....	19
3.2 Symbols.....	20
3.3 Abbreviations	21
4 Description of services	24
4.1 The DECT Packet Radio Service (DPRS).....	24
4.1.1 Service objectives	24
4.1.2 Characteristics of the DECT packet data service.....	25
4.1.3 Performance Objectives	26
4.1.4 DPRS U-plane Services	26
4.1.5 DPRS operation modes (Classes)	27
4.1.6 DPRS System Categories.....	27
4.2 Protocol architecture.....	28
4.2.1 Reference configuration for Internet Protocol and LANs	29
4.2.1.1 Reference configuration for Internet Protocol.....	29
4.2.1.2 Reference configuration for IEEE 802.3 [13].....	30
4.3 Service and feature definitions	30
4.3.1 PHL service definitions	31
4.3.2 MAC service definitions	31
4.3.3 DLC service definitions	33
4.3.4 NWK feature definitions.....	34
4.3.5 Application service definitions.....	36
4.3.6 Distributed Communication.....	36
4.3.7 Management Entity.....	36
4.3.8 Call Control (CC) and Mobility Management (MM) Service Class.....	37
4.3.9 U-plane Service and Interworking type	37
4.3.10 DPRS System Categories.....	37
4.4 General Class/Service/Interworking support.....	38
4.5 System categories	38
4.5.1 Mapping between DPRS categories and features/services	38
4.5.2 Supported data rates for equipment declaring compliance to a data category	40
4.5.3 Indication of compliance with a data category	42
5 PHL requirements	43
5.1 Physical Layer services	43
5.2 Modulation schemes.....	43
5.3 PHL service to procedure mapping	44
5.4 PHL layer procedures.....	44
5.4.1 General radio requirements.....	44
5.4.2 Minimum Normal Transmit Power (NTP).....	44
5.4.3 Radio receiver sensitivity.....	45
5.4.4 Z-field	45
5.4.5 Sliding collision detection	45
5.4.6 Physical channel availability.....	45
5.4.7 Synchronization window	45
5.4.8 Power management.....	45
5.4.9 Fast hopping radio	45

6	MAC layer requirements	46
6.1	MAC services	46
6.2	MAC service to procedure mapping	47
7	DLC-layer requirements	52
7.1	DLC services	52
7.2	DLC feature to procedure mapping	52
8	NWK layer requirements	53
8.1	NWK features	54
8.2	NWK feature to procedure mapping	55
8.3	Application features	59
8.4	Application feature to procedure mapping	60
8.5	Distributed Communications	60
8.5.1	Distributed Communications features	60
8.6	Distributed Communications feature to procedure mapping	60
9	Management Entity Requirements	61
9.1	Introduction	61
9.1.1	Management Entity (ME) operation modes	61
9.1.2	Management Entity (ME) mode to procedures mapping	62
9.2	Description of the DPRS operation principles	62
9.2.1	General	62
9.2.2	Service class 1	63
9.2.3	Service class 2	63
9.2.4	Service class 3	63
9.2.5	Service class 4	63
9.3	Resource and physical connection management for Class 1 and Class 2 systems	64
9.3.1	Requirements applicable to the Fixed Part (FP)	64
9.3.1.1	Conditions for resumption and management procedures	64
9.3.1.1.1	General	64
9.3.1.1.2	ME procedures for FT initiated connection resumption	64
9.3.1.2	Connection Suspension conditions	66
9.3.1.2.1	General	66
9.3.1.2.2	Connection suspension due to no data activity	66
9.3.1.2.3	Connection suspension due to violation of the minimum number of bearers (MAC Bandwidth command)	66
9.3.1.2.4	Connection suspension by loss of all received bearers	66
9.3.1.2.5	Activation of Fast Scan mode and/or high duty cycle paging detection after Connection suspension	67
9.3.1.3	Conditions for Bandwidth modification	67
9.3.1.3.1	General	67
9.3.2	Requirements applicable to the Portable Part (PP)	67
9.3.2.1	Conditions for connection resumption	67
9.3.2.1.1	Procedure for PT initiated Connection resumption	68
9.3.2.1.2	"RFP-busy-for-data" flag	68
9.3.2.1.3	Waiting time for collision avoidance after deactivation of "RFP-busy-for-data" flag	68
9.3.2.1.4	Bandwidth after resumption	68
9.3.2.1.5	Resumption rejection by the FT	68
9.3.2.2	Conditions for Connection Suspension	68
9.3.2.2.1	General	68
9.3.2.2.2	Connection suspension due to no data activity	69
9.3.2.2.3	Connection suspension due to violation of the minimum number of bearers (MAC Bandwidth command)	69
9.3.2.2.4	Connection suspension by loss of all received bearers	69
9.3.2.2.5	Activation of fast scan mode after Connection suspension	69
9.3.2.3	Conditions for Bandwidth modification	69
9.3.2.3.1	General	69
9.3.2.3.2	Rules for the bandwidth request by the PP	69
9.4	Logical Connection and virtual call management	70
9.4.1	Requirements for class 1 devices	70
9.4.2	Requirements for class 2 devices	70
9.4.2.1	General Description	70

9.4.2.2	Normal procedures of virtual call setup and release.....	71
9.4.2.2.1	Identification of the call as a DPRS call.....	71
9.4.2.2.2	Bandwidth attributes of the call.....	71
9.4.2.2.3	Creation of DLC link and MAC logical connection.....	71
9.4.2.2.4	Temporary states during the setup procedure.....	71
9.4.2.3	Abnormal release of Virtual Calls.....	71
9.4.2.4	Release of Logical Connection.....	72
9.4.2.5	The handshake (stay alive) procedure.....	72
9.4.3	Requirements for class 3 devices.....	73
9.4.3.1	General Description.....	73
9.4.3.1.1	Identification of the call as a DPRS call.....	73
9.4.3.1.2	Connection attributes.....	73
9.4.4	Requirements for class 4 devices.....	73
9.4.4.1	General Description.....	73
9.4.4.1.1	Identification of the call as a DPRS call.....	73
9.5	Resource and physical connection management for Class 3 and Class 4 devices.....	73
9.5.1	Simplified Class 3 connection management.....	73
9.5.2	Suspend management (Tx side).....	73
9.5.3	Suspend management (Rx side).....	74
9.5.4	Resume management.....	74
9.5.5	Stay alive (timer control).....	74
9.5.6	Stay alive (periodic resume).....	74
9.5.7	Simplified Class 4 connection management.....	74
10	MAC layer procedures.....	74
10.1	General.....	74
10.1.1	Frame and multiframe structure.....	74
10.1.2	Bit mappings.....	75
10.1.2.1	Multiple bitmappings rule.....	75
10.1.3	Void.....	75
10.1.4	Scrambling.....	75
10.1.5	Error control.....	75
10.1.6	Void.....	75
10.1.7	Void.....	75
10.1.8	RFP idle receiver scan sequence.....	75
10.1.9	PT receiver scan sequence.....	75
10.1.10	PT states and state transitions.....	76
10.1.10.1	PT states and state transitions for PTs not supporting fast setup.....	76
10.1.10.2	PT states and state transitions for PTs supporting fast setup.....	76
10.1.10.2.1	Fast setup control information provided by the FT.....	77
10.1.10.2.2	PT states and state transitions when PT and FT supports complete setup detection.....	77
10.1.10.2.3	PT states and state transitions when PT and FT supports Selective setup detection only.....	78
10.1.10.2.4	Fast setup control information provided using MAC paging.....	78
10.1.11	Identities.....	78
10.2	Non continuous broadcast.....	79
10.2.1	Request for specific Q channel information.....	79
10.2.2	Request for a new dummy.....	79
10.3	Downlink broadcast.....	79
10.3.1	N _T messages.....	79
10.3.2	Q _T messages.....	80
10.3.2.1	Q _T - static system information.....	80
10.3.2.2	Q _T - FP capabilities.....	81
10.3.2.2.1	Standard FP Capabilities.....	81
10.3.2.2.2	Extended FP Capabilities.....	81
10.3.2.2.3	Extended FP Capabilities part 2.....	82
10.3.2.3	Q _T - SARI list contents.....	82
10.3.2.4	Multiframe number.....	82
10.4	Paging broadcast.....	83
10.4.1	Paging message formats.....	83
10.4.1.1	Long or full page message format.....	83
10.4.1.2	Short page message format.....	84
10.4.1.3	Zero length page message format.....	84

10.4.1.4	MAC resume and control page message format.....	85
10.4.1.5	MAC layer information in zero and short length paging messages.....	85
10.4.1.5.1	RFP status.....	85
10.4.2	MAC layer information messages procedures.....	86
10.4.2.1	Blind slot information for circuit mode service.....	86
10.4.2.2	Bearer handover/replacement information.....	87
10.4.2.3	Other bearer position.....	87
10.4.2.4	Recommended other bearer position.....	87
10.4.2.5	Dummy or C/L bearer position.....	87
10.4.2.6	C/L bearer position.....	87
10.4.2.7	RFP-status and Modulation Types.....	87
10.4.2.8	Blind slot information for packet mode service.....	87
10.4.3	Paging Procedures.....	87
10.4.3.1	LCE Paging.....	87
10.4.3.2	MAC Paging.....	88
10.4.3.2.1	Support of MAC Paging commands for resume and paging detection control.....	88
10.4.3.2.2	Support of MAC Paging codes for control of fast setup.....	88
10.4.4	Paging detection.....	88
10.4.4.1	Normal duty cycle.....	88
10.4.4.2	High duty cycle.....	89
10.4.4.3	Low duty cycle.....	89
10.5	Logical Connection Setup.....	89
10.6	Logical Connection Release.....	89
10.7	Connection Modification.....	90
10.7.1	Connection Modification to change bandwidth.....	90
10.7.1.1	Bandwidth negotiation.....	90
10.7.1.1.1	Bandwidth negotiation with A-field messages.....	91
10.7.1.1.2	Bandwidth negotiation with B-field messages.....	91
10.7.1.1.3	Order and sequence of operations.....	92
10.7.1.2	Bandwidth modification.....	92
10.7.1.2.1	Order and sequence of operations.....	93
10.7.1.3	Suspend.....	93
10.7.1.4	Resume.....	97
10.7.1.5	Bandwidth modification rejection and error handling.....	97
10.7.1.5.1	Error handling.....	98
10.7.2	Connection modification to change service type, slot type, modulation type or adaptive code rate.....	98
10.7.2.1	Connection modification to change MAC service type.....	98
10.7.2.2	Connection modification to change slot type.....	99
10.7.2.3	Connection modification to change the modulation scheme and adaptive code rate.....	99
10.7.2.4	ATTRIBUTES_T.req/cfm.....	99
10.8	Physical Connection Setup.....	100
10.8.1	Single bearer physical connection setup.....	100
10.8.2	Multibearer Physical Connection setup.....	101
10.9	Physical Connection Release.....	101
10.10	Bearer Setup.....	101
10.10.1	Duplex bearer setup procedures.....	101
10.10.1.1	MAC control messages.....	101
10.10.1.2	PT initiated initial duplex bearer setup (pilot bearer).....	103
10.10.1.2.1	Prerequisites.....	103
10.10.1.2.2	Usage of channel list procedures.....	103
10.10.1.2.3	Detailed procedure description.....	103
10.10.1.3	FT initiated initial duplex bearer setup (pilot bearer).....	105
10.10.1.3.1	Prerequisites.....	106
10.10.1.3.2	Usage of channel list procedures.....	106
10.10.1.3.3	Detailed procedure description.....	106
10.10.1.4	PT initiated additional duplex bearer setup.....	108
10.10.1.4.1	Use of the procedure and Master side.....	108
10.10.1.4.2	Prerequisites.....	108
10.10.1.4.3	Usage of channel list procedures.....	108
10.10.1.4.4	Detailed procedure description.....	110
10.10.1.5	FT initiated additional duplex bearer setup.....	113
10.10.2	Double simplex bearer setup.....	113

10.10.2.1	MAC control messages	113
10.10.2.2	Upstream double simplex bearer setup	115
10.10.2.2.1	Use of the procedure and T-side.....	115
10.10.2.2.2	Prerequisites	115
10.10.2.2.3	Channel selection and usage of channel list procedures	115
10.10.2.2.4	Detailed procedure description.....	116
10.10.2.3	Downstream double simplex bearer setup.....	117
10.10.2.3.1	Use of the procedure and T-side.....	118
10.10.2.3.2	Prerequisites	118
10.10.2.3.3	Channel selection and usage of channel list procedures	118
10.10.2.3.4	Detailed procedure description.....	118
10.11	Bearer Release procedures	120
10.11.1	Unacknowledged release	121
10.11.2	Crossed release (duplex bearers only)	121
10.11.3	Acknowledged release	121
10.11.4	Fast release.....	122
10.11.5	Definition of the procedure to use and the Master side for the different release cases	122
10.11.5.1	Suspend cases.....	122
10.11.5.1.1	FT initiated suspend	122
10.11.5.1.2	PT initiated suspend	123
10.11.5.2	Bandwidth modification cases	123
10.11.5.2.1	Reversal of asymmetric connection: from asymmetric downlink to uplink	123
10.11.5.2.2	Reversal of asymmetric connection: from asymmetric uplink to downlink	123
10.11.5.2.3	Modification from asymmetric downlink to symmetric	123
10.11.5.2.4	Modification from asymmetric uplink to symmetric	123
10.11.5.2.5	Modification from symmetric to asymmetric downlink (with release of duplex bearers).....	124
10.11.5.2.6	Modification from symmetric to asymmetric uplink (with release of duplex bearers).....	124
10.11.6	Listen for setup control codes in Release message	124
10.12	Advanced connection handover	124
10.13	I channel operation	124
10.13.1	Protected I channel error_detect mode.....	125
10.13.2	Protected I channel error_correct mode.....	125
10.13.2.1	Unilateral jump	125
10.13.2.2	Bearer reset	125
10.13.3	Connectionless SI _P mode	125
10.14	C channel operation.....	126
10.14.1	C _S channel.....	126
10.14.2	C _F channel.....	126
10.14.2.1	Priority schema of the C _F channel	126
10.15	Encryption	127
10.15.1	Encryption process - initialization and synchronization	127
10.15.2	Encryption mode control	128
10.15.2.1	M _T message	129
10.15.2.2	PT procedure for enabling encryption.....	129
10.15.2.3	PT procedure for disabling encryption.....	129
10.15.3	Handover encryption process.....	129
10.16	Quality control.....	129
10.16.1	RFPI handshake	129
10.16.2	PT frequency correction.....	129
10.16.3	Bearer quality report	130
10.16.3.1	Bearer quality report for asymmetric bearers.....	130
10.16.4	Bearer and connection control	130
10.16.5	A-CRC handshake	131
10.17	Physical channel selection.....	131
10.18	Bearer replacement.....	132
10.19	Bearer handover request.....	132
10.20	G _F channel	132
10.20.1	G _F channel data.....	132
10.20.1.1	G _F channel transmission.....	132
10.20.1.2	G _F channel reception	132
10.21	Time multiplexers.....	132
10.21.1	A-field Multiplexer	132

10.21.1.1	Tail Multiplexer (T-MUX).....	132
10.21.1.2	A-tail identifications.....	133
10.21.2	B-field control Multiplexer (E/U-MUX)	133
10.21.2.1	B-field control Multiplexer (E/U-MUX), basic modes	133
10.21.2.1.1	U-type Multiplexer	133
10.21.2.1.2	E-type Multiplexer, all MAC control	133
10.21.2.1.3	E/U-Mux priority schema	133
10.21.2.1.4	B-field identifications (basic)	133
10.21.2.2	B-field control Multiplexer (E/U-MUX), C _F modes	133
10.21.2.2.1	E-type Multiplexer, all modes	133
10.21.2.2.2	E/U-Mux priority schema	134
10.21.2.2.3	B-field identifications (C _F)	134
10.21.2.3	B-field control Multiplexer (E/U-MUX), E+U modes.....	134
10.21.2.3.1	E+U-type Multiplexer	134
10.21.2.3.2	E/U-Mux priority schema.....	134
10.21.2.3.3	B-field identifications (E+U type).....	134
10.22	I _{PF} channel	134
10.22.1	I _{PF} channel general	134
10.22.2	I _{PF} channel advanced procedures	135
10.22.3	I _{PF} channel error_correct procedures	135
10.22.4	SI _{PF} channel	135
10.23	A-field (M _T) procedures	135
10.23.1	General.....	135
10.23.2	PT initiated A-field advanced bearer setup.....	135
10.23.2.1	M _T access request message	136
10.23.2.2	M _T Attributes_T.req/cfm message	136
10.23.3	A-field connection/bearer release	137
10.23.3.1	M _T message	138
10.23.4	A-field bearer handover request.....	138
10.23.4.1	M _T message	138
10.23.5	A-field connection handover request	138
10.23.5.1	M _T message	138
11	DLC layer procedures	139
11.1	LU10 Enhanced Frame RELay service (EFREL)	139
11.1.1	Window size	139
11.1.2	U-plane transmission class 2.....	140
11.1.2.1	Sending side procedures.....	140
11.1.2.2	Receiving side procedure.....	140
11.1.3	SDU transmission and delivery mode.....	140
11.2	FU 10 framing (FU10a, FU10b, FU10c).....	140
11.2.1	FU10a	140
11.2.2	FU10b	141
11.2.3	FU10c	141
11.2.3.1	Insertion of FU10c frames in FU10a frames of the opposite link	141
11.3	Class A operation	142
11.3.1	Class A link establishment.....	142
11.3.1.1	Lower Layer Management Entity (LLME) establishment of a MAC connection.....	142
11.3.2	Class A acknowledged information transfer	144
11.3.3	Class A link release.....	144
11.3.4	Class A link re-establishment	144
11.4	Class U operation	144
11.4.1	Class U use of LLN for unacknowledged information transfer	145
11.4.2	Class U link establishment.....	145
11.4.3	Class U unacknowledged information transfer	145
11.4.4	Class U unacknowledged release.....	145
11.5	Lc frame delimiting and sequencing service	145
11.5.1	C _S channel fragmentation and recombination.....	145
11.5.2	C _F channel fragmentation and recombination.....	145
11.5.3	Selection of logical channels (C _S and C _F).....	145
11.6	Broadcast Lb service	145
11.6.1	Normal broadcast.....	145

11.6.2	Expedited broadcast.....	147
11.7	Connection handover.....	147
11.7.1	Class A connection handover.....	147
11.7.1.1	Voluntary handover.....	148
11.7.1.2	Associated procedure.....	148
11.7.1.2.1	LLME connection handover management.....	148
11.7.1.3	Exceptional case.....	148
11.7.1.3.1	Receipt of a request for link release.....	148
11.8	Connection modification.....	148
11.9	Encryption switching.....	150
11.9.1	Associated procedure.....	150
11.9.1.1	Providing Encryption key to the MAC layer.....	150
11.9.2	Exceptional cases.....	150
11.9.2.1	Encryption fails.....	150
11.9.2.2	Connection handover of ciphered connections.....	150
11.10	Connectionless point-to-multipoint transmission.....	150
12	NWK layer procedures.....	151
12.1	PT initiated virtual call request.....	151
12.2	FT initiated virtual call request.....	152
12.3	Terminal capability indication.....	153
12.4	Internal call keypad.....	156
12.5	Call Resources/Parameters negotiation.....	156
12.5.1	General requirements.....	156
12.5.2	Allowable values on initiating side.....	157
12.5.3	Negotiation process.....	160
12.5.4	Allowable values in the answer.....	161
12.5.5	Default values for class 2 on initiating side.....	165
12.5.6	Exceptional cases.....	167
12.5.7	IP address allocation (IP IWU only).....	167
12.6	Service Change procedures.....	167
12.6.1	Service change - Bandwidth Change (including symmetry type indicator).....	167
12.6.1.1	Associated procedures.....	170
12.6.1.1.1	Timer F/P < CC_service > management.....	170
12.6.1.2	Exceptional cases.....	170
12.6.1.2.1	Service change request is rejected.....	170
12.6.1.3	Examples.....	170
12.6.2	Service change - slot type change.....	171
12.6.2.1	Associated procedures.....	171
12.6.2.2	Exceptional cases.....	171
12.6.2.3	Examples.....	171
12.6.3	Service change - MAC service change.....	172
12.6.3.1	Associated procedures.....	172
12.6.3.2	Exceptional cases.....	172
12.6.3.3	Examples.....	172
12.6.4	Service change - modulation schema change.....	172
12.6.4.1	Associated procedures.....	172
12.6.4.2	Exceptional cases.....	172
12.6.4.3	Examples.....	172
12.6.5	Service change - DPRS Management Class and other Call-attributes change.....	173
12.6.5.1	Associated procedures.....	173
12.6.5.2	Exceptional cases.....	173
12.6.5.3	Examples.....	173
12.6.6	Service change - MAC Packet lifetime, DLC Window size, DLC Transit delay and C _F channel attributes change.....	173
12.6.6.1	Associated procedures.....	174
12.6.6.2	Exceptional cases.....	174
12.6.6.3	Examples.....	174
12.7	Service change - IWU-attributes change.....	174
12.7.1	IWU-attributes change - General.....	174
12.7.1.1	Associated procedures.....	175
12.7.1.2	Exceptional cases.....	175

12.7.1.3	Examples	175
12.7.2	Interworking type change	175
12.7.3	IP address change (IP IWU)	175
12.7.4	Maximum SDU size change	175
12.8	Dynamic Parameters Allocation.....	175
12.8.1	General requirements.....	175
12.8.2	Sent IE and Default IE Dynamic Parameter Allocation.....	176
12.8.2.1	Sent-IE mechanism	176
12.8.2.2	Default-IE mechanisms	176
12.8.2.3	Support of these mechanisms	176
12.8.2.4	Simultaneous use of both mechanisms (one from each side).....	177
12.8.3	Transport of the <<SETUP CAPABILITY>> IE (when used).....	177
12.8.4	Service and parameter settings support indication (PT or FT).....	178
12.8.5	Application media protocol support indication (PT and FT).....	181
12.8.6	Allowed and mandatory values for DPRS Class 2 PT and FT devices.....	183
12.8.7	Allowed values for DPRS Class 3 and 4 devices (PT or FT)	185
12.8.8	Transport with {MM-INFO-SUGGEST} message (FT to PT).....	187
12.8.9	Transport with {CLMS-FIXED} message (FT to PT).....	187
12.8.10	Class 2 Default Dynamic Parameters Allocation for PT and FT devices	187
12.9	Cipher-switching initiated by PT.....	188
12.10	Temporary Identity Assign.....	189
12.10.1	Associated procedures	189
12.10.1.1	Timer F-< MM_ident.1 > management.....	189
12.10.2	Exceptional cases.....	190
12.10.2.1	PT rejects the identity assignment.....	190
12.11	Indirect FT initiated link establishment.....	190
12.11.1	Indirect FT initiated link establishment for devices supporting complete MAC control procedures (DPRS-M.5).....	190
12.11.1.1	Initial setup paging.....	190
12.11.1.1.1	Assumptions for Short paging format or for Full format with IPUI.....	190
12.11.1.1.2	Coding for Full paging format with TPUI.....	190
12.11.1.1.3	Message in case of short format	191
12.11.1.1.4	Message in case of full format with TPUI.....	192
12.11.1.1.5	Message in case of full format with IPUI.....	193
12.11.1.2	DPRS Resume paging.....	193
12.11.1.2.1	Assumptions for Short paging format.....	193
12.11.1.2.2	Coding for Full paging format with TPUI.....	193
12.11.1.2.3	Message in case of short format	194
12.11.1.2.4	Message in case of full format with TPUI.....	195
12.11.1.2.5	LCE Resume Procedure description.....	196
12.11.2	Indirect FT initiated link establishment for devices supporting simplified A-field MAC control procedures (DPRS-M.30)	196
12.11.2.1	Initial setup paging.....	196
12.11.2.1.1	Assumptions for Short paging format or for Full format with IPUI.....	196
12.11.2.1.2	Coding for Full paging format with TPUI.....	196
12.11.2.1.3	Message in case of short format	197
12.11.2.1.4	Message in case of full format with TPUI.....	197
12.11.2.2	DPRS Resume paging.....	198
12.11.2.2.1	Assumptions for Short paging format.....	198
12.11.2.2.2	Coding for Full paging format with TPUI.....	198
12.11.2.2.3	Message in case of short format	198
12.11.2.2.4	Message in case of full format with TPUI.....	199
12.11.2.2.5	LCE Resume Procedure description.....	200
12.12	Fast paging	200
12.13	Collective and Group Ringing.....	200
12.14	Direct FT initiated link establishment	201
12.14.1	Exceptional case	202
12.14.1.1	Link establishment failure.....	202
12.15	Void.....	203
12.16	Broadcast attributes management.....	203
12.16.1	Higher Layer capabilities.....	203
12.16.2	Extended Higher Layer capabilities.....	203

12.16.3	Extended Higher Layer capabilities part 2.....	204
12.17	U-plane handling.....	204
12.18	Management of MM procedures.....	205
12.19	Management - PMID.....	205
12.20	Length of NWK layer messages.....	205
12.21	Identities.....	206
13	Distributed Communications.....	206
13.1	Void.....	206
13.2	General Requirements.....	206
13.2.1	DCDL-net.....	206
13.2.2	Subscription.....	206
13.2.3	Communication.....	206
13.3	Procedure description.....	206
13.3.1	HyP Identities.....	206
13.3.2	Membership Access Rights Allocation.....	206
13.3.3	Re-initialization of membership access rights.....	207
13.3.4	Members Data Transfer.....	207
13.3.5	Presence/Absence Indication.....	207
13.3.6	Bandwidth management.....	207
13.3.7	Direct Link Establishment.....	207
13.3.8	Indirect Link Establishment.....	207
13.3.9	MASTER management.....	208
13.3.9.1	MASTER assign.....	208
13.3.9.2	MASTER Change.....	208
13.3.9.3	DCDL-net System bearer management.....	208
13.3.10	Common Subscription Database management.....	208
13.3.11	Handover issues.....	208
13.4	Elements of Messages/Information Elements.....	208
13.5	Usage of PPs or FPs in DCDL-net.....	208
Annex A (normative):	Operating parameters.....	209
A.1	ME operating parameters.....	209
A.1.1	Constants (applicable to class 1 and class 2 devices).....	209
A.1.2	Equations.....	209
A.1.2.1	Waiting time for collision avoidance (WtA).....	209
A.1.2.1.1	Description.....	209
A.1.2.1.2	Formula.....	209
A.1.2.2	Waiting time for congestion avoidance (WtB).....	210
A.1.2.2.1	Description.....	210
A.1.2.2.2	Formula.....	210
A.1.3	Variable parameters (class 2 systems only).....	210
A.1.3.1	Parameters set by the FP (class 2 systems only).....	210
A.1.3.2	Negotiable parameters between FP and PP (class 2 systems only).....	211
A.1.3.2.1	Conditions of negotiation.....	211
A.1.3.2.1.1	Negotiation of T909.....	211
A.1.3.2.1.2	Negotiation of T911.....	211
A.1.4	Configuration capabilities for class 1 devices.....	212
A.2	Default coding of <<IWU-ATTRIBUTES>>, <<CALL-ATTRIBUTES >>, <<CONNECTION-ATTRIBUTES >>, <<WINDOW SIZE >>, <<TRANSIT DELAY >> and <<SETUP-CAPABILITY >> information elements for DPRS Basic Services.....	215
A.2.1	Default setup attributes for basic service "light data service, with Class 4 DPRS management" (code "1001"B).....	215
A.2.2	Default setup attributes for basic service "light data service with Class 3 DPRS management" (code "1010"B).....	218
Annex B (normative):	Interworking conventions for the Frame Relay (FREL) service.....	220
B.1	Scope of this annex.....	220
B.1.1	Typical configuration for the Frame Relay service.....	220
B.2	Specific codings for mobility class 2.....	221

B.2.1	IWU-ATTRIBUTES information element coding	221
B.2.1.1	Profile subtype attributes (octet group 6) of IWU-ATTRIBUTES information element.....	222
B.2.1.1.1	IEEE 802.3/Ethernet	222
B.2.1.1.2	IEEE 802.5 (Token-Ring)	222
B.2.1.1.3	Internet Protocol (IP).....	223
B.2.1.1.3.1	Dynamic IP address allocation	224
B.2.1.1.4	DPRS Generic media encapsulation	224
B.2.1.1.4.1	Description of the different fields:.....	224
B.2.1.1.4.2	Optional control octets	225
B.2.1.1.4.3	D-GMEP Protocol identifier codes.....	227
B.2.2	IWU attributes implemented	228
B.3	Generic Frame Relay service interworking conventions.....	228
B.3.1	DLC U-plane service.....	228
B.3.2	Transmission bit order.....	228
B.3.3	Support of SDU size.....	229
B.3.4	SI _P connectionless downlink	229
B.4	IEEE 802.3/Ethernet.....	229
B.4.1	Typical configuration	229
B.4.1.1	Examples of implementation of the external transport network	229
B.4.2	Specific interworking conventions	230
B.4.2.1	Use of the connectionless downlink SI _P service	231
B.4.2.2	Special conventions for mobility class 1 systems	231
B.5	IEEE 802.5 (token ring)	231
B.5.1	Typical configuration	231
B.5.1.1	Examples of implementation of the external transport network	231
B.5.2	Specific interworking conventions	232
B.5.2.1	Special conventions for mobility class 1 systems	232
B.5.2.2	Use of the connectionless downlink SI _P service	232
B.6	Internet protocol	232
B.6.1	Typical configuration	232
B.6.1.1	Examples of implementation of the external transport network	232
B.6.2	Specific interworking conventions	233
B.6.2.1	Special conventions for mobility class 1 systems	233
B.7	Point-to-Point Protocol.....	233
B.7.1	Typical configuration	233
B.7.1.1	Examples of implementation of the external transport network	233
B.7.2	Specific interworking conventions	234
B.7.2.1	Special conventions for mobility class 1 systems	234
B.8	Interworking conventions for DPRS Generic Media Encapsulation transport mechanism	234
B.8.1	General	234
B.8.2	Interworking Requirements	235
B.8.2.1	U-plane format and protocol elements.....	235
B.8.2.1.1	Description of the protocol elements of the U-plane header	236
B.8.2.2	SDU handling and interface to DLC.....	236
B.8.2.2.1	Transmitter side procedure.....	236
B.8.2.2.2	Receiver side procedure	237
B.8.3	Application protocols	238
B.8.3.1	General.....	238
B.8.3.2	List of protocols with specific description in the present document.....	238
B.8.3.3	HTTP limited set nr.1	239
B.8.3.4	HTTP limited set nr.2 (Common HTTP profile)	240
B.8.3.5	HTTP limited set nr.3 (Extended HTTP profile)	240
B.8.3.6	Electronic mail (Limited set nr. 1).....	240
B.8.4	Interworking to external networks.....	241
B.8.4.1	Generic Multiprotocol Interworking to External IP Networks	241
B.8.4.2	Multi-context Interworking to an application proxy.....	242
B.8.4.3	Simplified single-context Interworking to External Networks (or to an application proxy).....	242

Annex C (normative):	Interworking conventions for character-oriented services	244
C.1	Scope	244
C.1.1	Scenario A	246
C.1.2	Scenario B	246
C.2	Specific coding for mobility class 2	247
C.2.1	IWU-Attribute coding	247
C.2.2	Default-values	250
C.2.3	Negotiation of the V.24-parameters	250
C.3	Generic interworking conventions	251
C.3.1	PAD functionality.....	251
C.3.1.1	Character formatting	251
C.3.2	Support of SDU size.....	251
C.3.3	LU10 SDU delivery mode.....	252
C.4	V.24 circuits	252
C.4.1	General	252
C.4.2	Encapsulation	252
C.4.2.1	Description.....	252
C.4.2.2	Framing.....	252
C.4.2.3	Coding of encapsulation	253
C.4.2.3.1	DCE-emulation side interpretation.....	253
C.4.2.3.2	DTE-emulation side interpretation.....	253
C.4.2.4	SDU Structure.....	254
C.4.3	Interworking procedures and conventions.....	254
C.4.3.1	General.....	254
C.4.3.1.1	Data forwarding conditions	254
C.4.3.1.2	Dataflow Control.....	255
C.4.3.1.2.1	Software dataflow control	255
C.4.3.1.2.2	Hardware dataflow control	255
C.4.3.1.3	Transmission of U-plane data procedure	255
C.4.3.1.4	Receive of U-plane data procedure	255
C.4.3.1.5	V.24 signalling	255
C.4.3.1.6	Configuration a V.24 interface during a Connection	255
C.4.3.2	Fall back procedure.....	256
C.4.3.3	Procedure at the DCE-emulation side IWU	256
C.4.3.3.1	DTE-initiated VC establishment.....	256
C.4.3.3.2	DCE-initiated VC establishment.....	256
C.4.3.3.3	V.24 call release.....	256
C.4.3.4	Procedure at the DTE-emulation side IWU	256
C.4.3.4.1	DCE-initiated VC establishment.....	257
C.4.3.4.2	DTE-initiated VC establishment	257
C.4.3.4.3	V.24 call release	257
C.5	Definition of User Control Information Elements.....	257
C.5.1	Mandatory UIEs	257
C.5.2	Optional UIEs.....	257
C.5.3	Information Element Identifier.....	258
Annex D (normative):	Support of double and long slot.....	259
D.1	Double and long slot support (2-level modulation).....	259
D.1.1	General	259
D.1.2	Requirements.....	259
D.1.2.1	Frame structure and slot numbering.....	259
D.1.2.2	Multibearer connections	259
D.1.2.3	Modulation schemes	259
D.1.2.4	Void	259
D.1.2.5	Bit MAPs.....	259
D.1.2.6	C-MUX.....	259
D.1.2.7	Scrambling.....	260
D.1.2.8	CRC	260