



SLOVENSKI STANDARD
SIST EN 300 324-1 V1.2.3:2005

01-april-2005

Vmesniki V pri digitalnih krajevnih centralah (LE) – Vmesnik V5.1 za podporo dostopovnemu omrežju (AN) – 1. del: Specifikacija vmesnika V5.1

V interfaces at the digital Local Exchange (LE); V5.1 interface for the support of Access Network (AN); Part 1: V5.1 interface specification

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 324-1 V1.2.3:2005](https://standards.iteh.ai/catalog/standards/sist/17d4b864-a065-4b9e-b7c3-61d3539eadb2/sist-en-300-324-1-v1-2-3-2005)

[https://standards.iteh.ai/catalog/standards/sist/17d4b864-a065-4b9e-b7c3-](https://standards.iteh.ai/catalog/standards/sist/17d4b864-a065-4b9e-b7c3-61d3539eadb2/sist-en-300-324-1-v1-2-3-2005)

[61d3539eadb2/sist-en-300-324-1-v1-2-3-2005](https://standards.iteh.ai/catalog/standards/sist/17d4b864-a065-4b9e-b7c3-61d3539eadb2/sist-en-300-324-1-v1-2-3-2005)

Ta slovenski standard je istoveten z: EN 300 324-1 Version 1.2.3

ICS:

| | | |
|-----------|--|----------------------------------|
| 33.040.30 | Komutacijski in signalizacijski sistem | Switching and signalling systems |
|-----------|--|----------------------------------|

SIST EN 300 324-1 V1.2.3:2005 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 324-1 V1.2.3:2005

<https://standards.iteh.ai/catalog/standards/sist/17d4b864-a065-4b9e-b7c3-61d3539eadb2/sist-en-300-324-1-v1-2-3-2005>

EN 300 324-1 V1.2.3 (1999-06)

European Standard (Telecommunications series)

V interfaces at the digital Local Exchange (LE); V5.1 interface for the support of Access Network (AN); Part 1: V5.1 interface specification

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 324-1 V1.2.3:2005](https://standards.iteh.ai/catalog/standards/sist/17d4b864-a065-4b9e-b7c3-61d3539eadb2/sist-en-300-324-1-v1-2-3-2005)

<https://standards.iteh.ai/catalog/standards/sist/17d4b864-a065-4b9e-b7c3-61d3539eadb2/sist-en-300-324-1-v1-2-3-2005>



Reference

REN/SPS-09050-1 (30090iq0.PDF)

Keywords

V interface, V5 interface, LE, AN

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Prefecture de Grasse (06) N° 7803/88

<https://standards.etsi.org/standards/sist-en-300-324-1-v1-2-3-2005>

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from

<http://www.etsi.org>

If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

| | |
|---|----|
| Intellectual Property Rights..... | 14 |
| Foreword | 14 |
| Introduction | 15 |
| 1 Scope..... | 17 |
| 2 References..... | 18 |
| 3 Definitions, symbols and abbreviations | 19 |
| 3.1 Definitions | 19 |
| 3.2 Symbols and abbreviations | 21 |
| 4 Electrical and physical interface requirements | 23 |
| 5 Procedural interface requirements | 28 |
| 6 Services and architecture aspects and requirements | 31 |
| 6.1 On-demand services..... | 31 |
| 6.1.1 PSTN..... | 31 |
| 6.1.2 ISDN Basic Access (ISDN-BA)..... | 32 |
| 6.2 Permanent Line (PL) capability | 32 |
| 6.3 Semi-permanent leased line | 32 |
| 6.4 Permanent leased line services..... | 33 |
| 7 Control and provisioning..... | 34 |
| 7.1 Control principles | 34 |
| 7.1.1 General requirements and assumptions | 34 |
| 7.1.2 Control of ISDN user port for the PL capability | 36 |
| 7.1.2.1 Statements and assumptions..... | 36 |
| 7.1.2.2 ISDN and PL capability..... | 36 |
| 7.1.2.3 Decoupling of AN and LE FSM..... | 36 |
| 7.2 Provisioning strategy and requirements | 36 |
| 7.2.1 General..... | 36 |
| 7.2.2 Provisioning requirements..... | 36 |
| 8 Protocol architecture and multiplexing structure..... | 38 |
| 8.1 Functional description..... | 38 |
| 8.2 Protocol requirements for PSTN and ISDN..... | 39 |
| 8.3 Time slots..... | 40 |
| 8.4 Time slot allocation for C-channels | 40 |
| 8.5 L2 sublayering and multiplexing on C-channels | 41 |
| 8.6 L3 multiplexing..... | 41 |
| 8.7 Congestion control..... | 41 |
| 8.7.1 Flow control end to end..... | 41 |
| 8.7.2 Congestion control on the V5.1 interface..... | 41 |
| 8.7.3 Blocking of ISDN user ports at L2..... | 41 |
| 8.7.4 Flow control using LAPV5-DL mechanisms..... | 42 |
| 9 Envelope Function sublayer of LAPV5 (LAPV5-EF)..... | 42 |
| 9.1 Frame structure for peer-to-peer communication..... | 42 |
| 9.1.1 General | 42 |
| 9.1.2 Flag sequence | 42 |
| 9.1.3 Interframe time fill | 42 |
| 9.1.4 Envelope function address field | 42 |
| 9.1.5 Envelope information field..... | 43 |
| 9.1.6 Transparency | 43 |
| 9.1.7 FCS | 43 |
| 9.1.8 Format convention..... | 43 |
| 9.1.9 Invalid frames..... | 43 |

| | | |
|------------|---|----|
| 9.1.10 | Frame aborts..... | 43 |
| 9.2 | Format of fields for data link envelope peer-to-peer communication | 44 |
| 9.2.1 | Envelope function address field format..... | 44 |
| 9.2.2 | Address field variables | 44 |
| 9.2.2.1 | Address field extension bit | 44 |
| 9.2.2.2 | EFaddr | 44 |
| 10 | Data link sublayer of LAPV5 (LAPV5-DL)..... | 44 |
| 10.1 | Frame structure for peer-to-peer communication..... | 44 |
| 10.1.1 | General..... | 44 |
| 10.1.2 | Link address field | 45 |
| 10.1.3 | Control field | 45 |
| 10.1.4 | Information field | 45 |
| 10.1.5 | Format convention..... | 45 |
| 10.2 | Invalid frames | 45 |
| 10.3 | Elements of procedures and formats of fields for data link sublayer peer-to-peer communication..... | 45 |
| 10.3.1 | Link address field format | 45 |
| 10.3.2 | Link address field variables..... | 45 |
| 10.3.2.1 | Address field extension (EA) bit | 45 |
| 10.3.2.2 | Command/response field bit | 45 |
| 10.3.2.3 | V5DLaddr..... | 46 |
| 10.3.3 | Control field formats | 46 |
| 10.3.4 | Control field parameters and associated state variables | 46 |
| 10.3.5 | Frame types | 46 |
| 10.4 | Definition of the peer-to-peer procedures of the data link sublayer..... | 46 |
| 10.4.1 | General..... | 46 |
| 10.4.2 | Procedure for the use of the Poll/Final (P/F) bit..... | 48 |
| 10.4.3 | Terminal Endpoint Identifier (TEI) management procedures | 48 |
| 10.4.4 | Automatic negotiation of data link layer parameters | 48 |
| 10.4.5 | Procedures for establishment and release of multiple frame operation | 48 |
| 10.4.5.1 | Establishment of multiple frame operation..... | 48 |
| 10.4.5.1.1 | General..... | 48 |
| 10.4.5.1.2 | Establishment procedures..... | 49 |
| 10.4.5.1.3 | Procedure on expiry of timer T200..... | 49 |
| 10.4.5.2 | Information transfer | 50 |
| 10.4.5.3 | Termination of multiple frame operation..... | 50 |
| 10.4.5.4 | Link-not-established state | 50 |
| 10.4.5.5 | Collision of unnumbered commands and responses | 50 |
| 10.4.5.5.1 | Identical transmitted and received commands..... | 50 |
| 10.4.5.5.2 | Different transmitted and received commands..... | 50 |
| 10.4.5.6 | Unsolicited DM response and SABME command..... | 50 |
| 10.4.6 | Procedures for information transfer in multiple frame operation | 51 |
| 10.4.7 | Re-establishment of multiple frame operation..... | 51 |
| 10.4.7.1 | Criteria for re-establishment | 51 |
| 10.4.7.2 | Procedures | 51 |
| 10.4.8 | Exception condition reporting and recovery | 51 |
| 10.4.9 | List of system parameters | 52 |
| 10.4.10 | Data link monitor function | 52 |
| 10.4.10.1 | General | 52 |
| 10.4.10.2 | Data link layer supervision in the multiple-frame-established state..... | 52 |
| 10.4.10.3 | Connection verification procedures | 52 |
| 10.4.11 | PSTN and control data link FSM and requirements..... | 52 |
| 10.4.11.1 | General | 52 |
| 10.4.11.2 | Data link FSM | 53 |
| 11 | AN frame relay sublayer | 55 |
| 11.1 | General..... | 55 |
| 11.2 | Invalid frames | 55 |
| 11.3 | Detailed description of the AN frame relay function | 56 |
| 11.3.1 | Frame received from LE..... | 56 |
| 11.3.2 | Frame received from ISDN user port | 56 |

| | | |
|-----------|---|----|
| 12 | Sublayer-to-sublayer communication and MF | 57 |
| 12.1 | LAPV5-EF to LAPV5-DL communication | 57 |
| 12.2 | LAPV5-DL to LAPV5-EF communication | 57 |
| 12.3 | AN-FR to LAPV5-EF communication | 57 |
| 12.4 | LAPV5-EF to AN-FR communication | 57 |
| 13 | PSTN signalling protocol specification and L3 multiplexing | 57 |
| 13.1 | General | 57 |
| 13.1.1 | Introduction | 57 |
| 13.1.2 | Separation of responsibilities | 58 |
| 13.1.3 | National specific PSTN signal information elements | 58 |
| 13.2 | PSTN protocol entity definition | 59 |
| 13.2.1 | Definition of PSTN path states and explanation | 59 |
| 13.2.1.1 | Path states in the AN (AN(PSTN)) | 59 |
| 13.2.1.2 | Path states in the LE (LE(PSTN)) | 59 |
| 13.2.2 | Definition of PSTN protocol primitives, messages and timers | 60 |
| 13.3 | PSTN protocol message definition and content | 61 |
| 13.3.1 | Establish | 62 |
| 13.3.2 | Establish ACK | 62 |
| 13.3.3 | Signal | 63 |
| 13.3.4 | Signal ACK | 63 |
| 13.3.5 | Status | 63 |
| 13.3.6 | Status enquiry | 64 |
| 13.3.7 | Disconnect | 64 |
| 13.3.8 | Disconnect complete | 64 |
| 13.3.9 | Protocol parameter | 65 |
| 13.4 | General message format and information element coding | 65 |
| 13.4.1 | Overview | 65 |
| 13.4.2 | Protocol discriminator | 66 |
| 13.4.3 | L3addr | 66 |
| 13.4.4 | Message type | 66 |
| 13.4.5 | Coding of other information elements | 67 |
| 13.4.6 | Single octet information elements | 68 |
| 13.4.6.1 | Pulse notification | 68 |
| 13.4.6.2 | Line-information | 68 |
| 13.4.6.3 | State | 68 |
| 13.4.6.4 | Autonomous-signalling-sequence | 69 |
| 13.4.6.5 | Sequence-response | 69 |
| 13.4.7 | Information elements with variable length format | 69 |
| 13.4.7.1 | Sequence-number | 69 |
| 13.4.7.2 | Cadenced-ringing | 70 |
| 13.4.7.3 | Pulsed-signal | 71 |
| 13.4.7.4 | Steady-signal | 72 |
| 13.4.7.5 | Digit-signal | 73 |
| 13.4.7.6 | Recognition-time | 74 |
| 13.4.7.7 | Enable-autonomous-acknowledge | 74 |
| 13.4.7.8 | Disable-autonomous-acknowledge | 75 |
| 13.4.7.9 | Cause | 76 |
| 13.4.7.10 | Resource-unavailable | 77 |
| 13.4.7.11 | Enable-metering | 77 |
| 13.4.7.12 | Metering-report | 78 |
| 13.4.7.13 | Attenuation | 79 |
| 13.5 | PSTN call control procedures | 79 |
| 13.5.1 | General | 80 |
| 13.5.2 | Handling of error conditions | 80 |
| 13.5.2.1 | Protocol discriminator error | 81 |
| 13.5.2.2 | L3addr error | 81 |
| 13.5.2.3 | Message type error | 81 |
| 13.5.2.4 | Information element out of sequence | 82 |
| 13.5.2.5 | Repeated information elements | 82 |
| 13.5.2.6 | Mandatory information element missing | 82 |

| | | |
|-------------|--|----|
| 13.5.2.7 | Unrecognized information element..... | 83 |
| 13.5.2.8 | Content error of mandatory information element..... | 83 |
| 13.5.2.9 | Content error of optional information element | 83 |
| 13.5.2.10 | Unexpected message..... | 84 |
| 13.5.2.11 | Optional information element not allowed | 84 |
| 13.5.2.12 | Optional information element missing | 84 |
| 13.5.2.13 | Status enquiry procedure | 84 |
| 13.5.2.14 | Status procedure | 85 |
| 13.5.3 | Path related procedures | 86 |
| 13.5.3.1 | Path initiation by AN..... | 87 |
| 13.5.3.1.1 | Subscriber seizure request..... | 87 |
| 13.5.3.1.2 | Subscriber seizure confirmation..... | 87 |
| 13.5.3.2 | Path initiation by LE..... | 88 |
| 13.5.3.2.1 | Establish request | 88 |
| 13.5.3.2.2 | Establish acknowledge | 89 |
| 13.5.3.3 | Path collision | 89 |
| 13.5.3.3.1 | Originating call prevail | 90 |
| 13.5.3.3.2 | Destination call prevail | 90 |
| 13.5.3.4 | Path active | 90 |
| 13.5.3.4.1 | Normal operation | 90 |
| 13.5.3.4.2 | Exceptional procedures | 91 |
| 13.5.3.5 | Disconnecting path | 91 |
| 13.5.3.5.1 | Disconnect request..... | 92 |
| 13.5.3.5.2 | Disconnect acknowledge..... | 93 |
| 13.5.3.6 | Line information procedure | 93 |
| 13.5.3.6.1 | Normal operation | 93 |
| 13.5.3.6.2 | Exceptional procedures | 94 |
| 13.5.4 | Non-path related procedures | 94 |
| 13.5.4.1 | Protocol parameter procedures | 94 |
| 13.5.4.1.1 | Normal operation..... | 94 |
| 13.5.4.1.2 | Exceptional procedures..... | 94 |
| 13.5.4.2 | Port blocking procedures | 95 |
| 13.5.4.3 | Restart procedure..... | 95 |
| 13.5.5 | L3 error detection procedure..... | 96 |
| 13.5.5.1 | Multiple SIGNAL message operation - variables, sequence numbers and timers | 96 |
| 13.5.5.1.1 | Modulus | 96 |
| 13.5.5.1.2 | Send sequence variable S(S) | 96 |
| 13.5.5.1.3 | Acknowledge sequence variable S(A)..... | 96 |
| 13.5.5.1.4 | Send sequence number M(S) | 96 |
| 13.5.5.1.5 | Receive sequence variable S(R)..... | 96 |
| 13.5.5.1.6 | Receive sequence number M(R) | 97 |
| 13.5.5.1.7 | Timer Tt..... | 97 |
| 13.5.5.1.8 | Timer Tr..... | 97 |
| 13.5.5.2 | Multiple SIGNAL message operation - procedures..... | 97 |
| 13.5.5.2.1 | Initialization | 97 |
| 13.5.5.2.2 | Sending a SIGNAL message..... | 97 |
| 13.5.5.2.3 | Sending a SIGNAL ACK message..... | 97 |
| 13.5.5.2.4 | Receiving a SIGNAL message..... | 97 |
| 13.5.5.2.5 | Receiving a SIGNAL ACK message..... | 97 |
| 13.5.5.2.6 | Start of timer Tr | 98 |
| 13.5.5.2.7 | Stop of timer Tr..... | 98 |
| 13.5.5.2.8 | Timeout of timer Tr | 98 |
| 13.5.5.2.9 | Start of timer Tt..... | 98 |
| 13.5.5.2.10 | Stop of timer Tt..... | 98 |
| 13.5.5.2.11 | Timeout of timer Tt..... | 98 |
| 13.5.5.2.12 | Receiving a DISCONNECT message | 98 |
| 13.5.5.3 | Multiple SIGNAL message operation - values | 98 |
| 13.5.5.3.1 | Number of outstanding SIGNAL messages | 98 |
| 13.5.5.3.2 | Timer Tt..... | 98 |
| 13.5.5.3.3 | Timer Tr..... | 98 |

| | | |
|------------|--|-----|
| 13.6 | List of system parameters..... | 99 |
| 13.7 | AN and LE side state tables..... | 99 |
| 14 | Control requirements and protocol..... | 105 |
| 14.1 | ISDN user port status indication and control protocol..... | 105 |
| 14.1.1 | General aspects..... | 105 |
| 14.1.2 | Events and function elements relevant for the control of the state machines..... | 107 |
| 14.1.3 | ISDN user port FSMs, AN (ISDN port) and LE (ISDN port)..... | 109 |
| 14.1.3.1 | Description of the states..... | 109 |
| 14.1.3.2 | Definition of port control states..... | 110 |
| 14.1.3.2.1 | ISDN user port FSM - AN (ISDN port)..... | 110 |
| 14.1.3.2.2 | ISDN User port FSM - LE (ISDN port)..... | 110 |
| 14.1.3.3 | Principles and procedures..... | 111 |
| 14.1.3.3.1 | General..... | 111 |
| 14.1.3.3.2 | Blocking..... | 111 |
| 14.1.3.3.3 | Blocking request..... | 111 |
| 14.1.3.3.4 | Co-ordinated unblocking..... | 112 |
| 14.1.3.3.5 | Activation..... | 112 |
| 14.1.3.4 | ISDN port FSM at the AN..... | 113 |
| 14.1.3.5 | ISDN port FSM at the LE..... | 115 |
| 14.1.4 | Performance monitoring aspects..... | 115 |
| 14.2 | PSTN user port status indication and control protocol..... | 116 |
| 14.2.1 | General aspects..... | 116 |
| 14.2.2 | Events and function elements relevant for the control of the state machines..... | 116 |
| 14.2.3 | PSTN user port FSM, AN (PSTN port) and LE (PSTN port)..... | 117 |
| 14.2.3.1 | Description of the states..... | 117 |
| 14.2.3.2 | Definition of port control states..... | 117 |
| 14.2.3.2.1 | PSTN user port FSM - AN (PSTN port)..... | 117 |
| 14.2.3.2.2 | PSTN user port FSM - LE (PSTN port)..... | 118 |
| 14.2.3.3 | Principles and procedures..... | 118 |
| 14.2.3.3.1 | General..... | 118 |
| 14.2.3.3.2 | Blocking..... | 118 |
| 14.2.3.3.3 | Blocking request..... | 118 |
| 14.2.3.3.4 | Co-ordinated unblocking..... | 119 |
| 14.2.3.4 | PSTN port FSM at the AN..... | 119 |
| 14.2.3.5 | PSTN port FSM at the LE..... | 119 |
| 14.3 | Interface L1 maintenance requirements and protocol..... | 120 |
| 14.3.1 | Events and failure reports..... | 120 |
| 14.3.2 | Detection algorithm for events and signals..... | 121 |
| 14.3.3 | V5.1 interface L1 FSM..... | 121 |
| 14.3.4 | Requirements and procedures for the additional functions..... | 122 |
| 14.4 | Control protocol..... | 122 |
| 14.4.1 | Control protocol message definition and content..... | 122 |
| 14.4.1.1 | PORT CONTROL message..... | 123 |
| 14.4.1.2 | PORT CONTROL ACK message..... | 123 |
| 14.4.1.3 | COMMON CONTROL message..... | 124 |
| 14.4.1.4 | COMMON CONTROL ACK message..... | 124 |
| 14.4.2 | General message format and information element coding..... | 124 |
| 14.4.2.1 | Overview..... | 124 |
| 14.4.2.2 | Protocol discriminator information element..... | 125 |
| 14.4.2.3 | L3addr information element..... | 125 |
| 14.4.2.4 | Message type information element..... | 125 |
| 14.4.2.5 | Other information elements..... | 126 |
| 14.4.2.5.1 | Coding rules..... | 126 |
| 14.4.2.5.2 | Performance grading information element..... | 126 |
| 14.4.2.5.3 | Rejection cause information element..... | 126 |
| 14.4.2.5.4 | Control function element information element..... | 127 |
| 14.4.2.5.5 | Control function ID information element..... | 127 |
| 14.4.2.5.6 | Variant information element..... | 128 |
| 14.4.2.5.7 | Interface ID information element..... | 128 |
| 14.4.3 | State definitions of the control protocol..... | 129 |

| | | |
|-----------------------------|---|------------|
| 14.4.3.1 | Port control protocol..... | 129 |
| 14.4.3.2 | Common control protocol..... | 129 |
| 14.4.4 | Control protocol procedures..... | 129 |
| 14.4.4.1 | General | 129 |
| 14.4.4.2 | Handling of error conditions..... | 130 |
| 14.4.4.2.1 | Protocol discriminator error | 130 |
| 14.4.4.2.2 | L3addr error | 130 |
| 14.4.4.2.3 | Message type error | 130 |
| 14.4.4.2.4 | Repeated information elements | 130 |
| 14.4.4.2.5 | Mandatory information element missing..... | 131 |
| 14.4.4.2.6 | Unrecognized information element..... | 131 |
| 14.4.4.2.7 | Content error of mandatory information elements | 131 |
| 14.4.4.2.8 | Content error of conditional information element..... | 131 |
| 14.4.4.2.9 | Conditional information element not allowed | 131 |
| 14.4.4.3 | Start traffic indication | 131 |
| 14.4.4.4 | Stop traffic indication | 132 |
| 14.4.4.5 | Port control protocol procedure..... | 132 |
| 14.4.4.6 | Common control protocol procedure..... | 133 |
| 14.4.4.7 | Timers for the control protocol..... | 133 |
| 14.4.4.8 | AN and LE side state tables..... | 134 |
| 14.5 | V5.1 re-provisioning procedures | 135 |
| 14.5.1 | General aspects..... | 135 |
| 14.5.2 | Events and states | 136 |
| 14.5.2.1 | Events | 136 |
| 14.5.2.2 | Definition of the AN and LE states for the re-provisioning procedures | 136 |
| 14.5.3 | Re-provisioning FSMs | 136 |
| 14.5.3.1 | AN (variant&ID) and LE (variant&ID) state tables for the verification procedure..... | 137 |
| 14.5.3.2 | AN (re-pro) and LE (re-pro) state tables for the re-provisioning synchronization procedure..... | 137 |
| 14.5.4 | Procedures..... | 138 |
| 14.5.4.1 | Request variant and ID | 138 |
| 14.5.4.2 | Verify re-provisioning | 138 |
| 14.5.4.3 | Re-provisioning synchronization | 139 |
| 14.5.4.4 | Restart procedure..... | 139 |
| Annex A (normative): | Requirements for the support of the PL capability through an ISDN-BA..... | 140 |
| Annex B (normative): | Assumptions and requirements for the support of semi-permanent leased lines..... | 141 |
| B.1 | General..... | 141 |
| B.2 | Signalling associated with semi-permanent leased lines | 141 |
| B.3 | User ports | 141 |
| B.4 | Requirements for non-ISDN user ports for semi-permanent leased lines..... | 142 |
| Annex C (normative): | Basic requirements of the system management functions in AN and LE..... | 143 |
| Annex D (normative): | Use of the protocol information elements for national PSTN protocols | 156 |
| D.1 | Introduction..... | 156 |
| D.2 | The placement of information elements..... | 157 |
| D.2.1 | Information elements within the ESTABLISH message..... | 157 |
| D.2.2 | Information elements within the ESTABLISH-ACK message | 157 |
| D.2.3 | Information elements within the SIGNAL message..... | 158 |
| D.2.4 | Information elements within the DISCONNECT message | 158 |
| D.2.5 | Information elements within the DISCONNECT-COMplete message..... | 158 |
| D.2.6 | Information elements within the PROTOCOL-PARAMETER message | 159 |

| | | |
|-----------|--|-----|
| D.3 | The information elements | 159 |
| D.3.1 | Line-information information elements..... | 159 |
| D.3.1.1 | Impedance marker reset..... | 159 |
| D.3.1.2 | Impedance marker set..... | 159 |
| D.3.1.3 | Low loop impedance | 159 |
| D.3.1.4 | Anomalous loop impedance | 160 |
| D.3.1.5 | Anomalous line condition received | 160 |
| D.3.2 | Pulse-notification information element | 160 |
| D.3.3 | Autonomous-signalling-sequence information element | 160 |
| D.3.4 | Sequence-response information element..... | 160 |
| D.3.5 | Cadenced-ringing information element..... | 160 |
| D.3.6 | Pulsed-signal information element..... | 161 |
| D.3.6.1 | The pulse type | 161 |
| D.3.6.2 | The suppression indicator..... | 161 |
| D.3.6.2.1 | Suppression indicator value 00..... | 161 |
| D.3.6.2.2 | Suppression indicator value 01..... | 161 |
| D.3.6.2.3 | Suppression indicator value 10..... | 161 |
| D.3.6.2.4 | Suppression indicator value 11 | 161 |
| D.3.6.3 | The pulse duration type | 162 |
| D.3.6.4 | The acknowledgement request indicator | 162 |
| D.3.6.5 | The number of pulses | 162 |
| D.3.7 | Use of pulsed signals | 162 |
| D.3.7.1 | Pulsed normal polarity | 162 |
| D.3.7.2 | Pulsed reverse polarity | 162 |
| D.3.7.3 | Pulsed battery on C-wire..... | 162 |
| D.3.7.4 | Pulsed on-hook..... | 162 |
| D.3.7.5 | Pulsed reduced battery..... | 163 |
| D.3.7.6 | Pulsed no battery | 163 |
| D.3.7.7 | Meter pulse..... | 163 |
| D.3.7.8 | Initial ring..... | 163 |
| D.3.7.9 | Pulsed off-hook | 163 |
| D.3.7.10 | Pulsed b-wire connected to earth..... | 163 |
| D.3.7.11 | Register recall (timed open loop)..... | 163 |
| D.3.7.12 | Earth loop pulse | 163 |
| D.3.7.13 | 50 Hz pulse..... | 163 |
| D.3.7.14 | Pulsed b-wire connected to battery..... | 163 |
| D.3.7.15 | Pulsed a-wire connected to earth..... | 163 |
| D.3.7.16 | Pulsed a-wire connected to battery..... | 163 |
| D.3.7.17 | Pulsed c-wire connected to earth..... | 163 |
| D.3.7.18 | Pulsed c-wire disconnected | 164 |
| D.3.7.19 | Pulsed normal battery | 164 |
| D.3.7.20 | Pulsed a-wire disconnected | 164 |
| D.3.7.21 | Pulsed b-wire disconnected..... | 164 |
| D.3.7.22 | Ramp to reversed polarity | 164 |
| D.3.7.23 | Ramp to normal polarity..... | 164 |
| D.3.8 | Use of steady signals..... | 164 |
| D.3.8.1 | Normal-polarity | 164 |
| D.3.8.2 | Reversed-polarity | 164 |
| D.3.8.3 | Battery on c-wire | 164 |
| D.3.8.4 | No battery on c-wire..... | 164 |
| D.3.8.5 | Off hook (loop closed) | 164 |
| D.3.8.6 | On hook (loop open) | 165 |
| D.3.8.7 | Battery on a-wire | 165 |
| D.3.8.8 | No battery on b-wire | 165 |
| D.3.8.9 | Reduced battery..... | 165 |
| D.3.8.10 | No battery..... | 165 |
| D.3.8.11 | Alternate reduced power/no power | 165 |
| D.3.8.12 | No battery on a-wire..... | 165 |
| D.3.8.13 | Normal battery | 165 |
| D.3.8.14 | Stop ringing..... | 165 |

| | | |
|------------|---|-----|
| D.3.8.15 | Start pilot frequency | 165 |
| D.3.8.16 | Stop pilot frequency | 165 |
| D.3.8.17 | A-wire on earth..... | 165 |
| D.3.8.18 | Low impedance on b-wire | 166 |
| D.3.8.19 | B-wire connected to earth..... | 166 |
| D.3.8.20 | B-wire disconnected from earth | 166 |
| D.3.8.21 | Battery on b-wire..... | 166 |
| D.3.8.22 | Low loop impedance | 166 |
| D.3.8.23 | High loop impedance | 166 |
| D.3.8.24 | Anomalous loop impedance | 166 |
| D.3.8.25 | A-wire disconnected from earth | 166 |
| D.3.8.26 | C-wire on earth..... | 166 |
| D.3.8.27 | C-wire disconnected from earth | 166 |
| D.3.9 | Digit-signal information element | 166 |
| D.3.10 | Recognition-time information element..... | 167 |
| D.3.11 | Enable-autonomous-acknowledge information element..... | 167 |
| D.3.11.1 | Suppression indicator value 00..... | 167 |
| D.3.11.2 | Suppression indicator value 01..... | 167 |
| D.3.11.3 | Suppression indicator value 10..... | 167 |
| D.3.11.4 | Suppression indicator value 11..... | 167 |
| D.3.12 | Default values for the Enable-autonomous-acknowledge information element | 168 |
| D.3.13 | Use of the Autonomous-signalling-sequence | 168 |
| D.3.14 | Disable-autonomous-acknowledge information element | 168 |
| D.3.15 | Enable-metering information element..... | 168 |
| D.3.15.1 | The pulse type | 168 |
| D.3.15.2 | The rate type..... | 168 |
| D.3.15.3 | The reporting pulse count..... | 168 |
| D.3.15.4 | The repetition indicator | 169 |
| D.3.15.5 | The suppression indicator..... | 169 |
| D.3.15.6 | The pulse duration type | 169 |
| D.3.16 | Metering-report information element..... | 169 |
| D.3.16.1 | The pulse count..... | 169 |
| D.3.16.2 | The Report type..... | 169 |
| D.3.16.2.1 | Report type value 00..... | 169 |
| D.3.16.2.2 | Report type value 01..... | 169 |
| D.3.16.2.3 | Report type value 10..... | 169 |
| D.3.16.2.4 | Report type value 11..... | 170 |
| D.3.16.3 | The failure reason..... | 170 |
| D.3.17 | Attenuation information element..... | 170 |
| D.4 | Signalling sequences in the event of failure of a V5.1 interface to return a user port to the idle condition before releasing the signalling path | 170 |
| D.4.1 | Protocol implications of going directly to the NULL state | 170 |
| D.4.2 | Protocol implications of going to the BLOCKED state | 171 |

| | | |
|-------------------------------|--|------------|
| D.5 | Leaving the BLOCKED state..... | 171 |
| D.6 | Pre-defined PSTN port states..... | 171 |
| D.7 | The line parked condition | 171 |
| D.8 | Information element meaning | 171 |
| D.9 | Coding of pulse duration types | 172 |
| D.10 | Ring signals and their placement in V5 messages | 172 |
| D.11 | Resource unavailable | 172 |
| Annex E (informative): | Service scenarios, architecture and functional definition of access arrangements with AN at the LE..... | 173 |
| E.1 | Conclusions on multiple V5 interface applications | 173 |
| E.2 | Conclusions on architecture aspects | 173 |
| E.3 | Implementation of Q _{AN} | 174 |
| Annex F (informative): | The concept and requirements for the upgrade of a V5.1 interface to a V5.2 interface | 175 |
| Annex G (informative): | Use of function element primitives in the V5 PSTN protocol | 176 |
| G.1 | Introduction..... | 176 |
| G.2 | FE primitives used in the PSTN protocol entity in the AN | 176 |
| G.2.1 | FE-subscriber_seizure..... | 176 |
| G.2.2 | FE-subscriber_release..... | 176 |
| G.2.3 | FE-line_information..... | 177 |
| G.2.4 | FE-line_signal..... | 177 |
| G.3 | FE primitives used in the PSTN protocol entity in the LE..... | 177 |
| G.3.1 | FE-establish_request..... | 177 |
| G.3.2 | FE-establish_acknowledge_indication..... | 177 |
| G.3.3 | FE-establish_indication..... | 178 |
| G.3.4 | FE-establish_acknowledge..... | 178 |
| G.3.5 | FE-disconnect_request..... | 178 |
| G.3.6 | FE-disconnect_complete_request | 178 |
| G.3.7 | FE-line_signal_request | 178 |
| G.3.8 | FE-line_signal_indication | 179 |
| G.3.9 | FE-protocol_parameter_request..... | 179 |
| G.3.10 | FE-disconnect_complete_indication..... | 179 |

| | | |
|-------------------------------|---|------------|
| Annex H (informative): | PSTN protocol; explanatory notes and information flow..... | 180 |
| H.1 | Explanatory notes..... | 180 |
| H.2 | Information flow diagrams..... | 182 |
| Annex J (informative): | AN requirement for pulse dialling | 185 |
| Annex K (informative): | L3 error detection procedure | 186 |
| K.1 | Variables and sequence numbers | 186 |
| K.2 | Values of counters and timers..... | 187 |
| K.3 | Procedures..... | 187 |
| K.4 | Examples of the error detection mechanism | 187 |
| Annex L (informative): | SDL diagrams | 189 |
| L.1 | SDL diagrams for the AN side..... | 189 |
| L.1.1 | System description..... | 189 |
| L.1.2 | Block descriptions | 191 |
| L.1.2.1 | Block description of the PSTN protocol | 191 |
| L.1.2.2 | Block description of the control protocol..... | 192 |
| L.1.2.3 | Block description of the ISDN port status FSM..... | 193 |
| L.1.2.4 | Block description of the PSTN port status FSM | 193 |
| L.1.2.5 | Block description of the system management | 194 |
| L.1.3 | Explanation of SDL symbols | 195 |
| L.1.4 | PSTN protocol procedure | 195 |
| L.1.4.1 | Scope..... | 195 |
| L.1.4.2 | Path states..... | 195 |
| L.1.4.3 | SDLs..... | 196 |
| L.1.5 | Control protocol procedures | 208 |
| L.1.5.1 | Scope..... | 208 |
| L.1.5.2 | States | 208 |
| L.1.5.3 | SDLs..... | 208 |
| L.1.5.3.1 | Port control protocol..... | 209 |
| L.1.5.3.2 | Common control protocol..... | 211 |
| L.1.6 | Port status FSM control | 213 |
| L.1.6.1 | Scope..... | 213 |
| L.1.6.2 | States | 213 |
| L.1.6.3 | SDLs..... | 213 |
| L.1.6.3.1 | ISDN port status FSM control | 214 |
| L.1.6.3.2 | PSTN port status FSM control..... | 222 |
| L.1.7 | System management procedure..... | 225 |
| L.1.7.1 | Scope..... | 225 |
| L.1.7.2 | States | 225 |
| L.1.7.3 | SDLs..... | 225 |
| L.2 | SDL diagrams for the LE side..... | 236 |
| L.2.1 | System description | 236 |
| L.2.2 | Block descriptions | 238 |
| L.2.2.1 | Block description of the PSTN protocol | 238 |
| L.2.2.2 | Block description of the control protocol..... | 239 |
| L.2.2.3 | Block description of the ISDN port status FSM..... | 240 |
| L.2.2.4 | Block description of the PSTN port status FSM | 240 |
| L.2.2.5 | Block description of the system management | 241 |
| L.2.3 | Explanation of SDL symbols | 241 |
| L.2.4 | PSTN protocol procedure | 242 |
| L.2.4.1 | Scope..... | 242 |
| L.2.4.2 | Path states..... | 242 |
| L.2.4.3 | SDLs..... | 242 |
| L.2.5 | Control protocol procedures | 252 |

| | | |
|-------------------------------|--|------------|
| L.2.5.1 | Scope..... | 252 |
| L.2.5.2 | States | 252 |
| L.2.5.3 | SDLs..... | 252 |
| L.2.5.3.1 | Port control protocol..... | 253 |
| L.2.5.3.2 | Common control protocol..... | 255 |
| L.2.6 | Port status FSM control | 257 |
| L.2.6.1 | Scope..... | 257 |
| L.2.6.2 | States | 257 |
| L.2.6.3 | SDLs..... | 257 |
| L.2.6.3.1 | ISDN port status FSM control | 258 |
| L.2.6.3.2 | PSTN port status FSM control..... | 263 |
| L.2.7 | System management procedure..... | 266 |
| L.2.7.1 | Scope..... | 266 |
| L.2.7.2 | States | 266 |
| L.2.7.3 | SDLs..... | 266 |
| Annex M (informative): | Structures used in the V5.1 interface..... | 279 |
| Annex N (informative): | Protocol architecture for PSTN and ISDN user port control | 280 |
| N.1 | Scope..... | 280 |
| N.2 | ISDN user port status control..... | 280 |
| N.2.1 | Functional split between LE and AN | 280 |
| N.2.2 | Information transfer between LE and AN..... | 280 |
| N.2.3 | Activation/deactivation procedure | 281 |
| N.3 | PSTN user port control - information transfer between LE and AN | 282 |
| Annex P (informative): | Items identified to be pre-defined or provisioned | 283 |
| Annex Q (informative): | Bibliography..... | 284 |
| Annex R (informative): | Index | 285 |
| History | | 287 |