

ETSI EN 303 276 V1.1.1 (2017-11)



**Maritime Broadband Radiolink operating within the bands
5 852 MHz to 5 872 MHz and/or 5 880 MHz to 5 900 MHz
for ships and off-shore installations
engaged in coordinated activities;
Harmonised Standard covering the essential requirements
of article 3.2 of Directive 2014/53/EU**

PREVIEW
https://standards.etsi.org/standards-search/standards/303-276-v1-1-1-11
411d-9303-98dffb-ecce-303-276-v1-1-11

Reference

DEN/ERM-TG26-514

Keywordsbroadband, data, harmonised standard, maritime,
radio**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Symbols and abbreviations.....	8
3.1 Symbols.....	8
3.2 Abbreviations	8
4 General and operational requirements.....	9
4.0 Environmental profile.....	9
4.1 Construction	9
4.2 Controls and indicators.....	9
4.3 Safety precautions	9
4.4 Labeling.....	10
4.5 Frequencies.....	10
4.6 Polarization.....	10
4.7 Antenna gain	10
4.8 Self-monitoring	10
4.9 Adaptive transmitter power control.....	10
5 General conditions of measurements	10
5.1 Test site and general arrangements for measurements.....	10
5.2 General	11
5.3 Test signals.....	11
5.4 Bit error measurements	11
5.5 Transceiver data interface.....	11
5.6 Impedance	11
5.7 Tests of equipment with a notch filter.....	12
5.8 Facilities for access	12
5.8.1 Coupling arrangements.....	12
5.8.2 Arrangements for measurements with messages	12
5.9 Modes of operation of the transmitter	12
6 Test conditions	12
6.1 Normal test signals	12
6.2 Normal test conditions.....	12
6.2.1 Normal temperature and humidity	12
6.2.2 Normal power source.....	13
6.2.2.1 Mains voltage and frequency	13
6.2.2.2 Battery power source.....	13
6.2.2.3 Other power sources.....	13
6.3 Extreme test conditions	13
6.3.0 General requirements.....	13
6.3.1 Extreme temperatures	13
6.3.2 Extreme values of test power source	13
6.3.2.1 Mains voltage and frequency	13
6.3.2.2 Battery power source.....	13
6.3.2.3 Other power sources.....	13
6.3.3 Procedure for tests at extreme temperatures	13
7 Environmental tests	14
7.1 Introduction.....	14
7.2 Procedure.....	14

7.3	Performance check	14
7.4	Vibration test	14
7.4.1	Purpose	14
7.4.2	Method of measurement	14
7.4.3	Requirement.....	15
7.5	Damp heat	15
7.5.1	Purpose	15
7.5.2	Method of measurement	15
7.5.3	Requirement.....	15
8	Transmitter	15
8.1	Frequency error	15
8.1.1	Definition.....	15
8.1.2	Method of measurement	15
8.1.3	Limits.....	16
8.2	Transmitter EIRP.....	16
8.2.1	Definition.....	16
8.2.2	Method of measurement	16
8.2.3	Limits.....	16
8.3	Transmitter spectrum mask	16
8.3.1	Definition.....	16
8.3.2	Method of measurement	16
8.3.3	Limits.....	17
8.4	Transmitter spurious emission.....	17
8.4.1	Definition.....	17
8.4.2	Method of measurement	17
8.4.3	Limits.....	17
9	Receiver.....	18
9.1	Maximum usable sensitivity.....	18
9.1.1	Definition.....	18
9.1.2	Method of measurement	18
9.1.3	Limits.....	18
9.2	Error behaviour at high input levels	18
9.2.1	Definition.....	18
9.2.2	Method of measurement	18
9.2.3	Limits.....	19
9.3	Co-channel rejection.....	19
9.3.1	Definition.....	19
9.3.2	Method of measurement	19
9.3.3	Limits.....	19
9.4	Adjacent channel selectivity.....	19
9.4.1	Definition.....	19
9.4.2	Method of measurement	19
9.4.3	Limits.....	20
9.5	Blocking or desensitization	20
9.5.1	Definition.....	20
9.5.2	Method of measurement	20
9.5.3	Limits.....	20
9.6	Spurious emissions	20
9.6.1	Definition.....	20
9.6.2	Method of measurement	21
9.6.3	Limit	21
10	Testing for compliance with technical requirements.....	21
10.1	Environmental conditions for testing	21
10.2	Interpretation of the measurement results	21
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	23
Annex B (informative):	Bibliography.....	24

Annex C (informative):	Change history	25
History		26

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/433fd06d-db67-411d-9303-98dfb13d0ec4/etsi-en-303-276-v1.1.1-2017-11>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.4] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

National transposition dates

Date of adoption of this EN:	22 August 2017
Date of latest announcement of this EN (doa):	30 November 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2018
Date of withdrawal of any conflicting National Standard (dow):	31 May 2019

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies technical characteristics and methods of measurements for maritime mobile broadband radiocommunication systems (MBR) radio equipment intended to operate in the 5,8 GHz band.

Table 1: Radiocommunications service frequency bands

Radiocommunications service frequency bands	
Transmit	5 852 MHz to 5 900 MHz
Receive	5 852 MHz to 5 900 MHz

The present document applies to systems utilizing integral electronically phase steered antennae applicable for communications between vessels and between vessels and platforms engaged in coordinated off-shore activities.

The present document covers the essential requirements of article 3.2 of Directive 2014/53/EU [i.1] under the conditions identified in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-T E.161 (02-2001): "Arrangement of digits, letters and symbols on telephones and other devices that can be used for gaining access to a telephone network".
- [2] Recommendation ITU-T O.153 (10-1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [3] ISO 25862:2009: "Ships and marine technology -- Marine magnetic compasses, binnacles and azimuth reading devices".
- [4] ETSI TS 103 052 (V1.1.1) (03-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

- [i.2] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.3] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.4] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Symbols and abbreviations

3.1 Symbols

For the purposes of the present document, the following symbols apply:

C_F	Minimum number of frames
dB_c	Level (dB) below carrier
dBm	Level (dB) relative to 1 mW
N	Number of transmitted bits
ppm	parts per million (10^{-6})
Q	Q factor is a resonator parameter
V	Volt

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ac	alternating current
BER	Bit Error Rate
CRC	Cyclic Redundancy Check
dc	direct current
EC	European Commission
EFTA	European Free Trade Association
EIRP	Equivalent Isotropically Radiated Power
EN	European Norm
ERP	Effective Radiated Power
EU	European Union
EUT	Equipment Under Test
FER	Frame Error Rate
ISO	International Organization for Standardization
ITU-T	International Telecommunication Union - Telecommunication standardization sector
LHCP	Left Hand Circular Polarization
MBR	Maritime Broadband Radiolink
RF	Radio Frequency
TR	Technical Report
TS	Technical Specification

4 General and operational requirements

4.0 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer, but as a minimum, shall be that specified in the test conditions contained in the present document. The equipment shall comply with all the technical requirements of the present document which are identified as applicable in annex A at all times when operating within the boundary limits of the declared operational environmental profile.

4.1 Construction

The mechanical and electrical construction and finish of the equipment shall conform in all respects to good engineering practice, and the equipment shall be suitable for use on board ships.

All controls shall be of sufficient size to enable the usual control functions to be easily performed and the number of controls should be the minimum necessary for simple and satisfactory operation.

For the purpose of conformance testing, relevant technical documentation shall be supplied with the equipment.

The equipment shall be capable of operating on single frequency channels.

The MBR shall be equipped with an automatic mechanism for reducing the power level to the level necessary to achieve acceptable Bit Error Rate (BER).

It shall not be possible to transmit while any frequency synthesizer used within the transmitter is out of lock.

4.2 Controls and indicators

The equipment shall have a channel selector and shall indicate the channel at which the installation is set. The channel designator shall be legible irrespective of the external lighting conditions.

Where an input panel on the equipment for entering the digits 0 - 9 is provided, this shall conform to Recommendation ITU-T E.161 [1].

The equipment shall have the following additional controls and indicators:

- an on/off switch for the entire installation with a visual indication that the installation is in operation;
- a means for reducing the brightness of the equipment illumination to zero;
- a visual indication that the equipment is transmitting.

The equipment shall also meet the following requirements:

- the user shall not have access to any control which, if wrongly set, might impair the technical characteristics of the equipment.

4.3 Safety precautions

Measures shall be taken to protect the equipment against the effects of overcurrent or overvoltage.

Measures shall be taken to prevent damage to the equipment if the electrical power source produces transient voltage variations and to prevent any damage that might arise from an accidental reversal of polarity of the electrical power source.

Means shall be provided for earthing exposed metallic parts of the equipment.

All components and wiring in which the dc or ac voltage (other than radio-frequency voltage) produce, singly or in combination, peak voltages in excess of 50 V shall be protected against any accidental access and shall be automatically isolated from all electrical power sources if the protective covers are removed. Alternatively, the equipment shall be constructed in such a way as to prevent access to components operating at such voltages unless an appropriate tool is used such as a nut-spanner or screwdriver. Conspicuous warning labels shall be affixed both inside the equipment and on the protective covers.

The information in any volatile memory device shall be protected from interruptions in the power supply of up to 60 s duration.

4.4 Labeling

All controls, instruments, indicators and ports shall be clearly labelled.

Details of the power supply from which the equipment is intended to operate shall be clearly indicated on the equipment.

The transmitter may operate with high emitted radio power and the antenna shall be labelled with the minimum safe distance from the antenna.

The compass safe distance as defined in ISO 25862 [3] (Method B) shall be stated on the equipment or in the technical manual.

4.5 Frequencies

The equipment shall be capable of operating on the frequencies 5 862 MHz and/or 5 890 MHz.

4.6 Polarization

The equipment shall operate with vertical or left hand circular polarization (LHCP).

4.7 Antenna gain

The antenna gain shall be declared by the equipment manufacturer.

4.8 Self-monitoring

The MBR equipment shall be self-monitoring and should a malfunction be detected which could cause harmful interference, the MBR shall automatically cease its transmissions.

4.9 Adaptive transmitter power control

The MBR equipment shall have a transmitter power adaptive control where the output power of the transmitter is automatically reduced to the lowest necessary level.

The adaptive transmitter power control shall be able to reduce the MBR output power by at least 25 dB.

5 General conditions of measurements

5.1 Test site and general arrangements for measurements

Measurements of all equipment with integral antenna shall be done by radiated measurements.

Descriptions of the anechoic chamber and radiated measurement arrangements are included in ETSI TS 103 052 [4].