



**Integrated broadband cable  
telecommunication networks (CABLE);  
IPv6 Transition Technology Engineering and  
Operational Aspects;  
Part 6: 6RD**

*ETSI STANDARD PREVIEW*  
*(not for circulation)*  
*https://standards.etsi.org/standards-search/a02e819d-ad6c-4c1f-a7f5-ea1601246166/103-443-6-v1.1.1-*

---

Reference

DTS/CABLE-00018-6

---

Keywords

cable, HFC, IPv6

---

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
Modal verbs terminology.....	4
Introduction .....	4
1 Scope .....	6
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	8
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations .....	8
4 General Considerations .....	10
4.1 Background .....	10
4.2 General Overview.....	11
4.3 Vendor Considerations .....	11
5 Gap Analysis .....	12
5.1 Consideration .....	12
5.2 Overview .....	12
6 Domain Functionality.....	13
6.1 End to End Network Domains .....	13
6.2 CPE Home Network Domain .....	13
6.3 Access Network Domain.....	14
6.4 Core Network Domain .....	14
6.5 Data Centre Domain.....	14
6.6 DMZ Service Domain .....	14
6.7 Transit and Peering Service Domain .....	14
6.8 Management and Monitoring Domain .....	15
6.9 Security Domain.....	15
7 Technical Considerations .....	15
7.1 Hardware .....	15
7.2 MTU and fragmentation .....	15
7.3 Reliability .....	16
7.4 Quality of Service.....	16
8 LSN and CPE Requirements .....	16
8.1 General .....	16
8.2 LSN .....	16
8.3 CPE .....	17
9 6RD Feature Requirements .....	17
10 Network node Requirements .....	20
10.1 BR Network node Hardware Feature and Topology .....	20
10.2 Network node specific requirements .....	20
10.2.1 General considerations.....	20
10.2.2 Integrated topology requirements .....	20
10.2.3 Hairpin topology requirements .....	22
10.3 Scalability.....	23
10.4 Performance .....	23
History .....	25

---

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Integrated broadband cable telecommunication networks (CABLE).

The present document is part 6 of a multi-part deliverable. Full details of the entire series can be found in part 1 [20].

---

## Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

**"must"** and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

Considering the depletion of IPv4 addresses, transition to IPv6 is required in order to enable continued growth of the customer base connected to cable networks and ensure service continuity for existing and new customers. High-quality connectivity to all kinds of IP-based services and networks is essential in today's business and private life.

The present document accommodates an urgent need in the industry to implement and integrate the IPv6 transition technologies as specified by ETSI TS 101 569-1 [1] into their cable networks. The choice of the technology implemented depends on factors such as the business needs, current deployed architectures and plans for cost effectively transition from IPv4 to IPv6.

Current global IPv4 address space was projected to be depleted around the middle of 2012; depletion for the operator was estimated around end 2012. As part of the resulting roll-out of IPv6 in the operator's network, specific measures had to be taken to allow a smooth transition and coexistence between IPv4 and IPv6. ETSI developed requirements to address transition from IPv4 to IPv6 specifying six transition technologies as given by ETSI TS 101 569-1 [1] that were at the time considered to be the most appropriate to assist cable operators to transition their cable networks to IPv6.

Since then the industry has acquired more experience with the technology options settling in the main for DS-Lite across the cable network market and NAT64 IPv6 transition technologies across the mobile market.

The objective of the present document is to define the operational and engineering requirements to enable engineers to implement a seamless transition of the cable networks to IPv6 with the application of the 6RD transition technology.

The present document is the final part of a companion of ETSI standards developed in 4 phases to provide the cable sector in particular cable operators engineering and operational staff a standardized approach when integrating one of the five IPv6 transition technologies, NAT64, DS-Lite, 464XLAT, 6RD and MAP-E.

The first phase assessed the different IPv6 transition technology options being defined by industry with recommendation for the most appropriate with consideration of current network architectures, ensuring adequate scale and a cost effective transition approach from IPv4 to IPv6 as the IPv4 addresses deplete. The objective being to examine the pros and cons of the IPv6 transition technologies and recommend the most cost effective solution that would enable the cable operators to minimize the cost of upgrades to their existing network plant whilst maintain continuity of services to their present and new added customers. The details of the study are given by ETSI TR 101 569 [i.2].

In the second phase an ETSI technical specification was developed to specify technical requirements for six transition technologies that industry were considering for use by Cable Operators depending on the current state of their deployed cable network architecture, service model requirements and their IPv6 transition strategy as the IPv4 addresses depleted. These six IPv6 transition technologies are specified by ETSI TS 101 569-1 [1], covering NAT64, DSLite, 6RD, NAT44, 464XLAT and MAP-E.

In the third phase ETSI developed a series of conformance test specifications to enable the compliance verification of the five IPv6 transition technologies, NAT64, DS-Lite, 464XLAT, 6RD and MAP-E that were specified during phase 2 standardization. The conformance tests are developed against the requirements given by the ETSI TS 101 569-1 [1]. The series of conformance tests developed for each of the four transition technologies, are as given by ETSI TS 103 238 parts 1 [2] and to 3 [4] respectively for NAT64; ETSI TS 103 239 parts 1 [5] to 3 [7] respectively for MAP-E; ETSI TS 103 241 parts 1 [8] to 3 [10] respectively for DS-Lite; ETSI TS 103 242 parts 1 [11] to 3 [13] respectively for XLAT and ETSI TS 103 243 parts 1 [14] to 3 [16] respectively for 6RD.

Phase 4 is the present project phase for development of technical specifications covering the operational and engineering requirements with the present document being Part 6 of a multi-part series covering the IPv6 transition technology 6RD.

DOCSIS® is a registered Trade Mark of Cable Television Laboratories, Inc., and is used in the present document with permission.

**ETSI STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standard/standard-sist/a028194-ad6c-4c1f-a7f5-ea181a0172bc/etsi-ts-103-443-6-v1.1.1>  
2016-08

---

# 1 Scope

The present document presents the engineering and operational requirements for the application of the IPv6 transition technology 6RD as defined by ETSI TS 101 569-1 [1] (IPv6 Transition Requirements) implemented within an integrated broadband cable network end to end across its network domains.

The present document is Part 6 of a multi-part series and presents the operational aspects of the IPv6 transition technology 6RD across the cable network domains.

Only those elements of the network that have to be engineered to operate the IPv6 transition technology 6RD are presented. Descriptions and interface details of network elements that do not change are already addressed by the relevant equipment cable standards and therefore this information is not included in the present document.

The conformity of the 6RD implementation is relevant when assessing its implementation and operational requirements across the cable network to ensure the implementation is correctly engineered to conform to the requirements of the base standard ETSI TS 101 569-1 [1]. These conformance tests are not specified in the present document as they are already specified by ETSI TS 103 243 parts 1 [14] to 3 [16].

The operational aspects for the IPv6 transition technology 6RD are considered when engineered end to end across the cable network domains;

- CPE Home Networking Domain
- Access Network Domain
- Core Network Domain
- Data Centre Domain
- DMZ Service Domain
- Transit and Peering Domain
- Management and Monitoring Domain
- Security Domain

The present document specifies the requirements to be considered when the defined IPv6 transition technology 6RD is engineered across the cable network domains.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 101 569-1: "Integrated Broadband Cable Telecommunication Networks (CABLE); Cable Network Transition to IPv6 Part 1: IPv6 Transition Requirements".

- [2] ETSI TS 103 238-1: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for NAT64 technology; Part 1: Protocol Implementation Conformance Statement (PICS) proforma".
- [3] ETSI TS 103 238-2: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for NAT64 technology; Part 2: Test Suite Structure and Test Purposes (TSS&TP)".
- [4] ETSI TS 103 238-3: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for NAT64 technology; Part 3: Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".
- [5] ETSI TS 103 239-1: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for MAP-E technology; Part 1: Protocol Implementation Conformance Statement (PICS) proforma".
- [6] ETSI TS 103 239-2: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for MAP-E technology; Part 2: Test Suite Structure and Test Purposes (TSS&TP)".
- [7] ETSI TS 103 239-3: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for MAP-E technology; Part 3: Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".
- [8] ETSI TS 103 241-1: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for DS-Lite technology; Part 1: Protocol Implementation Conformance Statement (PICS) proforma".
- [9] ETSI TS 103 241-2: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for DS-Lite technology; Part 2: Test Suite Structure and Test Purposes (TSS&TP)".
- [10] ETSI TS 103 241-3: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for DS-Lite technology; Part 3: Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".
- [11] ETSI TS 103 242-1: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for 464XLAT technology; Part 1: Protocol Implementation Conformance Statement (PICS) proforma".
- [12] ETSI TS 103 242-2: "Integrated broadband cable telecommunication networks (CABLE) Testing; Conformance test specifications for 464XLAT technology; Part 2: Test Suite Structure and Test Purposes (TSS&TP)".
- [13] ETSI TS 103 242-3: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for 464XLAT technology; Part 3: Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".
- [14] ETSI TS 103 243-1: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for 6rd technology; Part 1: Protocol Implementation Conformance Statement (PICS) proforma".
- [15] ETSI TS 103 243-2: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for 6rd technology; Part 2: Test Suite Structure and Test Purposes (TSS&TP)".
- [16] ETSI TS 103 243-3: "Integrated broadband cable telecommunication networks (CABLE); Testing; Conformance test specifications for 6rd technology; Part 3: Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".
- [17] IETF RFC 5969: "IPv6 Rapid Deployment on IPv4 Infrastructures (6rd) -- Protocol Specification".
- [18] IETF RFC 4459 (April 2006): "MTU and Fragmentation Issues with In-the-Network Tunneling".
- [19] IETF RFC 2983 (October 2000): "Differentiated Services and Tunnels".

- [20] ETSI TS 103 443-1: "Integrated broadband cable telecommunication networks (CABLE); IPv6 Transition Technology Engineering and Operational Aspects; Part 1: General".
- [21] IETF RFC 4787: "Network Address Translation (NAT) Behavioral Requirements for Unicast UDP".
- [22] IETF RFC 5382: "NAT Behavioral Requirements for TCP".
- [23] IETF RFC 5508: "NAT Behavioral Requirements for ICMP".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CableLabs.

NOTE: Available at <http://www.cablelabs.com/specs>

- [i.2] ETSI TR 101 569: "Access, Terminals, Transmission and Multiplexing (ATTM); Integrated Broadband Cable and Television Networks; Cable Network Transition to IPv6".

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**4in6**: encapsulation of IPv4 packets within IPv6 packet format

**NAT44**: network address translation from an IPv4 address to another IPv4 address

**P Router**: label switching router acting as a transit router in the core network of an MPLS network

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

6PE	IPv6 Provider Edge
6RD	IPv6 Rapid Deployment
6VPE	IPv6 VPN Provider Edge
AAA	Authentication, Authorization and Accounting
ALG	Application Layer Gateway
AMPS	Amplifiers
AS	Autonomous System
ASCII	American Standard Code for Information Interchange
ASIC	Application Specific Integrated Circuit
B4	Basic Bridging BroadBand element
BFD	Bidirectional Forwarding Detection
BGP	Border Gateway Protocol
BNG	Broadband Network Gateway
BR	Boarder Routers



CDP	Cisco Discovery Protocol
CE	Customer Edge
CEF	Cisco Express Forwarding
CMTS	Cable Modem Termination System
CoPP	Control Plane Policing
CPE	Customer Premises Equipment
CPU	Central Processing Unit
DAD	Duplicate Address Detection
dCEF	distributed Cisco Express Forwarding
DCU	Destination Class Usage
DHCP	Dynamic Host Configuration
DMZ	Demilitarised Zone
DNS	Domain Name System
DOCSIS 3.0	Data over Cable System Interface Specification version 3.0
DR	Data Retention
DSCP	Differentiated Services Code Point
DS-Lite	Dual Stack-Lite
ECMP	Equal-Cost-Multi-Path
ESM	Enterprise Subscriber Management
FTP	File Transfer Protocol
GRT	Global Routing Table
GW	Gateway
GW	GateWay
HA	High Availability
HFC	Hybrid Fibre Coax
HSRP	Hot Standby Router Protocol
ICMP	Internet Control Message Protocol
ID	IDentifier
IGP	Interior Gateway Protocol
IMIX	Internet Mix
IP	Internet Protocol
IPFIX	IP Flow Information Export
IPv4	IP version 4
IPv6	IP version 6
IRB	Integrated Routing and Bridging
ISIS	Intermediate System to Intermediate System
ISP	Internet Service Provider
ISSU	In-Service Software Upgrade
IXPE	Internet Exchange Provider Edge
L2	Layer 2
LAN	Local Area Network
LDP	Label Distribution Protocol
LI	Lawful Intercept
LLDP	Link Layer Discovery Protocol
LSN	Large Scale NAT
MAP-E	Mapping of Address and Port - Encapsulation mode
MFIB	Multicast Forwarding Information Base
MLD/L2	Multicast Listener Discovery / Layer 2
MLD/L2	Multicast Listener Discovery/ Layer 2
MP BGP	MultiProtocol Boarder Gateway Protocol
MP	MultiProtocol
MPLS	MultiProtocol Label Switching
MSS	Maximum Segment Size
MSTP	Multiple Spanning Tree Protocol
MT	Multi-Topology
MTU	Maximum Transmission Unit
NAT	Network Address Translation
NAT44	Network Address Translation IPv4 to IPv4
NAT64	Network Address Translation IPv6 to IPv4
NCC	Network Coordination Center
ND	Neighbour Discovery
NDP	Neighbour Discovery Protocol

NFv9	Netflow Version 9
NPU	Network Processing Unit
NSF/GR	Non-Stop Forwarding Graceful Restart
NTP	Network Time Protocol
NUD	Neighbour Unreachability Detection
OAM	Operation, Administration and Maintenance
PCP	Port Control Protocol
PE	Provider Edge
PIM	Protocol Independent Multicasting
PPTP	Point-to-Point Tunneling Protocol
PPTP	Point-to-Point Tunnelling Protocol
PS-BGP	Pretty Secure Boarder Gateway Protocol
QoS	Quality of Service
QPPB	QoS Policy Propagation via Boarder Gateway Protocol
RADIUS	Remote Authentication Dial-In User Service
RDT	Reliable Data Transfer
RG	Residential Gateway
RIPE NCC	Réseaux IP Européens Network Coordination Centre
RIPE	Réseaux Internet Protocol Européens
RIR	Regional Internet Registry
RSTP	Rapid Spanning Tree Protocol
RTCP	Real-Time Transmission Control Protocol
RTP	Real-Time Protocol
RTSP	Real-Time Streaming Protocol
SCU	Source Class Usage
SEND	Secure Neighbour Discovery
SIP	Session Initiated Protocol
SNMP	Simple Network Management Protocol
SSH	Secure SHell
SSO	Stateful SwitchOver
SVI	Switched Virtual Interface
SYSLOG	Syslog Protocol
TACACS	Terminal Access Controller Access Control System
TCP	Transmission Control Protocol
UDP	User Datagram Protocol
VLAN	Virtual LAN
VPLS	Virtual Protocol Local Area Network Service
VPN	Virtual Private Network
VRF	Virtual Routing and Forwarding
VRRP	Virtual Router Redundancy Protocol
XLAT	transLATor
XML	eXtensible Markup Language

---

## 4 General Considerations

### 4.1 Background

The present document is part of a series of ETSI technical specifications specifying requirements to engineer and operate the 6RD transition technology end to end across a cable operator's network. Its implementation would ensure the network provider can continue to provide business continuity throughout the depletion of publicly routable IPv4 addresses and the subsequent rollout and migration to IPv6 in the operator's network.

To aid this transition some sectors of industry are currently evaluating 6RD as their chosen technology to mitigate the gap and lack of integration and compatibility between IPv4 and IPv6.