



**Intelligent Transport Systems (ITS);
Testing;
Conformance test specifications for
Decentralized Environmental Notification
Basic Service (DEN);**

Part 2: Test Suite Structure and Test Purposes (TSS & TP)

PREVIEW
iTech Standards (http://www.it-techstandards.com/standards/17e09f17-62f2-44ae-8103-1120071f155e/etsi-ts-102-869-2-v1.4.1-
<https://standards.it-europe.net/standards/17e09f17-62f2-44ae-8103-1120071f155e/etsi-ts-102-869-2-v1.4.1->

Reference

RTS/ITS-00158

Keywords

ITS, testing, TSS&TP

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references	6
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	6
4 Test Suite Structure (TSS).....	7
4.1 Structure for DEN tests	7
4.2 Test groups	7
4.2.1 Introduction.....	7
4.2.2 Root	7
4.2.3 Groups	7
4.2.4 Categories	7
5 Test Purposes (TP)	8
5.1 Introduction	8
5.1.1 TP definition conventions.....	8
5.1.2 TP Identifier naming conventions.....	8
5.1.3 Rules for the behaviour description.....	8
5.1.4 Sources of TP definitions.....	8
5.1.5 Mnemonics for PICS reference.....	8
5.2 Test purposes for DEN	9
5.2.1 Message Transmission.....	9
5.2.1.1 Message Format	9
5.2.1.2 Event Generation.....	10
5.2.1.3 Event Update.....	14
5.2.1.4 Event Termination.....	16
5.2.1.5 Message Repetition	20
5.2.1.6 Lower-layer parameters	26
5.2.2 Message Reception	27
5.2.3 Keep-Alive Forwarding	32
Annex A (informative): Bibliography.....	40
History	41

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document is part 2 of a multi-part deliverable covering Conformance test specification for Decentralized Environmental Notification Basic Service (DEN) as identified below:

- Part 1: "Test requirements and Protocol Implementation Conformance Statement (PICS) pro forma";
- Part 2: "Test Suite Structure and Test Purposes (TSS & TP)";**
- Part 3: "Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document provides the Test Suite Structure and Test Purposes (TSS & TP) for Decentralized Environmental Notification Basic Service (DEN) as defined in ETSI EN 302 637-3 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [7].

The ISO standard for the methodology of conformance testing (ISO/IEC 9646-1 [4] and ISO/IEC 9646-2 [5]) as well as the ETSI rules for conformance testing (ETSI ETS 300 406 [8]) are used as a basis for the test methodology.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 302 637-3 (V1.2.2): "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 3: Specifications of Decentralized Environmental Notification Basic Service".
- [2] ETSI TS 102 869-1 (V1.4.1): "Intelligent Transport Systems (ITS); Testing; Conformance test specifications for Decentralized Environmental Notification Basic Service (DEN); Part 1: Test requirements and Protocol Implementation Conformance Statement (PICS) pro forma".
- [3] ETSI TS 102 871-1 (V1.3.1): "Intelligent Transport Systems (ITS); Testing; Conformance test specifications for GeoNetworking ITS-G5; Part 1: Test requirements and Protocol Implementation Conformance Statement (PICS) pro forma".
- [4] ISO/IEC 9646-1 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 1: General concepts".
- [5] ISO/IEC 9646-2 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 2: Abstract Test Suite specification".
- [6] ISO/IEC 9646-6 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 6: Protocol profile test specification".
- [7] ISO/IEC 9646-7 (1995): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".
- [8] ETSI ETS 300 406 (1995): "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EG 202 798 (V1.1.1): "Intelligent Transport Systems (ITS); Testing; Framework for conformance and interoperability testing".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 302 637-3 [1], ISO/IEC 9646-6 [6] and ISO/IEC 9646-7 [7] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATS	Abstract Test Suite
BO	Inopportune test events for Behaviour tests
BTP	Basic Transport Protocol
BTP-B	Basic Transport Protocol Type B
BV	valid test events for Behaviour tests
CAN	Controller Area Network
CLT	Current Local Time
DE	Data Element
DEN	Decentralized Environmental Notification
DENM	Decentralized Environmental Notification Message
EVGN	Message transmission - Event Generation
EVRP	Message transmission - Message Repetition
EVTR	Message transmission - Event Termination
EVUP	Message transmission - Event Update
GBC	Geographically-Scoped Broadcast
ISO	International Organization for Standardization
ITS	Intelligent Transportation Systems
ITS-S	Intelligent Transport System - Station
IUT	Implementation Under Test
KAFW	Keep-alive Forwarding
MSGF	Message Format
MSRV	Message reception
PAR	Message transmission - Lower-layer parameters
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
SSP	Service Specific Permissions
TI	Timer tests
TP	Test Purposes
TS	Test Suite
TSS	Test Suite Structure

4 Test Suite Structure (TSS)

4.1 Structure for DEN tests

Table 1 shows the DEN Test Suite Structure (TSS) including its subgroups defined for conformance testing.

Table 1: TSS for DEN

Root	Group	category
DEN	Message format	Valid
	Event Generation	Valid
	Event Update	Valid and Inopportune
	Event Termination	Valid, Inopportune and Timer
	Message Repetition	Valid
	Lower-layer parameters	Valid
	Message reception	Valid and Inopportune
	Keep-alive Forwarding	Valid and Timers

The test suite is structured as a tree with the root defined as DEN. The tree is of rank 2 with the first rank a functional area and the second rank is the standard ISO conformance test categories.

4.2 Test groups

4.2.1 Introduction

The test suite has a total of three levels. The first level is the root. The second level separates the root into various functional areas. The third level is the standard ISO conformance test categories.

4.2.2 Root

The root identifies the Decentralized Environmental Notification Basic Service (DEN) given in ETSI EN 302 637-3 [1].

4.2.3 Groups

This level contains height functional areas identified as:

- Message format
- Event Generation
- Event Update
- Event Termination
- Message Repetition
- Lower-layer parameters
- Message reception
- Keep-alive Forwarding

4.2.4 Categories

This level contains the standard ISO conformance test categories behaviour: valid events and inopportune events and Timer.

5 Test Purposes (TP)

5.1 Introduction

5.1.1 TP definition conventions

The TP definition is built according to ETSI EG 202 798 [i.1].

5.1.2 TP Identifier naming conventions

The identifier of the TP is built according to table 2.

Table 2: TP naming convention

Identifier:	TP/<root>/<gr>/<x>/<nn>		
	<root> = root	DEN	
	<gr> = group	MSGF	Message transmission - Message format
		EVGN	Message transmission - Event Generation
		EVUP	Message transmission - Event Update
		EVTR	Message transmission - Event Termination
		EVRP	Message transmission - Message Repetition
		PAR	Message transmission - Lower-layer parameters
		MSRV	Message reception
		KAFW	Keep-alive Forwarding
	<x> = type of testing	BV	Behaviour: Valid event tests
		BO	Behaviour: Inopportune event tests
		TI	Timer tests
	<nn> = sequential number		01 to 99

5.1.3 Rules for the behaviour description

The description of the TP is built according to ETSI EG 202 798 [i.1].

ETSI EN 302 637-3 [1] does not use the finite state machine concept. As consequence, the test purposes use a generic "Initial State" that corresponds to a state where the IUT is ready for starting the test execution. Furthermore, the IUT shall be left in this "Initial State", when the test is completed.

Being in the "Initial State" refers to the starting point of the initial device configuration. There are no pending actions, no instantiated buffers or variables, which could disturb the execution of a test.

5.1.4 Sources of TP definitions

All TPs are specified according to ETSI EN 302 637-3 [1].

5.1.5 Mnemonics for PICS reference

To avoid an update of all TPs when the PICS document is changed, table 3 introduce mnemonics name and the correspondence with the real PICS item number.

The PICS item column refers to Table/Item of ETSI TS 102 869-1 [2].

Table 3: Mnemonics for PICS reference

Mnemonic	PICS item
PICS_DENM_GENERATION	A.2/1
PICS_DENM_UPDATE	A.2/2
PICS_DENM_REPETITION	A.2/3
PICS_DENM_CANCELLATION	A.2/4
PICS_DENM_NEGATION	A.2/5
PICS_DENM_RECEPTION	A.2/6
PICS_DENM_KAF	A.2/7
PICS_IMPACT_REDUCTION	A.12/2
PICS_SECURITY	ETSI TS 102 871-1 [3], A.32/12

5.2 Test purposes for DEN

5.2.1 Message Transmission

5.2.1.1 Message Format

TP Id	TP/DEN/ MSGF/BV-01
Test objective	Check that protocolVersion is set to 1 and messageID is set to 1
Reference	ETSI EN 302 637-3 [1], clause B.1
PICS Selection	PICS_DENM_GENERATION
Initial conditions	
with { the IUT being in the "initial state" }	
Expected behaviour	
ensure that { when { the IUT receives an AppDENM_Trigger request from the application layer } then { the IUT sends a valid DENM containing ITS PDU header containing protocolVersion indicating value 1 and containing messageID indicating value 1 }	

TP Id	TP/DEN/ MSGF/BV-02
Test objective	Check that sent DENM contains at least one 'trace' DE
Reference	ETSI EN 302 637-3 [1], clause 6.1.3.2
PICS Selection	PICS_DENM_GENERATION
Initial conditions	
with { the IUT being in the "initial state" }	
Expected behaviour	
ensure that { when { the IUT receives an AppDENM_Trigger request from the application layer } then { the IUT sends a valid DENM containing location container containing at least one 'trace' }	

5.2.1.2 Event Generation

TP Id	TP/DEN/EVGN/BV-01
Test objective	Check that DEN Basic Service generates a new DENM on reception of a valid AppDENM_Trigger request
Reference	ETSI EN 302 637-3 [1], clause 6.1.2.1
PICS Selection	PICS_DENM_GENERATION
Initial conditions	
with { the IUT being in the "initial state" }	
Expected behaviour	
ensure that { when { the IUT receives an AppDENM_Trigger request from the application layer } then { the IUT sends a valid DENM } }	

TP Id	TP/DEN/EVGN/BV-02
Test objective	Check that a new ActionID value is assigned for each newly generated DENM
Reference	ETSI EN 302 637-3 [1], clause 6.1.1.1
PICS Selection	PICS_DENM_GENERATION
Initial conditions	
with { the IUT being in the "initial state" and the IUT having generated several events }	
Expected behaviour	
ensure that { when { the IUT is requested to generate a new event } then { the IUT sends a valid DENM containing management container containing actionID indicating an unused value } }	

TP Id	TP/DEN/EVGN/BV-03
Test objective	Check that a newly created ActionID contains the StationID of the originating ITS-S that detected the event
Reference	ETSI EN 302 637-3 [1], clause 6.1.1.1
PICS Selection	PICS_DENM_GENERATION
Initial conditions	
with { the IUT being in the "initial state" }	
Expected behaviour	
ensure that { when { the IUT is requested to generate a new event } then { the IUT sends a valid DENM containing management container containing actionID containing originatingStationID indicating its own StationID } }	

TP Id	TP/DEN/EVGN/BV-04
Test objective	Check that cause and subcause values included in DENM as provided by application
Reference	ETSI EN 302 637-3 [1], clauses 7.1.4, B.17
PICS Selection	PICS_DENM_GENERATION
Initial conditions	
with { the IUT being in the "initial state" }	
Expected behaviour	
ensure that { when { the IUT receives an AppDENM_trigger request from the application layer containing situation container containing eventType containing causeCode indicating Value1 containing subCauseCode indicating Value2 } then { the IUT sends a valid DENM containing situation container containing eventType containing causeCode indicating Value1 containing subCauseCode indicating Value2 } }	

TP Id	TP/DEN/EVGN/BV-05
Test objective	Check that referenceTime is set to the current time when generating a DENM for a new event
Reference	ETSI EN 302 637-3 [1], clause 8.2.1.3
PICS Selection	PICS_DENM_GENERATION
Initial conditions	
with { the IUT being in the "initial state" and the IUT having generated several events }	
Expected behaviour	
ensure that { when { the IUT is requested to generate a new event } then { the IUT sends a valid DENM containing management container containing referenceTime indicating CLT } }	

TP Id	TP/DEN/EVGN/BV-07
Test objective	Check that sequenceNumber is set to a next unused value each time an event is detected
Reference	ETSI EN 302 637-3 [1], clauses 6.1.1.1 and 8.2.1.2
PICS Selection	PICS_DENM_GENERATION
Initial conditions	
with { the IUT being in the "initial state" and the IUT having generated several events and the IUT having generated its last DENM containing management container containing actionID containing sequenceNumber indicating SEQ1 and no active event being associated with sequenceNumber SEQ1 + 1 }	
Expected behaviour	
ensure that { when { the IUT is requested to generate a new event } then { the IUT sends a valid DENM containing management container containing actionID containing sequenceNumber indicating SEQ1 + 1 } }	