



SLOVENSKI STANDARD

SIST EN 302 307-2 V1.1.1:2015

01-oktober-2015

Digitalna videoradiodifuzija (DVB) - Druga generacija strukture okvirov, kodiranja kanalov in modulacijskih sistemov za radiodifuzijo, interaktivne storitve, novinarstvo in druge širokopasovne satelitske aplikacije - 2. del: Priključki DVB-S2 (DVB-S2X)

Digital Video Broadcasting (DVB) - Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications - Part 2: DVB-S2 Extensions (DVB-S2X)

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 307-2 V1.1.1:2015](https://standards.iteh.ai/catalog/standards/sist/a68dcf17-ee6e-4fde-b4c6-3f5c71a8225f/sist-en-302-307-2-v1-1-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/a68dcf17-ee6e-4fde-b4c6-3f5c71a8225f/sist-en-302-307-2-v1-1-1-2015>

Ta slovenski standard je istoveten z: EN 302 307-2 Version 1.1.1

ICS:

33.170	Televizijska in radijska difuzija	Television and radio broadcasting
--------	-----------------------------------	-----------------------------------

SIST EN 302 307-2 V1.1.1:2015	en
--------------------------------------	-----------

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 307-2 V1.1.1:2015

<https://standards.iteh.ai/catalog/standards/sist/a68dcf17-ee6e-4fde-b4c6-3f5c71a8225f/sist-en-302-307-2-v1-1-1-2015>

ETSI EN 302 307-2 V1.1.1 (2015-02)



EUROPEAN STANDARD

**Digital Video Broadcasting (DVB);
Second generation framing structure, channel coding and
modulation systems for Broadcasting,
Interactive Services, News Gathering and
other broadband satellite applications;
Part 2: DVB-S2 Extensions (DVB-S2X)**

EBU
OPERATING EUROVISION

DVB[®]
Digital Video
Broadcasting

Reference

DEN/JTC-DVB-341-2

Keywords

BSS, digital, DVB, modulation, satellite, TV

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 307-2 V1.1.1:2015

<https://standards.iteh.ai/catalog/standards/sist/a68dcf17-ee6e-4fde-b4c6-3f5c71a8224f/etsi-en-302-307-2-v1-1-1-2015>

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

© European Broadcasting Union 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	9
3 Symbols and abbreviations.....	9
3.1 Symbols.....	9
3.2 Abbreviations	9
4 Transmission system description.....	9
4.1 System definition.....	9
4.2 System architecture	9
4.3 System configurations	10
5 Subsystems specifications	14
5.1 Mode adaptation	14
5.1.1 Input Interfaces	14
5.1.2 Input stream synchronizer (optional, not relevant for single TS - BS)	14
5.1.3 Null-Packet Deletion (ACM and Transport Stream only)	14
5.1.4 CRC-8 encoder (for packetized streams only)	14
5.1.5 Merger/Slicer	14
5.1.6 Base-Band Header insertion	14
5.1.7 GSE High Efficiency Mode (GSE-HEM)	15
5.1.8 Channel bonding for multi-tuner (L) receivers	16
5.1.8.1 Introduction to channel bonding	16
5.1.8.2 Channel bonding for TS transmission	16
5.1.8.3 Channel bonding for GSE transmission	18
5.2 Stream Adaptation	19
5.2.1 Padding	19
5.2.2 BB scrambling	19
5.3 FEC Encoding	19
5.3.1 Outer encoding (BCH).....	21
5.3.2 Inner encoding (LDPC)	21
5.3.2.1 Inner coding for normal FECFRAME.....	21
5.3.2.2 Inner coding for short and medium FECFRAME	22
5.3.3 Bit interleaver	22
5.4 Constellations and Bit mapping.....	24
5.4.0 Bit mapping into $\pi/2$ BPSK constellation (VL-SNR modes)	24
5.4.1 Bit mapping into QPSK constellation	24
5.4.2 Bit mapping into 8PSK and 8APSK constellations	24
5.4.3 Bit mapping into 16APSK constellation	25
5.4.4 Bit mapping into 32APSK constellations	27
5.4.5 Bit mapping into 64APSK constellations	29
5.4.6 Bit mapping into 128APSK constellations	33
5.4.7 Bit mapping into 256APSK constellations	34
5.5 Physical Layer (PL) framing	40
5.5.1 Dummy PLFRAME insertion	41
5.5.2 PL signalling	41
5.5.2.1 SOF field.....	43
5.5.2.2 MODCOD field.....	43
5.5.2.3 TYPE field	45
5.5.2.4 PLS code, no time slicing.....	45

5.5.2.5	VL-SNR Header.....	46
5.5.2.6	Shortening and Puncturing of VL-SNR MODCODs	47
5.5.3	Pilot Insertion.....	48
5.5.4	Physical layer scrambling	48
5.5.4.1	PL scrambling for VL-SNR frames	49
5.5.4.1.1	$\pi/2$ -BPSK modulated frames.....	49
5.6	Baseband shaping and quadrature modulation	49
6	Error performance	50
Annex A (normative):	Signal spectrum at the modulator output.....	52
Annex B (normative):	Addresses of parity bit accumulators for $n_{ldpc} = 64\ 800$.....	54
Annex C (normative):	Addresses of parity bit accumulators for $n_{ldpc} = 16\ 200$ and $n_{ldpc} = 32\ 400$.....	91
Annex D (normative):	Additional tools	95
D.1	Implementation of TS based channel bonding	95
D.1.1	Transmitting side.....	95
D.1.2	Receiving side (informative)	95
D.2	Void.....	95
D.3	Void.....	95
D.4	Void.....	95
D.5	Signalling of reception quality via return channel (Normative for ACM).....	96
Annex E (normative):	Super-Framing Structure (optional).....	98
E.1	Purpose of Super-Framing Structure.....	98
E.2	Specification of Super-Frame as a Container.....	98
E.2.1	Super-Frame Structure	98
E.2.2	Start of Super-Frame (SOSF) Field.....	99
E.2.3	Super-Frame Format Indicator (SFFI) Field.....	99
E.2.4	Two-Way Scrambling	100
E.2.4.1	Scrambling Sequence Generation.....	100
E.2.4.2	Two-Way Scrambling Method	101
E.3	Format Specifications as Super-Frame Content.....	102
E.3.1	Super-Frame-aligned Pilots (SF-Pilots).....	102
E.3.1.1	Specification of SF-Pilots Type A	103
E.3.2	Format Specification 0: DVB-S2X.....	103
E.3.2.1	Pilot structure.....	104
E.3.2.2	Modified VL-SNR-frame	104
E.3.3	Format Specification 1: DVB-S2 legacy	105
E.3.4	Format Specification 2: Bundled PLFRAME (64 800 payload Size) with SF-Pilots.....	105
E.3.4.1	Bundled PLFRAME (64 800 payload) Definition	106
E.3.4.2	PLHEADER Specification for Bundled PLFRAMEs (64 800 payload)	107
E.3.4.3	SF-Pilot Structure	109
E.3.5	Format Specification 3: Bundled PLFRAME (16 200 Payload Size) with SF-Pilots.....	110
E.3.5.1	Bundled PLFRAME Definition	111
E.3.5.2	PLHEADER Specification for Short Bundled PLFRAME.....	112
E.3.5.3	SF-Pilot Structure	113
E.3.6	Format Specification 4: Flexible Format with VL-SNR PLH tracking.....	114
E.3.6.1	Super-Frame Header (SFH)	115
E.3.6.2	SFH-Trailer (ST)	116
E.3.6.3	Physical Layer Header (PLH).....	117
E.3.6.3.1	PLSCODE Definition.....	117
E.3.6.3.2	PLH Protection Levels	117
E.3.6.3.3	Signalling of MOD/COD/SPREAD and TYPE	118

E.3.6.3.4	Field for ISI or SID or TSN	119
E.3.6.3.5	SOF Sequence	119
E.3.6.4	PLFRAME structure	120
E.3.6.5	Pilot structure.....	120
E.3.6.5.1	SF-Pilots.....	120
E.3.6.5.2	Special VL-SNR Pilots	120
E.3.6.6	Spreading and Signalling Rules	121
E.3.6.7	Dummy Frame Definition.....	121
E.3.6.7.1	Dummy frames with deterministic content	122
E.3.6.7.2	Dummy frames with arbitrary content	122
E.3.7	Format Specifications 5 - 15: Reserved.....	122
E.4	Signalling of additional reception quality parameters via return channel (Normative for Interference Management at the Gateway).....	123
Annex F:	For future use	125
Annex G:	For future use	126
Annex H (informative):	Examples of possible use of the System.....	127
H.1	Void.....	127
H.2	Void.....	127
H.3	Void.....	127
H.4	Void.....	127
H.5	Void.....	127
H.6	Void.....	127
H.7	Satellite transponder models for simulations	127
H.8	Phase noise masks for simulations	129
Annex I (normative):	ACM Command.....	130
Annex J:	For future use	131
Annex K:	For future use	132
Annex L:	For future use	133
Annex M (normative):	Transmission format for wideband satellite transponders using time-slicing (optional).....	134
History		135

iTech STANDARD PREVIEW
(standards.itech.ai)

SIST EN 302 307-2 V1.1.1:2015
<https://standards.itech.ai/catalog/standards/sist/a68dc117-ec6e-41de-b4c6-3f5c71e82259/sist-en-302-307-2-v1-1-1-2015>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by Joint Technical Committee (JTC) Broadcast of the European Broadcasting Union (EBU), Comité Européen de Normalisation ELECTrotechnique (CENELEC) and the European Telecommunications Standards Institute (ETSI).

NOTE: The EBU/ETSI JTC Broadcast was established in 1990 to co-ordinate the drafting of standards in the specific field of broadcasting and related fields. Since 1995 the JTC Broadcast became a tripartite body by including in the Memorandum of Understanding also CENELEC, which is responsible for the standardization of radio and television receivers. The EBU is a professional association of broadcasting organizations whose work includes the co-ordination of its members' activities in the technical, legal, programme-making and programme-exchange domains. The EBU has active members in about 60 countries in the European broadcasting area; its headquarters is in Geneva.

European Broadcasting Union
CH-1218 GRAND SAconnex (Geneva)
Switzerland

Tel: +41 22 717 21 11

Fax: +41 22 717 24 81

standards.iteh.ai SIST EN 302 307-2 V1.1.1:2015

<https://standards.iteh.ai/catalog/standards/sist/a68dcf17-ee6e-4fde-b4c6->

The Digital Video Broadcasting Project (DVB) is an industry-led consortium of broadcasters, manufacturers, network operators, software developers, regulatory bodies, content owners and others committed to designing global standards for the delivery of digital television and data services. DVB fosters market driven solutions that meet the needs and economic circumstances of broadcast industry stakeholders and consumers. DVB standards cover all aspects of digital television from transmission through interfacing, conditional access and interactivity for digital video, audio and data. The consortium came together in 1993 to provide global standardization, interoperability and future proof specifications.

The present document is part 2 of a multi-part deliverable covering the optional extensions of the DVB-S2 system, denoted "DVB-S2X", as identified below:

Part 1: "DVB-S2";

Part 2: "DVB-S2 Extensions (DVB-S2X)".

National transposition dates

Date of adoption of this EN:	13 February 2015
Date of latest announcement of this EN (doa):	31 May 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2015
Date of withdrawal of any conflicting National Standard (dow):	30 November 2015

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "may not", "need", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The optional extensions of the S2 system have been approved in 2014 and are identified by the S2X denomination. Such extensions are non-backwards-compatible with EN 302 307 (V1.1.1) [4], are optional for the implementation of new receivers under EN 302 307-1 [3], but are normative for the implementation of receivers under the present document: mapping of specific S2X building blocks to application areas is specified in Table 1. For every S2X application area, as defined in Table 1, the configurations for the corresponding S2 application area, as defined in EN 302 307-1 [3], Table 1, will be implemented. In case of conflicts the definition of the S2X application area applies.

The present document targets the core application areas of S2 (Digital Video Broadcasting, forward link for interactive services using ACM, Digital Satellite News Gathering and professional digital links such as video point-to-point or Internet trunking links), and new application areas requiring very-low carrier-to-noise and carrier-to-interference operation (VL-SNR).

In particular for DTH, a possible use case is the launch of UHDTV-1 (e.g. 4k) television services in Ku-/Ka-band that will adopt HEVC encoding. In this context it may be desirable to eventually use fragments of smaller blocks of capacity on two or three DTH transponders and bond them into one logical stream. This permits to maximize capacity exploitation by avoiding the presence of spare capacity in individual transponders and/or to take maximum advantage of statistical multiplexing.

The S2X system offers the ability to operate with very-low carrier-to-noise and carrier-to-interference ratios (SNR down to -10 dB), to serve markets such as airborne (business jets), maritime, civil aviation internet access, VSAT terminals at higher frequency ranges or in tropical zones, small portable terminals for journalists and other professionals. Furthermore, the S2X system provides transmission modes offering significantly higher capacity and efficiency to serve professional links characterized by very-high carrier-to-noise and carrier-to-interference ratios conditions.

The present document reuses the S2 system architecture, while adding finer MODCOD steps, sharper roll-off filtering, technical means for bonding of multiple transponders and additional signalling capacity by means of an optional periodic super-frame structure, extended PLHEADER signalling schemes and the support of GSE-Lite signals.

The present document maintains the same clause numbering as EN 302 307-1 [3], in order to facilitate cross-reference.

1 Scope

The present document specifies the optional extensions of the S2 system, identified by the S2X denomination.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 101 545-1 (V1.1.1): "Digital Video Broadcasting (DVB); Second Generation DVB Interactive Satellite System (DVB-RCS2); Part 1: Overview and System Level specification".
- [2] ETSI TS 102 606-1 (V1.2.1): "Digital Video Broadcasting (DVB); Generic Stream Encapsulation (GSE); Part 1: Protocol".
- [3] ETSI EN 302 307-1: "Digital Video Broadcasting (DVB); Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications; Part 1: DVB-S2".
- [4] ETSI EN 302 307 (V1.1.1): "Digital Video Broadcasting (DVB); Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications".
- [5] ETSI EN 300 468: "Digital Video Broadcasting (DVB); Specification for Service Information (SI) in DVB systems".
- [6] ETSI TS 102 606-2: "Digital Video Broadcasting (DVB); Generic Stream Encapsulation (GSE); Part 2: Logical Link Control (LLC)".
- [7] ETSI ETS 300 801: "Digital Video Broadcasting (DVB); Interaction channel through Public Switched Telecommunications Network (PSTN)/ Integrated Services Digital Networks (ISDN)".
- [8] ETSI EN 301 195: "Digital Video Broadcasting (DVB); Interaction channel through the Global System for Mobile communications (GSM)".
- [9] ETSI ES 200 800: "Digital Video Broadcasting (DVB); DVB interaction channel for Cable TV distribution systems (CATV)".
- [10] ETSI ETS 300 802: "Digital Video Broadcasting (DVB); Network-independent protocols for DVB interactive services".
- [11] ETSI EN 301 790: "Digital Video Broadcasting (DVB); Interaction channel for satellite distribution systems".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Symbols and abbreviations

3.1 Symbols

For the purposes of the present document, the symbols given in EN 302 307-1 [3] apply.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in EN 302 307-1 [3] and the following apply:

128APSK	128-ary Amplitude and Phase Shift Keying
256APSK	256-ary Amplitude and Phase Shift Keying
64APSK	64-ary Amplitude and Phase Shift Keying
BPSK	Binary Phase Shift Keying
CU	Capacity Unit
GSE	Generic Stream Encapsulation
GSE-HEM	Generic Stream Encapsulation - High Efficiency Mode
HEVC	High Efficiency Video Coding
SF	Super-Frame
SFFI	Super-Frame Format Indicator
SFH	Super-Frame Header
SOSF	Start Of Super-Frame
ST	Super-Frame header Trailer
UHDTV	Ultra High Definition TeleVision
VL-SNR	Very Low - Signal to Noise Ratio

4 Transmission system description

See EN 302 307-1 [3], clause 4.

4.1 System definition

See EN 302 307-1 [3], clause 4.1.

4.2 System architecture

See EN 302 307-1 [3], clause 4.2.

The present document reuses the S2 system architecture as described in EN 302 307-1 [3], Figure 1, while adding finer MODCOD steps, sharper roll-off filtering, technical means allowing time-slicing of wide-band signals (for a reduced processing speed in the receiver), technical means for bonding of multiple transponders, among other technologies.

Additional signalling capacity is provided:

- an optional periodic super-frame structure with signalling of the format of the super-frame content and further benefits like simplifying synch recovery at VL-SNR and allowing periodic pilot structures and PL-Scramblers;
- an extended PLHEADER signalling scheme to support the additional MODCODs;
- an extended PLHEADER signalling scheme to support Mobile Frames (VL-SNR);
- a high-efficiency BBFRAME mode (GSE-HEM), similar to the T2 and C2 systems, to transport GSE/GSE-Lite packets;
- signalling of streams which are GSE-Lite compliant.

4.3 System configurations

See EN 302 307-1 [3], clause 4.3.

Table 1 associates the S2X system elements to the applications areas. All elements in Table 1 are optional in transmitting and receiving equipment complying with the S2 specification. At least "Normative" subsystems and functionalities shall be implemented in the transmitting and receiving equipment to comply with the present document for a specific application area.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 307-2 V1.1.1:2015](https://standards.iteh.ai/catalog/standards/sist/a68dcf17-ee6e-4fde-b4c6-3f5c71a8225f/sist-en-302-307-2-v1-1-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/a68dcf17-ee6e-4fde-b4c6-3f5c71a8225f/sist-en-302-307-2-v1-1-1-2015>

Table 1: S2X System configurations and application areas

System configurations		Broadcast services	Interactive services	DSNG	Professional services	VL-SNR
FECFRAME (normal) (see MODCODs below)	64 800 (bits)					
QPSK	1/4, 1/3, 2/5 (S2-MODCODs)	N	N	N	N	N
	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 (S2-MODCODs)	N	N	N	N	N
	13/45	N	N	N	N	N
	9/20; 11/20	N	N	N	N	N
	8PSK	3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (S2-MODCODs)	N	N	N	N
	23/36; 25/36; 13/18	N	N	N	N	N
8APSK-L (note 7)	5/9; 26/45	N	N	N	N	N
16APSK	2/3, 3/4, 4/5, 5/6, 8/9, 9/10 (S2-MODCODs)	N	N	N	N	N
	26/45; 3/5; 28/45; 23/36; 25/36; 13/18; 7/9; 77/90	N	N	N	N	N
16APSK-L (note 7)	5/9; 8/15; 1/2; 3/5; 2/3	N	N	N	N	N
32APSK	3/4, 4/5, 5/6, 8/9, 9/10 (S2-MODCODs)	N	N	N	N	N
	32/45; 11/15; 7/9	N	N	N	N	N
32APSK-L (note 7)	2/3	N	N	N	N	N
64APSK	11/15; 7/9; 4/5; 5/6	O	N	N	N	O
64APSK-L (note 7)	32/45; 25/36; 13/18; 7/9	O	N	N	N	O
128APSK	3/4; 7/9	NA	O	O	N	NA
256APSK	32/45; 3/4	NA	O	O	N	NA
256APSK-L (note 7)	29/45; 2/3; 31/45; 11/15	NA	O	O	N	NA
FECFRAME (short) (see MODCODs below)	16 200 (bits)					

System configurations		Broadcast services	Interactive services	DSNG	Professional services	VL-SNR
QPSK	1/4, 1/3, 2/5 (S2-MODCODs)	NA	N	O	N	N
	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9 (S2-MODCODs)	NA	N	O	N	N
	11/45; 4/15; 14/45; 7/15 8/15; 32/45	NA	N	O	N	N
8PSK	3/5, 2/3, 3/4, 5/6, 8/9 (S2-MODCODs)	NA	N	O	N	N
	7/15; 8/15; 26/45; 32/45	NA	N	O	N	N
16APSK	2/3, 3/4, 4/5, 5/6, 8/9 (S2-MODCODs)	NA	N	O	N	N
	7/15; 8/15; 26/45; 3/5; 32/45	NA	N	O	N	N
32APSK	3/4, 4/5, 5/6, 8/9 (S2-MODCODs)	NA	N	O	N	N
	2/3; 32/45	NA	N	O	N	N
VL-SNR Header (see MODCODs below) (note 1)		O	O	O	NA	N
QPSK	2/9 (normal)	NA	O	O	NA	N
BPSK	1/5; 4/15; 1/3 (short)	NA	O	O	NA	N
	1/5; 11/45; 1/3 (medium)	NA	O	O	NA	N
BPSK-S Spreading Factor 2	1/5; 11/45 (short)	NA	O	O	NA	N
Super-frame		NA	O	O	O	O
Part 2 PLHEADER (note 5)	8-bits	N	N	N	N	N
Extended PLHEADER For Wide-band mode (note 5)	8+8 bits (time slicing)	O	O	NA	O	O
GSE-High Efficiency Mode	For GSE/GSE-Lite (note 6)	N	N	N	N	N
Roll-off 0,15; 0,10 and 0,05		N	N	N	N	N
Channel bonding (note 2)		N (note 3)	NA	NA	O	NA

System configurations		Broadcast services	Interactive services	DSNG	Professional services	VL-SNR
VCM (note 4)		N	N	N	N	N
ACM		NA	N	O	O	N
N = normative, O = optional, NA = not applicable.						
NOTE 1: Ability to skip VL-SNR frames: Normative.						
NOTE 2: Requires Input Stream Synchronizer, Null-Packet Deletion and Dummy Frame insertion.						
NOTE 3: Normative for broadcast services in case of optional multiple tuner receivers.						
NOTE 4: Any S2X receiver shall be able to recognize the whole set of MODCODS within the PLHeader and skip the XFECFrame if the MODCOD is not supported.						
NOTE 5: Part 2 PLHEADER and Extended PLHEADER for wideband transponders (Part 1 [3] or Part 2, annex M) cannot coexist in the same carrier but either can coexist with the VL-SNR header.						
NOTE 6: GSE is optional while support for GSE-Lite in GSE-HEM is normative across all the services.						
NOTE 7: xxx-L= MODCODs optimized for quasi-linear channels.						

iTeh STANDARD PREVIEW
(standards.itih.ai)

SIST EN 302 307-2 V1.1.1 2015

<https://standards.itih.ai/catalog/standards/sist/a68dcff7-ee6e-4ffe-b4c6-3f5c71a8225f/sist-en-302-307-2-v1-1-1-2015>