

SLOVENSKI STANDARD oSIST ISO 11476:2011

01-marec-2011

Papir, karton in lepenka - Določanje beline po CIE, C/2° (pogoji osvetlitve v prostoru)

Paper and board -- Determination of CIE whiteness, C/2 degrees (indoor illumination conditions)

Papier et carton -- Détermination du degré de blanc CIE C/2 degrés (éclairage intérieur)

Ta slovenski standard je istoveten z: ISO 11476:2010

<u>ICS:</u>

85.060 Papir, karton in lepenka Paper and board

oSIST ISO 11476:2011

en

oSIST ISO 11476:2011



INTERNATIONAL STANDARD

ISO 11476

Second edition 2010-08-01

Paper and board — Determination of CIE whiteness, C/2° (indoor illumination conditions)

Papier et carton — Détermination du degré de blanc CIE C/2° (éclairage intérieur)



Reference number ISO 11476:2010(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Page

Forew	ord	iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Principle	3
5	Apparatus and equipment	3
6	Calibration	4
7	Sampling and conditioning	5
8	Preparation of test pieces	5
9	Procedure	5
10	Calculation and expression of results	5
11	Precision	6
12	Test report	7
Annex	A (normative) Spectral characteristics of reflectometers for determining tristimulus values	8
Annex	B (normative) UV calibration service	11
Biblio	graphy	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 11476 was prepared by Technical Committee ISO/TC 6, *Paper, board and pulps*. It is based on the CIE whiteness formula, published in CIE 15:2004, *Colorimetry*.

This second edition cancels and replaces the first edition (ISO 11476:2000), which has been technically revised to include the option to condition samples before measurements.

Paper and board — Determination of CIE whiteness, C/2° (indoor illumination conditions)

1 Scope

This International Standard specifies the procedure to be used for determining the CIE whiteness of papers and boards, in order to obtain values which correspond to the visual appearance of white papers and boards, with or without fluorescent whitening agents, when they are viewed indoors. It is based on radiance factor data obtained over the full visible spectral range (VIS) in contrast to the measurement of ISO brightness, which is limited to the blue region of VIS. This International Standard also specifies the procedures for the determination of CIE tint values and the fluorescent component of CIE whiteness.

In addition, it specifies a method for adjustment of the UV content to correspond to that of CIE illuminant C ^{[10][11]}, since the results obtained when fluorescent whitening agents are present are dependent upon the UV content of the radiation falling upon the sample. The CIE illuminant C is taken to be representative of indoor illumination conditions because it contains a suitable proportion of UV radiation ^{[12][13]}. This method is not applicable to coloured papers containing fluorescent dyes. It is specific to the situation where the fluorescence occurs in the blue region of the visible spectral range.

This International Standard is read in conjunction with ISO 2469.

NOTE 1 It is recognized that the CIE whiteness equation was developed in the context of the CIE standard illuminant D65 ^[6], but the similarity between the relative spectral power curves for the C and D65 illuminants within the visible region and the closeness of their correlated colour temperatures (6 770 K and 6 500 K respectively) are taken as a justification for the use of the analogous whiteness equation with the CIE illuminant C.

NOTE 2 A related International Standard, ISO 11475^[4] specifies the procedure for obtaining values corresponding to the appearance of papers viewed under the CIE standard illuminant D65.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 186, Paper and board — Sampling to determine average quality

ISO 2469, Paper, board and pulps — Measurement of diffuse radiance factor

ISO 2470-1, Paper, board and pulps — Measurement of diffuse blue reflectance factor — Part 1: Indoor daylight conditions (ISO brightness)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

reflectance factor

R

ratio of the radiation reflected by a body to that reflected by the perfect reflecting diffuser under the same conditions

NOTE The reflectance factor is usually expressed as a percentage.

3.2

intrinsic reflectance factor

reflectivity R_{∞}

reflectance factor of a layer or pad of the material thick enough to be opaque, i.e. such that increasing the thickness of the pad by doubling the number of sheets results in no change in the measured reflectance factor

3.3

radiance factor

β

ratio of the radiance of a body to that of the perfect reflecting diffuser under the same conditions of illumination and viewing

NOTE For fluorescent (luminescent) materials, the total radiance factor, β , is the sum of two portions, the reflected radiance factor, β_s , and the luminescent radiance factor, β_L , so that

$\beta = \beta_{\rm S} + \beta_{\rm L}$

For non-fluorescent materials, the reflected radiance factor, β_{s} , is simply the reflectance factor, *R*.

3.4

intrinsic radiance factor

 β_{∞}

radiance factor of a layer or pad of the material thick enough to be opaque, i.e. such that increasing the thickness of the pad by doubling the number of sheets results in no change in the measured radiance factor

NOTE For fluorescent (luminescent) materials, the intrinsic total radiance factor, β_{∞} , is the sum of two portions, the intrinsic reflected radiance factor, $\beta_{\infty,S}$, and the intrinsic luminescent radiance factor, $\beta_{\infty,L}$, so that

 $\beta_{\infty} = \beta_{\infty,\mathsf{S}} + \beta_{\infty,\mathsf{L}}$

For non-fluorescent materials, the intrinsic reflected radiance factor, $\beta_{\infty,S}$, is simply the intrinsic reflectance factor, R_{∞} .

3.5

CIE whiteness

measure of CIE whiteness derived from the CIE tristimulus values determined under the conditions specified in this International Standard

NOTE The CIE whiteness is expressed in CIE whiteness units.

3.6

green/red tint

 T_{W}

measure of the deviation from CIE whiteness of the test material towards the green or red region

NOTE 1 The deviation is expressed as CIE tint units.

NOTE 2 A positive value of T_w indicates a greenish tint and a negative value indicates a reddish tint.