
**Natural gas — Natural gas for use
as a compressed fuel for vehicles —**

**Part 2:
Specification of the quality**

*Gaz naturel — Gaz naturel pour usage comme carburant comprimé
pour véhicules —*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Partie 2: Spécification de la qualité

ISO/TR 15403-2:2006

<https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/TR 15403-2:2006](https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006)

<https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006>

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Water content	2
4 Sulfur compounds	2
5 Particulate matter.....	3
6 Higher hydrocarbons.....	3
7 CO ₂	3
8 Free oxygen.....	3
9 Glycol/Methanol	4
10 Oil content	4
Annex A (informative) Corrosive components.....	6

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[ISO/TR 15403-2:2006](https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006)

<https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In exceptional circumstances, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example), it may decide by a simple majority vote of its participating members to publish a Technical Report. A Technical Report is entirely informative in nature and does not have to be reviewed until the data it provides are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TR 15403-2 was prepared by Technical Committee ISO/TC 193, *Natural gas*.

ISO/TR 15403 consists of the following parts, under the general title *Natural gas* — *Natural gas for use as a compressed fuel for vehicles*:

- *Part 1: Designation of the quality*
- *Part 2: Specification of the quality* (Technical Report)

Introduction

In 2000, ISO 15403, *Natural gas — Designation of the quality of natural gas for use as a compressed fuel for vehicles*, was published.

The word “designation” was used in the title of this International Standard as no range of values, or limits could be stated as specifications or requirements for natural gas components in quality standards. This question was resolved during development of ISO 13686, *Natural gas — Quality designation*, which pertains to natural gas as supplied through transmission and distribution piping systems. The rationale for this stance is that, since natural gas is a natural product and does not need the sophisticated processing such as applied to crude oil, it is not possible to specify an exact gas quality. This is especially applicable to natural gas engines as enabled by precise fractionating in crude oil distillation (petrol/diesel).

During the review of ISO/CD 15403-1, comments regarding the need for “specifications” instead of “designation” were received from several countries including the Netherlands, Sweden and the United States. In addition, the text was circulated to CEN/TC 326, *Gas Supply for Natural Gas Vehicles*, which concluded that “the actual version is too general and does not help in the matter”.

Therefore, ISO/TC 193 decided to prepare a Technical Report as ISO/TR 15403-2 to give the existing information on specifications of compressed natural gas.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/TR 15403-2:2006](https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006)

<https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/TR 15403-2:2006](#)

<https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006>

Natural gas — Natural gas for use as a compressed fuel for vehicles —

Part 2: Specification of the quality

1 Scope

This Technical Report addresses the specifications of natural gas as a compressed fuel for vehicles as an addendum to ISO 15403-1. Specifically, it is intended to satisfy requests for quantitative data.

The following are critical items regarding gas composition:

- water content;
- sulfur compounds;
- particulate matter;
- higher hydrocarbons;
- CO₂;
- free oxygen;
- glycol/methanol;
- oil content
- corrosive components;

iTeh STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006>
[ISO/TR 15403-2:2006](#)

This Technical Report pertains only to compressed natural gas as it enters the fuel containers on the vehicle. It does not apply to the natural gas delivered to a refuelling station. Any alteration of the natural gas supply composition to meet these specifications is clearly the responsibility of the refuelling station operator.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15403-1:2006, *Natural gas — Natural gas for use as a compressed fuel for vehicles — Part 1: Designation of the quality*

ISO 18453:2004, *Natural gas — Correlation between water content and water dew point*

SAE J1616, *Recommended Practice for Compressed Natural Gas Vehicles*

3 Water content

ISO 15403-1 clearly requires that the dew point of the compressed natural gas in the containers shall be low enough to preclude the formation of liquid under any circumstances of pressure and temperature. It gives refuelling station operators the opportunity to meet this condition in accordance with local geographic conditions. A graph of water content of natural gases as a function of absolute pressure and temperature is provided in ISO 15403-1:2006, Figure E.1. From this graph, the dew point and water content, expressed in grams per cubic metre, can be determined for any pressure up to 25 000 kPa and ambient temperature from – 30 °C to + 40 °C.

Reference is made to ISO 18453.

A refuelling station operator can determine the lowest ambient temperature recorded for his area and set a water content accordingly. The formation of hydrates in the container or piping should be prevented.

In a Note to Figure E.1 in ISO 15403-1:2006, a water content of less than 30 mg/m³ is stated as a satisfactory level for expected pressure and temperature. This can be considered a specification and the system shall be fitted and maintained with dryers to achieve such a condition.

In the presence of free water, the following metal components, unless they are manufactured from corrosion-resistant materials, are prone to corrosion:

- a) storage cylinder in the vehicle;
- b) stationary storage cylinder in the refuelling station;
- c) piping;
- d) refuelling coupling;
- e) valves in general;
- f) regulator;
- g) injection system.

iteh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/TR 15403-2:2006](https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006)

<https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006>

Another safety feature is the fact that a refuelling compressor breaks down if liquid water is present.

See Table 1 for general specifications.

4 Sulfur compounds

In the presence of sulfur, the following metal components, unless they are manufactured from corrosion-resistant materials, are prone to corrosion:

- a) storage cylinder in the vehicle;
- b) stationary storage cylinders of the refuelling station;
- c) piping;
- d) refuelling coupling;
- e) valves in general;
- f) regulator;
- g) injection systems.

If there is water present, any amount of sulfur can increase corrosion. The limit value for mass concentration of total sulfur is 120 mg/m³. This amount of total sulfur avoids excessive exhaust-catalyst poisoning. The limits for the sulfur in specific sulfur components should be sulfur in the form of H₂S ≤ 5 mg/m³ and sulfur in the form of mercaptans ≤ 15 mg/m³.

See Table 1 for general specifications.

5 Particulate matter

Pipeline gas is technically free of dust and dirt, but it is a long-standing practice to incorporate filters into gas appliances. Many utilities use filters or screens upstream of meters for debris protection. Good practice dictates the installation of filters or screens in advance of compressors at refuelling stations.

It is essential to keep debris out of the vehicle containers. To this purpose, SAE J1616 recommends at least a 5 µm filter on the fuel line feeding the vehicle container. This usage constitutes a specification for debris control. Of course, such filters shall be maintained and changed as necessary.

Recommended filters include the following:

- refuelling connector 40 µm;
- injection system/regulator 5 µm;
- injectors 1 µm.

See Table 1 for general specifications.

6 Higher hydrocarbons

[ISO/TR 15403-2:2006](https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006)

[https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-](https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006)

[5c38063de9e6/iso-tr-15403-2-2006](https://standards.iteh.ai/catalog/standards/sist/6222fcac-12b1-4bab-ba6e-5c38063de9e6/iso-tr-15403-2-2006)

A safety feature is the fact that a compressor can break down if hydrocarbon liquid is present. All rubber components can be affected.

The maximum allowable mole fraction of propane and butane that corresponds to 1 % of the original gaseous volume gives an indication for the liquid condensation volume for various low ambient temperatures and worst-gas-storage pressure conditions. This is given in ISO 15403-1:2006, Annex A.

See Table 1 for general specifications.

7 CO₂

In the presence of liquid water, any CO₂ can be converted to an acid compound that can cause corrosion. All metal components can be affected, especially the storage cylinder. A volume-fraction limit of 0,03 is recommended.

See Table 1 for general specifications.

8 Free oxygen

The volume-fraction limit of free oxygen is put at 0,03.

See Table 1 for general specifications.