



DRAFT INTERNATIONAL STANDARD ISO/DIS 15869.3

ISO/TC 197

Secretariat: SCC

Voting begins on:
2008-03-26

Voting terminates on:
2008-05-26

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Gaseous hydrogen and hydrogen blends — Land vehicle fuel tanks

Hydrogène gazeux et mélanges d'hydrogène gazeux — Réservoirs de carburant pour véhicules terrestres

ICS 43.060.40

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/DIS 15869.3](https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918ec38b/iso-dis-15869.3)

[https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-](https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918ec38b/iso-dis-15869.3)

In accordance with the provisions of Council Resolution 15/1993 this document is circulated in the English language only.

Conformément aux dispositions de la Résolution du Conseil 15/1993, ce document est distribué en version anglaise seulement.

Member bodies are reminded to consult relevant national interests in each of the technical fields concerned [*Hydrogen technologies (ISO/TC 197)*, *Road vehicles (ISO/TC 22)* and *Gas cylinder design (ISO/TC 58/SC 3)*] before returning their ballot to the Central Secretariat.

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 15869.3](https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918cc38b/iso-dis-15869-3)

<https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918cc38b/iso-dis-15869-3>

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	3
4 Service conditions.....	5
4.1 General.....	5
4.2 Expected service	6
4.3 Working pressure	6
4.4 Maximum filling pressure.....	6
4.5 Filling cycles.....	6
4.5.1 General.....	6
4.5.2 Reduced number of filling cycles	6
4.6 Design temperature.....	6
4.7 Gas composition	6
4.8 External surfaces.....	6
4.9 Fire effects	7
5 Information to be recorded	7
5.1 General.....	7
5.2 Statement of service.....	7
5.3 Design drawings and information.....	7
5.4 Stress analysis report	8
5.5 Material property data	8
5.6 Fire protection	8
5.7 Manufacturing data	8
6 Materials	8
6.1 Compatibility.....	8
6.2 Steel	9
6.3 Stainless steels	9
6.4 Aluminium alloys.....	9
6.5 Resins	9
6.6 Fibres	9
6.7 Plastic liners	9
6.8 Metal end bosses.....	9
7 Design requirements	10
7.1 General.....	10
7.2 Test pressure.....	10
7.3 Burst pressure and fibre stress ratio.....	10
7.3.1 Fuel tank	10
7.3.2 Liner	11
7.4 Stress analysis	11
7.5 Maximum defect size.....	11
7.6 Fire protection	12
8 Construction and workmanship	12

8.1	Materials	12
8.2	Type 3 metal liner	12
8.3	Neck threads, neck ring, foot ring, attachment for support	13
8.4	Forming	13
8.5	Fibre winding.....	13
8.6	Curing of thermosetting resins.....	13
8.7	Auto-frettage	14
8.8	Exterior environmental protection.....	14
9	Type (qualification) tests	14
9.1	Qualification of new designs	14
9.2	Generic type tests	15
9.2.1	General	15
9.2.2	Material tests for steel fuel tanks and liners	15
9.2.3	Material tests for aluminium alloy fuel tanks and liners.....	15
9.2.4	Material tests for stainless steel liners.....	16
9.2.5	Material tests for plastic liners	16
9.2.6	Resin properties tests.....	16
9.2.7	Hydrostatic burst pressure test.....	16
9.2.8	Ambient temperature pressure cycling test.....	16
9.2.9	Leak-before-break (LBB) test.....	16
9.2.10	Bonfire test.....	17
9.2.11	Penetration test	17
9.2.12	Chemical exposure test	17
9.2.13	Composite flaw tolerance test	17
9.2.14	Accelerated stress rupture test	17
9.2.15	Extreme temperature pressure cycling test.....	17
9.2.16	Impact damage test.....	17
9.2.17	Permeation test	17
9.2.18	Boss torque test.....	17
9.2.19	Hydrogen gas cycling test	17
9.3	Exemptions to generic type tests	18
9.4	Qualification of design changes.....	18
9.5	Alternative type tests	20
10	Production and batch tests.....	20
10.1	Production tests	20
10.2	Batch tests.....	21
10.2.1	General requirements	21
10.2.2	Required tests	21
10.2.3	Periodic ambient temperature pressure cycling test.....	22
10.3	Failure to meet batch and production test requirements	23
11	Markings	24
12	Preparation for dispatch	25
Annex A (informative)	Rationale for number of filling cycles.....	26
Annex B (normative)	Test methods and acceptance criteria.....	29
Annex C (informative)	Verification of stress ratios using strain gauges	38
Annex D (informative)	NDE defect size by flawed fuel tank cycling.....	39
Annex E (normative)	Alternative type tests	40
Bibliography.....		43

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15869 was prepared by Technical Committee ISO/TC 197, *Hydrogen technologies*, ISO/TC 22 *Road vehicles* and ISO/TC 58/SC 3 *Gas cylinder design*.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 15869.3](https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918cc38b/iso-dis-15869-3)

<https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918cc38b/iso-dis-15869-3>

Introduction

Fuel tanks for on-board storage of compressed gaseous hydrogen and hydrogen blends as fuels for land vehicle service are required to maintain or improve on the level of safety currently existing for land vehicle applications. These requirements are achieved by:

- a) specifying service conditions precisely and comprehensively as a firm basis for both fuel tank design and use;
- b) using an appropriate method to assess cyclic pressure fatigue life and to establish allowable defect sizes in metal tanks or liners;
- c) requiring design qualification tests;
- d) requiring non-destructive testing and inspection of all production fuel tanks;
- e) requiring destructive tests on fuel tanks and tank material taken from each batch of fuel tanks produced;
- f) requiring manufacturers to specify the acceptable in-service damage levels for their design; and
- g) requiring manufacturers to specify as part of their design, the safe service conditions for their fuel tanks.

Designs meeting the requirements of this International Standard:

- a) will have a fatigue life that exceeds the expected service, and
- b) will demonstrate appropriate strength and durability for expected service conditions.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 15869.3

[https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-](https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918cc38b/iso-dis-15869-3)

[31a0918cc38b/iso-dis-15869-3](https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918cc38b/iso-dis-15869-3)

Gaseous hydrogen and hydrogen blends — Land vehicle fuel tanks

1 Scope

This International Standard specifies the requirements for lightweight refillable fuel tanks intended for the on-board storage of high-pressure compressed gaseous hydrogen or hydrogen blends on land vehicles.

This International Standard is not intended as a specification for fuel tanks used for solid, liquid hydrogen or hybrid cryogenic-high pressure hydrogen storage applications.

This International Standard is applicable for fuel tanks of steel, stainless steel, aluminium or non-metallic construction material, using any design or method of manufacture suitable for its specified service conditions.

This Standard applies to the following types of fuel tank designs:

- Type 1 – Metal fuel tanks;
- Type 2 – Hoop wrapped composite fuel tanks with a metal liner;
- Type 3 – Fully wrapped composite fuel tanks with a metal liner;
- Type 4 – Fully wrapped composite fuel tanks with no metal liner.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 306, *Plastics — Thermoplastic materials — Determination of Vicat softening temperature (VST)*

ISO 527-2, *Plastics — Determination of tensile properties — Part 2: Test conditions for moulding and extrusion plastics*

ISO 2808, *Paints and varnishes — Determination of film thickness*

ISO 4624, *Paints and varnishes — Pull-off test for adhesion*

ISO 6506-1, *Metallic materials — Brinell hardness test — Part 1: Test method*

ISO 7225, *Gas cylinders — Precautionary labels*

ISO 7866:1999, *Gas cylinders — Refillable seamless aluminium alloy gas cylinders — Design, construction and testing*

ISO/DIS 15869.3

ISO 9809-1:1999, *Gas cylinders — Refillable seamless steel gas cylinders — Design, construction and testing — Part 1: Quenched and tempered steel cylinders with tensile strength less than 1 100 MPa*

ISO 9809-2:2000, *Gas cylinders — Refillable seamless steel gas cylinders — Design, construction and testing — Part 2: Quenched and tempered steel cylinders with tensile strength greater than or equal to 1 100 MPa*

ISO 11114-4, *Transportable gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 4: Test methods for selecting metallic materials resistant to hydrogen embrittlement*

ISO 11439, *Gas cylinders — High pressure cylinders for the on-board storage of natural gas as a fuel for automotive vehicles*

ISO/TS 14687-2, *Hydrogen fuel — Product specification — Part 2: Proton exchange membrane (PEM) fuel cell applications for road vehicles*

EN 1964-3:2000, *Transportable gas cylinders — Specification for the design and construction of refillable transportable seamless steel gas cylinders of water capacities from 0,5 litre up to and including 150 litres — Part 3: Cylinders made of seamless stainless steel with an Rm value of less than 1100 MPa*

EN 12862:2000, *Transportable gas cylinders — Specification for the design and construction of refillable transportable welded aluminium alloy gas cylinders*

EN 13322-2:2003/ A1:2006, *Transportable gas cylinders — Refillable welded steel gas cylinders — Design and construction — Part 2: Stainless steel*

ASTM B 117, *Standard Practice for Operating Salt Spray (Fog) Apparatus*

ASTM D 522, *Standard Test Methods for Mandrel Bend Test of Attached Organic Coatings*

ASTM D 1308, *Standard Test Method for Effect of Household Chemicals on Clear and Pigmented Organic Finishes*

ASTM D 2344, *Standard Test Method for Short-Beam Strength of Polymer Matrix Composite Materials and Their Laminates*

ASTM D 2794, *Standard Test Method for Resistance of Organic Coatings to the Effects of Rapid Deformation (Impact)*

ASTM D 3170, *Standard Test Method for Chipping Resistance of Coatings*

ASTM D 3418, *Standard Test Method for Transition Temperatures and Enthalpies of Fusion and Crystallization of Polymers by Differential Scanning Calorimetry*

ASTM G 154, *Standard Practice for Operating Fluorescent Light Apparatus for UV Exposure of Nonmetallic Materials*

3 Terms and definitions

3.1

auto-frettage

pressure application procedure used in manufacturing composite fuel tanks with metal liners, which strains the liner past its yield point

NOTE Auto-frettage results in the liner having compressive stresses and the fibres having tensile stresses at zero internal pressure.

3.2

auto-frettage pressure

pressure within the over-wrapped composite fuel tank at which the required distribution of stresses between the liner and the over-wrap is established

3.3

batch of composite fuel tanks

group of not more than 200 fuel tanks plus fuel tanks for destructive testing, or if greater, one shift of successive production of fuel tanks, successively produced from qualified liners having the same size, design, specified materials of construction and manufacturing process

3.4

batch of metal fuel tanks/liners

group of not more than 200 fuel tanks/liners plus fuel tanks/liners for destructive testing, or if greater, one shift of successive production of metal fuel tanks/liners, successively produced having the same nominal diameter, wall thickness, design, specified material of construction, manufacturing process, equipment for manufacturing and heat treatment, and conditions of time, temperature and atmosphere during heat treatment

<https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918cc38b/iso-dis-15869-3>

3.5

batch of non-metallic liners

group of not more than 200 liners plus liners for destructive testing, or if greater, one shift of successive production of non-metallic liners, successively produced having the same nominal diameter, wall thickness, design, specified material of construction and manufacturing process

3.6

burst pressure

pressure that causes the bursting of a pressure vessel subjected to a constant increase of pressure during a destructive test

3.7

controlled tension winding

process used in manufacturing hoop-wrapped composite fuel tanks with metal liners by which compressive stresses in the liner and tensile stresses in the over-wrap at zero internal pressure are obtained by winding the reinforcing filaments under high tension

3.8

design change

change in the selection of structural materials or dimensional changes exceeding the tolerances as on the design drawings

3.9

finished fuel tanks

fuel tanks, which are ready for use, typical of normal production, complete with identification marks and external coating including integral insulation specified by the manufacturer, but free from non-integral insulation or protection

3.10

fully wrapped composite fuel tank

fuel tank with an over-wrap having a filament wound reinforcement both in the circumferential and axial direction of the fuel tank

3.11

hoop-wrapped composite fuel tank

fuel tank with an over-wrap having a filament wound reinforcement in a substantially circumferential pattern over the cylindrical portion of the liner so that the filament does not carry any significant load in a direction parallel to the longitudinal axis of the fuel tank

3.12

hydrogen blend

mixture of natural gas and hydrogen

3.13

hydrogen storage system

system on a land vehicle comprised of the fuel tank and all closure devices (e.g. shut-off valves, check valves and thermally activated pressure relief devices) and piping that contains hydrogen at the working pressure

3.14

leakage

release of gas through a crack, pore, unbonded or similar defect

NOTE Permeation through the wall of a Type 4 fuel tank that is less than the rates described in B.16 is not considered leakage.

3.15

liner

container that is used as an inner shell, on which reinforcing fibres are filament wound to reach the necessary strength

3.16

manufacturer

organization responsible for the design, manufacturing and testing of fuel tanks

3.17

over-wrap

reinforcement system of filament and resin applied over the liner

3.18

thermally activated pressure relief device

device that activates by temperature to release pressure and prevent a fuel tank from bursting due to fire effects and which will activate regardless of fuel tank pressure

3.18

passenger vehicles

vehicles designed and constructed primarily for the carriage of persons (e.g. cars and buses)

STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 15869.3
<https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdb-31a0918cc38b/iso-dis-15869-3>

3.19**pre-stress**

process of applying auto-fretage or controlled tension winding

3.20**service conditions**

conditions that the fuel tank will experience in service and which includes on-road exposure to environmental factors (road salt, acids, bases, temperature extremes) and expected usage (pressure cycles associated with filling and defilling during service and driving, static pressure associated with vehicle parking, etc.)

3.21**settled pressure**

gas pressure when a given settled temperature is reached

3.22**settled temperature**

uniform gas temperature after any change in temperature, caused by filling, has dissipated

3.23**stress ratio**

stress in fibre at specified minimum burst pressure divided by stress in fibre at working pressure

3.24**test pressure**

required pressure applied during a pressure test

3.25**working pressure**

nominal working pressure

settled pressure of compressed gas at a uniform temperature of 15 °C in a full fuel tank

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 15869.3

<https://standards.iteh.ai/catalog/standards/sist/9aeb5ee0-ca75-4190-8cdh-31a0918cc38b/iso-dis-15869-3>

4 Service conditions**4.1 General**

The specified service conditions provide the basis for the design, manufacturing, inspection, and testing of fuel tanks that are to be mounted on land vehicles and used to store compressed gaseous hydrogen or hydrogen blends at ambient temperatures for use as a fuel on these vehicles.

The specified service conditions are also intended to provide information on how fuel tanks made in accordance with this International Standard may safely be used, for:

- a) manufacturers of fuel tanks;
- b) owners of fuel tanks;
- c) designers or contractors responsible for the installation of fuel tanks;
- d) designers or owners of equipment used to refuel land vehicle fuel tanks;
- e) suppliers of gaseous hydrogen and hydrogen blends; and
- f) regulatory authorities that have jurisdiction over fuel tank use.

ISO/DIS 15869.3

The service conditions do not cover external loading that may arise from vehicle collisions, etc.

4.2 Expected service

The expected service for which fuel tanks are safe shall be specified by the fuel tank manufacturer.

4.3 Working pressure

The working pressure shall be specified by the fuel tank manufacturer for gaseous hydrogen and hydrogen blends settled at a temperature of 15 °C.

4.4 Maximum filling pressure

Fuel tanks shall be designed to be filled up to a maximum pressure, which does not exceed 1,25 times the working pressure, regardless of filling conditions or temperature, and which settle to a pressure of not greater than the working pressure at the settled temperature of 15 °C.

4.5 Filling cycles

4.5.1 General

Except as permitted in 4.5.2, fuel tanks shall be designed for 11 250 fill cycles, representing a 15-year life of use in commercial heavy-duty vehicles (see Annex A).

4.5.2 Reduced number of filling cycles

A reduced number of 5 500 filling cycles may be specified for the lifetime of the vehicle. Fuel tanks with the reduced number of filling cycles may be qualified per 9.2 or 9.5. In the case of fuel tanks with a reduced number of filling cycles and qualified per 9.2, these fuel tanks shall only be used in conjunction with a tamper-proof counter system that records the number of fill cycles and terminates usage of the fuel tank before the reduced number of fill cycles is exceeded.

4.6 Design temperature

Fuel tanks shall be designed to be suitable for use in the following material temperature range: – 40 °C to 85 °C. Transient gas temperatures during filling and discharge may vary locally beyond these limits.

4.7 Gas composition

Fuel tanks shall be designed to be filled with compressed gaseous hydrogen and/or hydrogen blends containing more than 2 % hydrogen by volume, combined with dry natural gas. The gas composition shall comply with the following:

- a) compressed hydrogen gas shall comply with the composition specified in ISO/TS 14687-2;
- b) compressed natural gas used in hydrogen blends may vary as stated in the dry gas composition limits specified in ISO 11439.

4.8 External surfaces

Fuel tank external surfaces shall be designed to withstand mechanical and chemical exposure conditions as reflected in the type tests specified in Clause 9.

4.9 Fire effects

Fuel tanks shall be protected from fire effects using non-reclosing thermally activated pressure relief devices. Non-reclosing pressure-activated pressure relief devices can only be used in parallel with thermally activated pressure relief devices. Under no circumstances shall a thermally activated pressure relief device require the operation of the pressure-activated pressure relief device in order to function.

NOTE In the selection of thermally activated pressure relief devices, the requirements of the ANSI/IAS PRD 1-1998/Addenda PRD 1a-1999 may be used as guidance until a standard on pressure relief devices for hydrogen service is available.

The fire protection of fuel tanks may also be supplemented by the use of thermal insulation.

5 Information to be recorded

5.1 General

The fuel tank manufacturer shall keep on file the information specified herein. This information shall be retained for the intended life of the fuel tank.

5.2 Statement of service

A statement of service shall be provided to the user. This statement of service shall include the following:

- a) the name and address of the fuel tank manufacturer;
- b) a description of the fuel tank design, including fuel tank identification, working pressure (MPa), fuel tank type, diameter (mm), length (mm), internal volume (l), empty weight (kg), and valve thread type;
- c) a statement that the fuel tank design is suitable for use in the service conditions provided in Clause 4;
- d) a statement of the maximum service conditions for which the fuel tank was designed;
- e) a statement of the maximum number of filling cycles for which the fuel tank was designed;
- f) a statement of the working pressure for which the fuel tank was designed;
- g) a specification for the fire protection system approved by the fuel tank manufacturer using non-reclosing thermally activated pressure relief devices and, if used, thermal insulation;
- h) a specification for the support methods, protective coatings and any other items required, but not provided with the fuel tank;
- i) any other information and instructions necessary to ensure the safe use and inspection of the fuel tank.

5.3 Design drawings and information

All fuel tank drawings and related technical data shall be kept on file by the fuel tank manufacturer and shall show the following information:

- a) title, reference number, date of issue, and revision numbers with dates of issue, if applicable;
- b) reference to a Type 1, Type 2, Type 3, or Type 4 design;