
**Hygrothermal performance of
buildings — Calculation and presentation
of climatic data —**

**Part 2:
Hourly data for design cooling load**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Performance hygrothermique des bâtiments — Calcul et présentation
des données climatiques —*

*Partie 2: Données horaires pour la charge de refroidissement de
conception*

ISO 15927-2:2009

<https://standards.iteh.ai/catalog/standards/sist/18f2e040-7488-43ac-8a3f-e3f3e1bb5966/iso-15927-2-2009>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15927-2:2009

<https://standards.iteh.ai/catalog/standards/sist/18f2e040-7488-43ac-8a3f-e3f3e1bb5966/iso-15927-2-2009>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and units	2
3.1 Terms and definitions	2
3.2 Symbols and units	3
4 Method of determination	3
4.1 Sources of data	3
4.2 Identification of the design days	3
5 Data for the design of air conditioning systems	5
6 Presentation of the design days	6
7 Presentation of the data for the design of air conditioning systems	6
Annex A (informative) Example of the procedure for identifying a design day	7

ITIH STANDARD PREVIEW

(standards.iteh.ai)

ISO 15927-2:2009

<https://standards.iteh.ai/catalog/standards/sist/18f2e040-7488-43ac-8a3f-e3f3e1bb5966/iso-15927-2-2009>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15927-2 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 89, *Thermal performance of buildings and building components*, in collaboration with Technical Committee ISO/TC 163, *Thermal performance and energy use in the built environment*, Subcommittee SC 2, *Calculation methods*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

ISO 15927 consists of the following parts, under the general title *Hygrothermal performance of buildings — Calculation and presentation of climatic data*: [ISO 15927-2:2009](https://standards.iteh.ai/catalog/standards/sist/18f2e040-7488-43ac-8a3f-e33e1bb5966/iso-15927-2-2009)

- *Part 1: Monthly means of single meteorological elements*
- *Part 2: Hourly data for design cooling load*
- *Part 3: Calculation of a driving rain index for vertical surfaces from hourly wind and rain data*
- *Part 4: Hourly data for assessing the annual energy use for heating and cooling*
- *Part 5: Data for design heat load for space heating*
- *Part 6: Accumulated temperature differences (degree-days)*

Introduction

The choice of design load for space cooling is a matter of balancing user needs against cost. On the one hand, users expect a cooling system to maintain the internal temperatures needed for health and comfort; on the other hand, very high cooling loads can arise from extreme meteorological conditions. It is usually uneconomic to design cooling systems for rare extremes, as this leads to high capital cost and, usually, to lower operational efficiency of the system. The highest cooling loads occur with a combination of high daily mean dry-bulb temperature and dewpoint temperature, high daily total irradiation, low daily swing in temperature and low wind speed. Data are therefore needed on the values of these parameters when they occur in combination at specific return periods.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 15927-2:2009

<https://standards.iteh.ai/catalog/standards/sist/18f2e040-7488-43ac-8a3f-e3f3e1bb5966/iso-15927-2-2009>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15927-2:2009

<https://standards.iteh.ai/catalog/standards/sist/18f2e040-7488-43ac-8a3f-e3f3e1bb5966/iso-15927-2-2009>

Hygrothermal performance of buildings — Calculation and presentation of climatic data —

Part 2: Hourly data for design cooling load

1 Scope

This part of ISO 15927 gives the definition and specifies methods of calculation and presentation of the monthly external design climate to be used in determining the design cooling load of buildings and the design of air conditioning systems.

Depending on the building type, a range of parameters can be used to define the individual days of hourly or three-hourly data in each calendar month that impose a cooling load likely to be exceeded on 5 %, 2 % and 1 % of days.

The parameters that are always used in the selection are dry-bulb temperature and total global solar irradiation (or sunshine hours). The daily swing in dry-bulb temperature, dewpoint temperature and wind speed and any other parameters relevant to particular buildings may also be included.

Hourly peak values of dry-bulb temperature and dewpoint temperature are needed for the design of air conditioning systems.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15927-1, *Hygrothermal performance of buildings — Calculation and presentation of climatic data — Part 1: Monthly means of single meteorological elements*

World Meteorological Organization (WMO), *Guide to Meteorological Instruments and Methods of Observation*, No. 8, 6th Edition, 1996¹⁾

1) World Meteorological Organization: <http://www.wmo.ch/pages/catalogue/New%20HTML/frame/engfil/8.html>.

3 Terms, definitions, symbols and units

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 15927-1 and the following apply.

3.1.1

hourly value

average of instantaneous values of a parameter measured during an hour or value observed at a particular moment (e.g. on the hour)

NOTE Hourly values can be estimated by interpolation from data measured at three-hour intervals.

3.1.2

daily mean value

average of 24 hourly values or eight 3-hourly values of a parameter during a day from 00:00 to 23:00 or 01:00 to 24:00

3.1.3

dry-bulb temperature

air temperature measured in a thermometer screen or with similar shielding from solar radiation

3.1.4

daily swing in dry-bulb temperature

difference between the maximum and minimum dry-bulb temperatures in one day

3.1.5

dewpoint temperature

temperature to which air is cooled to become saturated with the same water vapour content

[ISO 15927-2:2009](#)

3.1.6

global solar irradiation on a horizontal surface

total solar energy falling on a horizontal surface in a given period

<https://standards.iteh.ai/catalog/standards/sist/18f2e040-7488-43ac-8a3f-bb5966/iso-15927-2-2009>

NOTE

Global solar irradiation is the sum of the direct and diffuse solar irradiation received by the surface in the period.

3.1.7

summer external design day

day from any calendar month with a specified return period for extreme values of the significant meteorological parameters, for example: temperature, temperature swing, dewpoint temperature, solar irradiation and wind speed

3.2 Symbols and units

Symbol	Quantity	Unit
\hat{I}_s	daily total global solar irradiation	kWh/(m ² ·d)
\hat{h}_s	daily total sunshine hours	h
v	wind speed	m/s
\bar{v}	daily mean wind speed	m/s
θ	dry-bulb temperature	°C
$\bar{\theta}$	daily mean dry-bulb temperature	°C
θ_d	dewpoint temperature	°C
$\bar{\theta}_d$	daily mean dewpoint temperature	°C
θ_{sw}	daily swing in dry-bulb temperature	K

Subscript $x\%$, as in $p_{x\%}$, represents the value of a parameter that is exceeded on 100 - x % of days.

(standards.iteh.ai)

4 Method of determination

ISO 15927-2:2009

4.1 Sources of data

<https://standards.iteh.ai/catalog/standards/sist/18f2e040-7488-43ac-8a3f-e3f3e1bb5966/iso-15927-2-2009>

Hourly files of meteorological data, containing at least the dry-bulb temperature and global solar irradiation or sunshine hours for at least 10 years, shall be analysed. Other parameters, such as dewpoint temperature or daily swing in temperature and wind speed, may be included if design days are needed for specific purposes. The parameters used shall be fully reported.

NOTE Global solar irradiation is preferred to sunshine hours as it gives a better index of the performance of the building; however, solar radiation data are available from very few stations compared to sunshine hours.

Methods for calculating meteorological parameters are given in ISO 15927-1.

The meteorological data shall have been measured in accordance with WMO Guide No. 8, 1996.

4.2 Identification of the design days

4.2.1 The procedure in 4.2.2 to 4.2.5 describes the use of dry-bulb temperature, global solar irradiation or sunshine hours, dewpoint temperature, daily temperature swing and wind speed to construct design days. The same principles may be applied to the use of any other parameters appropriate to specific buildings.

4.2.2 Identify the parameters that are to be used to construct the design days. Daily mean dry-bulb temperature and daily total global solar radiation or daily total sunshine hours, shall be included in all cases; daily mean dewpoint temperature, daily temperature swing and daily mean wind speed may also be included.