

Designation: B 899 - 05

Standard Terminology Relating to Non-ferrous Metals and Alloys¹

This standard is issued under the fixed designation B 899; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 To promote precise understanding and interpretation of standards, reports, and other technical writings promulgated by Committee B02.

1.2 To standardize the terminology used in these documents.

1.3 To explain the meanings of technical terms used within these documents for those not conversant with them.

2. Referenced Documents

- 2.1 ASTM Standards: ²
- **B** 6 Specification for Zinc
- B 29 Specification for Refined Lead
- B 32 Specification for Solder Metal
- **B** 39 Specification for Nickel
- **B** 69 Specification for Rolled Zinc
- **B** 86 Specification for Zinc and Zinc-Aluminum (ZA) Alloy Foundry and Die Castings
- B 160 Specification for Nickel Rod and Bar
- B 161 Specification for Nickel Seamless Pipe and Tube
- B 163 Specification for Seamless Nickel and Nickel Alloy Condenser and Heat-Exchanger Tubes
- B 164 Specification for Nickel-Copper Alloy Rod, Bar, and Wire
- **B** 165 Specification for Nickel-Copper Alloy (UNS N04400) Seamless Pipe and Tube
- B 166 Specification for Nickel-Chromium-Iron Alloys (UNS N06600, N06601, N06603, N06690, N06693, N06025, and N06045) and Nickel-Chromium-Cobalt-Molybdenum Alloy (UNS N06617) Rod, Bar, and Wire
- B 167 Specification for Nickel-Chromium-Iron Alloys (UNS N06600, N06601, N06603, N06690, N06693, N06025, and N06045) and Nickel-Chromium-Cobalt-Molybdenum Alloy (UNS N06617) Seamless Pipe and Tube
- B 240 Specification for Zinc and Zinc-Aluminum (ZA)

- B 327 Specification for Master Alloys Used in Making Zinc Die Casting Alloys
- **B** 333 Specification for Nickel-Molybdenum Alloy Plate, Sheet, and Strip
- **B** 339 Specification for Pig Tin
- **B 407** Specification for Nickel-Iron-Chromium Alloy Seamless Pipe and Tube
- **B** 408 Specification for Nickel-Iron-Chromium Alloy Rod and Bar
- B 418 Specification for Cast and Wrought Galvanic Zinc Anodes
- B 423 Specification for Nickel-Iron-Chromium-Molybdenum-Copper Alloy (UNS N08825 and N08221) Seamless Pipe and Tube
- B 425 Specification for Ni-Fe-Cr-Mo-Cu Alloy (UNS N08825 and UNS N08221) Rod and Bar
- B 434 Specification for Nickel-Molybdenum-Chromium-Iron Alloys (UNS N10003, UNS N10242) Plate, Sheet, and Strip
- B 435 Specification for UNS N06002, UNS N06230, UNS N12160, and UNS R30556 Plate, Sheet, and Strip
- B 444 Specification for Nickel-Chromium-Molybdenum-
- Columbium Alloys (UNS N06625 and UNS N06852) and Nickel-Chromium-Molybdenum-Silicon Alloy (UNS N06219) Pipe and Tube
- B 445 Specification for Nickel-Chromium-Iron-Columbium-Molybdenum-Tungsten Alloy (UNS N06102) Seamless Pipe and Tube³
- B 446 Specification for Nickel-Chromium-Molybdenum-Columbium Alloy (UNS N06625), Nickel-Chromium-Molybdenum-Silicon Alloy (UNS N06219), and Nickel-Chromium-Molybdenum-Tungsten Alloy (UNS N06650) Rod and Bar
- **B 463** Specification for UNS N08020, UNS N08026, and UNS N08024 Alloy Plate, Sheet, and Strip
- B 471 Specification for UNS N08020, UNS N08026, and UNS N08024 Nickel Alloy Spring Wire³
- B 473 Specification for UNS N08020, UNS N08024, and UNS N08026 Nickel Alloy Bar and Wire
- B 475 Specification for UNS N08020, UNS N08024, and UNS N08026 Nickel Alloy Round Weaving Wire

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

¹ This terminology is under the jurisdiction of ASTM Committee B02 on Nonferrous Metals and Alloys and is the direct responsibility of Subcommittee B02.91 on Terminology.

Current edition approved Nov. 1, 2005. Published December 2005. Originally approved in 1999. Last previous edition approved in 2004 as B 899-04.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

Alloys in Ingot Form for Foundry and Die Castings

³ Withdrawn.

- **B** 511 Specification for Nickel-Iron-Chromium-Silicon Alloy Bars and Shapes
- B 512 Specification for Nickel-Chromium-Silicon Alloy (UNS N08330) Billets and Bars
- B 518 Specification for Nickel-Chromium-Iron-Molybdenum-Tungsten Alloy (UNS N06102) Rod and Bar³
- B 535 Specification for Nickel-Iron-Chromium-Silicon Alloys (UNS N08330 and N08332) Seamless Pipe and Tube
- **B** 536 Specification for Nickel-Iron-Chromium-Silicon Alloys (UNS N08330 and N08332) Plate, Sheet, and Strip
- B 575 Specification for Low-Carbon Nickel-Chromium-Molybdenum, Low-Carbon Nickel-Chromium-Molybdenum-Copper, Low-Carbon Nickel-Chromium-Molybdenum-Tantalum, and Low-Carbon Nickel-Chromium-Molybdenum-Tungsten Alloy Plate, Sheet, and Strip
- B 582 Specification for Nickel-Chromium-Iron-Molybdenum-Copper Alloy Plate, Sheet, and Strip
- B 599 Specification for Nickel-Iron-Chromium-Molybdenum-Columbium Stabilized Alloy (UNS N08700) Plate, Sheet, and Strip
- B 620 Specification for Nickel-Iron-Chromium-Molybdenum Alloy (UNS N08320) Plate, Sheet, and Strip
- **B 622** Specification for Seamless Nickel and Nickel-Cobalt Alloy Pipe and Tube
- B 625 Specification for UNS N08925, UNS N08031, UNS N08932, UNS N08926, UNS N08354, and UNS R20033 Plate, Sheet, and Strip
- B 637 Specification for Precipitation-Hardening Nickel Alloy Bars, Forgings, and Forging Stock for High-Temperature Service
- B 639 Specification for Precipitation Hardening Cobalt-Containing Alloys (UNS R30155 and UNS R30816) Rod, Bar, Forgings, and Forging Stock for High-Temperature Service
- B 649 Specification for Ni-Fe-Cr-Mo-Cu-N Low-Carbon Alloys (UNS N08925, UNS N08031, UNS N08354, and UNS N08926), and Cr-Ni-Fe-N Low-Carbon Alloy (UNS R20033) Bar and Wire
- **B 667** Practice for Construction and Use of a Probe for Measuring Electrical Contact Resistance
- B 672 Specification for Nickel-Iron-Chromium-Molybdenum-Columbium Stabilized Alloy (UNS N08700) Bar and Wire
- B 677 Specification for UNS N08925, UNS N08354, and UNS N08926 Seamless Pipe and Tube
- **B 688** Specification for Chromium-Nickel-Molybdenum-Iron (UNS N08366 and UNS N08367) Plate, Sheet, and Strip
- **B** 690 Specification for Iron-Nickel-Chromium-Molybdenum Alloys (UNS N08366 and UNS N08367) Seamless Pipe and Tube
- B 691 Specification for Iron-Nickel-Chromium-Molybdenum Alloys (UNS N08366 and UNS N08367) Rod, Bar, and Wire
- B 709 Specification for Iron-Nickel-Chromium-Molybdenum Alloy (UNS N08028) Plate, Sheet, and Strip

- B 710 Specification for Nickel-Iron-Chromium-Silicon Alloy Welded Pipe
- B 718 Specification for Nickel-Chromium-Molybdenum-Cobalt-Tungsten-Iron-Silicon Alloy (UNS N06333) Plate, Sheet, and Strip
- B 719 Specification for Nickel-Chromium-Molybdenum-Cobalt-Tungsten-Iron-Silicon Alloy (UNS N06333) Bar
- B 722 Specification for Nickel-Chromium-Molybdenum-Cobalt-Tungsten-Iron-Silicon Alloy (UNS N06333) Seamless Pipe and Tube
- B 723 Specification for Nickel-Chromium-Molybdenum-Cobalt-Tungsten-Iron-Silicon Alloy (UNS N06333) Welded Pipe
- B 726 Specification for Nickel-Chromium-Molybdenum-Cobalt-Tungsten-Iron-Silicon Alloy (UNS NO6333) Welded Tube
- B 729 Specification for Seamless UNS N08020, UNS N08026, and UNS N08024 Nickel-Alloy Pipe and Tube
- B 739 Specification for Nickel-Iron-Chromium-Silicon Alloy Welded Tube
- B 749 Specification for Lead and Lead Alloy Strip, Sheet, and Plate Products
- **B** 750 Specification for GALFAN (Zinc-5 % Aluminum-Mischmetal) Alloy in Ingot Form for Hot-Dip Coatings
- B 751 Specification for General Requirements for Nickel and Nickel Alloy Welded Tube
- B 756 Specification for Nickel-Chromium-Molybdenum-Tungsten Alloy (UNS N06110) Rod and Bar
- B 759 Specification for Nickel-Chromium-Molybdenum-Tungsten Alloys (UNS N06110) Pipe and Tube
- **B** 775 Specification for General Requirements for Nickel and Nickel Alloy Welded Pipe
- **B 791** Specification for Zinc-Aluminum (ZA) Alloy Foundry and Die Castings³
- B 792 Specification for Zinc Alloys in Ingot Form for Slush Casting
- **B 805** Specification for Precipitation Hardening Nickel Alloys UNS N07716, N07725, N07773, N07776, and N09777, Bar and Wire
- B 814 Specification for Nickel-Chromium-Iron-Molybdenum-Tungsten Alloy (UNS N06920) Plate, Sheet, and Strip
- B 818 Specification for Cobalt-Chromium-Nickel-Molybdenum-Tungsten Alloy (UNS R31233) Plate, Sheet and Strip
- B 834 Specification for Pressure Consolidated Powder Metallurgy Iron-Nickel-Chromium-Molybdenum (UNS N08367) and Nickel-Chromium-Molybdenum-Columbium (Nb) (UNS N06625) Alloy Pipe Flanges, Fittings, Valves, and Parts
- **B 892** Specification for ACuZinc5 (Zinc-Copper-Aluminum) Alloy in Ingot Form for Die Castings
- **B 894** Specification for ACuZinc5 (Zinc-Copper-Aluminum) Alloy Die Castings
- B 897 Specification for the Configuration of Zinc and Zinc Alloy Jumbo and Block Ingot

3. Significance and Use

3.1 The terms defined in this document are generic in respect to the standards under the jurisdiction of Committee B02 on Nonferrous Metals and Alloys. The same terms may have different definitions in other ASTM technical committees.

3.2 Some definitions may differ within the committee because of limitations on items such as weights or dimensions. In such cases the terms will be more precisely defined in the *Terminology* section of the standards in which these terms are used.

4. Index of Terms

4.1 Alphabetical Listing of Terms average diameter bar billet can cathodic protection coiled sheet compact contact resistance contact resistance probe die casting fill pin fineness flats flat sheet foundry casting galvanic anode graphite permanent mold casting heat ingot liquidus lot lot number melt nominal wall part permanent mold casting pig pipe plate powder powder blend precious metals pressure die casting producer rod rough part saline electrolyte sand casting seamless pipe semi-permanent mold casting shapes sheet shot solidus sponge

spring wire strip thin-wall tube tube weaving wire welded pipe wire

5. Terminology

5.1 Terms and Their Definitions

average diameter, n—the average of the maximum and minimum outside the diameters, as determined at any one section of the pipe or tube.
B 160, B 161, B 163, B 165, B 167, B 407, B 423, B 444, B 445, B 535, B 622, B 677, B 690, B 710, B 722, B 723, B 726, B 729, B 739, B 751, B 759, B 775

bar, n—an elongated, forged or rolled metal product with uniform strength, length and section (such as rectangular, square, round, oval or hexagonal).B 327, B 518

Note 1—In the following standards the term "bar" has a similar definition, but with greater and more specific detail. **B 160, B 164, B 166, B 408, B 425, B 446, B 473, B 511, B 512, B 637, B 639, B 649, B 672, B 691, B 719, B 756, B 805**

billet, *n*—a formed shape that may be further worked, or a solid, semifinished, round, or rectangular product that has been hot-worked by forging, rolling, or extrusion.

can, *n*—the container used to encapsulate the powder during the pressure consolidation process; it is removed from the final part.
 B 834
 cathodic protection, *n*—protection of a metal from corrosion

by making it a cathode through the galvanic sacrifice of a <u>solution</u> less noble metal or through an impressed electric current.

- sist/B783793-df0d-4f0d-9701-01e7cc9c8cf/astm-b899-05 B 418
 - coiled sheet, n—sheet in coils with slit edges.
 B 69
 compact, n—the consolidated powder from one can; it may be used to make one or more parts.
 B 834
 - **contact resistance**, *n*—the resistance to current flow between two touching bodies, consisting of constriction resistance and film resistance. **B 667**
 - **contact resistance probe,** *n*—an apparatus for determining electrical contact resistance characteristics of a metal surface.

DISCUSSION—Probe, in this instance, should be distinguished from the classical tool whose function it is to touch or move an object.

die casting, n—a casting process in which molten metal is injected under high velocity and pressure into a metal die and solidified; also, a product produced by such a process. Alternately known as pressure die casting.
B 6, B 240, B 892, B 894

fill pin, *n*—the part of the compact in the spout used to fill the can; it is usually integral to the part produced.B 834

fineness, *n*—a measure of the purity of precious metals expressed in parts per thousand.

flat sheet, n—sheet with sheared, silt, or sawed edges that has been flattened or leveled.
B 69