

---

---

**Ships and marine technology — Marine  
evacuation systems — Means of  
communication**

*Navires et technologie maritime — Systèmes d'évacuation en mer —  
Moyens de communication*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 27991:2008

[https://standards.iteh.ai/catalog/standards/sist/a1951cc6-9d68-4552-8547-  
e639f3718de0/iso-27991-2008](https://standards.iteh.ai/catalog/standards/sist/a1951cc6-9d68-4552-8547-e639f3718de0/iso-27991-2008)



Reference number  
ISO 27991:2008(E)

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 27991:2008

<https://standards.iteh.ai/catalog/standards/sist/a1951cc6-9d68-4552-8547-e639f3718de0/iso-27991-2008>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword.....	iv
Introduction .....	v
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions.....	1
4 General.....	2
4.1 General principles.....	2
4.2 Means of communication.....	2
5 Performance requirements .....	3
5.1 General.....	3
5.2 Visual signals .....	3
5.3 Audible communication .....	4
6 Testing .....	4
Bibliography .....	5

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 27991:2008

<https://standards.iteh.ai/catalog/standards/sist/a1951cc6-9d68-4552-8547-e639f3718de0/iso-27991-2008>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 27991 was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 1, *Lifesaving and fire protection*.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 27991:2008

<https://standards.iteh.ai/catalog/standards/sist/a1951cc6-9d68-4552-8547-e639f3718de0/iso-27991-2008>

## Introduction

This International Standard is intended to provide guidelines on how to ensure safe communication and aid the control of an evacuation between the embarkation station and the platform or survival craft on ships fitted with marine evacuation systems (MES) as required by the International Convention for the Safety of Life at Sea (SOLAS). Considering the importance of the availability of uniform and clearly perceptible means of communication, this International Standard is intended to define and specify acceptable means of communication in conjunction with the operation of MES in order to ensure safe and rapid evacuation of ships fitted with MES.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 27991:2008

<https://standards.iteh.ai/catalog/standards/sist/a1951cc6-9d68-4552-8547-e639f3718de0/iso-27991-2008>

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

ISO 27991:2008

<https://standards.iteh.ai/catalog/standards/sist/a1951cc6-9d68-4552-8547-e639f3718de0/iso-27991-2008>

# Ships and marine technology — Marine evacuation systems — Means of communication

## 1 Scope

This International Standard specifies means of communication between an MES embarkation station and the platform or survival craft secured to the end of system passage as required by SOLAS regulation III/6.4.4.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60529, *Degrees of protection provided by enclosures (IP code)*

iTeh STANDARD PREVIEW

## 3 Terms and definitions (standards.iteh.ai)

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### communication

<https://standards.iteh.ai/catalog/standards/sist/a1951cc6-9d68-4552-8547-e639f3718de0/iso-27991-2008>

means of passing essential information between the relevant persons assigned to operate the MES

### 3.2

#### controller

person in charge overall at the embarkation station

### 3.3

#### marine evacuation system

##### MES

appliance for the rapid transfer of persons from the embarkation deck of a ship to a floating survival craft

### 3.4

#### passage

portion of the MES that provides the means of transfer of persons between the embarkation station and the platform or survival craft

### 3.5

#### platform

floating platform which may be fitted at the bottom of the passage to hold evacuees awaiting entry to survival craft

### 3.6

#### receiver

person normally located at the exit of the passage to assist the persons exiting the passage and direct them into survival craft

## 3.7

**survival craft**

craft capable of sustaining the lives of persons in distress from the time of abandoning the ship

## 4 General

### 4.1 General principles

**4.1.1** The means of communication shall facilitate the safe command and control of an MES evacuation. All means of communication shall be simple and clear, easily understood, and unambiguous.

**4.1.2** The communication would normally be between the entrances and exits of the MES passage, where normally there would be positioned a controller and receiver(s), respectively. The messages requiring communication are as shown in Table 1, and are applicable to all MES, no matter what height or configuration (slide/chute/other). These support safe and controlled evacuation, and are the critical points of feedback during an evacuation.

**Table 1 — Messages requiring communication**

CONTROLLER side	RECEIVER side
Starting evacuation <sup>a</sup>	Ready to receive <sup>a</sup>
Stopping evacuation <sup>a</sup>	Stop evacuation <sup>a</sup>
Change pace of evacuation	Change pace of evacuation
Identify an incident has occurred	Identify an incident has occurred
<sup>a</sup> In the event of failure of the communications system, alternative means of communicating the indicated messages shall be clearly defined in the MES operating manual or in the vessel training manual.	

**4.1.3** All messages applicable to each MES shall be clearly defined in the MES operating manual.

**4.1.4** For an MES where the persons descending the system are visible to the controller and receiver along the complete length of the passage, and the controller and receiver are in clear sight of each other, it is sufficient to have only a visual form of communication, as feedback regarding how the evacuation is progressing can be observed by all the relevant personnel.

**4.1.5** For an MES that does not conform with 4.1.4, a communication system shall provide the controller with an audible or visual indication of the status of the person(s) descending the passage.

### 4.2 Means of communication

The means of communication may be visual or audible. Examples of such means of communication are listed below.

a) Visual:

- light signals, typically LED or lamps;
- hand signals.

b) Audible:

- verbal (i.e. unamplified voice);
- radio based;
- klaxon/horn/whistle/bullhorn.



## 5 Performance requirements

### 5.1 General

**5.1.1** The means of communication shall be ergonomically positioned, and shall not interfere with the operation of other life-saving appliances on the ship, particularly those adjacent to the equipment.

**5.1.2** All means of communication shall be capable of functioning correctly for the duration of an evacuation.

**5.1.3** The performance of the means of communication shall take into account

- background noise and vibration,
- lighting – artificial and strong, natural sunlight, as well as nighttime operation and backlighting,
- conditions of restricted or reduced visibility,
- environmental conditions [–30 °C to +65 °C, humidity, visibility (e.g. controller viewing receiver in snow storm), heavy weather (e.g. Beaufort 6)],
- robustness to withstand the conditions and forces generated during a deployment and evacuation, and
- possible confusion between individual MES communication systems as well as shipboard operational, emergency and damage control communications.

**5.1.4** The exact meaning of each signal shall be defined clearly in the MES operating manual and/or be in compliance with the vessel's training manual.

### 5.2 Visual signals

#### 5.2.1 General

The visual signals shall communicate clearly the relevant command and control information to the correct personnel.

#### 5.2.2 Light signals

**5.2.2.1** If red and green light signals are used, they should comply with the following internationally recognised format:

<i>Red</i>	stop/danger
<i>Green</i>	go/safe

**5.2.2.2** All light based means of communication shall be positioned local to the relevant operator, within their line of sight.

**5.2.2.3** Circuitry and other components associated with the operation of light signals shall be positioned so as not to interfere with the evacuation of persons through the MES passage, and should be suitably sealed with respect to its positioning, typically a minimum IP55 for deck positioned equipment, and a minimum of IP66 for equipment used at the waterline, determined in accordance with IEC 60529.

**5.2.2.4** Lights shall be clearly visible under daylight conditions when fitted in their normal operating position.

**5.2.2.5** It shall be demonstrated that the power source for light signals is capable of powering them for a duration as determined in accordance with 5.1.2 with sufficient intensity to comply with 5.2.2.4.