



EUROPEAN STANDARD

**Terrestrial Trunked Radio (TETRA);
Conformance testing specification;
Part 1: Radio**

iTeh STANDARDS PREVIEW
(Standard Preview)
Full standard:
<https://standards.iteh.ai/catalog/standards/1240448f2-89ff-72f69e32e683/etsi-en-300-394-1-v3.3.0>

Reference

REN/TCCE-03233

Keywords

DMO, testing, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD REVIEW
(Standards.itec.be)
Full standard:
<http://www.etsi.org/standards/ist/100/e5-c5-2015-04>

Important notice

The present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|---|----|
| Intellectual Property Rights | 10 |
| Foreword..... | 10 |
| Modal verbs terminology..... | 10 |
| Introduction | 11 |
| 1 Scope | 12 |
| 2 References | 12 |
| 2.1 Normative references | 12 |
| 2.2 Informative references..... | 13 |
| 3 Definitions, symbols and abbreviations | 13 |
| 3.1 Definitions | 13 |
| 3.2 Symbols | 13 |
| 3.3 Abbreviations | 14 |
| 4 General | 14 |
| 4.1 Presentation of equipment for testing purposes..... | 14 |
| 4.1.1 Facilities and information required for testing..... | 15 |
| 4.1.2 Choice of radio frequency channels to be tested..... | 15 |
| 4.1.3 Interpretation of the measurement results | 16 |
| 4.2 Mechanical and electrical design..... | 16 |
| 4.2.1 General..... | 16 |
| 4.2.2 Controls | 16 |
| 4.2.3 Marking | 16 |
| 5 Radio test configuration, test signals and test modes | 16 |
| 5.1 General functional radio test configuration | 17 |
| 5.2 Radio test modes | 17 |
| 5.2.1 Test receive mode | 17 |
| 5.2.1.1 MS test receive mode for phase modulation | 18 |
| 5.2.1.2 BS test receive mode for phase modulation | 18 |
| 5.2.1.3 MS test receive mode for QAM (where supported) | 19 |
| 5.2.1.4 BS test receive mode for QAM (where supported) | 19 |
| 5.2.2 Test transmit mode..... | 20 |
| 5.2.2.1 MS testing for phase modulation | 20 |
| 5.2.2.2 Void..... | 20 |
| 5.2.2.3 BS testing for phase modulation | 20 |
| 5.2.2.4 MS testing for QAM (where supported) | 21 |
| 5.2.2.5 BS testing for QAM (where supported) | 21 |
| 5.3 Radio test signals..... | 22 |
| 5.3.1 General..... | 22 |
| 5.3.2 Test signal T1 (TETRA wanted signal, phase modulation) | 22 |
| 5.3.2.1 MS testing | 22 |
| 5.3.2.2 BS testing | 23 |
| 5.3.2.3 Void..... | 24 |
| 5.3.2.4 Void..... | 24 |
| 5.3.3 Test signal T2 (TETRA interferer) | 24 |
| 5.3.4 Test signal T3 (unmodulated interferer) | 24 |
| 5.3.5 Test signal T4 (TETRA wanted signal, QAM) | 24 |
| 5.3.5.1 MS testing | 24 |
| 5.3.5.1.1 Use of synchronization burst in frame 18 when testing CA MSs | 26 |
| 5.3.5.1.1a Use of frequency correction burst in frame 18 when testing DA MSs | 28 |
| 5.3.5.2 BS testing | 29 |
| 6 Test conditions | 30 |
| 6.1 General | 30 |

| | | |
|-----------|---|----|
| 6.2 | Power sources and ambient conditions..... | 30 |
| 6.2.1 | Normal test conditions | 30 |
| 6.2.2 | Extreme test conditions..... | 31 |
| 6.3 | Procedure for tests at extreme temperatures..... | 32 |
| 6.3.1 | Equipment designed for continuous operation..... | 32 |
| 6.3.2 | Equipment designed for intermittent operation..... | 32 |
| 7 | Technical characteristics | 32 |
| 7.1 | Transmitter parameter definitions and limits..... | 32 |
| 7.1.1 | Transmitter output power..... | 32 |
| 7.1.1.1 | Definition | 32 |
| 7.1.1.2 | Limit values for phase modulation and QAM | 33 |
| 7.1.2 | Unwanted output power in non-active transmit state..... | 33 |
| 7.1.2.1 | Definition | 33 |
| 7.1.2.2 | Limit values..... | 33 |
| 7.1.3 | Adjacent channel power due to modulation..... | 33 |
| 7.1.3.1 | Definition | 33 |
| 7.1.3.2 | Limit values for phase modulation..... | 33 |
| 7.1.3.3 | Limit values for QAM..... | 34 |
| 7.1.4 | Adjacent channel power due to switching transients | 35 |
| 7.1.4.1 | Definition | 35 |
| 7.1.4.2 | Limit values for phase modulation..... | 35 |
| 7.1.4.3 | Limit values for QAM..... | 35 |
| 7.1.5 | Unwanted emissions far from the carrier | 36 |
| 7.1.5.1 | Definition | 36 |
| 7.1.5.2 | Limit values for phase modulation..... | 36 |
| 7.1.5.3 | Limit values for QAM..... | 37 |
| 7.1.6 | Unwanted radiated emissions | 38 |
| 7.1.6.1 | Definition | 38 |
| 7.1.6.2 | Limit values..... | 38 |
| 7.1.7 | Unwanted emissions during the BLCH/CLCH (linearization) | 38 |
| 7.1.7.1 | Definition | 38 |
| 7.1.7.2 | Limit values for phase modulation..... | 38 |
| 7.1.7.3 | Limit values for QAM..... | 38 |
| 7.1.8 | Transmitter intermodulation attenuation..... | 39 |
| 7.1.8.1 | Definition | 39 |
| 7.1.8.2 | Limit values for phase modulation and QAM | 39 |
| 7.1.8.2.1 | MS Limit values | 39 |
| 7.1.8.2.2 | Limit values for single BS transmitter..... | 39 |
| 7.1.8.2.3 | Limit values for intra BS intermodulation | 39 |
| 7.2 | Receiver parameter definitions and limits | 40 |
| 7.2.1 | General..... | 40 |
| 7.2.2 | Nominal error rates | 40 |
| 7.2.2.1 | Definition | 40 |
| 7.2.2.2 | Limit values for phase modulation..... | 40 |
| 7.2.2.3 | Limit values for QAM..... | 40 |
| 7.2.3 | Reference sensitivity performance..... | 40 |
| 7.2.3.1 | Definition | 40 |
| 7.2.3.2 | Limit values for phase modulation..... | 41 |
| 7.2.3.3 | Limit values for QAM..... | 41 |
| 7.2.4 | Reference interference performance | 43 |
| 7.2.4.1 | Definition | 43 |
| 7.2.4.2 | Limit values for phase modulation..... | 43 |
| 7.2.4.3 | Limit values for QAM..... | 44 |
| 7.2.4.3.1 | Adjacent channel interference | 44 |
| 7.2.4.3.2 | Co-channel interference..... | 44 |
| 7.2.5 | Blocking characteristics | 45 |
| 7.2.5.1 | Definition | 45 |
| 7.2.5.2 | Limit values for phase modulation..... | 45 |
| 7.2.5.3 | Limit values for QAM..... | 45 |
| 7.2.6 | Spurious response rejection | 46 |
| 7.2.6.1 | Definition | 46 |

| | | |
|---------|---|----|
| 7.2.6.2 | Limit values for phase modulation | 46 |
| 7.2.6.3 | Limit values for QAM | 46 |
| 7.2.7 | Intermodulation response rejection | 47 |
| 7.2.7.1 | Definition | 47 |
| 7.2.7.2 | Limit values | 47 |
| 7.2.8 | Unwanted conducted emissions | 48 |
| 7.2.8.1 | Definition | 48 |
| 7.2.8.2 | Limit values | 48 |
| 7.2.9 | Unwanted radiated emissions | 48 |
| 7.2.9.1 | Definition | 48 |
| 7.2.9.2 | Limit values | 48 |
| 7.3 | Transmitter/receiver parameter definitions and limits | 48 |
| 7.3.1 | Modulation accuracy | 48 |
| 7.3.1.1 | Definition | 48 |
| 7.3.1.2 | Limit values for phase modulation | 48 |
| 7.3.1.3 | Limit values for QAM | 48 |
| 7.3.2 | Carrier frequency accuracy | 49 |
| 7.3.2.1 | Definition | 49 |
| 7.3.2.2 | Limit values | 49 |
| 7.3.3 | MS receiver performance for synchronization burst acquisition | 49 |
| 7.3.3.1 | Definition for phase modulation | 49 |
| 7.3.3.2 | Limit values for phase modulation | 49 |
| 7.3.3.3 | Definition for QAM modulation | 49 |
| 7.3.3.4 | Limit values for QAM modulation | 49 |
| 7.3.4 | MS frame alignment performance | 50 |
| 7.3.4.1 | Definition | 50 |
| 7.3.4.2 | Limit values | 50 |
| 7.3.5 | MS link control | 50 |
| 7.3.5.1 | Definition | 50 |
| 7.3.5.2 | Limit values | 50 |
| 8 | Methods of measurement for transmitter parameters | 51 |
| 8.1 | Transmitter output power | 51 |
| 8.1.1 | Transmitter output power for phase modulation | 51 |
| 8.1.1.1 | MS transmitter output power for phase modulation | 51 |
| 8.1.1.2 | BS transmitter output power for phase modulation | 52 |
| 8.1.2 | Transmitter output power for QAM | 53 |
| 8.1.2.1 | MS transmitter output power for QAM | 53 |
| 8.1.2.2 | BS transmitter output power for QAM | 54 |
| 8.2 | Unwanted output power in non active transmit state | 54 |
| 8.3 | Adjacent channel power due to modulation | 54 |
| 8.4 | Adjacent channel power due to switching transients | 55 |
| 8.5 | Unwanted emissions far from the carrier | 55 |
| 8.6 | Unwanted radiated emissions | 57 |
| 8.7 | Unwanted emissions during the BLCH/CLCH and BLCH-Q/CLCH-Q (linearization) | 57 |
| 8.7.1 | MS unwanted emissions during the CLCH (linearization) | 57 |
| 8.7.2 | BS unwanted emissions during the BLCH (linearization) | 58 |
| 8.7.3 | MS unwanted emissions during the CLCH-Q (linearization) | 58 |
| 8.7.4 | BS unwanted emissions during the BLCH-Q (linearization) | 58 |
| 8.8 | Transmitter intermodulation attenuation | 59 |
| 8.8.1 | MS Transmitter intermodulation attenuation | 59 |
| 8.8.2 | BS Transmitter intermodulation attenuation | 59 |
| 8.8.3 | Intra BS transmitter intermodulation attenuation | 59 |
| 9 | Methods of measurement for receiver parameters | 59 |
| 9.1 | General | 59 |
| 9.2 | Nominal error rates for phase modulation | 60 |
| 9.2.1 | MS nominal error rate | 60 |
| 9.2.2 | BS nominal error rate | 60 |
| 9.3 | Reference sensitivity performance | 60 |
| 9.3.1 | MS reference sensitivity performance for phase modulation | 60 |
| 9.3.2 | BS reference sensitivity performance for phase modulation | 61 |

| | | |
|-----------------------------|---|------------|
| 9.3.3 | MS reference sensitivity performance for QAM | 61 |
| 9.3.4 | BS reference sensitivity performance for QAM | 61 |
| 9.3.5 | PUEM performance | 61 |
| 9.4 | Reference interference performance..... | 61 |
| 9.4.1 | MS reference interference performance for phase modulation | 62 |
| 9.4.2 | BS reference interference performance for phase modulation..... | 62 |
| 9.4.3 | MS reference interference performance for QAM..... | 62 |
| 9.4.4 | BS reference interference performance for QAM..... | 63 |
| 9.5 | Blocking characteristics | 63 |
| 9.5.1 | MS blocking for phase modulation..... | 63 |
| 9.5.2 | BS blocking for phase modulation..... | 63 |
| 9.5.3 | MS blocking for QAM..... | 64 |
| 9.5.4 | BS blocking for QAM..... | 64 |
| 9.6 | Spurious response rejection..... | 64 |
| 9.6.1 | Phase Modulation | 64 |
| 9.6.2 | QAM | 65 |
| 9.7 | Intermodulation response rejection | 65 |
| 9.7.1 | MS intermodulation response rejection for phase modulation..... | 65 |
| 9.7.2 | BS intermodulation response rejection for phase modulation | 65 |
| 9.7.3 | MS intermodulation response rejection for QAM | 66 |
| 9.7.4 | BS intermodulation response rejection for QAM | 66 |
| 9.8 | Unwanted emissions..... | 66 |
| 9.9 | Unwanted radiated emissions | 67 |
| 10 | Methods of measurement for transmitter/receiver parameters..... | 67 |
| 10.1 | Modulation accuracy | 67 |
| 10.1.1 | MS modulation accuracy for phase modulation..... | 67 |
| 10.1.2 | BS modulation accuracy for phase modulation..... | 68 |
| 10.1.3 | Vector error magnitude at symbol time for phase modulation..... | 68 |
| 10.1.4 | MS modulation accuracy for QAM | 68 |
| 10.1.5 | BS modulation accuracy for QAM | 68 |
| 10.1.6 | Vector error magnitude at symbol time for QAM | 68 |
| 10.2 | Carrier frequency accuracy..... | 69 |
| 10.2.1 | MS carrier frequency accuracy for phase modulation | 69 |
| 10.2.2 | BS carrier frequency accuracy for phase modulation | 69 |
| 10.2.3 | MS carrier frequency accuracy for QAM | 70 |
| 10.2.4 | BS carrier frequency accuracy for QAM | 70 |
| 10.3 | MS receiver performance for synchronization acquisition..... | 71 |
| 10.3.1 | CA MS receiver performance for synchronization burst acquisition..... | 71 |
| 10.3.2 | DA MS receiver performance for frequency correction burst acquisition | 71 |
| 10.4 | MS Frame alignment performance | 71 |
| 10.5 | MS link control..... | 72 |
| 11 | Measurement uncertainty | 73 |
| 11.1 | Transmitter | 73 |
| 11.2 | Receiver..... | 77 |
| 11.3 | Transmitter/receiver parameter definitions and limits..... | 78 |
| 11.4 | Interpretation of measurement results | 79 |
| Annex A (normative): | TETRA receiver testing..... | 80 |
| A.1 | Frequencies of spurious response..... | 80 |
| A.2 | Test cases and test conditions for BS and MS receivers | 80 |
| A.3 | Test signal T1/T4, content of BSCH, BSCH-Q/T, BNCH/T and BNCH-Q/T | 110 |
| Annex B (normative): | Radio test system functions | 117 |
| B.1 | Test transmitter and receiver | 117 |
| B.1.1 | General | 117 |
| B.1.2 | Sampling system | 117 |
| B.1.2.1 | General..... | 117 |
| B.1.2.2 | TETRA filter..... | 117 |

| | | |
|-----------|---|-----|
| B.1.2.3 | Adjacent channel power measurements | 118 |
| B.1.2.4 | Modulation accuracy measurements..... | 118 |
| B.1.2.5 | Measurement of unwanted output power in the non-active transmit state | 118 |
| B.1.3 | Spectrum analyser | 118 |
| B.1.4 | Error rate tester..... | 118 |
| B.1.5 | Test signal requirements..... | 119 |
| B.1.5.1 | On channel test signal T1..... | 119 |
| B.1.5.2 | Interfering test signal T2..... | 119 |
| B.1.5.2.1 | Phase Modulated | 119 |
| B.1.5.2.2 | QAM Modulated | 119 |
| B.1.5.3 | Interfering test signal T3..... | 119 |
| B.1.5.4 | On channel test signal T4..... | 120 |
| B.1.6 | Propagation simulators | 120 |
| B.1.7 | Timing measurement unit..... | 120 |
| B.1.8 | Passive test system components | 120 |
| B.1.9 | Test system controller | 120 |

Annex C (normative): TETRA Test Connector Interface (TTCI)121

| | | |
|-----------|---|-----|
| C.1 | General | 121 |
| C.2 | Formal aspects..... | 121 |
| C.3 | TTCI, layer 1 | 122 |
| C.3.1 | Mechanical and electrical characteristics | 122 |
| C.3.2 | Transmission and reception characteristics | 122 |
| C.4 | TTCI, Layer 2..... | 122 |
| C.4.1 | General structure | 122 |
| C.4.2 | Frame structure..... | 122 |
| C.4.3 | Flow of I-frames on layer 2 | 123 |
| C.4.3.1 | Transmission of frames..... | 123 |
| C.4.3.2 | Reception of frames | 123 |
| C.4.3.3 | Parameters on layer 2 | 124 |
| C.5 | TTCI, Layer 3..... | 124 |
| C.5.1 | Message structure | 124 |
| C.5.2 | Definitions of the messages | 124 |
| C.5.2.1 | DATO | 124 |
| C.5.2.1.1 | Test equipment error handling | 126 |
| C.5.2.2 | Bi-directional operation of the TTCI | 126 |
| C.5.2.3 | Codec conformance testing | 127 |
| C.5.2.4 | ST indicator | 127 |
| C.6 | Control of MS/BS..... | 128 |
| C.6.1 | Manual intervention of MS/BS | 128 |
| C.6.2 | Bi-directional operation of the test interface | 128 |
| C.6.3 | MS controlled by T1..... | 128 |
| C.7 | Characteristics of the interface | 128 |
| C.7.1 | Mechanical characteristics of the interface..... | 128 |
| C.7.2 | Electric characteristics of the interface..... | 128 |
| C.8 | Codec conformance testing using the TTCI..... | 129 |
| C.8.1 | Codec conformance test methodology using the TTCI | 129 |

Annex D (normative): RF test facility using RF loop back130

| | | |
|-------|--|-----|
| D.1 | Introduction to the TETRA Test (TT) protocol for RF loop back test | 131 |
| D.1.1 | Outline requirements | 131 |
| D.1.2 | Test modes..... | 132 |
| D.1.3 | Switching for loop back test mode | 133 |
| D.2 | TETRA test entity | 133 |
| D.3 | TETRA RF loop back test protocol..... | 134 |

| | | |
|------------|--|------------|
| D.3.1 | Setting the TETRA MS into TETRA test mode | 134 |
| D.3.2 | TETRA test protocol | 135 |
| D.3.2.1 | Confirming that TETRA test mode is set..... | 135 |
| D.3.2.2 | Operating TETRA loop back | 136 |
| D.3.2.3 | Ending TETRA test mode..... | 136 |
| D.3.3 | Bad frame indication | 137 |
| D.3.4 | Channels required to be looped back..... | 137 |
| D.3.5 | TETRA loop back test scenarios | 137 |
| D.4 | TETRA Test (TT) PDU descriptions | 138 |
| D.4.1 | TT PDU description tables downlink | 138 |
| D.4.1.1 | D-LOOP COMMAND | 138 |
| D.4.1.2 | D-OPEN LOOP COMMAND | 138 |
| D.4.1.3 | D-TEST MODE CONFIRM COMMAND..... | 138 |
| D.4.1.4 | D-TEST MODE END COMMAND | 139 |
| D.4.2 | TT PDU description tables uplink | 139 |
| D.4.2.1 | U-LOOP CONFIRM..... | 139 |
| D.4.2.2 | U-OPEN LOOP CONFIRM | 139 |
| D.4.2.3 | U-TEST MODE CONFIRM | 140 |
| D.4.2.4 | U-TEST MODE END CONFIRM | 140 |
| D.4.3 | Information elements coding..... | 140 |
| D.4.3.1 | Loopback type | 140 |
| D.4.3.2 | Confirm..... | 141 |
| D.4.3.3 | MS power class..... | 141 |
| D.4.3.4 | PDU | 141 |
| D.4.3.5 | Receiver class | 142 |
| D.5 | TT use of MLE, LLC and MAC..... | 142 |
| D.6 | Message sequence charts and operation of TETRA loop back..... | 142 |
| D.7 | Introduction to the T1 and T4 test modes for RF loop back test..... | 142 |
| D.7.1 | Outline requirements | 143 |
| D.7.2 | T1/T4 Test Modes | 143 |
| D.7.3 | Switching for loop back test mode | 144 |
| D.8 | TETRA RF loop back T1 test mode (phase modulation)..... | 145 |
| D.8.1 | Setting TETRA equipment into T1 test mode | 145 |
| D.8.2 | T1 loop back test mode operation..... | 145 |
| D.8.3 | Logical channels to be looped back | 146 |
| D.8.4 | Return channel for logical channel loop back | 146 |
| D.8.4.1 | Type 1: TCH/7,2 + AACH | 147 |
| D.8.4.2 | Type 2: SCH/F + AACH | 147 |
| D.8.4.3 | Type 3: BSCH + SCH/HD + AACH | 147 |
| D.8.4.4 | Type 4: TCH/2,4 N = 1 + AACH | 148 |
| D.8.4.5 | Type 7: TCH/7,2 (uplink) | 148 |
| D.8.4.6 | Type 8: SCH/F (uplink) | 148 |
| D.8.4.7 | Type 9: STCH + STCH (uplink)..... | 148 |
| D.8.4.8 | Type 10: TCH/2,4 N = 1 (uplink) | 149 |
| D.8.4.9 | Type 11: SCH/HU + SCH/HU..... | 149 |
| D.8.4.10 | Type 15: TCH/S + TCH/S + AACH..... | 149 |
| D.8.4.11 | Type 16: TCH/S + TCH/S (uplink) | 149 |
| D.8.4.12 | Type 17: TCH/4,8 N = 1 + AACH | 150 |
| D.8.4.13 | Type 18: TCH/4,8 N = 1 (uplink) | 150 |
| D.8.4.14 | Type 19: TCH/S speech codec test (downlink)..... | 150 |
| D.8.4.15 | Type 20: TCH/S speech codec test (uplink) | 150 |
| D.8.4.16 | Type 21: TCH-P8/10,8 (downlink)..... | 151 |
| D.8.4.17 | Type 22: SCH-P8/HD + SCH-P8/HD..... | 151 |
| D.8.4.18 | Type 24: SCH-P8/F (downlink)..... | 151 |
| D.8.4.19 | Type 21: TCH-P8/10,8 (uplink)..... | 151 |
| D.8.4.20 | Type 24: SCH-P8/F (uplink)..... | 152 |
| D.8.4.21 | Type 23: SCH-P8/HU + SCH-P8/HU..... | 152 |
| D.8.5 | Loop back test scenarios..... | 152 |

| | | |
|-------------------------------|--|------------|
| D.9 | TETRA RF loop back T4 test mode (QAM)..... | 154 |
| D.9.1 | Setting TETRA equipment into T4 test mode | 154 |
| D.9.2 | T4 loop back test mode operation..... | 155 |
| D.9.3 | Logical channels to be looped back..... | 155 |
| D.9.4 | Return channel for logical channel loop back | 156 |
| D.9.4.1 | Type 27: SCH-Q/D with coding rates of 1/2 or 2/3 and error correction enabled | 157 |
| D.9.4.2 | Type 27: SCH-Q/D with error correction disabled or when the coding rate is 1 | 157 |
| D.9.4.3 | Type 26: SCH-Q/U with coding rates of 1/2 or 2/3 and error correction enabled | 158 |
| D.9.4.4 | Type 26: SCH-Q/U with coding rate of 1 or error correction disabled..... | 159 |
| D.9.4.5 | Type 25: SCH-Q/HU with coding rates of 1/2 or 2/3 and error correction enabled | 159 |
| D.9.4.6 | Type 25: SCH-Q/HU with coding rate of 1 or error correction disabled..... | 160 |
| D.9.4.7 | Type 28: SCH-Q/RA with error correction enabled | 160 |
| D.10 | Direct Mode Operation (DMO)..... | 160 |
| D.10.1 | Direct mode only mobile station (DO-MS) | 161 |
| D.10.2 | Dual mode switchable mobile station (DU-MS) | 161 |
| D.10.3 | Dual watch mobile station (DW-MS)..... | 161 |
| D.10.4 | Direct mode repeater (DM-REP)..... | 161 |
| D.10.5 | Direct mode gateway (DM-GATE)..... | 161 |
| D.10.6 | Direct mode repeater/gateway combination (DM-REP/GATE)..... | 161 |
| D.10.7 | DMO summary..... | 162 |
| Annex E (normative): | Using RF loop back to test a TETRA MS..... | 163 |
| E.1 | Introduction | 163 |
| E.2 | Expected mode of operation for testing a MS | 164 |
| E.3 | Recognition of TETRA Test mode by MS | 167 |
| E.4 | Using loop back to test traffic channels..... | 168 |
| E.4.1 | TCH/7,2..... | 170 |
| E.4.2 | TCH/S | 171 |
| E.4.3 | TCH/2,4, N = 8..... | 171 |
| E.4.4 | Control messages during loop back of traffic channels | 172 |
| Annex F (normative): | Direct Mode (DM) Conformance Testing..... | 173 |
| F.1 | Scope | 173 |
| F.2 | Definitions, symbols and abbreviations | 173 |
| F.3 | General | 173 |
| F.4 | Radio test modes | 173 |
| F.5 | Test conditions | 174 |
| F.6 | Additional tests for equipment which is capable of Direct Mode Operation | 175 |
| F.6.1 | DMO test transmit mode | 175 |
| F.6.2 | DMO transmitter output power profile..... | 175 |
| F.6.2.1 | DMO transmitter output power profile, limit values | 175 |
| F.6.2.2 | DMO transmitter output power profile, method of measurement..... | 175 |
| F.6.3 | DMO Carrier frequency accuracy | 176 |
| F.6.3.1 | DMO Carrier frequency accuracy, limit values | 176 |
| F.6.3.2 | DMO Carrier frequency accuracy, method of measurement | 176 |
| F.6.4 | DM-MS Slave synchronization accuracy | 176 |
| F.6.4.1 | DM-MS Slave synchronization accuracy, definition | 176 |
| F.6.4.2 | DM-MS Slave synchronization accuracy, limit values | 176 |
| F.6.4.3 | DM-MS Slave synchronization accuracy, method of measurement | 176 |
| Annex G (informative): | Change requests | 178 |
| History | 179 | |

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee TETRA and Critical Communications Evolution (TCCE), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document contains text concerning conformance testing of the equipment to which it relates. This text should be considered only as guidance and does not make the present document mandatory.

The present document is part 1 of a multi-part deliverable covering the conformance testing specification, as identified below:

Part 1: "Radio";

Part 2: "Protocol testing specification for Voice plus Data (V+D);

Part 4: "Protocol testing specification for Direct Mode Operation (DMO);"

Part 5: "Security".

NOTE: Part 2, part 4 and part 5 of this multi-part deliverable are in status "historical" and are not maintained.

Proposed national transposition dates

| | |
|--|---------------------------------|
| Date of latest announcement of this EN (doa): | 3 months after ETSI publication |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 6 months after doa |
| Date of withdrawal of any conflicting National Standard (dow): | 6 months after doa |

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**may not**", "**need**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document includes Direct Access and multislot receiver testing in addition to the earlier Release 2 tests and is aligned with ETSI EN 300 392-2 [1].

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1e2a67e5-c32b-48f2-89ff-72f69e32e683/etsi-en-300-394-1-v3.3.1-2015-04>

1 Scope

The present document specifies the minimum technical characteristics of TETRA Voice plus Data (V+D) Base Stations (BS) and Mobile Station (MS) equipment, and TETRA Direct Mode Operation (DMO) equipment, and the radio test methods used for type testing. Specific test methods for DMO equipment are defined in annex F of the present document. The purpose of these specifications is to provide a sufficient quality of radio transmission and reception for equipment operating in a TETRA system and to minimize harmful interference to other equipment. The present document is applicable to TETRA systems operating at radio frequencies in the range of 300 MHz to 1 GHz.

These specifications do not necessarily include all the characteristics which may be required by a user of equipment, nor do they necessarily represent the optimum performance achievable.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)" / ETSI TS 100 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)"

NOTE: The references EN 300 392-2 and TS 100 392-2 are two instances of the same document and the latest version of those is used as the normative reference. For a shorter presentation only EN 300 392-2 [1] is used as the reference in the present document.

[2] Recommendation ITU-T O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".

[3] ETSI EN 300 113-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".

[4] Recommendation ITU-T V.1: "Equivalence between binary notation symbols and the significant conditions of a two-condition code".

[5] ISO 2110:1989: "Information technology - Data communication - 25-pole DTE/DCE interface connector and contact number assignments".

[6] ETSI EN 300 395-4: "Terrestrial Trunked Radio (TETRA); Speech codec for full-rate traffic channel; Part 4: Codec conformance testing".

[7] ETSI EN 300 396-2: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 2: Radio aspects".

[8] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General Network Design".

- [9] ETSI EN 300 392-7: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".
- [10] ETSI ETS 300 392-11-22: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 11: Supplementary services stage 2; Sub-part 22: Dynamic Group Number Assignment (DGNA)".
- [11] ETSI EN 300 392-12-22: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 22: Dynamic Group Number Assignment (DGNA)".
- [12] ETSI EN 300 395-2: "Terrestrial Trunked Radio (TETRA); Speech codec for full-rate traffic channel; Part 2: TETRA codec".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.2] ETSI EN 300 396-1: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 1: General network design".
- [i.3] ETSI TS 101 293: "Digital cellular telecommunications system (Phase 2+); Individual equipment type requirements and interworking; Special conformance testing functions (3GPP TS 04.14)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 300 392-2 [1] and the following apply:

accreditation body: body that conducts and administers a laboratory accreditation system and grants accreditation

accredited laboratory: testing laboratory to which accreditation has been granted

receive band of the equipment: maximum frequency range (declared by the manufacturer) over which the receiver can be operated without reprogramming or realignment

testing laboratory: laboratory that performs tests

transmit band of the equipment: maximum frequency range (declared by the manufacturer) over which the transmitter can be operated without reprogramming or realignment

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 300 392-2 [1] and the following apply:

| | |
|-------------------|--|
| f_{lo} | local oscillator frequency applied to first receiver mixer |
| $if_1 \dots if_n$ | receiver intermediate frequencies |
| P_{MS} | access power |
| E | Stop bit |
| Message | Information on layer 3 |