



**Lawful Interception (LI);  
Retained data handling;  
Handover interface for the request and  
delivery of retained data**

*Standard PREVIEW*  
*Full standard available at <https://standards.iteh.ai/catalog/standards/sis/48c0-9a9b-14df42ac78ba/etsi-102-657-v1.15.1-2014-08>*

## Reference

RTS/LI-00119

## Keywords

handover, retention

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	8
Foreword.....	8
Modal verbs terminology.....	8
1 Scope .....	9
2 References .....	9
2.1 Normative references .....	9
2.2 Informative references.....	11
3 Definitions and abbreviations.....	11
3.1 Definitions.....	11
3.2 Abbreviations .....	12
4 Overview of handover interface.....	13
4.1 Reference model.....	13
4.2 Structure of document and applicable communication domains .....	15
4.3 Categories of retained data .....	16
4.4 Handover Interface port 1 (HI-A) and Handover Interface port 2 (HI-B).....	16
4.5 Model used for the RDHI.....	17
5 Handover interface message flows.....	17
5.1 Introduction .....	17
5.1.1 Summary of this clause.....	17
5.1.2 Message flow modes.....	17
5.1.3 Delivery cases .....	18
5.1.4 "Active" requests and "closed" requests.....	18
5.1.5 Errors and failure situations.....	18
5.1.5.1 Error and failure types.....	18
5.1.5.2 Request process failure feedback.....	19
5.1.5.3 Other errors .....	19
5.1.5.4 Missing messages.....	19
5.1.6 Cancelling a request.....	20
5.1.7 Delivery of results.....	20
5.1.8 State diagram .....	21
5.1.9 Supplementary Messages.....	22
5.2 Message flows for general situation .....	22
5.2.1 Delivery of a response .....	22
5.2.2 Cancellation of request .....	23
5.2.3 Multi-part delivery.....	24
5.3 Message flows for Authorized-Organization-initiated scenario.....	25
5.3.1 Delivery of results or a failure response .....	25
5.3.2 Cancellation of request .....	26
5.3.3 Multi-part delivery.....	27
5.4 Message types for HI-A and HI-B.....	28
5.5 HI-A and HI-B addressing.....	29
6 Definition of the elements for retained data messages.....	29
6.1 Header information.....	29
6.1.1 Use of header information .....	29
6.1.2 RequestID field specification.....	29
6.1.3 CSP Identifiers.....	30
6.1.3.1 Use of CSP identifiers (CSPID).....	30
6.1.3.2 Third Party CSP Identifier (thirdPartyCSPID).....	30
6.1.4 Timestamp (timeStamp) .....	30
6.2 Retained Data response .....	30
6.2.1 General.....	30
6.2.2 Additional information in response messages.....	31

6.2.2.1	Record number (recordNumber) .....	31
6.2.2.2	Response status (ResponseStatus).....	31
6.2.3	Volatile information.....	31
6.2.4	Unavailable parameters.....	31
6.3	Retained Data requests .....	31
6.3.1	Information contained within a request .....	31
6.3.2	Format of a request .....	32
6.3.3	Additional information in requests .....	33
6.3.3.1	Priority of a request.....	33
6.3.3.2	Maximum hits .....	33
6.3.3.3	Maximum records per batch.....	33
6.4	Error messages .....	33
7	Data exchange techniques .....	33
7.1	General .....	33
7.2	HTTP data exchange .....	34
7.2.1	Basic configuration .....	34
7.2.2	Single client/server .....	34
7.2.3	Mutual client/server .....	34
7.2.4	Details common to both single and mutual cases .....	34
7.3	Direct TCP data exchange .....	35
7.3.1	Application layer .....	35
7.3.2	Transport layer.....	35
7.3.2.1	Introduction.....	35
7.3.2.2	TCP settings .....	35
7.3.3	Network layer .....	36
7.3.4	Delivery networks.....	36
8	Security Measures .....	36
8.1	General .....	36
8.2	Connection Level Security .....	36
8.3	Application Level Security.....	36
8.4	Technical Security Measures.....	37
8.4.1	General.....	37
8.4.2	Connection Level.....	37
8.4.3	Application Level .....	37
8.4.3.1	Hashes .....	37
8.4.3.2	Digital Signatures.....	37
8.4.3.3	HI-B Non-Repudiation.....	38
8.4.3.4	Digital Signatures and Message Structure.....	38
<b>Annex A (normative):</b>	<b>Data fields .....</b>	<b>39</b>
A.1	Summary .....	39
A.1.1	Introduction to data fields.....	39
A.1.2	Choice of data modelling language .....	39
A.1.3	Overview .....	39
A.2	Parameter definition for common fields.....	40
A.2.1	RetainedDataHeader.....	40
A.2.1.1	Parameters.....	40
A.2.1.2	RequestID parameters.....	40
A.2.2	RetainedDataPayload .....	40
A.2.2.1	RequestMessage parameters .....	40
A.2.2.2	RequestAcknowledgement parameters .....	41
A.2.2.3	ResponseMessage parameters.....	41
A.2.2.4	GetStatusMessage parameters .....	41
A.2.2.5	StatusMessage parameters .....	41
A.2.2.6	ErrorMessage parameters .....	42
A.2.3	GenericSubscriberInfo.....	42
A.2.3.1	Parameters.....	42
A.2.3.2	OrganizationInfo parameters .....	42
A.2.3.3	IndividualInfo parameters.....	43

A.2.4	PaymentDetails.....	43
A.3	ASN.1 definitions.....	44
A.3.1	General.....	44
A.3.1.1	ASN.1 syntax tree.....	44
A.3.1.2	General remarks on ASN.1.....	44
A.3.2	ASN.1 Definitions for message headers.....	45
A.3.2.1	Message wrappers.....	45
A.3.2.2	Message headers.....	45
A.3.3	ASN.1 definitions for common fields.....	50
A.3.4	Schematic representation of top level ASN.1.....	53
<b>Annex B (normative): Service-specific details for telephony services.....</b>		<b>55</b>
B.1	Scope.....	55
B.2	Telephony fields.....	55
B.2.1	General.....	55
B.2.2	Telephony Subscriber.....	55
B.2.2.1	subscriber ID.....	55
B.2.2.2	genericSubscriberInfo.....	56
B.2.2.3	telephonySubscriberInfo.....	56
B.2.2.4	subscribedTelephonyServices.....	56
B.2.2.4.1	Description.....	56
B.2.3	Telephony Billing Details.....	57
B.2.3.1	BillingRecords.....	57
B.2.4	Telephony ServiceUsage.....	58
B.2.4.1	Parameters.....	58
B.2.4.2	PartyInformation.....	58
B.2.4.3	SMSInformation.....	59
B.2.4.4	MmsInformation.....	59
B.2.5	TelephonyDevice.....	59
B.2.5.1	General.....	59
B.2.6	TelephonyNetworkElement.....	60
B.2.6.1	General.....	60
B.2.6.2	Location parameters.....	60
B.2.6.2.1	General.....	60
B.2.6.2.2	GSM Location Information.....	61
B.2.6.2.3	UMTS Location Information.....	61
B.2.6.2.4	Extended Location.....	61
B.2.6.3	TransmitterDetails parameters.....	62
B.2.6.3.1	General.....	62
B.3	ASN.1 definitions for telephony.....	62
B.4	Schematic view of ASN.1 definitions.....	75
<b>Annex C (normative): Service-specific details for asynchronous message services.....</b>		<b>77</b>
C.1	Scope.....	77
C.2	Descriptions.....	77
C.2.1	General.....	77
C.2.2	MsgSubscriber.....	78
C.2.2.1	MsgSubscriberID.....	78
C.2.2.2	MsgStore.....	78
C.2.2.3	MsgStoreID.....	78
C.2.2.4	MsgAddress.....	78
C.2.2.5	MsgProviderID.....	78
C.2.3	MsgServiceUsage.....	79
C.2.3.1	MsgTransmission.....	79
C.2.3.2	MsgStoreOperation.....	79
C.2.4	MsgBillingDetails parameters.....	80
C.2.4.1	MsgBillingRecords.....	80

C.3	ASN.1 definitions for asynchronous message services .....	80
C.4	Schematic view of ASN.1 definitions .....	84
<b>Annex D (normative): Service-specific details for synchronous multi-media services .....</b>		<b>85</b>
D.1	Scope .....	85
D.2	Multimedia fields .....	85
D.2.1	General .....	85
D.2.2	Multimedia Subscriber .....	85
D.2.2.1	subscriberID .....	85
D.2.2.2	genericSubscriberInfo .....	86
D.2.2.3	multimediaSubscriberInfo .....	86
D.2.2.4	subscribedMultimediaServices .....	86
D.2.2.4.1	Description .....	86
D.2.3	MultimediaBillingDetails .....	87
D.2.3.1	MultimediaBillingDetails .....	87
D.2.3.2	MultimediaBillingAddress .....	87
D.2.3.3	MultimediaBillingRecords .....	88
D.2.4	Multimedia ServiceUsage .....	88
D.2.4.1	Parameters .....	88
D.2.4.2	PartyInformation .....	89
D.2.4.3	IMSInformation .....	89
D.2.4.4	MediaComponents .....	90
D.3	ASN.1 definitions for Multimedia .....	90
D.4	Schematic view of ASN.1 definitions .....	96
<b>Annex E (normative): Service-specific details for network access services .....</b>		<b>98</b>
E.1	Scope .....	98
E.2	Descriptions .....	98
E.2.1	General .....	98
E.2.2	NASubscriber .....	98
E.2.3	NAServiceSubscription .....	99
E.2.4	NAServiceUsage .....	99
E.2.5	NADevice .....	102
E.2.6	NANwElement .....	103
E.2.7	NABillingDetails .....	103
E.3	ASN.1 definitions for network access services .....	103
E.4	Schematic view of ASN.1 definitions .....	112
<b>Annex F (informative): Basic set of search routines for Retained Data .....</b>		<b>113</b>
F.1	Example set of search routines .....	113
F.1.1	Introduction .....	113
F.1.2	Summary of search case .....	113
F.1.3	Subscriber records .....	113
F.2	Telephony data .....	114
F.2.1	Telephony subscriber .....	114
F.2.2	Telephony billing details .....	114
F.2.3	Telephony service usage .....	114
F.2.4	Telephony network element .....	114
F.3	Messaging data .....	115
F.3.1	Message subscriber .....	115
F.3.2	Message service usage .....	115
F.4	Network Access data .....	115
F.4.1	NA subscriber .....	115
F.4.2	NA service usage .....	116

<b>Annex G (informative):</b>	<b>Examples of search routines .....</b>	<b>117</b>
G.1	Introduction .....	117
G.2	Example for telephony subscriber query in clause F.2.1.....	117
G.3	Example for telephony service usage query in clause F.2.3.....	118
<b>Annex H (informative):</b>	<b>Further information on data categories.....</b>	<b>119</b>
H.1	General .....	119
H.2	Further information on subscriber data .....	119
H.2.1	Subscriber data requests .....	119
H.2.2	Generic subscriber data records.....	120
H.2.3	Service Specific Subscriber Reply Data .....	120
H.3	Further information on usage data.....	121
H.3.1	Usage requests .....	121
H.3.2	Usage data categories .....	121
H.3.3	Usage: Traffic Data (Reply) .....	121
H.3.4	Usage: Traffic Data related information (Reply).....	121
H.3.5	Usage: communication independent user activities (Reply).....	122
H.3.6	Usage: network Activity Data (Reply) .....	122
H.4	Further information on network element data .....	122
H.4.1	Network element requests .....	122
H.4.2	Network Configuration Data Reply Data .....	122
<b>Annex I (informative):</b>	<b>Manual techniques.....</b>	<b>123</b>
<b>Annex J (informative):</b>	<b>Single versus multi-part deliveries.....</b>	<b>124</b>
J.1	General .....	124
J.2	Criteria for multi-part delivery .....	124
J.3	Subscriptions into the future.....	125
<b>Annex K (informative):</b>	<b>Change Request History.....</b>	<b>126</b>
History .....		129

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Lawful Interception (LI).

The ASN.1 module and XML schema are also available as an electronic attachment to the original document from the ETSI site (see details in clause A.3.1.2).

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**may not**", "**need**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.



---

# 1 Scope

The present document is based on requirements from TS 102 656 [2].

The present document contains handover requirements and a handover specification for the data that is identified in national legislations on Retained Data.

The present document considers both the requesting of retained data and the delivery of the results.

The present document defines an electronic interface. An informative annex describes how this interface may be adapted for manual techniques. Apart from in annex I, the present document does not consider manual techniques.

---

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] ETSI TS 102 656: "Lawful Interception (LI); Retained Data; Requirements of Law Enforcement Agencies for handling Retained Data".
- [3] ETSI TS 102 232-1: "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery; Part 1: Handover specification for IP delivery".
- [4] ISO 3166-1: "Codes for the representation of names of countries and their subdivisions -- Part 1: Country codes".
- [5] ISO 4217: "Codes for the representation of currencies and funds".
- [6] ETSI TS 101 671: "Lawful Interception (LI); Handover interface for the lawful interception of telecommunications traffic".

NOTE: Periodically TS 101 671 is published as ES 201 671. A reference to the latest version of the TS as above reflects the latest stable content from ETSI/TC LI.

- [7] ETSI EN 300 356 (all parts): "Integrated Services Digital Network (ISDN); Signalling System No.7 (SS7); ISDN User Part (ISUP) version 4 for the international interface".
- [8] ETSI TS 100 974: "Digital cellular telecommunications system (Phase 2+); Mobile Application Part (MAP) Specification (3GPP TS 09.02)".
- [9] ETSI TS 124 008: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Mobile radio interface Layer 3 specification; Core network protocols; Stage 3 (3GPP TS 24.008)".
- [10] Void.
- [11] ETSI TS 133 108: "Universal Mobile Telecommunications System (UMTS); LTE; 3G security; Handover interface for Lawful Interception (LI) (3GPP TS 33.108)".

- [12] ETSI TS 101 109 (V7.2.0): "Digital cellular telecommunications system (Phase 2+); Universal Geographical Area Description (GAD) (3GPP TS 03.32 version 7.2.0 Release 1998)".
- [13] FIPS PUB 186-2: "Digital Signature Standard (DSS)".
- [14] IETF RFC 2616: "Hypertext Transfer Protocol - HTTP/1.1".
- [15] IETF RFC 2818: "HTTP Over TLS".
- [16] ETSI TS 123 040: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Technical realization of the Short Message Service (SMS) (3GPP TS 23.040)".
- [17] IETF RFC 793: "Transmission Control Protocol".
- [18] IETF RFC 5681: "TCP Congestion Control".
- NOTE: IETF RFC 5681 obsoletes IETF RFC 2581: "TCP Congestion Control".
- [19] IETF RFC 6298: "Computing TCP's Retransmission Timer".
- NOTE: IETF RFC 6298 obsoletes IETF RFC 2988: "Computing TCP's Retransmission Timer".
- [20] IETF RFC 1122: "Requirements for Internet Hosts - Communication Layers".
- [21] IETF RFC 791: "Internet Protocol".
- [22] ETSI ES 282 002: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); PSTN/ISDN Emulation Sub-system (PES); Functional architecture".
- [23] IETF RFC 822: "Standard for the format of ARPA internet text messages".
- [24] IETF RFC 5322: "Internet Message Format".
- NOTE: IETF RFC 5322 obsoletes IETF RFC 2822: "Internet Message Format".
- [25] ETSI TS 123 228: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; IP Multimedia Subsystem (IMS); Stage 2 (3GPP TS 23.228)".
- [26] IETF RFC 3261: "SIP: Session Initiation Protocol".
- [27] IETF RFC 4506: "XDR: External Data Representation Standard".
- [28] ISO 13616-1:2007: "Financial services - International bank account number (IBAN) - Part 1: Structure of the IBAN".
- [29] ISO 9362:2009: "Banking - Banking telecommunication messages - Business identifier code (BIC)".
- [30] Void.
- [31] ETSI TS 125 413: "Universal Mobile Telecommunications System (UMTS); UTRAN Iu interface Radio Access Network Application Part (RANAP) signalling (3GPP TS 25.413)".
- [32] ETSI TS 129 274: "Universal Mobile Telecommunications System (UMTS); LTE; 3GPP Evolved Packet System (EPS); Evolved General Packet Radio Service (GPRS) Tunnelling Protocol for Control plane (GTPv2-C); Stage 3 (3GPP TS 29.274)".
- [33] ETSI TS 129 061: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Interworking between the Public Land Mobile Network (PLMN) supporting packet based services and Packet Data Networks (PDN) (3GPP TS 29.061)".

- [34] ETSI TS 129 118: "Universal Mobile Telecommunications System (UMTS); LTE; Mobility Management Entity (MME) - Visitor Location Register (VLR) SGs interface specification (3GPP TS 29.118)".
- [35] ETSI TS 123 272: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Circuit Switched (CS) fallback in Evolved Packet System (EPS); Stage 2 (3GPP TS 23.272)".
- [36] ETSI TS 133 234: "Universal Mobile Telecommunications System (UMTS); LTE; 3G security; Wireless Local Area Network (WLAN) interworking security (3GPP TS 33.234)".

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**authorized organization:** any authority legally authorized to request or receive retained data e.g. a Law Enforcement Agency

**Handover Interface A (HI-A):** administrative handover interface comprising requests for information and their responses

**Handover Interface B (HI-B):** data handover interface comprising the retained data transmission of information

**issuing authority:** any entity possessing the necessary jurisdiction and authority pursuant to law to compel a service provider to deliver retained subscriber information or traffic data specified in a query

**lawful authorization:** permission granted to an Authorized Organization under certain conditions to request specified telecommunications retained data and requiring co-operation from a network operator/service provider/access provider

NOTE: Typically, this refers to a warrant or order issued by a lawfully authorized body.

**location information:** information relating to the geographic, physical or logical location of an identity relating to an interception subject

**number:** any address (E.164, IP, email, URI) used for routing in a network or in a service on a user level or network/service level

**receiving authority:** any entity possessing the necessary authority pursuant to law and the technical means to receive retained subscriber information or traffic data delivered by a service provider

**request:** legal requirement for a Communications Service Provider (CSP) to disclose retained data in accordance with relevant national law

**response to request of information:** response from the CSP to the authorized organization acknowledging or rejecting a request for information

**retained data record:** set of data elements for a specific subscriber/user related to a specific service transaction

**service transaction:** instance of a service given by a CSP to a subscriber/user

**service transaction record:** set of data elements describing a service transaction (details to be determined)

**transmission of information:** transmission of retained data from the CSP to the receiving authority

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACK	Acknowledge
ADSL	Asymmetric Digital Subscriber Line
AO	Authorized Organization
APN	Access Point Name
ASCII	American Standard Code for Information Interchange
ASN	Abstract Syntax Notation
BER	Basic Encoding Rules
BIC	Business Identifier Code
CGI	Cell Global Identity
CPE	Customer Premises Equipment
CS	Circuit Switched
CSP	Communications Service Provider
CSPID	CSP Identifier
DNS	Domain Name System
DR	Data Retention
DSA	Digital Signature Algorithm
DSL	Digital Subscriber Line
DSS	Digital Signature Standard
DVD	Digital Versatile Disc or Digital Video Disc
ECGI	E-UTRAN Cell Global ID
EMS	Enhanced Messaging Service
EPS	Evolved Packet System
GGSN	Gateway GPRS Support Node
GPRS	General Packet Radio Service
GSM	Global System for Mobile communications
GW	Gateway
HI	Handover Interface
HI-A	Handover Interface A
HI-B	Handover Interface B
HTTP	HyperText Transfer Protocol
HTTPS	HyperText Transfer Protocol over Secure Socket Layer
IBAN	International Banking Account Number
ICCID	Integrated Circuit Card ID
ID	Identifier
IEI	Information Element Identifier
IMAP	Internet Message Access Protocol
IMEI	International Mobile Equipment Identity
IMEISV	IMEI Software Version
IMS	IP Multimedia Subsystem
IMSI	International Mobile Subscriber Identity
IP	Internet Protocol
IPSec	Internet Protocol Security
IRI	Intercept Related Information
ISDN	Integrated Services Digital Network
ISUP	ISDN User Part
LAN	Local Area Network
LEA	Law Enforcement Agency
LI	Lawful Interception
MAC	Media Access Control
MCC	Mobile Country Code
ME	Mobile Equipment
MF-B	Mediation Function B
MME	Mobility Management Entity
MMS	Multimedia Messaging Service
MNC	Mobile Network Code
MS	Mobile Station
MSC	Mobile Switching Centre

MSISDN	Mobile Subscriber ISDN number
MSN	Multiple Subscriber Number
NA	Network Access
NAS	Network Access Server
NAT	Network Address Translation
PAT	Port Address Translation
PDN	Public Data Network
PDP	Packet Data Protocol
PDU	Protocol Data Unit
PLMN	Public Land Mobile Network
PPP	Point-to-point protocol
PS	Packet Switched
PSTN	Public Switched Telephone Network
PUK	Personal Unblocking Key
RAI	Routing Area Identifier
RAT	Radio Access Technology
RD	Retained Data
RDHI	Retained Data Handover Interface
SAI	Service Area Identifier
SC	SMS Centre
SDP	Session Description Protocol
SGSN	Serving GPRS Support Node
SHA	Secure Hash Algorithm
SIM	Subscriber Identity Module
SIP	Session Initiation Protocol
SMS	Short Message Service
SMTP	Simple Mail Transfer Protocol
TAI	Tracking Area Identity
TCP	Transmission Control Protocol
TL	Latency Time
TLS	Transport Layer Security
TR	Time of the Request
TV	Television
UE	User Equipment
UMTS	Universal Mobile Telecommunication System
URI	Uniform Resource Identifier
UTF	Unicode Transformation Format
UTM	Universal Transverse Mercator
UTRAN	UMTS Terrestrial Radio Access Network
WGS	World Geodetic System
XML	eXtensible Markup Language

---

## 4 Overview of handover interface

### 4.1 Reference model

The generic Handover Interface adopts a two-port structure such that administrative request/response information (HI-A) and Retained Data Information (HI-B) are logically separated.

Figure 1 is the reference model for the request and transmission of retained telecommunications data.