
**Cryogenic vessels — Static vacuum-
insulated vessels —**

**Part 1:
Design, fabrication, inspection and tests**

Réceptacles cryogéniques — Réceptacles isolés sous vide statiques —

*Partie 1: Exigences de conception de fabrication, d'inspection, et
d'essais*

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sis/21009-1-2008>
255d-4bdc-94b7-52aba7bd610f/iso-21009-1-2008



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/046e42c7-255d-4bdc-94b7-52aba7bd610f/iso-21009-1-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols	5
5 General requirements.....	7
6 Mechanical loads	7
6.1 General.....	7
6.2 Load during the pressure test.....	7
7 Chemical effects	8
8 Thermal conditions.....	8
9 Material	8
9.1 Selection of materials.....	8
9.2 Inspection certificate.....	9
9.3 Materials for outer jackets and service equipment.....	9
10 Design	9
10.1 Design options	9
10.2 Common design requirements.....	9
10.3 Design by calculation.....	16
11 Fabrication.....	43
11.1 General.....	43
11.2 Cutting	43
11.3 Cold forming.....	47
11.4 Hot forming.....	49
11.5 Manufacturing tolerances.....	50
11.6 Welding.....	53
11.7 Non-welded permanent joints	54
12 Inspection and testing.....	54
12.1 Quality plan	54
12.2 Production control test plates.....	56
12.3 Non-destructive testing.....	57
12.4 Rectification	60
12.5 Pressure testing.....	60
13 Marking and labelling	61
14 Final assessment.....	62
15 Periodic inspection.....	62
Annex A (normative) Elastic stress analysis	63
Annex B (normative) Additional requirements for 9 % Ni steel	72
Annex C (normative) Pressure strengthening of vessels from austenitic stainless steels	74
Annex D (informative) Pressure limiting systems	85
Annex E (normative) Further use of the material cold properties to resist pressure loads.....	86
Annex F (informative) Specific weld details	90

Annex G (normative) **Additional requirements for flammable fluids** 94

Annex H (informative) **Relief devices**..... 95

Annex I (normative) **Outer jacket relief devices** 96

Annex J (informative) **Increased material property for austenitic stainless steel** 97

Annex K (normative) **Base materials** 98

Annex L (normative) **Cylindrical shells subject to external pressure (pressure on the convex surface) — Calculation** 107

Annex M (normative) **Design of openings in cylinders, spheres and cones — Calculation** 112

Annex N (normative) **Design of ends for internal pressure** 122

Bibliography 124

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/046e42c7-255d-4bdc-94b7-52aba7bd610f/iso-21009-1-2008>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 21009-1 was prepared by Technical Committee ISO/TC 220, *Cryogenic vessels*.

ISO 21009 consists of the following parts, under the general title *Cryogenic vessels — Static vacuum-insulated vessels*:

- *Part 1: Design, fabrication, inspection and tests*
- *Part 2: Operational requirements*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/046e42c7-255d-4bdc-94b7-52aba7bd610f/iso-21009-1-2008>

Cryogenic vessels — Static vacuum-insulated vessels —

Part 1: Design, fabrication, inspection and tests

1 Scope

This part of ISO 21009 specifies requirements for the design, fabrication, inspection and testing of static vacuum-insulated cryogenic vessels designed for a maximum allowable pressure of more than 0,5 bar.

This part of ISO 21009 applies to static vacuum-insulated cryogenic vessels for fluids as specified in 3.4 and does not apply to vessels designed for toxic fluids.

For static vacuum-insulated cryogenic vessels designed for a maximum allowable pressure of not more than 0,5 bar this International Standard may be used as a guide.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4126-2, *Safety devices for protection against excessive pressure — Part 2: Bursting disc safety devices*

ISO 4136, *Destructive tests on welds in metallic materials — Transverse tensile test*

ISO 9016, *Destructive tests on welds in metallic materials — Impact tests — Test specimen location, notch orientation and examination*

ISO 9606-1, *Approval testing of welders — Fusion welding — Part 1: Steels*

ISO 9606-2, *Qualification test of welders — Fusion welding — Part 2: Aluminium and aluminium alloys*

ISO 9712, *Non-destructive testing — Qualification and certification of personnel*

ISO 10474, *Steel and steel products — Inspection documents*

ISO 14732, *Welding personnel — Approval testing of welding operators for fusion welding and of resistance weld setters for fully mechanized and automatic welding of metallic materials*

ISO 15607, *Specification and qualification of welding procedures for metallic materials — General rules*

ISO 15613, *Specification and qualification of welding procedures for metallic materials — Qualification based on pre-production welding test*

ISO 15614-1, *Specification and qualification of welding procedures for metallic materials — Welding procedures test — Part 1: Arc and gas welding of steels and arc welding of nickel and nickel alloys*

ISO 21009-1:2008(E)

ISO 15614-2, *Specification and qualification of welding procedures for metallic materials — Welding procedure test — Part 2: Arc welding of aluminium and its alloys*

ISO 17636, *Non-destructive testing of welds — Radiographic testing of fusion-welded joints*

ISO 21010, *Cryogenic vessels — Gas/materials compatibility*

ISO 21013-3, *Cryogenic vessels — Pressure-relief accessories for cryogenic service — Part 3: Sizing and capacity determination*

ISO 21028-1 *Cryogenic vessels — Toughness requirements for materials at cryogenic temperature — Part 1: Temperatures below -80 °C*

ISO 21028-2 *Cryogenic vessels — Toughness requirements for materials at cryogenic temperature — Part 2: Temperatures between -80 °C and -20 °C*

ISO 23208, *Cryogenic vessels — Cleanliness for cryogenic service*

ISO 21009-2, *Cryogenic vessels — Static vacuum insulated vessels — Part 2: Operational requirements*

ISO 21011, *Cryogenic vessels — Valves for cryogenic service*

EN 10028-7, *Flat products made of steels for pressure purposes — Part 7: Stainless steels*

EN 13068-3, *Non-destructive testing — Radioscopic testing — Part 3: General principles of radioscopic testing of metallic materials by X- and gamma rays*

ASME Boiler and Pressure Vessel Code, *Section V: Nondestructive Examination*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

accessories

service equipment which has a safety related function with respect to pressure containment and/or control

EXAMPLE Accessories include protective or limiting devices, controlling and monitoring devices, valves and indicators.

3.2

automatic welding

welding in which the parameters are automatically controlled

NOTE Some of these parameters may be adjusted to a limited extent, either manually or automatically, during welding to maintain the specified welding conditions.

3.3

bursting disc device

non-reclosing pressure relief device ruptured by differential pressure

NOTE The bursting disc device is the complete assembly of installed components including, where appropriate, the bursting disc holder.

3.4

**cryogenic fluid
refrigerated liquefied gas**

gas which is partially liquid because of its low temperature

NOTE This includes totally evaporated liquids and supercritical fluids.

EXAMPLE In ISO 21009, the (refrigerated, but) non-toxic gases, and mixtures of them, shown in Table 1, are referred to as cryogenic fluids.

Table 1 — Refrigerated but non toxic gases

classification code	Identification number, name and description
3° A	<p>Asphyxiant gases</p> <p>1913 Neon, refrigerated liquid</p> <p>1951 Argon, refrigerated liquid</p> <p>1963 Helium, refrigerated liquid</p> <p>1970 Krypton, refrigerated liquid</p> <p>1977 Nitrogen, refrigerated liquid</p> <p>2187 Carbon dioxide, refrigerated liquid</p> <p>2591 Xenon, refrigerated liquid</p> <p>3136 Trifluoromethane, refrigerated liquid</p> <p>3158 Gas, refrigerated liquid, not otherwise specified (NOS)</p>
3° O	<p>Oxidizing gases</p> <p>1003 Air, refrigerated liquid</p> <p>1073 Oxygen, refrigerated liquid</p> <p>2201 Nitrous oxide, refrigerated liquid, oxidizing</p> <p>3311 Gas, refrigerated liquid, oxidizing, NOS</p>
3° F	<p>Flammable gases</p> <p>1038 Ethylene, refrigerated liquid</p> <p>1961 Ethane, refrigerated liquid</p> <p>1966 Hydrogen, refrigerated liquid</p> <p>1972 Methane, refrigerated liquid or natural gas, refrigerated liquid, with high methane content</p> <p>3138 Ethylene, acetylene and propylene mixture, refrigerated liquid, containing at least 71,5 % ethylene with not more than 22,5 % acetylene and not more than 6 % propylene</p> <p>3312 Gas, refrigerated liquid, flammable, NOS</p>
<p>The flammable gases and mixtures of them may be mixed with: helium, neon, nitrogen, argon, carbon dioxide.</p> <p>Oxidizing and flammable gases may not be mixed.</p> <p>NOTE The classification code, identification number, name and description are according to UN codes.</p>	

**3.5
documentation**

technical documents delivered by the manufacturer to the owner consisting of:

- all certificates establishing the conformity with this part of ISO 21009 (e.g. material, pressure test, cleanliness, safety devices);
- a short description of the vessel (including characteristic data, etc.);
- a list of fluids and their net mass for which the cryogenic vessel is designed;
- an operating manual (for the user) that contains
 - a short description of the vessel (including characteristic data, etc.),
 - a statement that the vessel is in conformity with this part of ISO 21009, and
 - the instructions for normal operation.

**3.6
gross volume of the inner vessel**

internal volume of the inner vessel, excluding nozzles, pipes etc. determined at minimum design temperature and atmospheric pressure

**3.7
handling loads**

loads exerted on the static cryogenic vessel in all normal transport operations including loading, unloading, pressure loading during transportation, installation, etc.

**3.8
inner vessel**

pressure vessel intended to contain the **cryogenic fluid** to be stored

**3.9
manufacturer of the static cryogenic vessel**

company that carries out the final assembly, including the final acceptance test, of the static cryogenic vessel

**3.10
maximum allowable pressure**

maximum pressure permissible at the top of the vessel in its normal operating position

**3.11
net volume of the inner vessel**

volume of the inner vessel, below the inlet to the relief devices, excluding nozzles, pipes etc., determined at minimum design temperature and atmospheric pressure

**3.12
normal operation**

intended operation of the vessel either up to the **maximum allowable pressure** or subjected to **handling loads**

**3.13
outer jacket**

gas-tight enclosure which contains the **inner vessel** and enables the vacuum to be established

**3.14
piping system**

tubes, pipes and associated components which can come in contact with **cryogenic fluids** including valves, fittings, pressure relief devices, and their supports

3.15**pressure****gauge pressure**

pressure relative to atmospheric pressure

3.16**relief plate**

plate retained by atmospheric pressure which allows relief of excess internal pressure, generally from the vacuum jacket

3.17**relief plug**

plug retained by atmospheric pressure which allows relief of excess internal pressure, generally from the vacuum jacket

3.18**service equipment**

measuring instruments, filling, discharge, venting, safety, pressurizing, cooling and thermal insulation devices

3.19**static cryogenic vessels**

thermally insulated vessel intended for use with one or more **cryogenic fluids** in a stationary condition

NOTE Static cryogenic vessels consist of inner vessel(s), an outer jacket and the piping system.

3.20**thermal insulation**

vacuum inter-space between the inner vessel and the outer jacket

NOTE The space may or may not be filled with material to reduce the heat transfer between the inner vessel and the outer jacket.

3.21**year built**

date of the final acceptance test of the final assembled cryogenic vessel at the manufacturer

4 Symbols

For the purposes of this document, the following symbols apply:

c	allowances for corrosion	mm
d_i	diameter of opening	mm
d_a	outside diameter of tube or nozzle	mm
f	narrow side of rectangular or elliptical plate	mm
l_b	buckling length	mm
n	number	—
p	design pressure as defined by 10.2.3.2.1 and 10.3.3.2	bar
p_e	allowable external pressure limited by elastic buckling	bar
p_k	strengthening pressure	bar

ISO 21009-1:2008(E)

p_p	allowable external pressure limited by plastic deformation	bar
p_s	maximum allowable gauge pressure	bar
p_T	test pressure [see 10.2.3.2.3]	bar
r	radius e.g. inside knuckle radius of dished end and cones	mm
s	minimum wall thickness	mm
s_e	actual wall thickness	mm
v	factor indicative of the utilisation of the permissible design stress in joints or factor allowing for weakenings	—
x	(decay-length zone) distance over which governing stress is assumed to act	mm
A	cross sectional area of reinforcing element	mm ²
A_s	elongation at fracture	%
C_β	design factors	—
D	shell diameter	mm
D_a	outside diameter e.g. of a cylindrical shell	mm
D_i	internal diameter e.g. of a cylindrical shell	mm
E	Young's modulus	N/mm ²
H	Safety coefficient for pressure test	—
I	moment of inertia of reinforcing element	mm ⁴
K	material property used for design (see 10.3.2.3.1)	N/mm ²
K_t	material property at t °C used for design (e.g. K_{20} for material property at 20 °C) (see 10.3.2.3.2)	N/mm ²
R	radius of curvature e.g. inside crown radius of dished end	mm
S	safety factor at design pressure	—
S_k	safety factor against elastic buckling at design pressure	—
S_p	safety factor against plastic deformation at design pressure	—
S_T	safety factor against plastic deformation at proof test pressure	—
Z	auxiliary value	—
ν	Poisson ratio	—
u	out-of-roundness	—
σ_k	design stress value	N/mm ²

5 General requirements

5.1 The static cryogenic vessel shall safely withstand the mechanical and thermal loads and the chemical effects encountered during pressure test and normal operation. These requirements are deemed to be satisfied if Clauses 6 to 11 are fulfilled. The vessel shall be tested in accordance with Clause 12, marked in accordance with Clause 13, and operated in accordance with ISO 21009-2.

5.2 Static cryogenic vessels shall be equipped with valves, pressure relief devices, etc. configured and installed in such a way that the vessel can be operated safely. The number of openings in the inner vessel for this equipment shall be kept to a minimum.

5.3 The static cryogenic vessel shall be clean for the intended service in accordance with ISO 23208.

5.4 The manufacturer shall retain the documents referred to in 3.5, and all supporting documentation (including that from his subcontractors if any), for a period required by regulation(s) (e.g. product liability). In addition the manufacturer shall retain all supporting and background documentation (including that from his subcontractors if any) which establishes that the vessel conforms to this part of ISO 21009.

6 Mechanical loads

6.1 General

The static cryogenic vessel shall resist the mechanical loads mentioned in Clause 6 without such deformation which could affect safety and which could lead to leakage.

The mechanical loads to be considered are:

- loads exerted during the pressure test as specified in 6.2;
- loads imposed during installation and removal of the vessel;
- dynamic loads during transport of the vessel.

The following loads shall be considered to act in combination where relevant:

- a pressure equal to the maximum allowable pressure in the inner vessel and pipework;
- the pressure exerted by the liquid when filled to capacity;
- loads produced by the thermal movement of the inner vessel, outer jacket and inter-space piping;
- full vacuum in the outer jacket;
- a pressure in the outer jacket equal to the set pressure of the relief device protecting the outer jacket;
- wind loads and other site conditions (e.g. seismic loads, thermal loads) to the vessel when filled to capacity.

6.2 Load during the pressure test

The load exerted during the pressure test used for calculation shall be:

$$p_T \geq H(p_s + 1)$$

where