
**Petroleum and natural gas industries —
Downhole equipment — Sand screens**

*Industries du pétrole et du gaz naturel — Equipement de fond de
puits — Tamis de contrôle de sable*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 17824:2009](https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009)

<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 17824:2009](https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009)

<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Abbreviated terms	6
5 Functional specification	6
5.1 General	6
5.2 Product type	7
5.3 Sand screen parameters	7
5.4 Well parameters	7
5.5 Operational parameters	7
5.6 Environmental compatibility	8
5.7 Compatibility with related well equipment	8
5.8 Design validation grades	8
5.9 Quality grades	8
5.10 Special quality requirements	8
6 Technical specification	9
6.1 General	9
6.2 Technical characteristics	9
6.3 Design criteria	9
6.4 Design verification	9
6.5 Design validation	10
6.6 Design changes	10
6.7 Design validation by scaling	11
7 Supplier/manufacturer requirements	13
7.1 General	13
7.2 Documentation and data control	13
7.3 Product identification	14
7.4 Quality control	14
8 Storage and transport	23
8.1 Storage	23
8.2 Product protection	23
8.3 Transport	23
Annex A (normative) Collapse pressure test	24
Annex B (normative) Burst pressure test	27
Annex C (informative) Sized-bead test method	30
Annex D (informative) Sand control screen illustrations	32
Annex E (informative) Wire-wrap screen illustrations	34
Annex F (informative) Pre-pack screen illustrations	35
Annex G (informative) Metal-mesh screen illustrations	36
Annex H (informative) Increased wire-wrap slot size inspection	37
Bibliography	38

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17824 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 4, *Drilling and production equipment*.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 17824:2009](https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009)

<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>

Introduction

This International Standard has been developed by user/purchasers and supplier/manufacturers of sand control screens intended for use in petroleum and natural gas wells. This International Standard provides requirements and information to both parties regarding the manufacture, mechanical properties and testing of sand control screens. Further, this International Standard addresses supplier/manufacturer requirements that set the minimum parameters with which it is necessary that supplier/manufacturers comply to claim conformity with this International Standard.

This International Standard is structured with grades of increased requirements for both design validation and quality control. Three design validation grades (V1, V2 and V3) and three quality grades (Q1, Q2 and Q3) provide the user/purchaser the choice of requirements to meet a specific preference or application. Design validation grade V3 and quality grade Q3 represent equipment designed and manufactured consistent with minimum industry practice.

Included within this International Standard are normative annexes A and B specifying test methods for determining the collapse and burst strength of sand control screens. Informative annexes C, D, E, F, G and H include measurement criteria for sand control screen filter media, illustrations of the three types of sand control screens, and increased wire-wrap slot size inspection requirements.

It is necessary that users of this International Standard be aware that requirements above those outlined in this International Standard can be needed for individual applications. This International Standard is not intended to inhibit a supplier/manufacturer from offering, or the user/purchaser from accepting, alternative equipment or engineering solutions. This can be particularly applicable where there is innovative or developing technology. Where an alternative is offered, it is the responsibility of the supplier/manufacturer to identify any variations from this International Standard and provide details.

<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 17824:2009

<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>

Petroleum and natural gas industries — Downhole equipment — Sand screens

1 Scope

This International Standard provides the requirements and guidelines for sand control screens for use in the petroleum and natural gas industries. Included are the requirements for design, design validation, functional evaluation, manufacturing, storage and transport. The requirements of this International Standard are applicable to wire-wrap screens, pre-pack screens and metal-mesh screens as defined herein.

The following items are outside the scope of this International Standard:

- expandable sand screens, slotted liners or tubing and accessory items such as centralizers or bull plugs;
- shunt screen technology, inflow control devices, downhole sensors and selective isolation devices, even where they can be an integral part of the sand control screen;
- screen filtration performance criteria, including test methods or analysis for sand retention efficiency;
- end connections of the basepipe.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 17824:2009](https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009)

<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>

2 Normative references

The following referenced documents are indispensable for the application of this document. The way in which these referenced documents are cited determines the extent (in whole or part) to which they apply. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10414-1:2008, *Petroleum and natural gas industries — Field testing of drilling fluids — Part 1: Water-based fluids*

ISO 11960, *Petroleum and natural gas industries — Steel pipes for use as casing or tubing for wells*

NOTE ISO 11960 has been back adopted by API as API SPEC 5CT. Therefore, for the purposes of the provisions of this International Standard which cite ISO 11960, API SPEC 5CT is equivalent to ISO 11960.

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

ISO 9000, *Quality management systems — Fundamentals and vocabulary*

ASME, *Boiler and Pressure Vessel Code BPVC — Section II: Materials: Part D: Properties*

ASME, *Boiler and Pressure Vessel Code BPVC — Section VIII: 1998, Div. 1, Appendix 8: Methods for Liquid Penetrant Examination (PT)*

ASME, *Boiler and Pressure Vessel Code BPVC — Section IX: Welding and Brazing Qualifications*

ASTM E11, *Standard Specification for Wire Cloth and Sieves for Testing Purposes*

ASTM E165, *Standard Test Method for Liquid Penetrant Examination*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 9000 and the following apply.

**3.1
annular gravel pack**
sized sand or synthetic proppant placed in the annulus outside the sand control screen during gravel packing

**3.2
basepipe**
tubulars that have perforations or slots to allow fluid flow through the screen jacket

NOTE See Figures E.1, F.1 and G.1.

**3.3
box handling length**
axial length of blank basepipe on a sand control screen, measured between the end of the box connection and the nearest component along the basepipe

NOTE See Figures D.4 and D.5.

**3.4
center break**
axial length of blank pipe between two screen jackets on a sand control screen

NOTE See Figure D.5.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

**3.5
component**
individual part of an assembly

[ISO 17824:2009](https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009)

**3.6
design family**
group of sand control screens wherein the configuration, materials, and functionality are the same and the design stress levels in relation to material mechanical properties are based on the same criteria

<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>

**3.7
design validation**
process of proving a design by testing to demonstrate conformity of the product to design requirements

[ISO/TS 29001]

**3.8
design verification**
process of examining the result of a given design or development activity to determine conformity with specified requirements

[ISO/TS 29001]

**3.9
direct-wrap screen**
sand screen in which the screen jacket rib wires are in direct contact with the base pipe along the axial length

NOTE See Annexes E and F.

**3.10
direct-wrap pre-pack screen**
pre-pack screen in which the inner screen, which may be wire-wrap or metal-mesh, is a direct-wrap screen

NOTE See Annex F.

3.11**downhole sensor**

device incorporated into the sand control screen to measure various downhole conditions

3.12**drainage or support layer**

component used in metal-mesh screens to provide structural support and/or to facilitate flow between the basepipe perforations and metal mesh

NOTE See Figure G.1.

3.13**drift OD**

minimum ID of the drift tool utilized to verify screen assembly OD clearance

3.14**end ring**

component used to seal the annular gap between the ends of the screen jacket and basepipe

3.15**filter media OD**

⟨metal-mesh screens⟩ metal-mesh OD

⟨wire-wrap screens⟩ wrap-wire OD

⟨pre-pack screens⟩ outermost wrap-wire OD

NOTE See Figures D.1, D.2 and D.3.

3.16**fluid-loss control pill**

fluid with a concentration of a wide array of sized particles that forms a filter cake that seals off a screen surface with little or no leak-off through the screen's slot openings or pores

3.17**gravel packing**

well completion method used for the purpose of excluding formation sand from entering the well bore and including a sand control screen, sized sand or synthetic proppant

3.18**inflow control device**

device incorporated into a sand control screen that regulates the flow into or along the basepipe

3.19**informative**

information that is meant to enlighten the user/purchaser or supplier/manufacturer, without containing requirements

3.20**job-lot traceable**

ability for parts to be identified as originating from a job lot which identifies the included heat(s)

3.21**joint overall length**

maximum axial length of the screen measured from the outer end of the box connection to the end of the pin thread on the basepipe

NOTE See Figures D.4 and D.5.

3.22

metal-mesh

metal fabric designed to filter solids, provide structural support and/or distribute flow

NOTE See Figure G.1.

3.23

metal-mesh roll

single, continuous spooling of mesh by the woven mesh manufacturer

3.24

metal-mesh screen

sand control screen that consists of one or more layers of metal-mesh as the filter media

NOTE See Annex G.

3.25

normative

instructions or procedures that shall be implemented by the user/purchaser or supplier/manufacturer in order to comply with this International Standard

3.26

pin handling length

axial length of blank basepipe on a sand screen assembly, measured between the last scratch of the pin thread and the nearest component along the OD of basepipe

NOTE See Figures D.4 and D.5.

3.27

pore size

supplier/manufacturer determined metal-mesh filter opening, typically expressed in microns

NOTE See Figure G.1.

ITeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 17824:2009
<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>

3.28

pre-pack screen

sand control screen consisting of two concentric screen jackets with the annulus in between containing a sized distribution of sand or synthetic proppant used as the filter media

NOTE See Annex F.

3.29

qualified person

individual with demonstrated skills or abilities gained through training or experience or both as measured against established requirements, such as standards or tests that enable the individual to perform a required function

3.30

sand control screen

mechanical filtration device used to retain the formation sand or annular gravel pack while allowing the passage of fluids into the production tubing

3.31

screen jacket

sub-assembly of the sand control screen that includes filter media and associated support components and which is secured to the basepipe

NOTE The screen jacket may include end rings, a drainage or support layer and/or a shroud.

3.32**screen jacket length**

axial length of the screen jacket, including any end rings

NOTE See Figures D.4 and D.5.

3.33**screen size**

OD designation of the basepipe

3.34**selective isolation device**

device that controls flow into the production string from selected zone(s) in a well

3.35**shroud**

perforated cylindrical component typically forming the outermost concentric layer of a screen and used to provide support and protection

NOTE See Figure G.1.

3.36**shunt screen technology**

additional flow conduits assembled onto the sand control screen to allow the gravel packing slurry to bypass blockages in the annulus between the well bore and the screen OD during gravel packing operations

3.37**slip-on screen**

sand screen where the screen jacket is manufactured separately and later installed over the perforated basepipe

NOTE See Annexes D and E.

3.38**slot**

opening between two consecutive wrap-wires in a wire-wrap screen

NOTE See Figures E.1 and F.1.

3.39**slot size**

width of the opening in a wire-wrap screen expressed in gage, with one gage equal to 25,4 μm (0,001 in)

3.40**support rib**

several parallel, longitudinal supports in a wire-wrap screen jacket that are spaced apart to form the structure around which the wrap-wire is wrapped and welded

NOTE See Figures E.1 and F.1.

3.41**wire-wrap screen**

sand control screen consisting of a wrap-wire helically wrapped and welded to a cylindrical array of internal support ribs positioned in the axial or long direction of the cylinder and used as the filter media

NOTE See Annex E.

3.42

wrap-wire

continuous wire in a wire-wrap screen jacket that is helically wrapped around and welded to longitudinal support ribs

NOTE See Figures E.1 and F.1.

3.43

wrap-wire reel

single continuous spooling of a formed wire

4 Abbreviated terms

- CB centre break
- COC certificate of compliance
- FEA finite element analysis
- FLC fluid loss control
- ga gage
- ID inside diameter
- LB box handling length
- LDP liquid dye penetrant
- LP pin handling length
- LS screen jacket length
- MTR material test report
- NDE non-destructive examination
- OD outside diameter
- ppf pounds per foot
- PSD particle size distribution
- QC quality control

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 17824:2009](https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009)

<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>

5 Functional specification

5.1 General

The user/purchaser shall provide a functional specification to order products that conform to this International Standard. The specification shall include the following requirements and operating conditions as the user/purchaser deems appropriate, and/or may identify the supplier/manufacturer's specific product. These requirements and operating conditions may be conveyed by means of a dimensional drawing, data sheet, or other suitable documentation.

5.2 Product type

The user/purchaser shall specify the sand control screen type (wire-wrap screen, pre-pack screen or metal-mesh screen) as defined by the filter media. It is recognized that there are screens that utilize one or more of these screen types in their construction; however, the product type is defined by the primary filter media.

5.3 Sand screen parameters

The user/purchaser shall specify the following sand screen parameters, as applicable:

- a) screen jacket length(s) and pin and box handling lengths;
- b) required slot size or pore size for sand retention of the annular gravel pack and/or formation sand;
- c) flow area of the screen for passage of fluids during well clean up, production and any stimulation activities;
- d) nominal basepipe size, mass, grade, alloy and end connections;
- e) drift OD;
- f) metallurgy requirements of screen jacket, rings, shrouds or other components;
- g) filter media type and size;
- h) centralization: type, quantity, material, maximum OD and location;
- i) joint length: R1, R2, R3 in accordance with ISO 11960, or other length as required;
- j) required collapse, burst and tensile ratings.

iTech STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/a3ec86e0-5b90-4a1b-983d-64f6bdfd85e7/iso-17824-2009>

5.4 Well parameters

The user/purchaser shall specify, as applicable, the following well parameters:

- a) drift ID of the casing or open hole ID, and any minimum restrictions through which it is necessary for the sand control screen to pass;
- b) IDs and ODs of tubing or casing sizes, the well's true vertical depth (TVD) and measured depth (MD), and a directional survey of the well, typically shown in a schematic;
- c) producing or perforation interval length.

5.5 Operational parameters

The user/purchaser shall specify, as applicable, the following operational parameters:

- a) chemical treatment, including the chemical components, pressure, temperature, pump rate and exposure time;
- b) fracturing/gravel packing, including proppant/gravel description, pumping rate, annular fluid velocity, proppant/fluid ratio, maximum anticipated pressure;
- c) fluid/mud type (chemical components, solids loading, solids size) and density that the screens can encounter;
- d) well intervention service equipment, such as wash tools, electric line, slick line, braided line, coiled tubing or snubbing equipment;