

First edition  
2008-12-01

Corrected version  
2009-03-15

---

---

**Non-destructive testing — Penetrant  
testing —**

Part 6:

**Penetrant testing at temperatures lower  
than 10 °C**

**iTeh STANDARD PREVIEW**  
*Essais non destructifs — Examen par ressuage —*  
*(standards.iteh.ai)* *Partie 6: Examen par ressuage à des températures inférieures à 10 °C*

[ISO 3452-6:2008](https://standards.iteh.ai/catalog/standards/sist/f9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008)

<https://standards.iteh.ai/catalog/standards/sist/f9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008>



Reference number  
ISO 3452-6:2008(E)

© ISO 2008

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 3452-6:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/f9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3452-6 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 138, *Non-destructive testing*, in collaboration with ISO Technical Committee TC 135, *Non-destructive testing*, Subcommittee SC 2, *Surface methods*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

ISO 3452 consists of the following parts, under the general title *Non-destructive testing — Penetrant testing*:

- *Part 1: General principles* [ISO 3452-6:2008](https://standards.iteh.ai/catalog/standards/sist/9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008)
- *Part 2: Testing of penetrant materials*
- *Part 3: Reference test blocks*
- *Part 4: Equipment*
- *Part 5: Penetrant testing at temperatures higher than 50 °C*
- *Part 6: Penetrant testing at temperatures lower than 10 °C*

This corrected version incorporates the following corrections:

- in the Introduction, reference to EN 571-1 has been replaced with reference to ISO 3452-1;
- the normative reference ISO 3452-1 carries a footnote stating its equivalency to EN 571-1;
- in 3.2, list item d), the phrase “this standard temperature range” has been replaced with “the working temperature range”;
- in 3.4, the second sentence of the first paragraph, the phrase “materials testing” has been replaced with “testing materials”;
- 4.1, list items c) and d), are made requirements, and the last sentence of item d) reworded for greater clarity;
- in 4.2.3, the four occurrences of the word “cloth” have been replaced with “cloths”;

- in the second paragraph of 5.1, the requirement that the degreaser be water soluble has been replaced by the statement “the degreaser has to be soluble in water”;
- minor editorial corrections are made in 4.2.2 and 5.4.2.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 3452-6:2008](https://standards.iteh.ai/catalog/standards/sist/f9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008)

<https://standards.iteh.ai/catalog/standards/sist/f9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008>

## Introduction

Temperatures lower than 10 °C can affect the properties of penetrant test materials. The use of penetrant materials and the testing of penetrant materials within the temperature range 10 °C to 50 °C are the subject of ISO 3452-1 and ISO 3452-2. This part of ISO 3452 addresses materials and their use at lower temperatures than 10 °C.

This part of ISO 3452 introduces the concept of process times being linked to working temperatures and accordingly users are recommended to ensure that testing products are correctly associated with process parameters in written instructions (procedures).

Testing products may be specifically developed and qualified for low temperature use but testing products qualified for use at normal temperatures, in some cases, may also be suitable for lower temperature use.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 3452-6:2008](https://standards.iteh.ai/catalog/standards/sist/f9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008)

<https://standards.iteh.ai/catalog/standards/sist/f9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 3452-6:2008

<https://standards.iteh.ai/catalog/standards/sist/f9335b46-9e65-47e7-915b-0d3132b2049e/iso-3452-6-2008>

# Non-destructive testing — Penetrant testing —

## Part 6:

# Penetrant testing at temperatures lower than 10 °C

## 1 Scope

This part of ISO 3452 specifies the testing requirements particular to applications at low temperatures (lower than + 10 °C) as well as the method for qualification of suitable testing products. It applies only to materials qualified for the relevant temperature range used in accordance with the manufacturer's instructions.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3059, *Non-destructive testing — Penetrant testing and magnetic particle testing — Viewing conditions*

ISO 3452-1, *Non destructive testing — Penetrant testing — Part 1: General principles*<sup>1)</sup>

ISO 3452-2, *Non-destructive testing — Penetrant testing — Part 2: Testing of penetrant materials*

ISO 3452-3, *Non-destructive testing — Penetrant testing — Part 3: Reference test blocks*

## 3 Low temperature penetrant testing

### 3.1 General principles

The general principles of ISO 3452-1 shall apply unless otherwise stated in this part of ISO 3452 or in the manufacturer's instructions.

Qualification tests are carried out by the manufacturer and if products are used within the stated range, no further tests are needed on site.

### 3.2 Technical principles

Depending on the temperature range, some specific problems might be encountered:

- a) moisture, or even ice, on the test object;
- b) lower evaporation rate of solvents and of non-aqueous wet developers than at higher temperatures;

---

1) ISO 3452-1 is equivalent to EN 571-1.

- c) when spray cans are used, pressure and spray quality may be affected;
- d) some penetrants may precipitate. In such a case, tests shall be carried out within the standard temperature range (10 °C to 50 °C) if the penetrants are to be used in the working temperature range.

### 3.3 Safety precautions

All relevant European, national and local regulations pertaining to health and safety, environmental requirements etc. shall be observed.

Depending on the temperature range, some specific rules shall be enforced:

- a) when heaters are used (either to warm up the test object, materials or the work environment), precautions shall be taken not to have vapours or spray of materials in contact with flames or hot surfaces;
- b) users shall wear clothes and gloves able to protect them from contact with very low temperature parts. Gloves used shall allow for applying materials without impairing the test;
- c) in very low temperature environment, some pieces of equipment (pens, cameras, etc.) may not properly work. Action shall be taken, either to keep them at an acceptable temperature until use (for instance by keeping them under clothing, close to the user's body) or by using equipment capable of functioning in such an environment.

### 3.4 Reference blocks/test panels

Care shall be taken while using reference block/test panels. It could be tempting to put these panels in a freezer, and to take them out when they have reached the targeted temperature for testing materials. Doing so places cold parts in contact with a warmer atmosphere, causing moisture to condense on these parts and the temperature to rise very quickly.

ISO 3452-6:2008

Therefore, tests shall be carried out in "real conditions": parts, users and testing materials are either outside or in a "climatic room" in which the temperature and humidity is capable of duplicating real conditions.

### 3.5 Viscosity and penetrant testing

If it is the case that the lower the temperature, the higher the liquid or gas viscosity, then note that higher viscosity is not a drawback to penetrant testing.

Capillary effect is far more powerful than the effect of the viscosity – very viscous, even jellified penetrants, can lead to very good crack detection.

### 3.6 Personnel qualification

Personnel carrying out testing in accordance with this part of ISO 3452 shall be suitably certified (see e.g. ISO 9712, EN 473). They shall also be knowledgeable of the special considerations for testing at lower temperatures (e.g. time limitations for inspection, special considerations of materials).

## 4 Low temperature penetrant testing process

### 4.1 General rules

The following rules apply:

- a) surface and discontinuities shall be free of any contaminant, even those stemming from the surface preparation;
- b) penetrant is applied on the part as per the most convenient means;



- c) when dwell time has elapsed, excess of penetrant shall be wiped from the surface with clean, lint-free rags or cloths and a penetrant remover in accordance with the manufacturer's recommendation (water should be avoided due to low temperatures);
- d) low temperature penetrant testing generally is not carried out in installations. A non-aqueous wet (solvent-based) developer shall be sprayed on the test object. In low temperature conditions, solvents evaporate far slower than usual. Therefore, care shall be taken that the solvent evaporation time be sufficient to achieve accurate indications;
- e) viewing conditions shall comply with the requirements of ISO 3059.

## 4.2 Special requirements

### 4.2.1 Surface preparation

Within the +10 °C to –5 °C range, the main trouble comes from water, either as liquid (moisture), frost or even ice.

Water is detrimental to the process. To get rid of it:

- a) gently warm the surface for several minutes to make water evaporate from discontinuities;  
and/or
- b) use a volatile, water soluble solvent, such as acetone or isopropyl alcohol (generally degreasers used before penetrant applications are hydrocarbon-based and do not in any way remove water);
- c) allow some minutes for evaporation, ensuring evaporation does not cool down the surface of the part enough to have water condensing on it again.

When the temperature is lower than –5 °C, check that there is no frost or ice. Any frost or ice shall be removed.

### 4.2.2 Penetrant application/dwell time

Penetrant may be sprayed from a spray can, provided pressure is sufficient. Any other convenient means of application may be used.

It is recommended to let the penetrant act twice as long as for the 10 °C to 50 °C range, as water is generally not completely removed from the discontinuities and can make it more difficult for the penetrant to enter.

### 4.2.3 Excess penetrant removal

Even if a water washable penetrant has been applied, the use of lint free cloths or wipes and a volatile penetrant remover according to the manufacturer's recommendation is a better choice than water.

First wipe as much penetrant as possible with clean lint free cloths or wipes.

Then use lint free cloths or wipes lightly moistened with the solvent to remove the remaining penetrant.

As a final step, use dry lint free cloths or wipes to take out the traces of penetrant/solvent.

Allow some minutes for solvent evaporation.

### 4.2.4 Developer application

Non-aqueous wet (solvent-based) developer is most suitable.

As it shall be sprayed, the most convenient means is a spray can.

The spray can shall be kept at 10 °C minimum to ensure an effective spray giving a thin, even layer.