ETSI TS 122 519 V12.0.0 (2014-10)



Universal Mobile Telecommunications System (UMTS);

Business Communication Requirements (3GPP TS 22.519 version 12.0.0 Release 12)



 Reference

 DTS/TSGS-0122519vc00

 Keywords

 LTE, UMTS

 ETSI

 650 Route des Lucioles

 F-06921 Sophia Antipolis Cedex - FRANCE

 Tel.: +33 4 92 94 42 00

 Fax: +33 4 93 65 47 16

 Siret N° 348 623 562 00017 - NAF 742 C

 Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/68

 Important notice

 The present document can be downloaded from: http://www.etsi.org

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <u>http://portal.etsi.org/tb/status/status.asp</u>

If you find errors in the present document, please send your comment to one of the following services: <u>http://portal.etsi.org/chaircor/ETSI_support.asp</u>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI. The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014. All rights reserved.

DECT[™], PLUGTESTS[™], UMTS[™] and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**[™] and LTE[™] are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <u>http://webapp.etsi.org/key/queryform.asp</u>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "may not", "need", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights			
Foreword			
Modal verbs terminology			
Foreword5			
Introd	Introduction		
1	Scope	6	
2	References	6	
3	Definitions and abbreviations	7	
3.1 3.2	Definitions	7 8	
4	Capabilities for the support of IP multimedia services	8	
4.1	General	8	
4.1.1	Types of traffic	8	
4.1.2	Business communication capabilities	9 Q	
414	Number naming and addressing		
4.1.5	Identification of session originator and terminator		
4.1.6	Charging and accounting requirements		
4.1.7	Regulatory requirements	12	
4.1.7.1	Lawful intercept	12	
4.1.7.2	2 Emergency service	12	
4.1.7.3	3 Identifying malicious communications	12	
4.1.7.4	Anonymous communications rejection	12	
4.1.8	Mobility	13	
4.1.8.1	Roaming	13	
4.1.9	Routing requirements.	13	
4.1.9.1	Routing to a NGCN user	13	
4.1.9.2	Communication admission control	13	
4.1.10	Communication admission control	13	
4.1.11	NGN/NGCN interconnection requirements	14	
4.2.1	NGCN site identifier		
4.2.2	Corporate network user identifier		
4.2.3	Authentication and security requirements	14	
4.3	Specific requirements for hosted enterprise services	14	
4.3.1	Security requirements for hosted enterprise services	14	
4.3.2	Capabilities provided to a HES user	15	
4.3.3	Capabilities provided to the enterprise	15	
4.3.3.1	Break-in	15	
4.3.3.2	2 Break-out	15	
4.4	Specific requirements for business trunking application	15	
4.4.1	Routeing capabilities	15	
4.4.1.1	D Brook in	13	
4.4.1.2	Break out	13	
4.4.1.4	Bulk rerouting	15	
4.4.2	Communication barring		
_			
5	PSTN/ISDN emulation service	16	
6	Codecs services	16	
7	7 Network attachment requirements		

7.1	General	16	
7.2	Specific requirements for virtual leased line	16	
7.2.1	Security requirements for virtual leased line	16	
8	CPE configuration	17	
9	Control of processing overload	17	
10	IP addressing	17	
11	NGN interconnection	17	
12	Transport stratum	17	
12.1	NGN/NGCN interconnection requirements	17	
12.1.1	Redundancy support	17	
12.2	Specific requirements for virtual leased line	17	
Annex A (informative): Change history			
Histo	History		



Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is structured in a similar manner to ETSLTS 181 005 [2] and the main clause numbering from this point in the document onwards therefore follows that document, with the scope of those clauses also following that of ETSLTS 181 005 [2].

As well as the interconnection of NGCN equipment to the NGN, the NGN can be used to host various business communication capabilities on behalf of an enterprise. These are:

- a) virtual leased line, where NGCN sites are interconnected through the NGN;
- b) business trunking application, where the NGN hosts transit capabilities between NGCNs, break-in capabilities from NGN to NGCN and break-out capabilities from NGCN to NGN; and
- c) hosted enterprise services, where an NGN hosts originating and/or terminating business communication capabilities for business communication users that are directly attached to an NGN.

These hosted capabilities may be hosted using the different capabilities described in different clauses in ETSI TS 181 005 [2] and therefore where appropriate the various clauses of the present document are broken up to further describe interconnection requirements, and these various hosted capabilities, as follows:

x.1 General;

- x.2 NGN/NGCN interconnection requirements;
- x.3 Specific requirements for hosted enterprise services;
- x.4 Specific requirements for business trunking application; and
- x.5 Specific requirements for virtual leased line.

This structure has been followed in 3GPP TS 22.519, even though 3GPP TS 22.228 [6] (the equivalent specification) is structured in a different manner.

1 Scope

The present document specifies network requirements:

- to support connection and interoperation of business communication capabilities (either hosted in NGCN or NGN) to the NGN; and
- to support connection and interoperation of business communication capabilities to other business communication capabilities (either hosted in NGCN or NGN); and
- to support connection and interoperation of business communication capabilities to other business communication capabilities located in or connected to the ISDN and PSTN; and
- to support PABX functionality (hosted enterprise services) in an NGN.

NOTE 1: Network requirements to support connection of NGCN directly connected to an NGN are specified.

NOTE 2: Attachment of legacy PBX functionality to the NGN is not specified in the present document. It is assumed that existing legacy service requirements apply in this case.

The present document also specifies network requirements for communication between NGCN capabilities (including user equipment) to other NGCN capabilities of the same enterprise through the NGN (e.g. geographically separated).

The present document does not specify NGCN services, nor does it specify network based application services provided to a user of an NGCN.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] Recommendation ITU-T E.164: "The international public telecommunication numbering plan".
- [2] ETSI TS 181 005 (V1.1.1): "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Services and Capabilities Requirements".
- [3] 3GPP TS 33.203: "3G security; Access security for IP-based services".
- [4] 3GPP TS 33.210: "3G security; Network Domain Security (NDS); IP network layer security".
- [5] ISO/IEC 11571: "Information technology Telecommunications and information exchange between systems Private Integrated Services Networks Addressing".
- [6] 3GPP TS 22.228: "Service requirements for the Internet Protocol (IP) multimedia core network subsystem (IMS); Stage 1".
- [7] ETSI TR 102 478 (V1.1.1): "Corporate telecommunication Networks (CN); Enterprise communication involving Next Generation carrier Networks (NGN)".
- [8] 3GPP TS 22.115: "Service aspects; Charging and billing".
- [9] 3GPP TS 33.106: "3G security; Lawful interception requirements".

[10]

3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [10] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [10].

business communication: any communication that is either:

- originated in an NGCN; or
- terminated in an NGCN; or
- originated in the NGN on behalf of an enterprise; or
- terminated in the NGN on behalf of an enterprise;

and which is subject to special arrangements between the NGN operator and the enterprise

business communication capabilities: any capability whether hosted in an NGCN or an NGN that enables and/or enriches Business Communication

NOTE: Business Trunking, Hosted Enterprise Services and Virtual Leased Line are examples of business communication capabilities hosted in NGN

Business Trunking (BT): connection of an NGCN to an NGN

business trunking application: NGN application that either provides transit capabilities between NGCNs, or, break-in capabilities from NGN to NGCN and/or break-out capabilities from NGCN to NGN

NOTE: A business trunking application may also provide additional services beyond basic breakin, breakout and transit capabilities to the NGCN.

corporate network user identifier: identifies a corporate network user on communications entering, leaving or transiting the NGN, either representing an originating corporate network user or as a globally routable target identity

Corporate telecommunication Network (CN): sets of enterprise premises equipment, owned by or managed on behalf of an enterprise that are located at geographically dispersed locations and are interconnected to provide telecommunication services to a defined group of users belonging to that enterprise

enterprise: unit of economic organization or activity, especially a business organization

Hosted Enterprise Services (HES): NGN application whereby the NGN hosts all originating and/or terminating business communication capabilities for enterprise users that are directly attached to NGN and have an IMS service subscription for this application in the NGN

Next Generation CN (NGCN): self-contained corporate network designed to take advantage of emerging IP-based communications solutions and that can have its own applications and service provisioning

- NOTE 1: For the purpose of the present document it is a corporate network that provides an IP-based interface to an NGN.
- NOTE 2: TR 102 478 [7] uses NGCN to collectively refer to IP-PBXs.

NGCN site: separate part of an NGCN

NOTE: An NGCN site might represent a part of an NGCN bound to a specific geographic location. When an NGCN site serves more than one geographic location then all locations served by that NGCN site would have access to an NGN concerned via the NGCN site's connectivity arrangement with that NGN. Communication between different NGCN sites belonging to the same NGCN can but need not pass through their respective NGN(s). For example, such communications might be routed by the NGN(s) only during periods of high traffic or equipment outage within the NGCN. An NGCN site can have access to its NGN either directly or via some other NGN that provides a transit capability. An NGCN can have NGCN Sites in different countries.

NGCN identifier: identifier by which an NGCN is known to an NGN with which it has a connectivity arrangement

public network traffic: traffic sent to or received from an NGN for processing according to the normal NGN rules

private network traffic: traffic sent to or received from an NGN for processing according to an agreed set of rules specific to an enterprise or a community of closely related enterprises

Private Numbering Plan (PNP): numbering plan explicitly relating to a particular private numbering domain, defined by the PISN Administrator of that domain

NOTE 1: See ISO/IEC 11571 [5].

NOTE 2: Terminology used in this definition and in relation to this term used in the text is as defined in ISO/IEC 11571 [5]. For the purposes of the present document a PISN and a NGCN can be regarded as equivalent.

PNP number: number belonging to a PNP

Augstandards sight PNP number: number belonging to a PNP
NOTE: See ISO/IEC 11571 [5].
3.2 Abbreviations
For the purposes of the present document, the following abbreviations apply:

BT	Business Trunking
CAC	Communication Admission Control
CN	Corporate telecommunication Network
HES	Hosted Enterprise Services &
IMS	IP Multimedia core network Subsystem
IP	Internet Protocol
NGCN	Next Generation Corporate Network
NGN	Next Generation Network
PBX	Private Branch Exchange
PNP	Private Numbering Plan
PSAP	Public Safety Answering Point
SLA	Service-Level Agreement
TIP	Termination Identity Interface
UE	User Equipment
UNI	User to Network Interface

Capabilities for the support of IP multimedia services 4

4 1 General

4.1.1 Types of traffic

The traffic generated or received on behalf of an NGCN can be either:

1) traffic sent to the NGN for processing according to normal rules of the NGN. This type of traffic is known as public network traffic;

- 2) traffic sent to the NGN for processing according to an agreed set of rules specific to an enterprise. This type of traffic is known as private network traffic. Private network traffic is normally within a single enterprise, but private network traffic can also exist between two different enterprises if not precluded for regulatory reasons.
- NOTE: An enterprise network may separately distinguish private network calls that originate in the NGN from private network calls that originate in the enterprise; this does not form part of the present document.

The NGN shall distinguish public network traffic from private network traffic. The NGN shall distinguish private network traffic belonging to one enterprise from that belonging to another enterprise.

Private network traffic may require different handling in the NGN compared to public network traffic, see for example clause 4.1.7 on regulatory requirements.

Except between closely-related enterprises where regulations permit, the NGN shall treat traffic between enterprises as public network traffic. In such cases, as part of the capabilities provided to the enterprise, the NGN can provide break-out and/or break-in capabilities on behalf of each enterprise.

For private network traffic the NGN shall be transparent to any extensions of the chosen signalling protocol, except where there is a specific need for NGN intervention required to deliver the service requested by the enterprise customer.

4.1.2 Business communication capabilities

The NGN can provide the following capabilities to an enterprise

- a) virtual leased line, where NGCN sites are interconnected through the NGN. No additional capabilities are provided by the NGN;
- b) business trunking application, where the NGN hosts transit capabilities between NGCNs, break-in capabilities from NGN to NGCN and break-out capabilities from NGCN to NGN. A business trunking application may also host additional capabilities beyond basic break-in, break-out and transit capabilities to the NGCN. Typically there is no corporate network terminal equipment connected directly to an NGN. The capabilities provided are defined in clause 4.4;
- c) hosted enterprise services, where an NGN hosts originating and/or terminating business communication capabilities for business communication users that are directly attached to an NGN and have an IMS service subscription for this application in this NGN. This is known commonly as IP-Centrex. The capabilities provided are defined in clause 4.3.

NOTE: NGCNs will not necessarily use IMS in their support of session-based capabilities.

4.1.3 Business models

Additionally to the business domain relationships as specified in 3GPP TS 22.228 [6] the NGN shall support the following business domain relationships:

a) NGCN to IMS relationship: NGCN is attached to an Access network that is connected to the NGN IMS with which the NGCN has a service agreement as shown in figure 4.1, the relationship is with the home IMS.





b) NGCN to Access network relationship: NGCN is connected to an Access Network as shown in figure 4.2. The relationships given in 3GPP TS 22.228 [6] would normally be sufficient to enable connectivity with the NGN, providing there is a relationship between the NGCN and the IMS. Relationship b may be required in some cases.