# INTERNATIONAL STANDARD

ISO 10318-2

First edition 2015-04-01

# **Geosynthetics** —

Part 2: **Symbols and pictograms** 

Géosynthétiques — Partie 2: Symboles et pictogrammes

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10318-2:2015 https://standards.iteh.ai/catalog/standards/sist/0e9a32d0-6446-4cf6-bb3a-d66dba30039d/iso-10318-2-2015



# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10318-2:2015 https://standards.iteh.ai/catalog/standards/sist/0e9a32d0-6446-4cf6-bb3a-d66dba30039d/iso-10318-2-2015



#### COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Con	tents		Pa	ge
Forew	ord			iv
1	Scope			1
2	Symbo	ols		1
	2.1	Proper	ty symbols	. 1
		2.1.1	Physical properties	. 1
		2.1.2	Hydraulic properties of GTX and of GTP	1
		213	Mechanical properties	1
	2.2	Graphi	cal symbols and pictograms  Products	. 3
		2.2.1	Products	. 3
		2.2.2	Functions	4
		2.2.3	Applications	. 5
Riblio	granhy	,		7

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10318-2:2015 https://standards.iteh.ai/catalog/standards/sist/0e9a32d0-6446-4cf6-bb3a-d66dba30039d/iso-10318-2-2015

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: Foreword — Supplementary information.

The committee responsible for this document is ISO/TC 221, Geosynthetics.

This second edition cancels and replaces the firsts-edition (ISO 10318:2005), which has been technically revised. https://standards.iteh.ai/catalog/standards/sist/0e9a32d0-6446-4cf6-bb3a-d66dba30039d/iso-10318-2-2015

ISO 10318 consists of the following parts, under the general title *Geosynthetics*:

- Part 1: Terms and definitions
- Part 2: Symbols and pictograms

# Geosynthetics —

## Part 2:

# Symbols and pictograms

### 1 Scope

The intent of this part of ISO 10318 is to define property symbols, graphical symbols, and pictograms used in EN and ISO geosynthetics standards. Definitions of particular or specific symbols and pictograms terms not included in this this part of ISO 10318 can be found in the International Standards describing appropriate test methods.

### 2 Symbols

#### 2.1 Property symbols

#### 2.1.1 Physical properties

	eh STAN	<u>NDARD PR</u>	H) V I H) W
Symbols	Units	References	Properties
d	mmtan	ISO 10318-1, 2.3.2.1	Thickness
b	m	ISO 10318-2:2015	Width
https://sta	andards. <b>10</b> h.ai/cata	log/standard <del>s/s</del> ist/0e9a32d	10-6446-4cf6-Uength
$\rho_A$	g/m <sup>2</sup> 66dba	180 <sup>9</sup> 10318 <sup>1</sup> 1, 12.3.2.21	5 Mass per unit area

#### 2.1.2 Hydraulic properties of GTX and of GTP

Symbols	Units	References	Properties
k <sub>n</sub>	m/s	ISO 10318-1, 2.3.3.3	Coefficient of permeability normal to the plane
ψ	s-1	ISO 10318-1, 2.3.3.6	Permittivity ( $\psi = k_n/d$ )
θ	l/(m⋅s)	ISO 10318-1, 2.3.3.8	Transmissivity $(\theta = k_{p} \cdot d)$
ν-index	mm/s	ISO 10318-1, 2.3.3.5	Velocity index
$q_{ m p}$	l/(m⋅s)	ISO 10318-1, 2.3.3.7	In-plane flow capacity
$q_{\mathrm{n}}$	l/(m <sup>2</sup> · s)	ISO 10318-1, 2.3.3.4	Flux normal to the plane
090	μm	ISO 10318-1, 2.3.3.1	Characteristic opening size

### 2.1.3 Mechanical properties

#### 2.1.3.1 Tensile characteristics

Symbols	Units	References	Properties
$\sigma_{ m y}$	МРа	ISO 10318-1, 2.3.4.1.2	Tensile stress at yield point

Symbols	Units	References	Properties
$T_{\epsilon}$	kN/m	ISO 10318-1, 2.3.4.2	Tensile strength at a given strain $\varepsilon$ (e.g. $T_3$ is the tensile strength at 3 % strain)
$\sigma_{ m f}$	МРа	ISO 10318-1, 2.3.4.1.3	Tensile stress at failure
$T_{ m f}$	kN/m	ISO 10318-1, 2.3.4.2.1	Tensile strength (related to the specimen width) at failure
$\sigma_{ m max}$	МРа	ISO 10318-1, 2.3.4.1.4	Maximum tensile stress
$T_{ m max}$	kN/m	ISO 10318-1, 2.3.4.2.2	Maximum tensile strength (related to the specimen width)
$T_{Jmax}$	kN/m	ISO 10318-1, 2.3.4.4.4	Maximum seam or joint strength
ξs	%	ISO 10318-1, 2.3.5.5	Joint or seam efficiency
J	kN/m or kPa	ISO 10318-1, 2.3.4.2.3	Tensile modulus

### 2.1.3.2 Frictional characteristics

Symbols	Teh References ARD	PR Properties
$\phi_{ extsf{s,GSY}}$	ISO 103184123.64rds.it	Friction angle between soil and GSY
$\phi_{ ext{GSY,GSY}}$	ISO 10318-1, 2 <u>13.6 1<sub>0318-2:201</sub></u>	Friction angle between GSY 5 and GSY
$f_{ m s,GSY}$	https://standards.iteh.ai/catalog/standards/sist/ ISO 10318-4,233.6.21/iso-10318	ciency) coefficient between soil and GSY

## 2.1.3.3 Loading characteristics

Symbols	Units	References	Properties
$F_{ m f}$	kN	_	Load recorded at failure in a tensile test
$F_{ m max}$	kN	_	Maximum load recorded in a tensile test
$F_{\rm p}$	kN	_	Puncture force in a static puncture test
$P_{\rm n}$	kN	_	Normal load in a compressive creep test
$P_{\mathrm{S}}$	kN	_	Shear load in a direct shear test

### 2.1.3.4 Other characteristics

Symbols	Units	Properties
D <sub>C</sub>	mm	Diameter of the hole, if any, expressed in mm, obtained in the cone drop test

# 2.2 Graphical symbols and pictograms


#### 2.2.1 Products

GTX		Geotextile
GBR		Geosynthetic barrier
GGR		Geogrid
GCO		Geocomposite
GNT	XXXXXXXXXXXXXX	Geonet
GBR-C	Z <i></i> Z <i></i> Z <i></i> Z	Clay geosynthetic barrier
GCE		Geocell
GMA	~~~~~	Geomat


# iTeh STANDARD PREVIEW (standards.iteh.ai)


ISO 10318-2:2015 https://standards.iteh.ai/catalog/standards/sist/0e9a32d0-6446-4cf6-bb3a-d66dba30039d/iso-10318-2-2015


#### 2.2.2 Functions



#### **Protection**








## 2.2.3 Applications


Reservoirs and dams

Liquid waste



https://standards.iteh.ai/catalog/standards/sist/0e9a32d0-6446-4cf6-bb3a-Canals d66dba30039d/iso-10318-2-2015 **Solid waste** 





Transportation infrastructure and roads

Foundations and retaining walls

