
**Rolling bearings — Accessories for
sleeve type linear ball bearings —**

Part 2:

**Boundary dimensions and tolerances for
series 5**

iTeh STANDARD PREVIEW
Roulements — Accessoires pour douilles à billes linéaires —
(standards.iteh.ai) *Partie 2: Dimensions d'encombrement et tolérances pour la série 5*

[ISO 13012-2:2009](https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009)

<https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009>



Reference number
ISO 13012-2:2009(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 13012-2:2009

<https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	2
4 Symbols	3
4.1 Closed and adjustable flangeless housings for series 5 sleeve type linear ball bearings	3
4.2 Open and open adjustable flangeless housings for series 5 sleeve type linear ball bearings	3
4.3 Standard height shaft support rails for series 5 sleeve type linear ball bearings	4
4.4 Flanged shaft support blocks for series 5 sleeve type linear ball bearings	4
4.5 Solid and tubular shafts for series 5 sleeve type linear ball bearings	4
5 Housings.....	5
5.1 General.....	5
5.2 Housings for series 5 sleeve type linear ball bearings	5
6 Shaft support rails	5
7 Shaft support blocks	5
8 Shafts	5
8.1 Material	5
8.2 Heat treatment.....	5
8.3 Geometrical tolerances	6
9 Boundary dimensions and tolerances.....	6
9.1 Housings.....	6
9.2 Shaft support rails	9
9.3 Shaft support blocks	10
9.4 Shafts	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13012-2 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*, Subcommittee SC 11, *Linear motion rolling bearings*.

ISO 13012 consists of the following parts, under the general title *Rolling bearings — Accessories for sleeve type linear ball bearings*:

— *Part 1: Boundary dimensions and tolerances for series 1 and 3*

— *Part 2: Boundary dimensions and tolerances for series 5*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 13012-2:2009](https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009)

<https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009>

Introduction

The use of sleeve type linear ball bearings can be facilitated by the selection of bearing housings, shafts, shaft support blocks and shaft support rails. These items, referred to as accessories, can aid in the application of the sleeve type linear ball bearings to achieve the desired criteria of smooth, accurate, low-friction linear motion free from chatter or stick-slip.

The appropriate selection of bearing housing type, shaft and shaft support should be established between the manufacturer and the user.

This part of ISO 13012 was developed to be used with ISO 10285.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 13012-2:2009

<https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 13012-2:2009

<https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009>

Rolling bearings — Accessories for sleeve type linear ball bearings —

Part 2: Boundary dimensions and tolerances for series 5

1 Scope

This part of ISO 13012 specifies the boundary dimensions, other relevant dimensions and their tolerances of accessories for sleeve type linear ball bearings which are specified in ISO 10285.

This part of ISO 13012 applies to:

housings —

closed and adjustable flangeless housings for series 5 sleeve type linear ball bearings,

open and open adjustable flangeless housings for series 5 sleeve type linear ball bearings;

shaft support rails —

standard height shaft support rails for series 5 sleeve type linear ball bearings;

shaft support blocks — <https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009>

flanged shaft support blocks for series 5 sleeve type linear ball bearings;

shafts —

solid and tubular shafts for series 5 sleeve type linear ball bearings.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 286-2, *ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts*

ISO 1132-1, *Rolling bearings — Tolerances — Part 1: Terms and definitions*

ISO 1302, *Geometrical Product Specifications (GPS) — Indications of surface texture in technical product documentation*

ISO 3754, *Steel — Determination of effective depth of hardening after flame or induction hardening*

ISO 5593, *Rolling bearings — Vocabulary*

ISO 10285:2007, *Rolling bearings — Sleeve type linear ball bearings — Boundary dimensions and tolerances*

ISO 15241, *Rolling bearings — Symbols for quantities*

ISO 24393, *Rolling bearings — Linear motion rolling bearings — Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1132-1, ISO 5593, ISO 10285, and ISO 24393 apply.

3.1 flangeless housing

(sleeve type linear ball bearing) bearing housing which has a face with bolt holes or threaded holes for attachment to a support surface nominally parallel to the bearing axis

[ISO 13012-1:2009]

3.2 closed housing

(sleeve type linear ball bearing) bearing housing in which the bearing seating is circumferentially continuous

[ISO 13012-1:2009]

3.3 adjustable housing

(sleeve type linear ball bearing) bearing housing with a longitudinal slit across its bearing seating which facilitates the mechanical adjustment of the bearing seating diameter

[ISO 13012-1:2009]

3.4 open housing

(sleeve type linear ball bearing) bearing housing with a longitudinal section removed to provide clearance over a shaft and support rail unit

[ISO 13012-1:2009]

iTeh STANDARD PREVIEW
(standard.itih.ai)

<https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009>

3.5 open adjustable housing

(sleeve type linear ball bearing) bearing housing which has the features of both open and adjustable sleeve type linear ball bearing housings

[ISO 13012-1:2009]

3.6 shaft support rail

longitudinal pedestal which provides continuous support to a shaft

NOTE Shaft support rails may be used with open sleeve type linear ball bearings.

[ISO 13012-1:2009]

3.7 shaft support block

block which provides support to a shaft

NOTE Shaft support blocks are normally used to support the shaft at its ends and can be used with closed sleeve type, adjustable sleeve type or open sleeve type linear ball bearings.

[ISO 13012-1:2009]

3.8 shaft

basically cylindrical rod along which a linear ball bearing traverses

[ISO 13012-1:2009]

4 Symbols

For the purposes of this document, the symbols given in ISO 15241 and the following apply.

The symbols (except those for tolerances) shown in Figures 1 to 5, and the values given in Tables 1 to 6 denote nominal dimensions unless specified otherwise.

NOTE Figures 1 to 5 are drawn schematically and do not necessarily show all design details.

4.1 Closed and adjustable flangeless housings for series 5 sleeve type linear ball bearings

See Table 1 and Figure 1.

A	(overall) width
D_a	seating diameter
F_w	bore diameter of ball complement of sleeve type linear ball bearing (reference)
G	designation of screw thread of attachment hole
H	distance from mounting face to centreline of seating diameter
H_1	(overall) height
J	centre distance between bolt holes (length)
J_1	centre distance between bolt holes (width)
L	length of housing
L_1	distance from side face to centreline of seating diameter
N	diameter of bolt hole

4.2 Open and open adjustable flangeless housings for series 5 sleeve type linear ball bearings

See Table 2 and Figure 2.

A	(overall) width
D_a	seating diameter
E	width of sector opening (at diameter D_a)
F_w	bore diameter of ball complement of sleeve type linear ball bearing (reference)
G	designation of screw thread of attachment hole
H	distance from mounting face to centreline of seating diameter
H_1	(overall) height
J	centre distance between bolt holes (length)
J_1	centre distance between bolt holes (width)
L	length of housing
L_1	distance from side face to centreline of seating diameter
α	angle of sector opening

4.3 Standard height shaft support rails for series 5 sleeve type linear ball bearings

See Table 3 and Figure 3.

- A (overall) width
- d outside diameter of shaft (reference)
- H distance from mounting face to centreline of shaft
- H_1 height of flange
- J centre distance between bolt holes (length)
- J_1 centre distance between bolt holes (width)
- M width of shaft support
- N diameter of bolt hole
- N_1 diameter of bolt hole (shaft attachment)
- β angle of shaft support

4.4 Flanged shaft support blocks for series 5 sleeve type linear ball bearings

See Table 4 and Figure 4.

- A (overall) width
- D_a seating diameter
- H distance from mounting face to centreline of seating diameter
- H_1 height of flange
- H_2 (overall) height
- J centre distance between bolt holes (length)
- L length of base
- N diameter of bolt hole

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/833440c9-7262-4557-954e-233baaa922f3/iso-13012-2-2009>

4.5 Solid and tubular shafts for series 5 sleeve type linear ball bearings

See Tables 5 and 6, and Figure 5

- d outside diameter of shaft
- d_s single outside diameter of shaft
- L length of shaft
- L_s actual length of shaft
- t straightness of shaft
- V_{dmp} variation of mean outside diameter of shaft
- V_{dsp} variation of outside diameter of shaft in a single plane
- Δ_{ds} deviation of a single outside diameter of shaft
- Δ_{Ls} deviation of the actual length of shaft

5 Housings

5.1 General

To facilitate the design and assembly of sleeve type linear ball bearings, specifically designed housings are available. Included in this part of ISO 13012 are the boundary dimensions and other related dimensions of sleeve type linear ball bearings series 5 as specified in ISO 10285:2007.

The housings specified in Tables 1 and 2, and the corresponding sleeve type linear ball bearings should be supplied by the same producer. The reason for this is that the fixation of the bearings in the housings is specified by the producer and is not covered by this part of ISO 13012.

5.2 Housings for series 5 sleeve type linear ball bearings

This part of ISO 13012 includes the following housing designs for series 5 linear ball bearings:

- closed and adjustable flangeless housings for series 5 sleeve type linear ball bearings (Table 1);
- open and open adjustable flangeless housings for series 5 sleeve type linear ball bearings (Table 2).

6 Shaft support rails

This part of ISO 13012 includes the following shaft support rails for sleeve type linear ball bearings:

- standard height shaft support rails for series 5 sleeve type linear ball bearings (Table 3).

7 Shaft support blocks

This part of ISO 13012 includes the following shaft support blocks for sleeve type linear ball bearings:

- flanged shaft support blocks for series 5 sleeve type linear ball bearings (Table 4).

8 Shafts

8.1 Material

Shafts covered by this part of ISO 13012 are precision hardened and ground steel shafts in both solid and tubular section. They are manufactured from high quality carbon steel or high quality carbon chrome steel and are either surface hardened or through hardened.

8.2 Heat treatment

8.2.1 Surface hardened shafts

The cylindrical surface of the shafts is heat treated to provide a basically uniform effective depth of hardening and a surface hardness of not less than 653 HV (58 HRC) over the entire operating length. The effective depth of hardening shall be determined in accordance with ISO 3754. This effective depth of hardening is the distance from the outside surface of the shaft to a material layer at which the hardness is approximately 80 % of the specified minimum surface hardness. End faces of shafts may remain unhardened.