
**Acoustics — Determination of
sound power levels of noise sources
— Guidelines for the use of basic
standards**

*Acoustique — Détermination des niveaux de puissance acoustique
émis par les sources de bruit — Lignes directrices pour l'utilisation
des normes de base*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 3740:2019](https://standards.iteh.ai/catalog/standards/sist/e145e416-3da7-4b54-86b9-6d9d3d508e2e/iso-3740-2019)

<https://standards.iteh.ai/catalog/standards/sist/e145e416-3da7-4b54-86b9-6d9d3d508e2e/iso-3740-2019>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 3740:2019

<https://standards.iteh.ai/catalog/standards/sist/e145e416-3da7-4b54-86b9-6d9d3d508e2e/iso-3740-2019>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Sound power level	7
4.1 Basic information.....	7
4.2 Reasons for the determination of sound power levels.....	7
4.3 Basic procedures for determining sound power levels.....	7
4.4 Quality of determined sound power levels.....	8
4.5 Noise emission declaration.....	8
5 Selection of the most appropriate method in the set of standards	9
5.1 Methods and quantities to be measured and determined.....	9
5.2 Considerations affecting the selection of a measurement method.....	9
5.3 Test environment.....	17
5.4 Selection of basic standards appropriate for measurements in laboratory rooms and special test rooms.....	17
5.4.1 General.....	17
5.4.2 Acoustical requirements on the sound field in laboratories and special test rooms.....	17
5.4.3 Background noise limitation.....	17
5.5 Selection of basic standards appropriate for in-situ measurements.....	18
5.5.1 General.....	18
5.5.2 Hemi-anechoic sound field check.....	19
5.6 Determination of high-frequency sound power levels.....	20
Annex A (informative) Basic International Standards specifying methods for determining sound power levels of machines, equipment and products — Main facts and requirements	21
Annex B (informative) Acoustical test environments	23
Annex C (informative) Measurement uncertainty	25
Annex D (informative) Case studies	28
Bibliography	34

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This third edition cancels and replaces the second edition (ISO 3740:2000), which has been technically revised. The main change compared to the previous edition is as follows:

— All of the basic standards covered by this document with the exception of the ISO 9614 series have been revised.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

For many users of machinery, equipment and products, the control of noise is a major issue which requires effective exchange of acoustical information. In this context, the main flow of information goes from the manufacturer to the purchaser, installer or user of the machines and products to describe the generated sound. In particular, information on source airborne noise emission is desired. Therefore, the sound power level, as the major parameter characterising airborne noise emission of sound sources, needs to be determined by measurement.

However, such measurements are only useful if the conditions under which they are carried out are specified; they yield defined acoustical quantities, and they are taken with standardized instruments.

Sound power levels are used for

- declaration of the noise emitted under defined conditions,
- verification of declared values,
- comparison of the noise emitted by machinery of various types and sizes,
- comparison with limits specified in a purchasing contract or a regulation,
- engineering work to control the noise emission of machinery,
- prediction of noise exposure of workers in indoor or outdoor work shops,
- prediction of noise in the environment.

International Standards describing basic methods for determining sound power level are

- ISO 3741 to ISO 3747 (sound power level determination using sound pressure level measurements),
- ISO 9614-1 to ISO 9614-3 (sound power level determination using sound intensity measurements),
- ISO/TS 7849-1 and ISO/TS 7849-2 (sound power level determination using vibration measurements).

These standards specify different methods for determination of sound power level and the achievable accuracy, characterized by the standard deviation of reproducibility of the method. Operating and mounting conditions, and the uncertainty associated with these conditions, are dealt with only in a very general manner. Specific and detailed requirements on the machinery or equipment under test are given in noise test codes prepared by machinery specific standards committees. They not only provide the necessary detailed information on the operating, installation and mounting conditions but also identify basic measurement standards that can be used and how a noise emission declaration and verification is made.

The standards mentioned above differ in their range of applications and their requirements with regard to the test environment. In practice, procedures that do not require special laboratory environments and additionally meet class 2 accuracy are particularly advantageous, especially to meet legal requirements. These include the procedures in standards ISO 3744, ISO 3747 and methods in ISO 9614-2.

To help technical committees in drafting noise test codes or to assist manufacturers of machines and equipment in determining the sound power level if a noise test code is not currently available, ISO 3740 introduces the set of twelve International Standards describing various methods for determining sound power levels of machinery, equipment and products taking into account the broad variety of practical situations for the sources under test (types of machinery, equipment and products), test environments, measurement instruments and the accuracy desired.

Some machinery, equipment and products emit high-frequency noise, which can be broad-band noise, narrow-band noise or discrete tones. ISO 9295 specifies four methods for the determination of sound power levels emitted by machinery, equipment and products in the frequency range covered by the 16 kHz octave band. In 5.6, ISO 9295 is briefly described.

ISO 3740:2019(E)

More detailed definitions than those specified in this document can be found in ISO 3741, ISO 3743-1, ISO 3743-2, ISO 3744, ISO 3745, ISO 3746 and ISO 3747, in ISO 9614-1 to ISO 9614-3, ISO/TS 7849-1, ISO/TS 7849-2, and in noise test codes for specific types of machinery, equipment and products.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 3740:2019](https://standards.iteh.ai/catalog/standards/sist/e145e416-3da7-4b54-86b9-6d9d3d508e2e/iso-3740-2019)

<https://standards.iteh.ai/catalog/standards/sist/e145e416-3da7-4b54-86b9-6d9d3d508e2e/iso-3740-2019>

Acoustics — Determination of sound power levels of noise sources — Guidelines for the use of basic standards

1 Scope

This document gives guidance for the use of a set of twelve basic International Standards (see [Tables 1, 2 and 3](#)) describing various methods for determining sound power levels from all types of machinery, equipment and products. It provides guidance on the selection of one or more of these standards, appropriate to any particular type of sound source, measurement environment and desired accuracy. The guidance given applies to airborne sound. It is for use in the preparation of noise test codes (see ISO 12001) and also in noise emission testing where no specific noise test code exists. Such standardized noise test codes can recommend the application of particular basic International Standard(s) and give detailed requirements on mounting and operating conditions for a particular family to which the machine under test belongs, in accordance with general principles given in the basic standards.

This document is not intended to replace any of the details of, or add any additional requirements to, the individual test methods in the basic International Standards referenced.

NOTE 1 Two quantities which complement each other can be used to describe the noise emission of machinery, equipment and products. One is the emission sound pressure level at a specified position and the other is the sound power level. The International Standards which describe the basic methods for determining emission sound pressure levels at work stations and at other specified positions are ISO 11200 to ISO 11205 (References [20] to [25]).

NOTE 2 The sound energy level mentioned in ISO 3741 to ISO 3747 is not addressed in this document as it is not mentioned in any legal requirement. Its application is limited to very special cases of a single burst of sound energy or transient sound defined in ISO 12001.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

emission

<acoustics> airborne sound radiated by a well-defined noise source (e.g. the machine under test) under specified operating and mounting conditions

Note 1 to entry: Emission values may be incorporated into a product noise declaration, product label and/or product specification. The basic noise emission quantities are the sound power level of the source itself and the emission sound pressure levels at the work station and/or at other specified positions (if any) in the vicinity of the source.

[SOURCE: ISO 12001:1996, 3.3, modified — Note 1 to entry "product noise declaration" added.]

3.2
sound power

P

through a surface, product of the sound pressure, p , and the component of the particle velocity, u_n , at a point on the surface in the direction normal to the surface, integrated over that surface

Note 1 to entry: Sound power is expressed in watts.

Note 2 to entry: The quantity relates to the rate at which airborne sound energy is radiated by a source.

[SOURCE: ISO 80000-8:2007, 8-16, modified — Notes 1 and 2 to entry added.]

3.3
sound power level

L_W
ten times the logarithm to the base 10 of the ratio of the *sound power*, P (3.2), of a source to a reference value, P_0 , expressed in decibels

$$L_W = 10 \lg \frac{P}{P_0} \text{ dB}$$

where the reference value, P_0 , is 1 pW

Note 1 to entry: If a specific frequency weighting as specified in IEC 61672-1 and/or specific frequency bands are applied, this is indicated by appropriate subscripts; e.g. L_{WA} denotes the A-weighted sound power level.

Note 2 to entry: This definition is technically in accordance with ISO 80000-8:2007, 8-23.

Note 3 to entry: $\lg () = \lg_{10} ()$ in all relevant parts of the standard.

[SOURCE: ISO/TR 25417:2007, 2.9, modified — Note 3 to entry added.]

3.4
structure vibration generated sound
airborne sound caused by structural vibration in the audible frequency range

Note 1 to entry: In the ISO/TS 7849 series, structure vibration generated sound is determined either from the vibratory velocity or from the vibratory acceleration of the surface of the solid structure.

[SOURCE: ISO/TS 7849-1:2009, 3.1, modified — Expression "In the ISO/TS 7849 series" used for clarification instead of "For the purpose of this part of ISO/TS 7849".]

3.5
sound pressure level

L_p
ten times the logarithm to the base 10 of the ratio of the square of the sound pressure, p , to the square of a reference value, p_0 , expressed in decibels

$$L_p = 10 \lg \frac{p^2}{p_0^2} \text{ dB}$$

where the reference value, p_0 , is 20 μPa

[SOURCE: ISO/TR 25417:2007, 2.2, modified — Notes 1 and 2 deleted.]

3.6 time-averaged sound pressure level

$L_{p,T}$

ten times the logarithm to the base 10 of the ratio of the time average of the square of the sound pressure, p , during a stated time interval of duration, T (starting at t_1 and ending at t_2), to the square of a reference value, p_0 , expressed in decibels

$$L_{p,T} = 10 \lg \left[\frac{\frac{1}{T} \int_{t_1}^{t_2} p^2(t) dt}{p_0^2} \right] \text{ dB}$$

where the reference value, p_0 , is 20 μPa

Note 1 to entry: In general, the subscript “ T ” is omitted since time-averaged sound pressure levels are necessarily determined over a certain measurement time interval.

Note 2 to entry: Time-averaged sound pressure levels are often A-weighted, in which case they are denoted by $L_{pA,T}$, which is usually abbreviated to L_{pA} .

Note 3 to entry: Adapted from ISO/TR 25417:2007, 2.3.

[SOURCE: ISO 3744:2010, 3.3]

3.7 single event time-integrated sound pressure level

L_E

ten times the logarithm to the base 10 of the ratio of the integral of the square of the sound pressure, p , of an isolated single sound event (burst of sound or transient sound) over a stated time interval T (starting at t_1 and ending at t_2), to a reference value, E_0 , expressed in decibels

$$L_E = 10 \lg \left[\frac{\int_{t_1}^{t_2} p^2(t) dt}{E_0} \right] \text{ dB}$$

where the reference value, E_0 , is $(20 \mu\text{Pa})^2 \text{ s} = 4 \times 10^{-10} \text{ Pa}^2 \text{ s}$

Note 1 to entry: This quantity can be obtained by

$$L_{p,T} + 10 \lg \left[\frac{T}{T_0} \right] \text{ dB}$$

where $T_0 = 1 \text{ s}$.

Note 2 to entry: When used to measure sound immission, this quantity is usually called “sound exposure level” (see ISO/TR 25417:2007).

[SOURCE: ISO 3744:2010, 3.4]

3.8 sound intensity

\vec{I}

$$\vec{I} = p \cdot \vec{u}$$

where

p is the sound pressure, in Pa;

\vec{u} is the sound particle velocity, in m/s.

Note 1 to entry: \vec{u} and \vec{I} are vectorial quantities.

**3.9
vibratory velocity**

v
root-mean square (RMS) value of the component of the velocity of a vibrating surface in the direction normal to the surface

Note 1 to entry: In ISO/TS 7849-1, the vibratory velocity is applied with an A-weighting, denoted v_A .

[SOURCE: ISO 7849-1:2009, 3.3, modified — Former Note 1 to entry deleted, expression "In ISO/TS 7849-1" used for clarification instead of "In this part of ISO/TS 7849" in former Note 2, now Note 1.]

**3.10
vibratory velocity level**

L_v
ten times the logarithm to the base 10 of the ratio of the square of the RMS value of the vibratory velocity, v , to the square of a reference value, v_0 , expressed in decibels:

$$L_v = 10 \lg \frac{v^2}{v_0^2} \text{ dB}$$

iTeh STANDARD PREVIEW
(standards.iteh.ai)

where

v is the RMS value of the vibratory velocity, in metres per second;

v_0 is the reference value for the velocity and is equal to 5×10^{-8} m/s.

Note 1 to entry: For airborne and structure vibration generated sound, the reference value, $v_0 = 50$ nm/s has the property that it leads, together with $p_0 = 2 \times 10^{-5}$ Pa, to the reference value of the intensity level $I_0 = 1 \times 10^{-12}$ W/m² and to a characteristic impedance of air of $p_0/v_0 = 400$ Pa·s/m.

Note 2 to entry: In ISO/TS 7849-1, the vibratory velocity level is applied as A-weighted vibratory velocity level, L_{vA} , by substituting v^2 for the A-weighted RMS v_A^2 in ISO/TS 7849-1:2009, Formula (6).

Note 3 to entry: In ISO 1683, two reference values for the velocity level are mentioned: $v_0 = 10^{-9}$ m/s and 5×10^{-8} m/s. The latter is intended for cases of airborne and structure vibration generated sound and is therefore used in ISO/TS 7849-1 and ISO/TS 7849-2. A choice of $v_0 = 10^{-9}$ m/s results in a vibratory velocity level which is 34 dB higher than the level used in both parts of ISO/TS 7849. Therefore, if $v_0 = 10^{-9}$ m/s is used, subtract 34 dB from the right-hand sides of the first formula in 3.10.

**3.11
radiation factor**

ϵ
factor expressing the efficiency of airborne sound power (3.2) radiation from the vibrating surface

Note 1 to entry: See ISO/TS 7849-1:2009, 4.4.1 to 4.4.4.

**3.12
background noise**

noise from all sources other than the noise source under test

Note 1 to entry: Background noise includes contributions from airborne sound, noise from structure-borne vibration, and electrical noise in the instrumentation.

[SOURCE: ISO 3744:2010, 3.15]

3.13**background noise level**

sound pressure level (3.5) measured when the source under test is not operating

Note 1 to entry: It is expressed in decibels.

3.14**extraneous vibratory velocity level**

vibratory velocity level (3.10) caused by all sources other than the source under test

Note 1 to entry: Extraneous vibratory velocity levels originate, for example, from coupled assemblies.

[SOURCE: ISO/TS 7849-1:2009, 3.9]

3.15**background noise correction**

K_1

correction applied to the mean (energy average) of the *time-averaged sound pressure levels* (3.6) over all the microphone positions on the measurement surface, to account for the influence of *background noise* (3.12)

Note 1 to entry: Background noise correction is expressed in decibels.

Note 2 to entry: The background noise correction is frequency dependent; the correction of a frequency band is denoted K_{1f} , where f denotes the relevant center frequency, and that in the case of A-weighting is denoted K_{1A} .

[SOURCE: ISO 3744:2010, 3.16]

3.16**environmental correction**

K_2

correction applied to the mean (energy average) of the *time-averaged sound pressure levels* (3.6) over all microphone positions on the measurement surface, to account for the influence of reflected or absorbed sound

Note 1 to entry: Environmental correction is expressed in decibels.

Note 2 to entry: The environmental correction is frequency dependent; the correction in the case of a frequency band is denoted K_{2f} , where f denotes the relevant mid-band frequency, and that in the case of A-weighting is denoted K_{2A} .

Note 3 to entry: In general, the environmental correction depends on the area of the measurement surface and usually K_2 increases with S .

[SOURCE: ISO 3744:2010, 3.17]

3.17**systematic deviation**

Δ_{sy}

deviation to account for a systematic difference between *sound power levels* (3.3) obtained using basic standards based on different physical rules

Note 1 to entry: Δ_{sy} is not covered in the basic standards. See 4.4 and Annex C.

Note 2 to entry: $\Delta_{sy,pl}$ describes specifically the systematic deviation between the sound power level yielded by the intensity method, $L_{W,I}$, compared with the result from free field sound pressure measurements, $L_{W,p}$: $\Delta_{sy,pl} = L_{W,p} - L_{W,I}$; otherwise $\Delta_{sy,pl}$ is also designated as near field error.

Note 3 to entry: Systematic deviations can also appear when environmental correction, K_2 , is determined according to different procedures from the basic standards.

**3.18
background noise index**

ΔL_p
index denoting the difference, in decibels, between the *sound pressure levels* (3.5) from the noise source under test in operation and the sound pressure levels of the *background noise* (3.12), both measured using an array of microphone positions over the measurement surface

**3.19
dynamic capability index**

L_d
index given by

$$L_d = \delta_{pI_0} - K$$

where

δ_{pI_0} is the pressure-residual intensity index, in decibels;

K is the bias error, in decibels.

Note 1 to entry: The dynamic capability index is expressed in decibels.

Note 2 to entry: The dynamic capability index describes the quality of the intensity measurement system to suppress unwanted background noise. It is used to check the attainment of the desired accuracy level, where K is selected to be 10 dB for grade 1 and 2 measurements and 7 dB for grade 3 measurements.

**3.20
standard deviation of reproducibility of the method**

σ_{R0}
uncertainty associated with a *sound power* (3.2) measurement method excluding the uncertainty due to the instability of the sound power of the source under test

Note 1 to entry: σ_{R0} is determined from round robin tests on an extreme stable source. It does not include uncertainty components like σ_{omc} and Δ_{sy} and consequently does not represent the total uncertainty.

**3.21
standard deviation due to operating and mounting conditions of the sound source**

σ_{omc}
uncertainty associated with the instability of the operating and mounting conditions for the particular source under test

**3.22
total standard deviation**

σ_{tot}
square root of the sum of the squares of the *standard deviation of reproducibility of the method* (3.20) and the *standard deviation due to operating and mounting conditions* (3.21)

$$\sigma_{tot} = \sqrt{\sigma_{R0}^2 + \sigma_{omc}^2}$$

**3.23
accuracy grade**

grade characterising three different classes of uncertainty in determining *sound power levels* (3.3) based on the *standard deviations of reproducibility of the method*, σ_{R0} (3.20)

Note 1 to entry: The grade classification provides an indication of the required measurement effort.

Note 2 to entry: It is described by typical upper bound values.

Note 3 to entry: σ_{R0} does not include uncertainty components like σ_{omc} and Δ_{sy} and consequently does not represent the total uncertainty.

3.24**expanded measurement uncertainty***U*

characteristic value identifying a range around the measurement result or calculation within which an estimate of values is expected to lie

4 Sound power level**4.1 Basic information**

The sound power level characterizes the mean airborne acoustic energy flow from the source into the environment for a given mounting and operating condition and represents an intrinsic acoustic characteristic of the source that is independent of the environment in which it is installed. It is often denoted as an A-weighted sound power level, L_{WA} , in dB.

4.2 Reasons for the determination of sound power levels

Example situations where the A-weighted sound power level of a machine, equipment and product can be of interest are:

- manufacturer noise emission declarations in the instructions and the sales literature according to regulations for machinery safety;
- customer need for input to sound exposure prediction models which can support legal requirements for carrying out a noise exposure risk assessment;
- customer need for comparison with the state of the art of noise emission, for comparing the data of competing machinery, equipment and products to support the “Buy Quiet” objective;
- checking the noise emission level of machinery, equipment and products in specifications regardless of the environment in which they operate.

4.3 Basic procedures for determining sound power levels

Sound pressure, sound intensity and vibratory velocity level measurements form the basis of different procedures to determine sound power level. These procedures include

- evaluation of the spatial mean-squared sound pressure built up in highly reflective environments (ISO 3741, ISO 3743-1, ISO 3743-2);
- comparison of the sound pressure levels in octave frequency bands of a noise source under test with those of a calibrated reference sound source (ISO 3747);
- evaluation of the flow of sound energy by a direct measurement of the sound intensity (ISO 9614-1, ISO 9614-2, ISO 9614-3) near the source or the free field approximation of the intensity through measurement of the squared sound pressure (ISO 3744, ISO 3745, ISO 3746) emitted by the source, both measurements carried out on an enveloping surface;
- evaluation of the partial flow of airborne sound energy emitted by vibrating solid structures of the machine, using measurements of the vibratory velocity over the surface of vibrating solid structures (ISO/TS 7849-1, ISO/TS 7849-2).

Microphones used to measure the sound pressure level at specific positions around the source under test measure the sum of the direct sound from the source and the contributions from other sound sources in the measurement room plus the sound which is reflected by walls, floor, ceiling and obstacles. Therefore, corrections to cope with these influences are required in practice. These are the background noise correction, K_1 , and the environmental correction, K_2 . Please refer to [Annex D](#) for examples of practical applications of ISO 3744 and ISO 3746.