

---

---

**Small craft — Permanently installed fuel  
systems**

*Petits navires — Systèmes à carburant installés à demeure*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 10088:2009

<https://standards.iteh.ai/catalog/standards/sist/507b5c8b-74b6-4120-9ed3-f48a446d4fc2/iso-10088-2009>



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 10088:2009

<https://standards.iteh.ai/catalog/standards/sist/507b5c8b-74b6-4120-9ed3-f48a446d4fc2/iso-10088-2009>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

Page

Foreword .....	iv
<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Terms and definitions .....</b>	<b>1</b>
<b>4 General requirements .....</b>	<b>3</b>
<b>4.1 Materials and design .....</b>	<b>3</b>
<b>4.2 Testing .....</b>	<b>4</b>
<b>4.3 Installation .....</b>	<b>4</b>
<b>5 Fuel pipes, hoses, connections and accessories .....</b>	<b>4</b>
<b>5.1 Fuel filling lines .....</b>	<b>4</b>
<b>5.2 Vent lines .....</b>	<b>5</b>
<b>5.3 Fuel distribution lines and fuel return lines .....</b>	<b>5</b>
<b>5.4 Hose fittings and hose clamping .....</b>	<b>6</b>
<b>5.5 Valves .....</b>	<b>7</b>
<b>5.6 Fuel filters .....</b>	<b>7</b>
<b>5.7 Labelling .....</b>	<b>7</b>
<b>Annex A (normative) Pressure testing .....</b>	<b>8</b>
<b>Bibliography .....</b>	<b>9</b>

[ISO 10088:2009](https://standards.iteh.ai/catalog/standards/sist/507b5c8b-74b6-4120-9ed3-f48a446d4fc2/iso-10088-2009)  
<https://standards.iteh.ai/catalog/standards/sist/507b5c8b-74b6-4120-9ed3-f48a446d4fc2/iso-10088-2009>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10088 was prepared by Technical Committee ISO/TC 188, *Small craft*.

This third edition cancels and replaces the second edition (ISO 10088:2001), which has been technically revised.

ITC STANDARD PREVIEW  
(standards.iteh.ai)  
<https://standards.iteh.ai/catalog/standards/sist/507b5c8b-74b6-4120-9ed3-f48a446d4fc2/iso-10088-2009>

# Small craft — Permanently installed fuel systems

## 1 Scope

This International Standard specifies the requirements for the design, materials, construction, installation and testing of permanently installed fuel systems as installed for internal combustion engines.

It applies to all parts of permanently installed diesel and petrol fuel systems as installed, from the fuel fill opening to the point of connection with the propulsion or auxiliary engine on inboard- and outboard-powered small craft of up to 24 m hull length.

Requirements for the design, materials, construction and testing of permanently installed fixed fuel tanks are given in ISO 21487.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1817, *Rubber, vulcanized — Determination of the effect of liquids*

[https://standards.iteh.ai/catalog/standards/sist/507b5c8b-74b6-4120-9ed3-](https://standards.iteh.ai/catalog/standards/sist/507b5c8b-74b6-4120-9ed3-89441451765e/iso-10088-2009)

ISO 7840:2004, *Small craft — Fire-resistant fuel hoses*

ISO 8469, *Small craft — Non-fire-resistant fuel hoses*

ISO 8846, *Small craft — Electrical devices — Protection against ignition of surrounding flammable gases*

ISO 10133, *Small craft — Electrical systems — Extra-low-voltage d.c. installations*

ISO 11105, *Small craft — Ventilation of petrol engine and/or petrol tank compartments*

ISO 11192, *Small craft — Graphical symbols*

ISO 13297, *Small craft — Electrical systems — Alternating current installations*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **accessible**

capable of being reached for inspection, removal or maintenance without removal of permanent craft structure

**NOTE** Hatches are not regarded as permanent craft structures in this sense, even if tools such as wrenches or screwdrivers are needed to open them. Hatches for inspection or maintenance of fuel tanks may be covered by uncut carpet, provided that all tank fittings can be inspected and maintained through other openings.

**3.2**  
**readily accessible**

capable of being reached quickly and safely for effective use under emergency conditions without the use of tools

**3.3**  
**permanently installed**

securely fastened so that tools need to be used for removal

**3.4**  
**anti-siphon valve**

demand valve which can be opened only by fuel pump suction to withdraw fuel from the tank and which will remain closed when the fuel pump is not operating, preventing siphon action created by a break or leakage at any point in the fuel distribution system

**3.5**  
**static floating position**

attitude in which the boat floats in calm fresh water according to light craft mass  $m_{LCC}$  as stated in ISO 8666 including a fuel tank filled to rated capacity and excluding all non-permanently attached interior and exterior equipment

**3.6**  
**petrol**

hydrocarbon fuel, or blend thereof, which is liquid at atmospheric pressure and is used in spark-ignition engines

**3.7**  
**diesel**

hydrocarbon fuel, or blend thereof, which is liquid at atmospheric pressure and is used in compression-ignition engines


**3.8**  
**spud**

rigid pipe or spigot used for the connection of pipes and hoses to tanks or components such as filters and pumps

**3.9**  
**swaged sleeve**

permanently attached fuel hose end fitting obtained by applying even compression to a metal sleeve or ferrule, sufficient to make the inner lining of the hose take up the shape of the insert and create a pressure seal

NOTE See Figure 1.



**Key**

- 1 hose
- 2 sleeve

**Figure 1 — Permanently attached end fitting**

**3.10****sleeve and threaded insert**

permanently attached fuel hose end fitting made by screwing an insert sleeve with threads into the hose and applying even compression to a metal sleeve or ring to secure the hose in place

NOTE This type of connection can be made with the sleeve placed on the outside of the hose and then screwing the threaded insert into the inner lining.

**3.11****compartment**

cabin or enclosure able to be closed to the outside of the craft

**3.12****craft's ground**

ground which is established by a conducting connection (intended or accidental) with the common ground (potential of the earth's surface), including any conductive part of the wetted surface of the hull

NOTE "Ground" is also known as "earth".

**4 General requirements****4.1 Materials and design**

**4.1.1** Individual components of the fuel system, and the fuel system as a whole, shall be designed to withstand the combined conditions of pressure, vibration, shocks, corrosion and movement encountered under normal operating conditions and storage.

**4.1.2** Each component of the fuel system, and the fuel system as a whole, shall be capable of operation within an ambient temperature range of  $-10^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$ , without failure or leakage, and be capable of being stored without operation within an ambient temperature range of  $-30^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$ , without failure or leakage.

**4.1.3** All materials used in the fuel system shall be resistant to deterioration by its designated fuel and to other liquids or compounds with which it may come into contact under normal operating conditions, e.g. grease, lubricating oil, bilge solvents and sea water.

**4.1.4** Petrol engine compartments and petrol tank compartments shall have ventilation and ignition protection in accordance with ISO 11105 and ISO 8846.

**4.1.5** The only outlets for drawing fuel from the fuel system shall be

- plugs in petrol filter bowls intended solely for the purpose of servicing the filter,
- plugs or valves in diesel filter bowls intended solely for the purpose of servicing the filter.

NOTE Tank openings are covered by ISO 21487.

**4.1.6** Each metal or metallic plated component of a petrol fuel fill system and fuel tank which is in contact with the fuel shall be grounded so that its resistance to the craft's ground is less than one ohm.

Grounding wires shall not be clamped between a hose and its pipe or spud.

**4.1.7** Fuel filling systems shall be designed to avoid blowback of fuel through the fill fitting. Fuel systems shall be tested in accordance with 4.2.3.

**4.1.8** Provision shall be made to prevent fuel overflow from the vent opening from entering the craft or the environment.

**4.1.9** All fuel system components in the engine compartment – excluding permanently installed fuel tanks, which are tested in accordance with ISO 21487 – (e.g. filters, water separators, and hoses) shall individually, or as installed in the craft, be capable of withstanding a 2,5 min fire test as specified in ISO 7840:2004, Annex A.

Fasteners supporting metal fuel lines constitute an exception to this requirement.

**4.1.10** Copper-base alloy fittings may be used for aluminium tanks if protected by a galvanic barrier to reduce galvanic corrosion.

**4.1.11** A means to determine fuel tank level or quantity shall be provided.

## 4.2 Testing

**4.2.1** After installation, the fuel system as a whole shall pass the pressure test specified in Annex A.

**4.2.2** Fuel system components that are small enough, such as fuel valves, and required to be fire tested according to 4.1.9 shall be tested as specified in ISO 7840:2004, Annex A, with the lower part mounted 250 mm above the surface of liquid in a pan of which the sides extend beyond the component by 150 mm. The component to be tested shall be a complete assembly and include all accessories intended to be attached directly to the component.

**4.2.3** There shall be no blow back of fuel through the fill fitting when filling at a rate of 30 l/min from 25 % to 75 % of the capacity on the tank label. For fuel tanks of 100 l capacity or less, the fill rate may be reduced to 20 l/min. (see 4.1.7). The test to determine compliance with this shall be performed on at least one craft or a representative installation.

## 4.3 Installation

**4.3.1** The fuel system shall be permanently installed. All component parts, except small connectors and fittings and short sections of flexible hoses, shall be independently supported.

**4.3.2** All valves and other components intended to be operated or observed during normal operation of the craft, or for emergency purposes, shall be readily accessible. All other components of the system shall be accessible. Tanks need not be accessible for removal.

**4.3.3** The clearance between a petrol fuel tank and a combustion engine shall not be less than 100 mm.

**4.3.4** The clearance between a petrol tank and dry exhaust component(s) shall not be less than 250 mm, unless an equivalent thermal barrier is provided.

**4.3.5** Fuel system electrical components shall be installed in accordance with ISO 10133 or ISO 13297.

**4.3.6** Fuel tanks and components of petrol fuel systems shall not be installed directly above batteries unless the batteries are protected against the effects of fuel leakage.

## 5 Fuel pipes, hoses, connections and accessories

### 5.1 Fuel filling lines

**5.1.1** The minimum inside diameter of the fill pipe system shall be 31,5 mm and the minimum inside diameter of fuel filling hoses shall be 38 mm.

**5.1.2** Fuel filling hoses located in the engine compartment shall be fire resistant, of type A1 or A2 in accordance with ISO 7840. Fuel fill hoses outside the engine compartment shall be of either type A1 or A2 in accordance with ISO 7840, or of type B1 or B2 in accordance with ISO 8469.



- 5.1.3** Fuel filling lines shall be self-draining to the tank when the craft is in its static floating position.
- 5.1.4** Fuel filling lines shall run as directly as practicable, preferably in a straight line from the deck plate or equivalent filling point to the tank.
- 5.1.5** The fuel filling system shall be designed so that accidental fuel spillage does not enter the craft when it is in its static floating position.
- 5.1.6** The distance between compartment ventilation openings and fuel fill openings shall be at least 400 mm, except where the craft's coaming, superstructure or hull creates a barrier to prevent fuel vapour entering the craft through the ventilation opening.
- 5.1.7** The fuel filling point shall be marked "petrol" or "diesel" and/or with a symbol specified in ISO 11192 to identify the type of fuel to be used.

## 5.2 Vent lines

- 5.2.1** Each fuel tank shall have a separate vent line.
- 5.2.2** Vent hoses located in the engine compartment shall be fire resistant, of type A1 or A2 in accordance with ISO 7840. Vent hoses outside the engine compartment shall be of either type A1 or A2 in accordance with ISO 7840, or type B1 or B2 in accordance with ISO 8469.
- 5.2.3** The cross-sectional area of any vent component shall not be less than 95 mm<sup>2</sup>.
- 5.2.4** Vent lines shall not have valves other than those that permit free flow of air and prevent flow of liquid (fluid) both in and out of the tank.
- 5.2.5** Vent lines shall be self-draining when the craft is in its static floating position.
- 5.2.6** The distance between compartment ventilation openings and fuel vent openings shall be at least 400 mm, except where the craft's coaming, superstructure or hull creates a barrier to prevent fuel vapour entering the craft through the ventilation opening.
- 5.2.7** The vent line shall be arranged to minimize intake of water without restricting the release of vapour or intake of air and shall not allow fuel or vapour overflow to enter the craft.
- 5.2.8** The vent-line termination or a gooseneck in the vent-line routing shall be arranged at sufficient height to prevent spillage of fuel through the vent line during filling and entry of water under normal operating conditions of the craft.
- On mono-hull sailing craft, the vent line shall be arranged to minimize the risk of fuel spillage or entry of water through the vent when sailing at a heel angle of up to 30°.
- 5.2.9** The vent lines on all fuel installations shall incorporate a flame arrester device that fulfils the requirements in 4.1.7 and 5.2.3.
- 5.2.10** For components installed in the vent line, the requirements in 5.2 apply.
- 5.2.11** For vent-line components in the engine compartment, with the ability to capture fuel, the fire test requirements in 4.1.9 apply.

## 5.3 Fuel distribution lines and fuel return lines

- 5.3.1** Metal fuel distribution and return lines shall be made of seamless annealed copper or copper–nickel or equivalent metal with a nominal wall thickness of at least 0,8 mm. Aluminium lines may be used for diesel fuel.