

---

---

**Information technology — Coding of  
audio-visual objects —**

**Part 4:  
Conformance testing**

**AMENDMENT 14: BSAC conformance**

**iTeh STANDARD PREVIEW**

*(standards.iteh.ai)* *Technologies de l'information — Codage des objets audiovisuels —  
Partie 4: Essai de conformité*

*ISO/IEC 14496-4:2004/Amd.14:2007*  
*AMENDEMENT 14: Conformité BSAC*  
<https://standards.iteh.ai/catalog/standards/sist/232c1c97-20e5-4790-87a7-578a53071e4b/iso-iec-14496-4-2004-amd-14-2007>

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 14496-4:2004/Amd 14:2007](https://standards.iteh.ai/catalog/standards/sist/232c1c97-20e5-4790-87a7-578a53071e4b/iso-iec-14496-4-2004-amd-14-2007)

<https://standards.iteh.ai/catalog/standards/sist/232c1c97-20e5-4790-87a7-578a53071e4b/iso-iec-14496-4-2004-amd-14-2007>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 14 to ISO/IEC 14496-4:2004 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

It specifies the conformance testing of BSAC multichannel and BSAC extensions as specified in ISO/IEC 14496-3:2005/Amd.2:2006 and ISO/IEC 14496-3:2005/Amd.5:2007.

<https://standards.iteh.ai/catalog/standards/sist/232c1c97-20e5-4790-87a7-578a53071e4b/iso-iec-14496-4-2004-amd-14-2007>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 14496-4:2004/Amd 14:2007](https://standards.iteh.ai/catalog/standards/sist/232c1c97-20e5-4790-87a7-578a53071e4b/iso-iec-14496-4-2004-amd-14-2007)

<https://standards.iteh.ai/catalog/standards/sist/232c1c97-20e5-4790-87a7-578a53071e4b/iso-iec-14496-4-2004-amd-14-2007>

# Information technology — Coding of audio-visual objects —

## Part 4: Conformance testing

### AMENDMENT 14: BSAC conformance

*In subclause 6.6.6 ER BSAC, replace:*

However, only mono or 2-channel stereo objects are supported.

*with:*

The multichannel ER BSAC object is supported with BSAC channel extension payload.

*In subclause 6.6.6.2.2 Test procedure, replace “Table 52” with “Table 52.A” (three occurrences).*

**(standards.iteh.ai)**

*At the end of subclause 6.6.6.2.2 Test procedure, add the following paragraph.*

<https://standards.iteh.ai/catalog/standards/sist/232c1c97-20e5-4790-87a7-976a560c9149/iso-14496-4-2007-amd-14-2007>

The conformance bitstreams corresponding to BSAC Extensions for the multichannel extension are the ‘er\_bs09’ ~ ‘er\_bs11’ as listed in Table 52.A. The conformance testing criterion for the multichannel extension is same as ER BSAC.

The conformance bitstreams corresponding to BSAC Extensions for the SBR extension are listed in Table 52.B. The conformance testing criterion for the SBR extension is specified in subclause 6.6.17. The SBR conformance test method of BSAC Extensions is different from that of HE-AAC in terms of parsing the SBR payload. In figure AMD8-2, the ‘Read store/input’ module is to parse the SBR payload from BSAC Extensions payload which can be realized by either decoding the whole BSAC Extensions payload or seeking the ‘sync\_word’ in the extensions payload.

The ‘coreSetup’ of naming convention for BSAC Extensions is the ‘xx\_sbr\_<nchan>\_<fs>’ where the ‘nchan’ represents the number of channel and the ‘fs’ is the sampling rate of SBR tool. By comparing the decoded wave with the reference wave for the different ‘highestLayer’, the ‘HF overlap’ decoding module specified in 14496-3:2005 subclause 4.5.2.11.4 can be checked if it’s implemented correctly. The testing criterion with ‘Diffmax’ and ‘RMS max’ shall be applied only when the bitstream is decoded up to top layer.

In subclause 6.6.6.2.3 Test sequences, change the table index from Table 52 to Table 52.A and extend Table 52.A with:

**Table 52.A — ER BSAC Object Type Test Compressed data for Mobile Audio Internetworking Profile Level 1-3 and Natural Audio Profile Level 1-2**

File base name	Content	Base Layer Bitrate (kbit/s)	Top Bitrate (kbit/s)	Top Layer (n)	number of ES	ES Bitrate (kbit/s)	number of channel	Intensity	MS	TNS	PNS	epConfig	SB A	highestLayer	Test Procedure
.....															
er_bs09_ep0	music	32	200/320	24/48	1	200/320	5 {1,0,3} (**)		Yes	Yes		0		24/48	
er_bs09_ep1	music	32	200/320	24/48	6	BL, 48/96, BL, 24/48, BL, 48/96	5 {1,0,3} (**)		Yes	Yes		1		0, 24/48, 0, 24/48, 0, 24/48 (*)	
er_bs10_ep0	music	32	120/192	24/48	1	120/192	3 {1,0} (**)		Yes	Yes		0		24/48	
er_bs10_ep1	music	32	120/192	24/48	4	BL, 48/96 BL, 24/48	3 {1,0} (**)		Yes	Yes		1		0, 24/48, 0, 24/48 (*)	
er_bs11_ep0	music	32	300/480	24/48	1	300/480	{1,0,4,3,5} (**)		Yes	Yes		0		24/48	
er_bs11_ep1	music	32	300/480	24/48	9	BL, 48/96, BL, 24/48, ,20/32 ,BL, 48/96, BL, 48/96	8 {1,0,4,3,5} (**)		Yes	Yes		1		0, 24/48, 0, 24/48, 0,4/16, 0, 24/48, 0, 24/48 (*)	

\* : The definition of 'highestLayer' for this bitstream is the highest layer of each BSAC extension payloads.

\*\* : The numbers in the bracket represent the 'channel\_configuration\_index' of each BSAC extension payload as defined in ISO/IEC 14496-3:2005, subclause 4.5.2.6.2.1.1, Table 4.84B - channel\_configuration\_index.

After Table 52.A in subclause 6.6.6.2.3 Test sequences, add the following table:

**Table 52.B — ER BSAC Object Type with SBR tool**

file base name	tool	content	bitrate (kbit/s)	nch	Core/SBR Sampling rate	QMF Identification	QMF Accuracy	Envelope Adjuster Accuracy	Grid control tests	Header Change Tests	Inverse Filtering Tests	Additional Sines Tests	CRC	Diff max	RMS max (linear value)	highestLayer	test procedure
er_bs12_sbr	twi	none	64	1	24/48kHz	y	y	-	-	-	-	y	-	-	-	0, 24, 48	
er_bs13_sbr	qmf	Sine Sweep	64	1	16/32kHz 22/44kHz 24/48kHz	-	Y	-	-	-	-	-	-	5	1.4	0, 24, 48	maxDiff/RMS
er_bs14_sbr	e	rectangle * 10Hz sine	128	2	16/32kHz 22/44kHz 24/48kHz	-	-	y	-	-	-	-	y <sup>A</sup>	90	2.0	0, 24, 48	maxDiff/RMS
er_bs15_sbr	gh	rectangle * 10Hz sine	64/128	1/2	16/32kHz 22/44kHz 24/48kHz	-	-	-	y	y	-	-	-	51	1.5	0, 24, 48	maxDiff/RMS
er_bs16_sbr	i	rectangle + noise	64/128	1/2	16/32kHz 22/44kHz 24/48kHz	-	-	-	-	-	y	-	y <sup>A</sup>	36	3.4	0, 24, 48	maxDiff/RMS
er_bs17_sbr	s	noise	64/128	1/2	16/32kHz 22/44kHz 24/48kHz	-	-	-	-	-	-	y	-	120	1.9	0, 24, 48	maxDiff/RMS
er_bs18_sbr	cm	music	64/128	1/2	16/32kHz 22/44kHz 24/48kHz	-	-	-	-	-	-	-	-	-	-	0, 24, 48	
er_bs19_sbr	cm	music	320	5.1	24/48kHz	-	-	-	-	-	-	-	-	-	-	24/48	
er_bs20_sbr	sig0	music	128/320	2/5	24/48kHz	-	-	-	-	-	-	-	-	-	-	24/48	
er_bs21_sbr	sig1	music	128/320	2/5	24/48kHz	-	-	-	-	-	-	-	-	-	-	24/48	
er_bs22_sbr	sig2	music	128/320	2/5	24/48kHz	-	-	-	-	-	-	-	-	-	-	24/48	
er_bs23_sbr	sr	music	128	2	16/32kHz 22/44kHz 24/48kHz 48/96kHz	-	-	-	-	-	-	-	-	-	-	24/48	

**A** CRC enabled for 32 kHz testvectors

After 6.6.6.1.2.2.3 general header(), add the following text:

**6.6.6.1.2.2.4 extended\_bsac\_raw\_data\_block()**

**channel\_configuration\_index** : shall be encoded with the value which is less than 6

The restrictions on the extended\_bsac\_raw\_data\_block() shall be applied as those of bsac\_raw\_data\_block().

In subclause 6.7.2.2 (Test procedure), extend Table 94 (EP tool test sequences) with:

Table 94 — EP tool test sequences

header_crclen				
header_rate				
header_protection		0	0	0
class_output_order				
class_reordered_output		0	0	0
class_crclen		10,10,9, 10,10,10	10,10,9, 10,10,9, 10	10,10,9,10, 8,10,10,10,10
class_rate		20,0,16, 0,8,0	20,0,16, 0	20,0,16,0, 0,8,0,8,0
class_length				
number_of_bits_for_length		10,14,9,13,10, 0	10,14,9,0	10,14,9,13, 9,10,13,10,0
class_optional		0,0,0,0,0,0	0,0,0,0,0	0,0,0,0,0, 0,0,0,0,0
interleave_switch				
termination_switch		0,0,0,0,0,0,0,0,0,0	0,0,0,0,0,0,0,0	0,0,0,0,0,0,0,0,0,0, 0,0,0,0,0,0,0,0,0,0
fec_type		0,0,0,0,0,0,0,0,0,0	0,0,0,0,0,0,0,0	0,0,0,0,0,0,0,0,0,0, 0,0,0,0,0,0,0,0,0,0
concatenated_flag				
crc_len_escape		0,0,0,0,0,0,0,0,0,0,0,0	0,0,0,0,0,0,0,0,0,0	0,0,0,0,0,0,0,0,0,0, 0,0,0,0,0,0,0,0,0,0
rate_escape		0,0,0,0,0,0,0,0,0,0,0,0	0,0,0,0,0,0,0,0,0,0	0,0,0,0,0,0,0,0,0,0, 0,0,0,0,0,0,0,0,0,0
length_escape		1,1,1,1,1,1,1,1,1,1,1,1	1,1,1,1,1,1,1,1,1,1	1,1,1,1,1,1,1,1,1,1, 1,1,1,1,1,1,1,1,1,1
number_of_class		6	4	9
number_of_concatenated_frame		1	1	1
bit_stuffing		1	1	1
interleave_type		1	1	1
number_of_predefinition_set		1	1	1
SamplingFrequencyIndex (if not specified: same as for epConfig=0,1)		-	-	-
directMapping		1	1	1
epConfig		3	3	3
layer		-	-	-
epSetup				
coreSetup				
er_bs09				
er_bs10				
er_bs11				

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO/IEC 14496-4:2008/Amd.14:2007  
<https://standards.iteh.ai/catalog/standards/sist/2c97-20e5-4790-87a7-578a53071e4b/iso-iec-14496-4-2008-amd-14-2007>



In subclause 6.12.1, extend Table 104a with:

Table 104a

Object type	sequence name	Main Audio Profile				Scalable Audio Profile				Speech Profile		Synthetic Audio Profile		
		Level 1	2	3	4	1	2	3	4	1	2	1	2	3
ER BSAC														
	er_bs01_ep0													
	....													
	er_bs09_ep0													
	er_bs09_ep1													
	er_bs09_ep3													
	er_bs10_ep0													
	er_bs10_ep1													
	er_bs10_ep3													
	er_bs11_ep0													
	er_bs11_ep1													
	er_bs11_ep3													

iTech STANDARD PREVIEW  
(standards.iteh.ai)

In subclause 6.12.1, extend Table 104b with:

ISO/IEC 14496-4:2004/Amd.14:2007  
Table 104b  
<https://standards.iteh.ai/catalog/standards/sist/252c1c97-20e5-4790-87a7-578a53071c4b/iso-iec-14496-4-2004-amd-14-2007>

Object type	sequence name	High Quality Audio Profile								Low Delay Audio Profile								Natural Audio Profile				Mobile Audio Networking Profile						
		Level 1	2	3	4	5	6	7	8	1	2	3	4	5	6	7	8	1	2	3	4	1	2	3	4	5	6	
ER BSAC																												
	er_bs01_ep0																											
	....																											
	er_bs09_ep0																											
	er_bs09_ep1																											
	er_bs09_ep3																											
	er_bs10_ep0																											
	er_bs10_ep1																											
	er_bs10_ep3																											
	er_bs11_ep0																											
	er_bs11_ep1																											
	er_bs11_ep3																											