
**Information technology —
Telecommunications and information
exchange between systems — Services
for Computer Supported
Telecommunications Applications (CSTA)
Phase III**

iTeh STANDARD PREVIEW

(standards.iteh.ai)
*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Services pour applications en
télécommunications supportées par ordinateur (CSTA) en phase III*

[ISO/IEC 18051:2007](https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007)

[https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-
edce8c754e67/iso-iec-18051-2007](https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 18051:2007](https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007)

<https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	xi
Introduction	xii
1 Scope	1
2 Conformance	1
2.1 Switching Function	1
2.1.1 Conformant Services	2
2.1.2 Conformant Events	2
2.1.3 CSTA Profiles	2
2.1.4 Support of Service Requests And Manual Mode	5
2.2 Special Resource Function Conformance	5
2.2.1 Conformant Services	6
2.2.2 Conformant Events	6
2.2.3 Support of Service Requests And Manual Mode	6
2.3 Computing Function Conformance	6
3 References	7
4 Definitions and Abbreviations	8
5 Functional Architecture	8
6 CSTA Operational Model	8
6.1 Switching Sub-Domain Model	9
6.1.1 Device	9
6.1.2 Call	42
6.1.3 Connection	49
6.1.4 Call State Definitions	53
6.1.5 Referencing Devices, Elements, Appearances and Device Configurations	54
6.1.6 Management of Dynamically-Assigned Identifiers	56
6.2 I/O Services	56
6.2.1 Data Path Definition	57
6.2.2 I/O Registration Services	58
6.2.3 Data Path States and Operational Model	58
6.2.4 I/O Services Example	58
6.3 Call Detail Record (CDR) Services	59
6.3.1 CDR Services Examples	59
6.4 Capabilities Exchange	61
6.4.1 Switching Function Capabilities	62
6.4.2 Device Capabilities	62
6.4.3 Dynamic Feature Availability	62
6.5 Switching Function Information Synchronization	63
6.5.1 Switching Function Level Information	63
6.5.2 Device Level Information	63
6.5.3 Call Level Information	63
6.6 Status Reporting Services	64
6.6.1 System Status	64
6.6.2 Monitoring	65
6.6.3 Snapshot Services	69
6.7 Additional Services, Features & Behaviour	69
6.7.1 Forwarding	69
6.7.2 Connection Failure	71
6.7.3 Recall	73
6.7.4 Call Back	74
6.7.5 External Calls	74
6.7.6 Tracking a Diverted Call	75

6.7.7 Media Stream Access	75
6.7.8 Routeing Services	79
6.7.9 Device Maintenance	84
6.7.10 Prompting	84
6.7.11 Telephony Tones Features	84
6.7.12 DTMF and Rotary Pulse Digits Features	85
6.7.13 Data Collection Services	85
7 Association Establishment	85
7.1 Implicit Association created using CSTA System Status service (initiated by Switching Function)	86
7.2 Implicit Association created using CSTA Request System Status service	86
7.3 Explicit Association created using ACSE	87
7.4 Explicit Association created using Ecma Application Session (ECMA-354) Services	88
8 Security Service	89
9 Generic Service Requirements	89
9.1 Service Request	89
9.2 Service Response (Acknowledgements)	90
9.2.1 Positive Acknowledgement Models	90
9.2.2 Negative Acknowledgement	91
9.3 Diagnostic Error Definitions	91
9.3.1 Error Categories	91
9.3.2 Error Values	92
9.4 Vendor Specific Extensions	93
9.4.1 Private Data	93
9.4.2 Escape Services and Private Event	94
9.5 General Services and Event Functional Requirements	95
9.5.1 Services	95
9.5.2 Events	97
10 CSTA Device Identifier Formats	97
10.1 Device Identifier Formats	97
10.1.1 Diable Digits	98
10.1.2 Switching Function Representation	99
10.1.3 Device Number	101
10.1.4 URI Representation	101
10.2 Functional Requirements	101
11 Template Descriptions	102
11.1 Service Template	102
11.1.1 Service Description	102
11.1.2 Service Request	103
11.1.3 Service Response	103
11.1.4 Operational Model	103
11.2 Event Template	104
11.2.1 Event Description	104
11.2.2 Event Parameters	104
11.2.3 Event Causes	104
11.2.4 Functional Requirements	104
11.3 Parameter Type Template	104
11.3.1 Parameter Type Description	105
11.3.2 Format	105
11.3.3 Functional Requirements	105
12 Parameter Types	105
12.1 Definitions	105
12.2 Defined Parameter Types	106
12.2.1 AccountInfo	107
12.2.2 AgentPassword	107

<https://standards.iteh.ai/catalog/standards/sis/725a983a-6aca-40d5-8116-edce8c754e67/iso-iec-18051-2007>
 ITeH STANDARD PREVIEW
 (standards.iteh.ai)

12.2.3 AuthCode	107
12.2.4 CallCharacteristics	108
12.2.5 CallLinkageData	108
12.2.6 CallQualifyingData	110
12.2.7 ChargingInfo	110
12.2.8 ConnectionInformation	111
12.2.9 ConnectionList	112
12.2.10 CorrelatorData	112
12.2.11 CSTAPrivateData	113
12.2.12 CSTASecurityData	114
12.2.13 DeviceHistory	114
12.2.14 ErrorValue	115
12.2.15 EventCause	126
12.2.16 LanguagePreferences	129
12.2.17 LocalConnectionState	130
12.2.18 MediaCallCharacteristics	130
12.2.19 MediaServiceType	132
12.2.20 MessageInfo	133
12.2.21 MonitorFilter	134
12.2.22 ServicesPermitted	134
12.2.23 SimpleCallState	135
12.2.24 SubjectOfCall	135
12.2.25 SystemStatus	136
12.2.26 TimelInfo	136
12.2.27 UserData	136
12.3 Identifier Parameter Types	137
12.3.1 AgentID	138
12.3.2 AssociatedCalledDeviceID	138
12.3.3 AssociatedCallingDeviceID	139
12.3.4 AuditoryApparatusID	ISO/IEC 18051:2007 139
12.3.5 ButtonID	https://standards.iteh.ai/catalog/standards/sist/725a983a-6aca-40d5-8196-edcc8e754e67/iso-iec-18051-2007 140
12.3.6 CalledDeviceID	140
12.3.7 CallingDeviceID	140
12.3.8 CDRCrossRefID	141
12.3.9 ConnectionID	141
12.3.10 DCCollCrossRefID	143
12.3.11 DeviceID	143
12.3.12 DisplayID	143
12.3.13 EscapeRegisterID	143
12.3.14 HookswitchID	144
12.3.15 IOCrossRefID	144
12.3.16 IORegisterReqID	144
12.3.17 LampID	144
12.3.18 MediaServiceInstanceID	145
12.3.19 MediaStreamID	145
12.3.20 MessageID	145
12.3.21 MonitorCrossRefID	145
12.3.22 NetworkCalledDeviceID	145
12.3.23 NetworkCallingDeviceID	146
12.3.24 RedirectionDeviceID	146
12.3.25 ResourceID	147
12.3.26 RingerID	147
12.3.27 RoutingCrossRefID	147
12.3.28 RouteRegisterReqID	148
12.3.29 ServiceCrossRefID	148
12.3.30 SubjectDeviceID	148
12.3.31 SysStatRegisterID	149

13 Capability Exchange Services	149
13.1 Services	149
13.1.1 Get CSTA Features	149
13.1.2 Get Logical Device Information	151
13.1.3 Get Physical Device Information	161
13.1.4 Get Switching Function Capabilities	165
13.1.5 Get Switching Function Devices	180
13.1.6 Switching Function Devices	182
14 System Services	186
14.1 Registration Services	186
14.1.1 Change System Status Filter	186
14.1.2 System Register	188
14.1.3 System Register Abort	190
14.1.4 System Register Cancel	191
14.2 Services	193
14.2.1 Request System Status	193
14.2.2 System Status	195
14.2.3 Switching Function Capabilities Changed	196
14.2.4 Switching Function Devices Changed	197
15 Monitoring Services	198
15.1 Services	198
15.1.1 Change Monitor Filter	199
15.1.2 Monitor Start	200
15.1.3 Monitor Stop	204
16 Snapshot Services	205
16.1 Services	205
16.1.1 Snapshot Call	205
16.1.2 Snapshot Device	209
16.1.3 Snapshot CallData	211
16.1.4 Snapshot DeviceData	213
17 Call Control Services & Events	215
17.1 Services	215
17.1.1 Accept Call	216
17.1.2 Alternate Call	218
17.1.3 Answer Call	221
17.1.4 Call Back Call-Related	223
17.1.5 Call Back Message Call-Related	226
17.1.6 Camp On Call	229
17.1.7 Clear Call	231
17.1.8 Clear Connection	234
17.1.9 Conference Call	237
17.1.10 Consultation Call	241
17.1.11 Deflect Call	246
17.1.12 Dial Digits	249
17.1.13 Directed Pickup Call	252
17.1.14 Group Pickup Call	255
17.1.15 Hold Call	259
17.1.16 Intrude Call	261
17.1.17 Join Call	265
17.1.18 Make Call	269
17.1.19 Make Predictive Call	274
17.1.20 Park Call	279
17.1.21 Reconnect Call	282
17.1.22 Retrieve Call	285
17.1.23 Send Message	286

iTech STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007>

17.1.24 Single Step Conference Call	291
17.1.25 Single Step Transfer Call	295
17.1.26 Transfer Call	298
17.2 Events	301
17.2.1 Bridged	301
17.2.2 Call Cleared	303
17.2.3 Conferenced	306
17.2.4 Connection Cleared	311
17.2.5 Delivered	315
17.2.6 Digits Dialed	320
17.2.7 Diverted	322
17.2.8 Established	327
17.2.9 Failed	332
17.2.10 Held	337
17.2.11 Network Capabilities Changed	339
17.2.12 Network Reached	342
17.2.13 Offered	346
17.2.14 Originated	351
17.2.15 Queued	354
17.2.16 Retrieved	358
17.2.17 Service Initiated	359
17.2.18 Transferred	362
18 Call Associated Features	366
18.1 Services	366
18.1.1 Associate Data	367
18.1.2 Cancel Telephony Tones	369
18.1.3 Change Connection Information	370
18.1.4 Generate Digits	373
18.1.5 Generate Telephony Tones	375
18.1.6 Send User Information	377
18.2 Events	379
18.2.1 Call Information	380
18.2.2 Charging	382
18.2.3 Digits Generated	383
18.2.4 Telephony Tones Generated	384
18.2.5 Service Completion Failure	386
19 Media Attachment Services & Events	389
19.1 Services	389
19.1.1 Attach Media Service	389
19.1.2 Detach Media Service	392
19.2 Events	395
19.2.1 Media Attached	395
19.2.2 Media Detached	396
20 Routing Services	398
20.1 Registration Services	399
20.1.1 Route Register	399
20.1.2 Route Register Abort	401
20.1.3 Route Register Cancel	402
20.2 Services	403
20.2.1 Re-Route	403
20.2.2 Route End	404
20.2.3 Route Reject	406
20.2.4 Route Request	408
20.2.5 Route Select	410
20.2.6 Route Used	412

21 Physical Device Features	414
21.1 Services	414
21.1.1 Button Press	415
21.1.2 Get Auditory Apparatus Information	416
21.1.3 Get Button Information	419
21.1.4 Get Display	420
21.1.5 Get Hookswitch Status	422
21.1.6 Get Lamp Information	424
21.1.7 Get Lamp Mode	426
21.1.8 Get Message Waiting Indicator	428
21.1.9 Get Microphone Gain	429
21.1.10 Get Microphone Mute	430
21.1.11 Get Ringer Status	432
21.1.12 Get Speaker Mute	434
21.1.13 Get Speaker Volume	435
21.1.14 Set Button Information	436
21.1.15 Set Display	437
21.1.16 Set Hookswitch Status	440
21.1.17 Set Lamp Mode	441
21.1.18 Set Message Waiting Indicator	442
21.1.19 Set Microphone Gain	444
21.1.20 Set Microphone Mute	445
21.1.21 Set Ringer Status	446
21.1.22 Set Speaker Mute	448
21.1.23 Set Speaker Volume	449
21.2 Events	451
21.2.1 Button Information	451
21.2.2 Button Press	452
21.2.3 Display Updated	452
21.2.4 Hookswitch	454
21.2.5 Lamp Mode	454
21.2.6 Message Waiting	455
21.2.7 Microphone Gain	456
21.2.8 Microphone Mute	457
21.2.9 Ringer Status	457
21.2.10 Speaker Mute	458
21.2.11 Speaker Volume	459
22 Logical Device Features	460
22.1 Services	460
22.1.1 Call Back Non-Call-Related	461
22.1.2 Call Back Message Non-Call-Related	462
22.1.3 Cancel Call Back	463
22.1.4 Cancel Call Back Message	465
22.1.5 Get Agent State	466
22.1.6 Get Auto Answer	468
22.1.7 Get Auto Work Mode	469
22.1.8 Get CallBack	470
22.1.9 Get Caller ID Status	472
22.1.10 Get Do Not Disturb	473
22.1.11 Get Forwarding	474
22.1.12 Get Last Number Dialed	478
22.1.13 Get Routeing Mode	479
22.1.14 Set Agent State	480
22.1.15 Set Auto Answer	484
22.1.16 Set Auto Work Mode	486
22.1.17 Set Caller ID Status	487

iTeh STANDARD PREVIEW

(standards.iteh.ai)

[ISO/IEC 18051:2007](https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007)

<https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007>

22.1.18 Set Do Not Disturb	489
22.1.19 Set Forwarding	490
22.1.20 Set Routeing Mode	492
22.2 Events	494
22.2.1 Agent Busy	494
22.2.2 Agent Logged Off	495
22.2.3 Agent Logged On	496
22.2.4 Agent Not Ready	497
22.2.5 Agent Ready	498
22.2.6 Agent Working After Call	499
22.2.7 Auto Answer	500
22.2.8 Auto Work Mode	501
22.2.9 Call Back	502
22.2.10 Call Back Message	502
22.2.11 Caller ID Status	503
22.2.12 Do Not Disturb	503
22.2.13 Forwarding	504
22.2.14 Routeing Mode	506
23 Device Maintenance Events	507
23.1 Events	507
23.1.1 Back In Service	507
23.1.2 Device Capabilities Changed	508
23.1.3 Out Of Service	508
23.1.4 Partially In Service	509
24 I/O Services	510
24.1 Registration Services	511
24.1.1 I/O Register	511
24.1.2 I/O Register Abort	512
24.1.3 I/O Register Cancel	513
24.2 I/O Services	514
24.2.1 Data Path Resumed	515
24.2.2 Data Path Suspended	516
24.2.3 Fast Data	517
24.2.4 Resume Data Path	519
24.2.5 Send Broadcast Data	520
24.2.6 Send Data	522
24.2.7 Send Multicast Data	524
24.2.8 Start Data Path	526
24.2.9 Stop Data Path	528
24.2.10 Suspend Data Path	529
25 Data Collection Services	531
25.1 Services	531
25.1.1 Data Collected	531
25.1.2 Data Collection Resumed	534
25.1.3 Data Collection Suspended	535
25.1.4 Resume Data Collection	536
25.1.5 Start Data Collection	537
25.1.6 Stop Data Collection	539
25.1.7 Suspend Data Collection	540
26 Voice Services & Events	541
26.1 Services	541
26.1.1 Activate	541
26.1.2 Clear	543
26.1.3 Concatenate Message	544
26.1.4 Deactivate	545

iTech STANDARD PREVIEW

(standards.itech.ai)

ISO/IEC 18051:2007

<https://standards.itech.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007>

26.1.5 Delete Message	546
26.1.6 Play Message	547
26.1.7 Query Voice Attribute	549
26.1.8 Queue	554
26.1.9 Record Message	555
26.1.10 Reposition	557
26.1.11 Resume	559
26.1.12 Review	560
26.1.13 Set Voice Attribute	562
26.1.14 Start	565
26.1.15 Stop	567
26.1.16 Suspend	569
26.1.17 Synthesize Message	571
26.2 Events	572
26.2.1 Bookmark Reached	573
26.2.2 Completed	574
26.2.3 DTMF Detected	574
26.2.4 Emptied	575
26.2.5 Interruption Detected	576
26.2.6 Not Recognized	576
26.2.7 Play	577
26.2.8 Recognized	578
26.2.9 Record	579
26.2.10 Review	580
26.2.11 Silence Timeout Expired	580
26.2.12 Speech Detected	581
26.2.13 Started	582
26.2.14 Stop	582
26.2.15 Suspend Play	583
26.2.16 Suspend Record	584
26.2.17 Voice Attribute Changed	585
26.2.18 Voice Error Occurred	587
27 Call Detail Record (CDR) Services	588
27.1 Services	588
27.1.1 Call Detail Records Notification	589
27.1.2 Call Detail Records Report	590
27.1.3 Send Stored Call Detail Records	595
27.1.4 Start Call Detail Records Transmission	596
27.1.5 Stop Call Detail Records Transmission	598
28 Vendor Specific Extensions Services & Events	599
28.1 Registration Services	599
28.1.1 Escape Register	599
28.1.2 Escape Register Abort	600
28.1.3 Escape Register Cancel	601
28.2 Services	603
28.2.1 Escape	603
28.2.2 Private Data Version Selection	604
28.3 Events	605
28.3.1 Private Event	605
Annex A (normative) Device Appearances	607
Annex B (normative) ISDN User-User Information Element Encoding for CSTA	615
Annex C (normative) Capability Bitmap Parameters Types	617
Annex D (informative) Connection State Transition Examples	683
Annex E (informative) Summary of changes in this edition	692

ITeH STANDARD PREVIEW
(standards.itech.ai)

ISO/IEC 18051:2007
<https://standards.itech.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 18051 was prepared by Ecma International (as ECMA-269) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This fourth edition cancels and replaces the third edition (ISO/IEC 18051:2005), which has been technically revised.

[ISO/IEC 18051:2007](https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007)

<https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007>

Introduction

This International Standard defines Phase III of Services for Computer Supported Telecommunications Applications (CSTA). This International Standard is part of a suite of Standards and Technical Reports for Phase III of CSTA. All of the Standards and Technical Reports in the suite are based on practical experience of Ecma member companies and each one represents a pragmatic and widely-based consensus.

Phase III of CSTA extends the previous Phase I and Phase II Standards in major theme directions as well as numerous details. This incorporates technology based upon the *versit* CTI Encyclopedia (Version 1.0), which was contributed to Ecma by *versit*.

The 3rd edition of ISO/IEC 18056, XML Protocol for Computer Supported Telecommunications Applications (CSTA) Phase III, specifies a set of XML schemas for this 4th edition of Phase III Services for CSTA.

The 3rd edition of ECMA-348, Web Services Description Language (WSDL) for CSTA Phase III, specifies a set of WSDL schemas for this 4th edition of Phase III Services for CSTA.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 18051:2007](https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007)

<https://standards.iteh.ai/catalog/standards/sist/725a983a-6aea-40d5-81f6-edce8c754e67/iso-iec-18051-2007>

Information technology — Telecommunications and information exchange between systems — Services for Computer Supported Telecommunications Applications (CSTA) Phase III

1 Scope

This International Standard specifies the Services and Event Reports for Computer-Supported Telecommunications Applications, Phase III (CSTA).

This International Standard is focused on providing application service interfaces to a Switching Function, Computing Function and a Special Resource Function. A CSTA application interface is disassociated from the various user-network interfaces and network-network interfaces CSTA applications may serve, observe or manipulate. Because CSTA operates with existing telecommunications interfaces indirectly, it operates generically, so that differences among various existing interfaces are hidden from CSTA applications. Support of user-to-network interfaces is outside the scope of CSTA.

Although most terminal equipment (TE) is suitable for use with CSTA, there will be instances of TE that will not be suitable in certain circumstances. Examples are:

- FAX terminals and modems that are unable to adjust their transmission modes to prevent carrier conflict when both parties are alerted via CSTA during call establishment;
- functional terminals that perform telecommunication functions outside the control of the Switching Function.

Services defined in this International Standard allow functional integration between a computing network and a telecommunications network. Computing platforms (i.e., Application Programming Interfaces - APIs) that support such functionally-integrated applications are outside the scope of this International Standard.

Communication between the computing and switching (i.e., telecommunications) networks may take place via intervening networks ranging from simple point-to-point connections to local- or wide-area telecommunications networks.

This International Standard is part of a suite of CSTA Standards and Technical Reports that provide a comprehensive description of the architectural and practical issues involved in applying, implementing, and utilizing CSTA-based computer telephony integration (CTI) applications.

2 Conformance

This Clause specifies the conformance requirements for a Switching Function, Special Resource Function, and a Computing Function.

Conformance requirements specify the parts of this International Standard that a CSTA conformant implementation shall support.

This International Standard specifies an operational model (Clause 6, "CSTA Operational Model" and Clause 9, "Generic Service Requirements") that defines a collection of objects (e.g. domains and sub-domains, logical and physical elements, calls) and the relationships between these objects.

The behaviours of CSTA-conformant services, features, and event reports are determined by this model.

2.1 Switching Function

In order to conform to this International Standard a switching function shall support the following as a minimum:

1. the requirements pertaining to CSTA features as specified in Clause 6, "CSTA Operational Model";
2. the requirements as specified in Clause 9, "Generic Service Requirements";

3. the Get Switching Function Capability service for all CSTA profiles specified in 2.1.3, "CSTA Profiles" unless otherwise noted in the profile;
4. at least one of the Application Association Establishment sequences, including the mandatory services specified in the sequence, as specified in Clause 7, "Association Establishment";
5. at least one of the profiles as specified in 2.1.3, "CSTA Profiles".

2.1.1 Conformant Services

In order to conform to a specific CSTA *service* an implementation shall support the following as a minimum:

1. the requirements of the service as specified by its service description, service request parameters, service response parameters, and operational model including connection state transitions, monitoring event sequences, and functional requirements;
2. the requirements associated with each parameter used in the service as specified by its parameter description, format, and functional requirements in Clause 12, "Parameter Types";
3. all of the events that are associated with its service completion criteria, as documented in its event monitoring tables;
4. for service requests that contain a device identifier parameter, an implementation shall support, at a minimum, the Diallable Digits format as specified in 10.1.1, "Diallable Digits".

2.1.2 Conformant Events

In order to conform to a specific CSTA *event* an implementation shall support the following as a minimum:

1. the requirements of the event as specified by its event description, event parameters, event causes, and functional requirements;
2. the requirements associated with each parameter used in the event as specified by its parameter description, format, and functional requirements in Clause 12, "Parameter Types";
3. for events that contain a device identifier parameter, an implementation shall support, at a minimum, the Switching Function Representation format as specified in 10.1.2, "Switching Function Representation".

2.1.3 CSTA Profiles

Some CSTA services and events are grouped together as profiles.

2.1.3.1 Basic Telephony Profile

This profile includes the following:

1. CSTA Services: Answer Call, Clear Connection, Make Call, Monitor Start (with the monitorType of device-type), and Monitor Stop.
2. CSTA Events: Connection Cleared, Delivered, Established, Failed, Network Reached, Originated, and Service Initiated.

Other CSTA services and events may be provided in any combination in addition to this set.

2.1.3.2 Routeing Profile

If the switching function supports Routeing Services as specified in Clause 20, "Routeing Services", it shall support a minimum set of Routeing Services that includes: Route Request, Route Select, and Route End (from the switching function only).

Other Routing services may be provided in any combination in addition to this set.

If a switching function supports the routing for digital data calls, then the Route Register and CSTA Route Register Cancel shall also be included in the minimum set.

2.1.3.3 Level 1a Voice Browser Profile

This profile includes the following:

1. CSTA Services: Answer Call, Clear Connection, Single Step Transfer Call (of a connected call), Monitor Start (with the monitorType of device-type), and Monitor Stop.
2. CSTA Events: Connection Cleared, Delivered, Established, Failed, and Transferred.

Note that the Get Switching Function Capability service is not a required service in this profile.

Other CSTA services and events may be provided in any combination in addition to this set.

2.1.3.4 Level 1b Voice Browser Profile

This profile includes the following:

1. CSTA Services: Answer Call, Clear Connection, Deflect Call (of a connected call), Monitor Start (with the monitorType of device-type), and Monitor Stop.
2. CSTA Events: Connection Cleared, Delivered, Diverted, Established, and Failed.

Note that the Get Switching Function Capability service is not a required service in this profile.

Other CSTA services and events may be provided in any combination in addition to this set.

2.1.3.5 Level 2 Voice Browser Profile

This profile includes the following:

All of the services and events in either the Level 1a Voice Browser Profile or the Level 1b Voice Browser Profile and the following:

1. additional CSTA Service: Make Call.
2. additional CSTA Events: Network Reached, Originated.

Other CSTA services and events may be provided in any combination in addition to this set.

2.1.3.6 Minimal uaCSTA Call Control Profile

This profile includes the following:

1. CSTA Services: Answer Call, Clear Connection, Deflect Call, Hold Call, Make Call, Retrieve Call, and Single Step Transfer.
2. CSTA Events: There are no CSTA events specified as part of this profile. This profile assumes that an application uses mechanisms defined outside of this International Standard (SIP Subscribe/Notify, for example) to obtain call/connection information that can be used in CSTA services rather than using CSTA events to obtain this information.

Note that the Get Switching Function Capability service is not a required service in this profile.

Other CSTA services (and events) may be provided in any combination in addition to this set.