INTERNATIONAL STANDARD

ISO 29861

First edition 2009-11-15

Document management applications — Quality control for scanning office documents in colour

Applications de gestion de document — Contrôle de la qualité pour le balayage de documents de bureau en couleurs

iTeh STANDARD PREVIEW (standards.iteh.ai)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 29861:2009 https://standards.iteh.ai/catalog/standards/sist/1dedbef0-db69-416b-95f0-4fd25790a916/iso-29861-2009



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org
Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 29861 was prepared by Technical Committee ISO/TC 171, *Document management applications*, Subcommittee SC 1, *Quality*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

Introduction

This International Standard is to be used in conjunction with ISO 12653 and describes procedures for the evaluation of output quality of a colour scanning system for office documents. ISO 12653-2 describes procedures for evaluating the output quality of a black-and-white scanning system for office documents, using the test target specified in ISO 12653-1.

Factors which affect the quality achieved by a document scanning system are:

- a) physical scanning irregularities;
- b) uniformity of exposure;
- c) chromatic sensitivity of the photosensing unit;
- d) contrast:
- e) threshold setting;
- f) reproduction of half-tones;
- g) resolution;

iTeh STANDARD PREVIEW

4fd25790a916/iso-29861-2009

(standards.iteh.ai)

h) scale.

The methods given in this International Standard https://standards.iteh.avcatalog/standards/sist/1dedbef0-db69-416b-95f0-

- can be used to
 - set up the system initially to yield satisfactory images,
 - check for consistent quality,
 - check that equivalent performance is being obtained from another system; and
- are intended to
 - enable the operator to check that the scanner is correctly set up,
 - inform the operator of the capabilities and limits of the scanner,
 - enable the user to monitor image quality over a period of time,
 - enable the user to draw up quality assessment procedures.

If the whole system is checked, from input to output, the results obtained can vary depending on the different items of equipment used. For example, one visual display unit screen might be poorly set up, giving worse quality than a well set up screen. It is thus important to establish the parts of the system on which to perform the tests. If tests are required for other parts of the system, then it might be necessary to repeat the tests as appropriate.

The regular use of the methods in this International Standard can ensure a given level of quality to be maintained.

Many systems include test procedures in their software. These tests can be performed in conjunction with the test methods defined in this International Standard.

This International Standard uses the test chart, Test Chart No.2 (CMYK), defined in ISO/IEC 15775:1999/Amd.1:2005, N4-1, as the test document.

iTeh STANDARD PREVIEW (standards.iteh.ai)

iTeh STANDARD PREVIEW (standards.iteh.ai)

Document management applications — Quality control for scanning office documents in colour

1 Scope

This International Standard specifies test methods for evaluating the consistency of the colour output quality over time from the colour reflection scanning of office documents.

It is applicable to assessing the output quality of colour scanners used in the office. It is particularly applicable where office documents containing half-tone and/or continuous tone colour areas are being scanned.

The test methods do not require specialist equipment that is not normally available in the office for the evaluation of the results. The test methods are based on the visual examination of the output of an office document scanner in comparison to the original test target.

It is not applicable to black-and-white only scanners or scanners used for the scanning of transparent or translucent documents. $iTeh\ STANDARD\ PREVIEW$

This International Standard is to be used in conjunction with ISO 12653, which specifies a test method for the evaluation of the quality of output from black-and-white office document scanners.

ISO 29861:2009

2 Normative references https://standards.iteh.ai/catalog/standards/sist/1dedbef0-db69-416b-95f0-4fd25790a916/jso-29861-2009

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12651, Electronic imaging — Vocabulary

ISO 12653-1, Electronic imaging — Test target for the black-and-white scanning of office documents — Part 1: Characteristics

ISO 12653-2, Electronic imaging — Test target for the black-and-white scanning of office documents — Part 2: Method of use

ISO/IEC 15775:1999/Amd.1:2005, Information technology — Office machines — Method of specifying image reproduction of colour copying machines by analog test charts — Realisation and application — Amendment 1

3 Terms and definitions

For the purposes of this International Standard, the terms and definitions given in ISO 12651 apply.

© ISO 2009 – All rights reserved

4 Preparation

4.1 Initial system set-up

Tests shall be run under typical office operational conditions. Any required warm-up period shall be allowed before these tests are carried out.

Where possible, the manufacturer's instructions with regards to initial cleanup of the equipment and calibration routines should be followed, using the manufacturer's target, before these tests are carried out.

A number of PC software manufacturers provide systems which enable the calibration of colour images created from colour scanning systems. Where such software is available, their results may be used to supplement the visual results detailed in Clause 6.

4.2 Black-and-white scanning

Tests specified in ISO 12653-1 and ISO 12653-2 which are applicable to the requirements for the quality control of black-and-white scanning shall be completed prior to the initiation of tests specified in this International Standard.

4.3 Use of image enhancement and compression

The quality of output of a scanning system can be modified by the use of image enhancement and compression techniques. If these techniques are to be used during any of the tests carried out in accordance with this International Standard, the system shall be operating under typical office conditions, with scanner settings as used for typical office documents.

(Standards.iteh.ai)

NOTE It could be an advantage during the initial testing to establish the best settings for these controls. Software changes can introduce different enhancement or compression techniques. New initial tests might be needed for validation after such changes.

https://standards.iteh.ai/catalog/standards/sist/1dedbef0-db69-416b-95f0-

4fd25790a916/iso-29861-2009

4.4 Test chart

4.4.1 General

Test Chart No.2 (CMYK), defined in ISO/IEC 15775:1999/Amd.1:2005, N4-1, shall be used as the test document for the methods given in this International Standard.

4.4.2 Scanning

When a test chart is scanned, it shall be positioned correctly in the scanner. If the scanner incorrectly moves the chart, the resultant image shall be rejected if any major quality problems are evident. For example, if the chart alignment is substantially incorrect due to a problem with the paper path, the chart shall be re-scanned.

4.5 Internal test systems

Many systems include test procedures in their software. These tests may be performed in conjunction with the test methods defined in this International Standard.

4.6 Scanning software

Often, settings within the scanning software will affect the colour reproduction obtained by the system, therefore the settings to be used when scanning the test chart shall, for comparative purposes, be agreed and documented.

The scanning software shall be configured in colour mode. Where there are more than one colour mode options, separate tests shall be carried out at each mode normally used in practice.

4.7 Frequency

The frequency of testing of a system should be set by the user, taking advice from the system supplier. A system should be tested prior to the scanning of a batch of documents and, where necessary, at the end of the batch.

The tests shall also be performed after any maintenance operation or when any system component is changed.

4.8 Colour reproduction

Prior to carrying out this test for the first time, the impact of any inaccuracies of colour reproduction in relation to the business applications running on the scanning system shall be assessed.

Where accurate colour reproduction is necessary for an effective business application, the tolerance allowable on colour reproduction should be minimal.

For non-critical applications, a wider tolerance may be applied.

5 Quantitative testing

The following procedures shall be included in the quantitative test methods, in conjunction with the methods recommended by the PC software manufacturer.

- Compare image files side by side on the same PC screen at a given point in time.

 (standards.iteh.ai)
- Where image compression is used, take care that compression does not significantly affect the quality of test images. Where practical, test image files should be saved in non-compressed format or as highest quality JPEG images. https://standards.iteh.ai/catalog/standards/sist/1dedbef0-db69-416b-95f0-
- The frequency of testing shall be chosen taking into account the volume of scanning work performed.
 - NOTE For high volume scanning operations, comparing a reference image from a particular scanner to a target tested on a daily or shift basis would be appropriate.
- Where image quality is assessed from image prints, new prints shall be made from the reference image at the same time as the test image.

6 Test procedures

6.1 General

One or more of the three tests given in this clause shall be chosen, as appropriate to the business application, each test corresponding to the applicable test element on the test chart, as shown in Table 1.

Test No. Characteristics measured **Picture** Purpose of the test 1 Colour reproduction **B3** Identify colour changes between original and image 2 Colour steps **B4** Assess ability to reproduce colour graduations 3 Colour resolution B5 Assess ability to resolve small characters in different colours

Table 1 — Description and list of test elements