

SLOVENSKI STANDARD
SIST-TS ETSI/TS 102 657 V1.16.1:2016
01-april-2016

Zakonito prestrezanje (LI) - Ravnanje z zadržanimi podatki - Izročilni vmesnik za zahtevo in izročanje zadržanih podatkov

Lawful Interception (LI) - Retained data handling - Handover interface for the request and delivery of retained data

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: SIST-TS ETSI/TS 102 657 V1.16.1:2016
<https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004-83a55a14913f/sist-ts-etsi-ts-102-657-v1-16-1-2016>

ICS:

33.040.40	Podatkovna komunikacijska omrežja	Data communication networks
35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment

SIST-TS ETSI/TS 102 657 V1.16.1:2016 en

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ETSI/TS 102 657 V1.16.1:2016](#)

<https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004-83a55a14913f/sist-ts-etsi-ts-102-657-v1-16-1-2016>

ETSI TS 102 657 V1.16.1 (2014-10)



**Lawful Interception (LI);
Retained data handling,
Handover (interface for the request and
delivery of retained data**

SIST-TS ETSI/TS 102 657 V1.16.1:2016
<https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004-83a55a14913f/sist-ts-etsi-ts-102-657-v1-16-1-2016>



Reference
RTS/LI-00123
Keywords
handover, retention

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ETSI/TS 102 657 V1.16.1:2016](#)
<https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004-83a55a14913f>
Important notice

The present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	11
3 Definitions and abbreviations.....	11
3.1 Definitions.....	11
3.2 Abbreviations	12
4 Overview of handover interface	13
4.1 Reference model.....	13
4.2 Structure of document and applicable communication domains	15
4.3 Categories of retained data	16
4.4 Handover Interface port 1 (HI-A) and Handover Interface port 2 (HI-B).....	16
4.5 Model used for the RDHI.....	17
5 Handover interface message flows.....	17
5.1 Introduction	17
5.1.1 Summary of this clause.....	17
5.1.2 Message flow modes.....	17
5.1.3 Delivery cases	18
5.1.4 "Active" requests and "closed" requests	18
5.1.5 Errors and failure situations SIST-TS ETSI/TS 102 657 V1.16.1:2016	18
5.1.5.1 Error and failure types https://standards.iteh.ai/catalog/standards/sist/102/657/v1.16.1/2016/error-and-failure-types	18
5.1.5.2 Request process failure https://standards.iteh.ai/catalog/standards/sist/102/657/v1.16.1/2016/request-process-failure	19
5.1.5.3 Other errors	19
5.1.5.4 Missing messages	19
5.1.6 Cancelling a request.....	20
5.1.7 Delivery of results.....	20
5.1.8 State diagram	21
5.1.9 Supplementary Messages.....	22
5.2 Message flows for general situation	22
5.2.1 Delivery of a response	22
5.2.2 Cancellation of request	23
5.2.3 Multi-part delivery	24
5.3 Message flows for Authorized-Organization-initiated scenario	25
5.3.1 Delivery of results or a failure response	25
5.3.2 Cancellation of request	26
5.3.3 Multi-part delivery	27
5.4 Message types for HI-A and HI-B	28
5.5 HI-A and HI-B addressing.....	29
6 Definition of the elements for retained data messages	29
6.1 Header information.....	29
6.1.1 Use of header information	29
6.1.2 RequestID field specification.....	29
6.1.3 CSP Identifiers.....	30
6.1.3.1 Use of CSP identifiers (CSPID)	30
6.1.3.2 Third Party CSP Identifier (thirdPartyCSPID)	30
6.1.4 Timestamp (timeStamp)	30
6.2 Retained Data response	30
6.2.1 General.....	30
6.2.2 Additional information in response messages	31

6.2.2.1	Record number (recordNumber)	31
6.2.2.2	Response status (ResponseStatus).....	31
6.2.3	Volatile information.....	31
6.2.4	Unavailable parameters.....	31
6.3	Retained Data requests	31
6.3.1	Information contained within a request	31
6.3.2	Format of a request	32
6.3.3	Additional information in requests	33
6.3.3.1	Priority of a request.....	33
6.3.3.2	Maximum hits	33
6.3.3.3	Maximum records per batch.....	33
6.4	Error messages	33
7	Data exchange techniques	34
7.1	General	34
7.2	HTTP data exchange	34
7.2.1	Basic configuration	34
7.2.2	Single client/server	34
7.2.3	Mutual client/server	34
7.2.4	Details common to both single and mutual cases	34
7.3	Direct TCP data exchange.....	35
7.3.1	Application layer	35
7.3.2	Transport layer.....	35
7.3.2.1	Introduction.....	35
7.3.2.2	TCP settings	36
7.3.3	Network layer	36
7.3.4	Delivery networks.....	36
8	Security Measures	36
8.1	General	36
8.2	Connection Level Security	36
8.3	Application Level Security	37
8.4	Technical Security Measures SIST-TS ETSI/TS 102 657 V1.16.1:2016	37
8.4.1	General..... https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004-83a55a14913f/sist-ts-etsi-ts-102-657-v1-16-1-2016	37
8.4.2	Connection Level..... 83a55a14913f/sist-ts-etsi-ts-102-657-v1-16-1-2016	37
8.4.3	Application Level	37
8.4.3.1	Hashes	37
8.4.3.2	Digital Signatures.....	38
8.4.3.3	HI-B Non-Repudiation.....	38
8.4.3.4	Digital Signatures and Message Structure.....	38
Annex A (normative):	Data fields	39
A.1	Summary	39
A.1.1	Introduction to data fields.....	39
A.1.2	Choice of data modelling language	39
A.1.3	Overview	39
A.2	Parameter definition for common fields.....	40
A.2.1	RetainedDataHeader.....	40
A.2.1.1	Parameters.....	40
A.2.1.2	RequestID parameters	40
A.2.2	RetainedDataPayload	40
A.2.2.1	RequestMessage parameters	40
A.2.2.2	RequestAcknowledgement parameters	41
A.2.2.3	ResponseMessage parameters.....	41
A.2.2.4	GetStatusMessage parameters	41
A.2.2.5	StatusMessage parameters	41
A.2.2.6	ErrorMessage parameters	42
A.2.3	GenericSubscriberInfo.....	42
A.2.3.1	Parameters.....	42
A.2.3.2	OrganizationInfo parameters	42
A.2.3.3	IndividualInfo parameters.....	43

A.2.4	PaymentDetails.....	43
A.3	ASN.1 definitions.....	44
A.3.1	General	44
A.3.1.1	ASN.1 syntax tree	44
A.3.1.2	General remarks on ASN.1	44
A.3.2	ASN.1 Definitions for message headers.....	45
A.3.2.1	Message wrappers.....	45
A.3.2.2	Message headers	45
A.3.3	ASN.1 definitions for common fields.....	50
A.3.4	Schematic representation of top level ASN.1.....	53

Annex B (normative): Service-specific details for telephony services.....55

B.1	Scope	55
B.2	Telephony fields.....	55
B.2.1	General	55
B.2.2	Telephony Subscriber.....	55
B.2.2.1	subscriber ID.....	55
B.2.2.2	genericSubscriberInfo	56
B.2.2.3	telephonySubscriberInfo	56
B.2.2.4	subscribedTelephonyServices	56
B.2.2.4.1	Description	56
B.2.3	Telephony Billing Details	57
B.2.3.1	BillingRecords	57
B.2.4	Telephony ServiceUsage	58
B.2.4.1	Parameters.....	58
B.2.4.2	PartyInformation	58
B.2.4.3	SMSInformation	59
B.2.4.4	MmsInformation	59
B.2.5	TelephonyDevice.....	59
B.2.5.1	General.....	59
B.2.6	TelephonyNetworkElement.....	60
B.2.6.1	General.....	60
B.2.6.2	Location parameters.....	60
B.2.6.2.1	General	60
B.2.6.2.2	GSM Location Information.....	61
B.2.6.2.3	UMTS Location Information	61
B.2.6.2.4	Extended Location	61
B.2.6.3	TransmitterDetails parameters	62
B.2.6.3.1	General	62
B.3	ASN.1 definitions for telephony	62
B.4	Schematic view of ASN.1 definitions	75

Annex C (normative): Service-specific details for asynchronous message services77

C.1	Scope	77
C.2	Descriptions.....	77
C.2.1	General	77
C.2.2	MsgSubscriber.....	78
C.2.2.1	MsgSubscriberID	78
C.2.2.2	MsgStore.....	78
C.2.2.3	MsgStoreID.....	78
C.2.2.4	MsgAddress	78
C.2.2.5	MsgProviderID	78
C.2.3	MsgServiceUsage	79
C.2.3.1	MsgTransmission	79
C.2.3.2	MsgStoreOperation	79
C.2.4	MsgBillingDetails parameters	80
C.2.4.1	MsgBillingRecords	80

C.3	ASN.1 definitions for asynchronous message services	80
C.4	Schematic view of ASN.1 definitions	84
Annex D (normative):	Service-specific details for synchronous multi-media services	85
D.1	Scope	85
D.2	Multimedia fields	85
D.2.1	General	85
D.2.2	Multimedia Subscriber	85
D.2.2.1	subscriberID.....	85
D.2.2.2	genericSubscriberInfo	86
D.2.2.3	multimediaSubscriberInfo	86
D.2.2.4	subscribedMultimediaServices	86
D.2.2.4.1	Description	86
D.2.3	MultimediaBillingDetails	87
D.2.3.1	MultimediaBillingDetails	87
D.2.3.2	MultimediaBillingAddress.....	87
D.2.3.3	MultimediaBillingRecords.....	88
D.2.4	Multimedia ServiceUsage	88
D.2.4.1	Parameters.....	88
D.2.4.2	PartyInformation.....	89
D.2.4.3	IMSIInformation	89
D.2.4.4	MediaComponents	90
D.3	ASN.1 definitions for Multimedia.....	90
D.4	Schematic view of ASN.1 definitions	96
Annex E (normative):	Service-specific details for network access services	98
E.1	Scope	98
E.2	Descriptions.....	98
E.2.1	General	98
E.2.2	NASubscriber	98
E.2.3	NAServiceSubscription	99
E.2.4	NAServiceUsage	99
E.2.5	NADevice	102
E.2.6	NANwElement	103
E.2.7	NABillingDetails.....	103
E.3	ASN.1 definitions for network access services	103
E.4	Schematic view of ASN.1 definitions	112
Annex F (informative):	Basic set of search routines for Retained Data.....	113
F.1	Example set of search routines	113
F.1.1	Introduction	113
F.1.2	Summary of search case	113
F.1.3	Subscriber records	113
F.2	Telephony data	114
F.2.1	Telephony subscriber	114
F.2.2	Telephony billing details	114
F.2.3	Telephony service usage	114
F.2.4	Telephony network element	114
F.3	Messaging data	115
F.3.1	Message subscriber.....	115
F.3.2	Message service usage.....	115
F.4	Network Access data	115
F.4.1	NA subscriber.....	115
F.4.2	NA service usage.....	116

Annex G (informative): Examples of search routines	117
G.1 Introduction	117
G.2 Example for telephony subscriber query in clause F.2.1.....	117
G.3 Example for telephony service usage query in clause F.2.3.....	118
Annex H (informative): Further information on data categories.....	119
H.1 General	119
H.2 Further information on subscriber data	119
H.2.1 Subscriber data requests	119
H.2.2 Generic subscriber data records.....	120
H.2.3 Service Specific Subscriber Reply Data.....	120
H.3 Further information on usage data.....	121
H.3.1 Usage requests.....	121
H.3.2 Usage data categories	121
H.3.3 Usage: Traffic Data (Reply)	121
H.3.4 Usage: Traffic Data related information (Reply).....	121
H.3.5 Usage: communication independent user activities (Reply).....	122
H.3.6 Usage: network Activity Data (Reply)	122
H.4 Further information on network element data.....	122
H.4.1 Network element requests	122
H.4.2 Network Configuration Data Reply Data	122
Annex I (informative): iTeh STANDARD PREVIEW	123
Annex J (informative): Single versus multi-part deliveries.....	124
J.1 General	124
J.2 Criteria for multi-part delivery <small>SIST-TS ETSI/TS 102 657 V1.16.1:2016 https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004</small>	124
J.3 Subscriptions into the future <small>area55a14913f/sist-ts-etsi-ts-102-657-v1-16-1-2016</small>	125
Annex K (informative): Change Request History.....	126
History	129

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Lawful Interception (LI).

The ASN.1 module and XML schema are also available as an electronic attachment to the original document from the ETSI site (see details in clause A.3.1.2).

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "may not", "need", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions). **(standards.iteh.ai)**

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

[SIST-TS ETSI/TS 102 657 V1.16.1:2016](#)

<https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004-83a55a14913f/sist-ts-etsi-ts-102-657-v1-16-1-2016>

1 Scope

The present document is based on requirements from TS 102 656 [2].

The present document contains handover requirements and a handover specification for the data that is identified in national legislations on Retained Data.

The present document considers both the requesting of retained data and the delivery of the results.

The present document defines an electronic interface. An informative annex describes how this interface may be adapted for manual techniques. Apart from in annex I, the present document does not consider manual techniques.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

iTeh STANDARD PREVIEW

2.1 Normative references (standards.iteh.ai)

The following referenced documents are necessary for the application of the present document.

- [1] SIST-TS ETSI/TS 102 657 V1.16.1:2016
Void <https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004-8255a149136sist-ts-etsi-ts-102-657-v1-16-1-2016>
- [2] ETSI TS 102 656: "Lawful Interception (LI); Retained Data; Requirements of Law Enforcement Agencies for handling Retained Data".
- [3] ETSI TS 102 232-1: "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery; Part 1: Handover specification for IP delivery".
- [4] ISO 3166-1: "Codes for the representation of names of countries and their subdivisions -- Part 1: Country codes".
- [5] ISO 4217: "Codes for the representation of currencies and funds".
- [6] ETSI TS 101 671: "Lawful Interception (LI); Handover interface for the lawful interception of telecommunications traffic".
- NOTE:** Periodically TS 101 671 is published as ES 201 671. A reference to the latest version of the TS as above reflects the latest stable content from ETSI/TC LI.
- [7] ETSI EN 300 356 (all parts): "Integrated Services Digital Network (ISDN); Signalling System No.7 (SS7); ISDN User Part (ISUP) version 4 for the international interface".
- [8] ETSI TS 100 974: "Digital cellular telecommunications system (Phase 2+); Mobile Application Part (MAP) Specification (3GPP TS 09.02)".
- [9] ETSI TS 124 008: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Mobile radio interface Layer 3 specification; Core network protocols; Stage 3 (3GPP TS 24.008)".
- [10] Void.
- [11] ETSI TS 133 108: "Universal Mobile Telecommunications System (UMTS); LTE; 3G security; Handover interface for Lawful Interception (LI) (3GPP TS 33.108)".

- [12] ETSI TS 101 109 (V7.2.0): "Digital cellular telecommunications system (Phase 2+); Universal Geographical Area Description (GAD) (3GPP TS 03.32 version 7.2.0 Release 1998)".
 - [13] FIPS PUB 186-2: "Digital Signature Standard (DSS)".
 - [14] IETF RFC 2616: "Hypertext Transfer Protocol - HTTP/1.1".
 - [15] IETF RFC 2818: "HTTP Over TLS".
 - [16] ETSI TS 123 040: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Technical realization of the Short Message Service (SMS) (3GPP TS 23.040)".
 - [17] IETF RFC 793: "Transmission Control Protocol".
 - [18] IETF RFC 5681: "TCP Congestion Control".
 - NOTE: IETF RFC 5681 obsoletes IETF RFC 2581: "TCP Congestion Control".
 - [19] IETF RFC 6298: "Computing TCP's Retransmission Timer".
 - NOTE: IETF RFC 6298 obsoletes IETF RFC 2988: "Computing TCP's Retransmission Timer".
 - [20] IETF RFC 1122: "Requirements for Internet Hosts - Communication Layers".
 - [21] IETF RFC 791: "Internet Protocol".
 - [22] ETSI ES 282 002: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); PSTN/ISDN Emulation Sub-system (PES); Functional architecture"
- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
- [23] IETF RFC 822: "Standard for the format of ARPA internet text messages".
 - [24] IETF RFC 5322: "Internet Message Format".
 - NOTE: IETF RFC 5322 obsoletes IETF RFC 2822: "Internet Message Format".
 - [25] ETSI TS 123 228: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; IP Multimedia Subsystem (IMS); Stage 2 (3GPP TS 23.228)".
 - [26] IETF RFC 3261: "SIP: Session Initiation Protocol".
 - [27] IETF RFC 4506: "XDR: External Data Representation Standard".
 - [28] ISO 13616-1:2007: "Financial services - International bank account number (IBAN) - Part 1: Structure of the IBAN".
 - [29] ISO 9362:2009: "Banking - Banking telecommunication messages - Business identifier code (BIC)".
 - [30] Void.
 - [31] ETSI TS 125 413: "Universal Mobile Telecommunications System (UMTS); UTRAN Iu interface Radio Access Network Application Part (RANAP) signalling (3GPP TS 25.413)".
 - [32] ETSI TS 129 274: "Universal Mobile Telecommunications System (UMTS); LTE; 3GPP Evolved Packet System (EPS); Evolved General Packet Radio Service (GPRS) Tunnelling Protocol for Control plane (GTPv2-C); Stage 3 (3GPP TS 29.274)".
 - [33] ETSI TS 129 061: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Interworking between the Public Land Mobile Network (PLMN) supporting packet based services and Packet Data Networks (PDN) (3GPP TS 29.061)".

- [34] ETSI TS 129 118: "Universal Mobile Telecommunications System (UMTS); LTE; Mobility Management Entity (MME) - Visitor Location Register (VLR) SGs interface specification (3GPP TS 29.118)".
- [35] ETSI TS 123 272: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Circuit Switched (CS) fallback in Evolved Packet System (EPS); Stage 2 (3GPP TS 23.272)".
- [36] ETSI TS 133 234: "Universal Mobile Telecommunications System (UMTS); LTE; 3G security; Wireless Local Area Network (WLAN) interworking security (3GPP TS 33.234)".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

authorized organization: any authority legally authorized to request or receive retained data e.g. a Law Enforcement Agency
iTeh STANDARD PREVIEW
(standards.iteh.ai)

Handover Interface A (HI-A): administrative handover interface comprising requests for information and their responses
SIST-TS ETSI/TS 102 657 V1.16.1:2016

Handover Interface B (HI-B): data handover interface comprising the retained data transmission of information
https://standards.iteh.ai/catalog/standards/sist/b837d11c-ea44-48ef-b004-85a5a149151/sist-ts-etsi-ts-102-657-v1-16-1-2016

issuing authority: any entity possessing the necessary jurisdiction and authority pursuant to law to compel a service provider to deliver retained subscriber information or traffic data specified in a query

lawful authorization: permission granted to an Authorized Organization under certain conditions to request specified telecommunications retained data and requiring co-operation from a network operator/service provider/access provider

NOTE: Typically, this refers to a warrant or order issued by a lawfully authorized body.

location information: information relating to the geographic, physical or logical location of an identity relating to an interception subject

number: any address (E.164, IP, email, URI) used for routing in a network or in a service on a user level or network/service level

receiving authority: any entity possessing the necessary authority pursuant to law and the technical means to receive retained subscriber information or traffic data delivered by a service provider

request: legal requirement for a Communications Service Provider (CSP) to disclose retained data in accordance with relevant national law

response to request of information: response from the CSP to the authorized organization acknowledging or rejecting a request for information

retained data record: set of data elements for a specific subscriber/user related to a specific service transaction

service transaction: instance of a service given by a CSP to a subscriber/user

service transaction record: set of data elements describing a service transaction (details to be determined)

transmission of information: transmission of retained data from the CSP to the receiving authority

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACK	ACKnowledge
ADSL	Asymmetric Digital Subscriber Line
AO	Authorized Organization
APN	Access Point Name
ASCII	American Standard Code for Information Interchange
ASN	Abstract Syntax Notation
BER	Basic Encoding Rules
BIC	Business Identifier Code
CGI	Cell Global Identity
CPE	Customer Premises Equipment
CS	Circuit Switched
CSP	Communications Service Provider
CSPID	CSP Identifier
DNS	Domain Name System
DR	Data Retention
DSA	Digital Signature Algorithm
DSL	Digital Subscriber Line
DSS	Digital Signature Standard
DVD	Digital Versatile Disc or Digital Video Disc
ECGI	E-UTRAN Cell Global ID
EMS	Enhanced Messaging Service
EPS	Evolved Packet System
GGSN	Gateway GPRS Support Node
GPRS	General Packet Radio Service
GSM	Global System for Mobile communications
GW	GateWay
HI	Handover Interface
HI-A	Handover Interface A
HI-B	Handover Interface B
HTTP	HyperText Transfer Protocol
HTTPS	HyperText Transfer Protocol over Secure Socket Layer
IBAN	International Banking Account Number
ICCID	Integrated Circuit Card ID
ID	IDentifier
IEI	Information Element Identifier
IMAP	Internet Message Access Protocol
IMEI	International Mobile Equipment Identity
IMEISV	IMEI Software Version
IMS	IP Multimedia Subsystem
IMSI	International Mobile Subscriber Identity
IP	Internet Protocol
IPSec	Internet Protocol Security
IRI	Intercept Related Information
ISDN	Integrated Services Digital Network
ISUP	ISDN User Part
LAN	Local Area Network
LEA	Law Enforcement Agency
LI	Lawful Interception
MAC	Media Access Control
MCC	Mobile Country Code
ME	Mobile Equipment
MF-B	Mediation Function B
MME	Mobility Management Entity
MMS	Multimedia Messaging Service
MNC	Mobile Network Code
MS	Mobile Station
MSC	Mobile Switching Centre

MSISDN	Mobile Subscriber ISDN number
MSN	Multiple Subscriber Number
NA	Network Access
NAS	Network Access Server
NAT	Network Address Translation
PAT	Port Address Translation
PDN	Public Data Network
PDP	Packet Data Protocol
PDU	Protocol Data Unit
PLMN	Public Land Mobile Network
PPP	Point-to-Point Protocol
PS	Packet Switched
PSTN	Public Switched Telephone Network
PUK	Personal Unblocking Key
RAI	Routing Area Identifier
RAT	Radio Access Technology
RD	Retained Data
RDHI	Retained Data Handover Interface
SAI	Service Area Identifier
SC	SMS Centre
SDP	Session Description Protocol
SGSN	Serving GPRS Support Node
SHA	Secure Hash Algorithm
SIM	Subscriber Identity Module
SIP	Session Initiation Protocol
SMS	Short Message Service
SMTP	Simple Mail Transfer Protocol
TAI	Tracking Area Identity
TCP	Transmission Control Protocol
TL	Latency Time
TLS	Transport Layer Security
TR	Time of the Request
TV	TeleVision
UE	User Equipment
UMTS	Universal Mobile Telecommunication System
URI	Uniform Resource Identifier
UTF	Unicode Transformation Format
UTM	Universal Transverse Mercator
UTRAN	UMTS Terrestrial Radio Access Network
WGS	World Geodetic System
XML	eXtensible Markup Language

Item STANDARD PREVIEW
(standards.iteh.ai)

4 Overview of handover interface

4.1 Reference model

The generic Handover Interface adopts a two-port structure such that administrative request/response information (HI-A) and Retained Data Information (HI-B) are logically separated.

Figure 1 is the reference model for the request and transmission of retained telecommunications data.