

Second edition
2004-06-15

Corrected version
2004-09-15

AMENDMENT 1
2008-02-01

**Road vehicles — Electrical disturbances
from conduction and coupling —**

Part 2:

**Electrical transient conduction along
supply lines only**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

AMENDMENT 1

*Véhicules routiers — Perturbations électriques par conduction et par
couplage*

ISO 7637-2:2004/Amd 1:2008

<https://standards.iteh.ai/catalog/standards/iso/7637-2:2004-06-15/iso-7637-2-2004-06-15-amd-1-2008>
*Partie 2: Transmission des perturbations électriques transitoires par
conduction uniquement le long des lignes d'alimentation*

AMENDEMENT 1



Reference number
ISO 7637-2:2004/Amd.1:2008(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 7637-2:2004/Amd 1:2008](https://standards.iteh.ai/catalog/standards/sist/7c120a74-ff25-42fb-8c41-0fcacb0eda5c/iso-7637-2-2004-amd-1-2008)

<https://standards.iteh.ai/catalog/standards/sist/7c120a74-ff25-42fb-8c41-0fcacb0eda5c/iso-7637-2-2004-amd-1-2008>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 7637-2:2004 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 3, *Electrical and electronic equipment*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 7637-2:2004/Amd 1:2008](https://standards.iteh.ai/catalog/standards/sist/7c120a74-ff25-42fb-8c41-0fcacb0eda5c/iso-7637-2-2004-amd-1-2008)

<https://standards.iteh.ai/catalog/standards/sist/7c120a74-ff25-42fb-8c41-0fcacb0eda5c/iso-7637-2-2004-amd-1-2008>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 7637-2:2004/Amd 1:2008

<https://standards.iteh.ai/catalog/standards/sist/7c120a74-ff25-42fb-8c41-0fcacb0eda5c/iso-7637-2-2004-amd-1-2008>

Road vehicles — Electrical disturbances from conduction and coupling —

Part 2: Electrical transient conduction along supply lines only

AMENDMENT 1

Page 18, Annex A

Replace the whole of Annex A with the following:

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 7637-2:2004/Amd 1:2008](https://standards.iteh.ai/catalog/standards/sist/7c120a74-ff25-42fb-8c41-0fcacb0eda5c/iso-7637-2-2004-amd-1-2008)
<https://standards.iteh.ai/catalog/standards/sist/7c120a74-ff25-42fb-8c41-0fcacb0eda5c/iso-7637-2-2004-amd-1-2008>

Annex A (informative)

Example of test severity levels associated with functional performance status classification

A.1 General

This annex gives examples of test severity levels which should be used in line with the principle of functional performance status classification (FPSC) described in ISO 7637-1.

A.2 Classification of test pulse severity level

The suggested minimum and maximum severity levels are given in columns III and IV in Tables A.1 and A.2.

A selected level and test time for testing at or in between these values may be chosen in accordance with the agreement between vehicle manufacturer and supplier. In cases where no specific values are defined, it is recommended to use levels selected from columns III and IV in Tables A.1 and A.2.

A.2.1 12 V electrical system

The recommended levels are given in Table A.1.

Table A.1 — Suggested test levels for 12 V system

Test pulse ^a	Selected test level ^b	Test level, U_s ^c				Minimum number of pulses or test time ^f	Burst cycle/pulse repetition time	
		V					min.	max.
		I	II	III min.	IV max.			
1	g	g	g	- 75	- 100	5 000 pulses	0,5 s	5 s
2a	g	g	g	+ 37	+ 50	5 000 pulses	0,2 s	5 s
2b	g	g	g	+ 10	+ 10	10 pulses	0,5 s	5 s
3a	g	g	g	- 112	- 150	1 h	90 ms	100 ms
3b	g	g	g	+ 75	+ 100	1 h	90 ms	100 ms
4	g	g	g	- 6	- 7	> 1 pulse	d	d
5 ^e	g	g	g	+ 65	+ 87	> 1 pulse	d	d

^a Test pulses as in 5.6.

^b Values agreed to between vehicle manufacturer and equipment supplier.

^c The amplitudes are the values of U_s as defined for each test pulse in 5.6.

^d Since the minimum number of test pulses is 1, no pulse cycle time is given. When several pulses are to be applied, a minimum delay of 1 min between pulses shall be allowed.

^e See 5.6.5 c). The test levels reflect the situation of load dump at generator rated speed. If a central load dump protection is used, apply test pulse 5b as defined in Figure 12 and use the values in Table 10.

^f The number of pulses/time is for durability test purposes.

^g The former levels I and II were deleted because they do not ensure sufficient immunity in road vehicles.

A.2.2 24 V electrical system

The recommended values are given in Table A.2.

Table A.2 — Suggested test levels for 24 V system

Test pulse ^a	Selected test level ^b	Test level, U_s ^c				Minimum number of pulses or test time ^f	Burst cycle/pulse repetition time	
		I	II	III min.	IV max.		min.	max.
1		g	g	- 450	- 600	5 000 pulses	0,5 s	5 s
2a		g	g	+ 37	+ 50	5 000 pulses	0,2 s	5 s
2b		g	g	+ 20	+ 20	10 pulses	0,5 s	5 s
3a		g	g	- 150	- 200	1 h	90 ms	100 ms
3b		g	g	+ 150	+ 200	1 h	90 ms	100 ms
4		g	g	- 12	- 16	> 1 pulse	d	d
5 ^e		g	g	+ 123	+ 173	> 1 pulse	d	d

^a Test pulses as in 5.6.
^b Values agreed to between vehicle manufacturer and equipment supplier.
^c The amplitudes are the values of U_s as defined for each test pulse in 5.6.
^d Since the minimum number of test pulses is 1, no pulse cycle time is given. When several pulses are to be applied, a minimum delay of 1 min between pulses shall be allowed.
^e See 5.6.5 c). The test levels reflect the situation of load dump at generator rated speed. If a central load dump protection is used, apply test pulse 5b as defined in Figure 12 and use the values in Table 10.
^f The number of pulses/time is for durability test purposes.
^g The former levels I and II were deleted because they do not ensure sufficient immunity in road vehicles.

A.3 Example of FPSC application, using test pulse severity levels

An example of severity levels is given in Table A.3. This table can be different for each kind of pulse, and for 12 V and 24 V electrical systems (levels from Tables A.1 and A.2).

Table A.3 — Example of FPSC application, using test pulse severity levels

	Category 1	Category 2	Category 3
L _{4i}	Level IV	Level IV	Level IV
L _{3i}	Level III	Level IV	Level IV
L _{2i}	Level III	Level III	Level IV
L _{1i}	Level III	Level III	Level III

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 7637-2:2004/Amd 1:2008
<https://standards.iteh.ai/catalog/standards/sist/7c120a74-ff25-42fb-8c41-0fcacb0eda5c/iso-7637-2-2004-amd-1-2008>

ICS 43.040.10

Price based on 3 pages