



SLOVENSKI STANDARD SIST ETS 300 446:1998

01-oktober-1998

F U X] ' g _ U c d f Y a U] b ' g] g h Y a] ' f F 9 G L ! ' G H U b X U f X ' Y Y _ f c a U] b Y b Y ' n X f i y ` ' j c g h] ' f 0 A 7 L
V f Y n j f j] b] ' h Y Z b g _] ' b U d f U j ' X f i [Y [Y b Y f U W] ' Y f H & Z _] X Y i ' Y ' c ' j ' Z Y _ j Y b b Y a
d U g i ' c X ' , * (Z % A < n ' X c ' , * , Z % A < n z j _ ' 1 b c ' g ' g h c f] h j U a] ' U j b Y [U X c g h c d U

Radio Equipment and Systems (RES); ElectroMagnetic Compatibility (EMC) standard for second generation Cordless Telephone (CT2) apparatus operating in the frequency band 864,1 MHz to 868,1 MHz, including public access services

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 446:1998](https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998)

<https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998>

Ta slovenski standard je istoveten z: **ETS 300 446 Edition 2**

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST ETS 300 446:1998

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 446:1998](#)

<https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 446

March 1997

Second Edition

Source: ETSI TC-RES

Reference: RE/RES-09037

ICS: 33.020

Key words: CT2, EMC, radio, testing

**Radio Equipment and Systems (RES);
ElectroMagnetic Compatibility (EMC) standard
for second generation Cordless Telephone (CT2) apparatus
operating in the frequency band 864,1 MHz to 868,1 MHz,
including public access services**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 446:1998](https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998)

<https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998>

Contents

Foreword	7
1 Scope	9
2 Normative references	9
3 Definitions and abbreviations	10
3.1 Definitions	10
3.2 Abbreviations	11
4 General test conditions	11
4.1 Test conditions	11
4.2 Arrangements for test signals at the input of the transceiver	11
4.2.1 Speech equipment	11
4.3 Normal test modulation	12
4.4 Connection of test signals for transceivers	12
4.4.1 RF connection	12
4.5 Connection of test signals for receiver-only equipment	12
4.5.1 RF connection	12
4.6 Receiver test signal level	12
4.7 Narrow band responses on receivers or receivers which are part of transceivers	12
4.8 Exclusion bands	13
4.8.1 Exclusion band for CT2 receivers and CT2 receiver parts of transceivers ...	13
4.8.2 Exclusion band for CT2 transmitter parts of transceivers	13
5 Performance assessment	13
5.1 General	13
5.2 Equipment classification	14
5.3 Ancillary equipment	14
5.4 Assessment of host connected equipment and plug-in cards	14
5.4.1 Alternative A: composite equipment	14
5.4.2 Alternative B: use of a test jig and three hosts	14
5.5 Performance assessment test procedure to verify no loss of user control functions or stored data for CT2 transceivers	15
5.6 Performance assessment of audio breakthrough	15
6 Performance criteria	16
6.1 Performance criteria for Continuous phenomena applied to CT2 Transceivers (CT)	17
6.2 Performance criteria for Transient phenomena applied to CT2 Transceivers (TT)	17
6.3 Performance criteria for Continuous phenomena applied to CT2 Receive-only equipment (CR)	17
6.4 Performance criteria for Transient phenomena applied to CT2 Receive-only equipment (TR)	17
7 Applicability overview tables	17
7.1 Emission	18
7.2 Immunity	18
8 Test methods and limits for emission tests of transceivers and/or receivers and/or ancillary equipment	19
8.1 Test configuration	19
8.2 Enclosure	19
8.2.1 Definition	19
8.2.2 Test method	19
8.2.3 Test limit	19
8.3 DC power input/output port	20

8.3.1	Definition.....	20
8.3.2	Test method.....	20
8.3.3	Test limit.....	20
8.4	AC mains power input/output port.....	20
8.4.1	Definition.....	20
8.4.2	Test method.....	21
8.4.3	Test limit.....	21
9	Test methods and levels for immunity tests of transceivers and/or receivers and/or ancillary equipment.....	21
9.1	Test configuration.....	21
9.2	Radio frequency electromagnetic field (80 to 1 000 MHz).....	22
9.2.1	Enclosure.....	22
9.2.1.1	Definition.....	22
9.2.1.2	Test method and level.....	22
9.2.1.3	Performance criteria.....	22
9.3	Electrostatic discharge.....	22
9.3.1	Definition.....	22
9.3.2	Test method and levels.....	22
9.3.3	Performance criteria.....	23
9.4	Fast transients common mode.....	23
9.4.1	Definition.....	23
9.4.2	Test method and levels.....	23
9.4.3	Performance criteria.....	24
9.5	RF common mode, 0,15 MHz to 80 MHz (current clamp injection).....	24
9.5.1	Definition.....	24
9.5.2	Test method and level.....	24
9.5.3	Performance criteria.....	25
9.6	Transients and surges, vehicular environment.....	25
9.6.1	Definition.....	25
9.6.2	Test method and level.....	25
9.6.3	Performance criteria.....	26
9.7	Voltage dips and interruptions.....	26
9.7.1	Definition.....	26
9.7.2	Test method and levels.....	26
9.7.3	Performance criteria.....	27
9.8	Surges, common and differential mode.....	27
9.8.1	Definition.....	27
9.8.2	Test method and levels.....	28
9.8.3	Performance criteria.....	28
Annex A (normative):	ETS 300 446, EMC Standard for Cordless Telephone (CT2) apparatus operating in the frequency band 864,1 MHz to 868,1 MHz including public access services.....	29
Annex B (normative):	Clauses and/or subclauses from I-ETS 300 131 [3] which are relevant for compliance with essential requirements of the EC Council Directives.....	30
B.1	CTAs without integral or supplied antenna.....	30
B.2	Unmodulated interfering carrier signal.....	30
B.3	Blocking due to spurious responses.....	31
B.4	Spurious emissions of the combined transmitter/receiver.....	31
Annex C (normative):	Clauses and/or subclauses from I-ETS 300 131 Second Edition [4] which are relevant for compliance with essential requirements of the EC Council Directives.....	32
C.1	CTAs without integral or supplied antenna.....	32
C.2	Unmodulated interfering carrier signal.....	32

C.3	Blocking due to spurious responses	33
C.4	Spurious emissions of the combined transmitter/receiver	33
Annex D (normative):	ERC Decision on the adoption of approval regulations for radio equipment to be used for cordless telephone apparatus operating in the mobile service in the frequency range 864,1 MHz to 868,1 MHz, based on the Interim European Telecommunications Standard (I-ETS) 300 131 [3], [4]	34
History.....		42

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 446:1998](https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998)

<https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 446:1998](https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998)

<https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998>

Foreword

This second edition European Telecommunication Standard (ETS) has been prepared by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This ETS is intended to become a Harmonized EMC Standard for equipment within the scope of I-ETS 300 131, the reference of which is intended to be published in the Official Journal of the European Communities referencing the Council Directive 89/336/EEC (EMC Directive).

The technical specifications which are relevant to the EMC Directive are listed in annexes A, B and C.

Transposition dates	
Date of adoption:	7 March 1997
Date of latest announcement of this ETS (doa):	30 June 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 December 1997
Date of withdrawal of any conflicting National Standard (dow):	31 December 1997

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 446:1998](https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998)

<https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 446:1998](https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998)

<https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-7fe70ed58594/sist-ets-300-446-1998>

1 Scope

This European Telecommunication Standard (ETS) covers the assessment of radio communication and ancillary equipment in respect of Electromagnetic Compatibility (EMC).

This ETS specifies the minimum performance and the methods of measurements of EMC on second generation Cordless Telephone (CT2) apparatus and ancillary equipment.

This ETS specifies the applicable EMC tests, the limits, and the performance criteria for digital radio equipment, operating in the frequency range 864,1 to 868,1 MHz, and for the associated ancillary equipment.

The environment classification used in this ETS refers to the environment classification used in the Generic Standards EN 50081-1 [1], EN 50082-1 [2], except the vehicular environment class which refers to ISO 7637 [6].

The EMC requirements have been selected to ensure an adequate level of compatibility for apparatus at residential, commercial, light industrial and vehicular environments. The levels however, do not cover extreme cases which may occur in any location but with a low probability of occurrence.

This ETS may not cover those cases where a potential source of interference which is producing individually repeated transient phenomena, or a continuous phenomena, is permanently present, e.g. a radar or broadcast site in the near vicinity. In such a case it may be necessary to use special protection applied to either the source of interference, or the interfered part, or both.

Compliance of radio equipment to the requirements of this ETS does not signify compliance to any requirement related to the use of the equipment (i.e. licensing requirements).

Compliance to this ETS does not signify compliance to any safety requirements. However, it is the responsibility of the assessor of the equipment that any observation regarding the equipment becoming dangerous or unsafe as a result of the application of the tests of this ETS, should be recorded in the test report.

[SIST ETS 300 446:1998](https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-71e70ed58594/sist-ets-300-446-1998)

2 Normative references

<https://standards.iteh.ai/catalog/standards/sist/979a7ef0-1477-44f3-b8b9-71e70ed58594/sist-ets-300-446-1998>

This ETS incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] EN 50081-1 (1992): "Electromagnetic compatibility - Generic emission standard. Part 1 Residential, commercial and light industry".
- [2] EN 50082-1 (1992): "Electromagnetic compatibility - Generic immunity standard. Part 1: Residential, commercial and light industry".
- [3] I-ETS 300 131 (1992): "Radio Equipment and Systems (RES); Common air interface specification to be used for the interworking between cordless telephone apparatus in the frequency band 864,1 MHz to 868,1 MHz, including public access services".
- [4] I-ETS 300 131 (1994), 2nd Edition: "Radio Equipment and Systems (RES); Common air interface specification to be used for the interworking between cordless telephone apparatus in the frequency band 864,1 MHz to 868,1 MHz, including public access services".
- [5] I-ETS 300 176: "Radio Equipment and Systems (RES); Digital European Cordless Telephone (DECT); Approval test specification".

- [6] ISO 7637 (1990): "Road vehicles - Electrical disturbance by conducting and coupling - Part 1: Passenger cars and light commercial vehicles with nominal 12 V supply voltage".
- ISO 7637 (1990): "Road vehicles - Electrical disturbance by conducting and coupling - Part 2: Commercial vehicles with nominal 24 V supply voltage - Electrical transient conduction along supply lines only".
- [7] EN 55022 (1994): "Limits and methods of measurement of radio disturbance characteristics of information technology equipment".
- [8] CISPR 16-1: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1: Radio disturbance and immunity measuring apparatus".
- [9] ENV 50140: "Electromagnetic Compatibility - Basic immunity standard - Radiated, radio-frequency electromagnetic field. Immunity test".
- [10] EN 61000-4-2: "Electromagnetic Compatibility (EMC) - Part 4: Testing and measurements techniques - Section 2: Electrostatic discharge immunity test".
- [11] EN 61000-4-4: "Electromagnetic Compatibility (EMC) - Part 4: Testing and measurements techniques - Section 4: Electrical fast transients/burst requirements".
- [12] EN 61000-4-6: "Electromagnetic Compatibility (EMC) - Part 4: Testing and measurements techniques - Section 6: Immunity to conducted disturbances, induced by radio-frequency fields".
- [13] EN 61000-4-11: "Electromagnetic Compatibility (EMC) - Part 4: Testing and measurements techniques - Section 11: Voltage dips, short interruptions and voltage variations immunity tests".
- [14] EN 61000-4-5: "Electromagnetic Compatibility (EMC) - Part 4: Testing and measurements techniques - Section 5: Surge immunity test".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this ETS the following definitions apply:

ancillary equipment: Equipment (apparatus), used in connection with a receiver or transceiver is considered as an ancillary equipment (apparatus) if:

- the equipment is intended for use in conjunction with a receiver, or transceiver to provide additional operational and/or control features to the radio equipment (e.g. to extend control to another position or location); and
- the equipment cannot be used on a stand alone basis to provide user functions independently of a receiver or transceiver; and
- the receiver or transceiver to which it is connected, is capable of providing some intended operation such as transmitting and/or receiving without the ancillary equipment (i.e. it is not a sub-unit of the main equipment essential to the main equipment basic functions).

base station equipment: Used to describe CT2 equipment including CFPs (Cordless Fixed Parts) and/or CPPs (Cordless Portable Parts) which are powered via an ac power input port or a dc power input port.

CT2 equipment: Apparatus which includes one or more transceivers and/or receivers and/or parts thereof which operate in the frequency band 864,1 MHz to 868,1 MHz.

host equipment: Any equipment which has a complete user functionality when not connected to the CT2 radio equipment, and to which the CT2 radio equipment provides additional functionality, and to which connection is necessary for the CT2 radio equipment to offer functionality.

integral antenna: An antenna designed to be connected to the equipment without the use of an external connector and considered to be part of the equipment. An integral antenna may be fitted internally or externally to the equipment.

manufacturer: The legal entity responsible for placing the product on the market.

mobile equipment: Used to describe all CT2 equipment powered by a vehicular power supply.

port: A particular interface of the specified equipment (apparatus) with the electromagnetic environment.

portable equipment: Used to describe all CT2 equipment powered by an internal battery.

NOTE: More than one of the equipment classifications may apply to certain equipment, as described in subclause 5.2, dependent upon the manufacturer's declaration of normal intended use.

3.2 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

CT2	second generation Cordless Telephone
CTA	Cordless Telephone Apparatus
CFP	Cordless Fixed Part
CPP	Cordless Portable Part
EMC	ElectroMagnetic Compatibility
EUT	Equipment Under Test
SPL	Sound Pressure Level

4 General test conditions

4.1 Test conditions

The equipment shall be tested under normal test conditions contained in the relevant product and basic standards or in the information accompanying the equipment, which are within the manufacturers declared range of humidity, temperature, and supply voltage.

The test conditions shall be recorded in the test report.

The test configuration shall be as close to normal intended use as possible and shall be recorded in the test report.

Whenever the EUT is provided with a detachable antenna, the EUT shall be tested with the antenna fitted in a manner typical of normal intended use.

For CT2 equipment parts for which connection to a host equipment is necessary to offer functionality the test configuration shall be as defined in subclause 5.4.

4.2 Arrangements for test signals at the input of the transceiver

4.2.1 Speech equipment

Audio input signals may be connected to the EUT either by a non-metallic acoustic tube or, if provided, electrical connections. The CT2 equipment shall not be modified to provide any electrical connection ports for the purposes of this test. Suitable test arrangements for the acoustic tube are described in I-ETS 300 176 [5].