

SLOVENSKI STANDARD oSIST prEN 303 345 V1.1.1:2016

01-september-2016

Radiodifuzni sprejemniki - Harmonizirani standard, ki zajema bistvene zahteve člena 3.2 direktive 2014/53/EU

Radio Broadcast Receivers - Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten z. (2016-07)

fb08f7178ef6/ksist-fpren-303-345-v1-1-7-2017

ICS:

33.060.20 Sprejemna in oddajna

oprema

Receiving and transmitting

equipment

oSIST prEN 303 345 V1.1.1:2016

en

oSIST prEN 303 345 V1.1.1:2016

iTeh STANDARD PREVIEW (standards.iteh.ai)

kSIST FprEN 303 345 V1.1.7:2017 https://standards.iteh.ai/catalog/standards/sist/ddec4a55-22ff-4471-9d9c-fb08f7178ef6/ksist-fpren-303-345-v1-1-7-2017 oSIST prEN 303 345 V1.1.1:2016

Draft ETSI EN 303 345 V1.1.1 (2016-07)



Broadcast Sound Receivers; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU

kSIST FprEN 303 345 V1.1.7:2017 https://standards.iteh.ai/catalog/standards/sist/ddec4a55-22ff-4471-9d9c-fb08f7178ef6/ksist-fpren-303-345-v1-1-7-2017

Reference

DEN/ERM-TG17-15

Keywords

broadcast, digital, Harmonised standard, radio, receiver

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la

Teh Sous-Préfecture de Grasse (06) N° 7803/88/ IEW

(standards.iteh.ai)

kSIST FprEN 303 345 V1.1.7:2017 https://standards.iteh.ai/catalog/standards/sist/ddec4a55-22ff-4471-9d9c-fb08f7178ef**Important_notice**-v1-1-7-2017

> The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT[™], **PLUGTESTS**[™], **UMTS**[™] and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**[™] and **LTE**[™] are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Annex	B (informative): Commentary on development of the present document	20
Annex	A (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU	19
1		10
5.3.6.1	Methods of measurement	
5.3.5.2 5.3.6	Unwanted emissions in the spurious domain	
5.3.5.1 5.3.5.2	AM and FM adjacent channel selectivity and blocking measurements	
5.3.5	Adjacent channel selectivity and blocking measurement methods	
5.3.4.2	DAB and DRM sensitivity measurements	
5.3.4.1	AM and FM sensitivity measurements	
5.3.4	Sensitivity measurement methods	
5.3.3	Generic measurement set-up for equipment for conducted testing	16
5.3.2	Generic measurement set-up for radiated testing.	15
5.3.1	Generic methods of measurement	
5.3	Methods of measurement	
5.2	Interpretation of the measurement results	
5.1	Environmental conditions for testing	
5 Т	Cesting for compliance with technical requirements	13
4.2.6.3	Conformance	13
4.2.6.2	Limits	
4.2.6.1	Definition	
4.2.6	Unwanted emissions in the spurious domain	
4.2.5.3	Conformance	
4.2.5.2	Limits	
4.2.5.1	Definition	
4.2.5	Adjacent channel selectivity and blocking pren-303-345-v1-1-7-2017.	
4.2.4.3	Conformance://standards.iteh.ai/catalog/standards/sist/ddec4a55-22ff-4471-9d9c-	
4.2.4.1	Limits <u>kSIST FprFN 303 345 V1 1 7:2017</u>	
4.2.4 4.2.4.1	Definition	10 10
4.2.3.4 4.2.4	DRM testing (standards.iteh.ai) Sensitivity	1U 10
4.2.3.3 4.2.3.4	DPM testing	10
4.2.3.2	FM testing	9
4.2.3.1	AM testing	
4.2.3	Test signal configurations	
4.2.2	Broadcast radio frequency bands	
4.2.1	Broadcast radio modulation methods	
4.2	Conformance requirements	
4.1	Environmental profile	
	Pechnical requirements specifications	
3.1 3.2	Abbreviations	
3 L 3.1	Definitions and abbreviations	
3 Г	Definitions and abbreviations	7
2.2	Informative references	
2.1	Normative references	
2 F	References	6
1 S	cope	6
Introdu	ction	5
Modal	verbs terminology	5
	rd	
Intellec	tual Property Rights	5

oSIST prEN 303 345 V1.1.1:2016

	4	Draft ETSI EN 303 345 V1.1.1 (2016-07)
Annex C (informative):	Change History	21
History		22

iTeh STANDARD PREVIEW (standards.iteh.ai)

kSIST FprEN 303 345 V1.1.7:2017 https://standards.iteh.ai/catalog/standards/sist/ddec4a55-22ff-4471-9d9c-fb08f7178ef6/ksist-fpren-303-345-v1-1-7-2017

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.9] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.I confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

(standards.iteh.ai)

Proposed national transposition dates

Date of latest announcement of this EN (doa) ef6/ksist-fpren-303-345-v1-1-7-20173 months after ETSI publication

Date of latest publication of new National Standard

or endorsement of this EN (dop/e):

Date of withdrawal of any conflicting National Standard (dow):

6 months after doa

18 months after doa

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document describes the requirements for radio broadcast receivers to meet the essential requirements of article 3.2 of Directive 2014/53/EU [i.1].

1 Scope

The present document applies to devices, including the supplied antenna, that receive broadcast sound services, whether analogue or digital modulation is used. Multi-function devices may also fall under the requirements of other documents.

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at http://docbox.etsi.org/Reference.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

	7 11 1
[1]	ETSI EN 300 401 (V1.4.1) (06-2006): "Radio Broadcasting Systems; Digital Audio Broadcasting
	(DAB) to mobile, portable and fixed receivers" (Standards.iteh.ai)
[2]	ETSI ES 201 980 (V4.1.1) (01-2014): "Digital Radio Mondiale (DRM); System Specification".
[3]	CENELEC EN 55032:2015: "Electromagnetic compatibility of multimedia equipment - Emission Requirements". 1008f7178ef6/ksist-fpren-303-345-v1-1-7-2017
[4]	CENELEC EN 55020:2007: "Sound and television broadcast receivers and associated equipment - Immunity characteristics - Limits and methods of measurement".
[5]	Recommendation ITU-R BS.559-2 (06/1990): "Objective measurement of radio-frequency protection ratios in LF, MF and HF broadcasting".
[6]	Recommendation ITU-R BS.468-4 (07/1986): "Measurement of audio-frequency noise voltage

2.2 Informative references

level in sound broadcasting".

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1]	Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the
	harmonisation of the laws of the Member States relating to the making available on the market of
	radio equipment and repealing Directive 1999/5/EC.

[i.2] ETSI TR 100 028-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".

7

Draft ETSI EN 303 345 V1.1.1 (2016-07)

[i.3]	ETSI TR 100 028-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
[i.4]	ECA table at www.efis.dk.
[i.5]	Recommendation ITU-R BS.1615-1: "Planning parameters for digital sound broadcasting at frequencies below 30 MHz".
[i.6]	Recommendation ITU-R BS.641: "Determination of radio-frequency protection ratios for frequency-modulated sound broadcasting".
[i.7]	CEPT/ERC/Recommendation 74-01E (2011): "Unwanted emissions in the spurious domain".
[i.8]	CISPR 35: "Electromagnetic Compatibility of Multimedia equipment - Immunity Requirements".
[i.9]	Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

adjacent channel selectivity: at a given frequency separation, the ratio of the maximum unwanted signal level to the wanted signal level necessary to provide a given level of audio quality 1. 21

blocking: at a given frequency separation, the ratio of the maximum AM unwanted signal level to the wanted signal level necessary to provide a given level of audio quality 303 345 V1.1.7:2017 https://standards.iteh.ai/catalog/standards/sist/ddec4a55-22ff-4471-9d9c-

built-in antenna: antenna that cannot be detached from the equipment/1-1-7-2017

dBm: decibels relative to 1 mW of power

dBQ: audio decibels after Recommendation ITU-R 468-4 [6] noise weighting and a quasi-peak detector have been applied

dB\muV: decibels relative to 1 μ V

 $dB\mu V/m$: decibels relative to 1 $\mu V/m$

external antenna: antenna designed to be connected to the equipment with the use of a 50 Ω or 75 Ω external connector

integral antenna: antenna designed to be connected to the equipment without the use of a 50 Ω or 75 Ω external connector and considered to be part of the equipment

NOTE: A device that uses a supplied earphone as the antenna has an integral antenna.

sensitivity: minimum wanted signal level required to provide a given level of audio quality

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAC Advanced Audio Coding AM Amplitude Modulation

AMSS Amplitude Modulation Signalling System

BS Broadcast Sound

CISPR Comité International Spécial des Perturbations Radioélectriques

В

DAB Digital Audio Broadcasting Digital Radio Mondiale DRM **ECA European Common Allocation** EEP **Equal Error Protection EFTA** European Free Trade Area **FAR** Fully Anechoic Room FM Frequency Modulation HF High Frequency

ITU-R International Telecommunications Union - Radiocommunications

LF Low Frequency MF Medium Frequency MSC Main Service Channel PC Personal Computer Radio Data System RDS RF Radio Frequency RM Robustness Mode **RMS** Root Mean Square SAC Semi Anechoic Chamber **SNR** Signal to Noise Ratio **TEM** Transverse Electro-Magnetic

UI User Interface VHF Very High Frequency

4 Technical requirements specifications

iTeh STANDARD PREVIEW

4.1 Environmental profiledards.iteh.ai)

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

608f7178ef6/ksist-fpren-303-345-v1-1-7-2017

4.2 Conformance requirements

4.2.1 Broadcast radio modulation methods

The following broadcast radio modulation methods are considered feasible within the current authorization regime in Europe:

- Amplitude modulation, with or without AMSS (AM).
- Frequency modulation, with or without RDS (FM).
- Digital Audio Broadcasting (DAB).
- Digital Radio Mondiale (DRM).

Broadcast radio receivers may include demodulation capability for one or more of these modulation methods. Conformance shall only be required for each of the modulation methods included in the receiver.

4.2.2 Broadcast radio frequency bands

The following frequency bands are identified in the ECA table [i.4] for broadcast radio services:

- Low frequency (LF): 148,5 kHz to 283,5 kHz.
- Medium frequency (MF): 526,5 kHz to 1 606,5 kHz.

- 9
- High Frequency (HF): 3 950 kHz to 4 000 kHz, 5 900 kHz to 6 200 kHz, 7 200 kHz to 7 450 kHz, 9 400 kHz to 9 900 kHz, 11 600 kHz to 12 100 kHz, 13 570 kHz to 13 870 kHz, 15 100 kHz to 15 800 kHz, 17 480 kHz to 17 900 kHz, 18 900 kHz to 19 020 kHz, 21 450 kHz to 21 850 kHz and 25 670 kHz to 26 100 kHz.
- VHF band I: 47 MHz to 68 MHz.
- VHF band II: 87,5 MHz to 108 MHz.
- VHF band III: 174 MHz to 240 MHz.

Broadcast radio receivers may include tuning capability for one or more of these frequency bands. Conformance shall only be required for each of the frequency bands included in the receiver.

4.2.3 Test signal configurations

4.2.3.1 AM testing

The generated AM signals (wanted, unwanted and blocking) shall be in accordance with table 1. The configuration is based on Recommendation ITU-R BS.1615-1 [i.5].

Table 1: AM configuration

Parameter	AM signals		
Parameter	Wanted	Unwanted	Blocking
Audio modulation		Weighted noise	
	1 kHz tone	Recommendation ITU-R	1 kHz tone
	L CTANDAI	BS 559-2 [5]	i khz tone
	Band-fimite	ed to 4,5 kHz	
Other modulation	40 %(standard	50 % gulasi neak	80 % depth
parameters	40 % (Standard	30 % quasi-peak	80 % deptil

kSIST FprEN 303 345 V1.1.7:2017

4.2.3.2 FM testing/standards.iteh.ai/catalog/standards/sist/ddec4a55-22ff-4471-9d9c-fb08f7178ef6/ksist-fpren-303-345-v1-1-7-2017

The generated FM signals (wanted and unwanted) and the blocking signal shall be in accordance with table 2. The configuration is based on Recommendation ITU-R BS.641 [i.6].

Table 2: FM configuration

Parameter	FM signals		AM signal
Parameter	Wanted	Unwanted	Blocking
Audio modulation	1 kHz tone	Weighted noise Recommendation ITU-R BS.559-2 [5]	1 kHz tone
	Band-limited to 15 kHz		
Other modulation parameters	±60,8 kHz peak deviation	32 kHz quasi-peak deviation (see note)	80 % depth
Pilot tone	None	None	
NOTE: This is equivalent to 19 kHz RMS deviation in the absence of pre-emphasis.			