

## SLOVENSKI STANDARD SIST EN 301 489-6 V1.4.1:2015

01-december-2015

Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) -Standard elektromagnetne združljivosti (EMC) za radijsko opremo in storitve - 6. del: Posebni pogoji za opremo digitalnih izboljšanih brezvrvičnih telekomunikacij (DECT)

Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 6: Specific conditions for Digital Enhanced Cordless Telecommunications (DECT) equipment

## (standards.iteh.ai)

<u>SIST EN 301 489-6 V1.4.1:2015</u> https://standards.iteh.ai/catalog/standards/sist/f1bd58c0-be7c-4b78-ad94-13fc51913f2c/sist-en-301-489-6-v1-4-1-2015

Ta slovenski standard je istoveten z: EN 301 489-6 V1.4.1

#### ICS:

| 33.060.01 | Radijske komunikacije na<br>splošno                            | Radiocommunications in general                         |
|-----------|--|--|
| 33.070.30 | Digitalne izboljšane<br>brezvrvične telekomunikacije<br>(DECT) | Digital Enhanced Cordless<br>Telecommunications (DECT) |
| 33.100.01 | Elektromagnetna združljivost<br>na splošno                     | Electromagnetic compatibility in general               |

SIST EN 301 489-6 V1.4.1:2015 en,fr,de

## iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 489-6 V1.4.1:2015</u> https://standards.iteh.ai/catalog/standards/sist/f1bd58c0-be7c-4b78-ad94-13fc51913f2c/sist-en-301-489-6-v1-4-1-2015



# ETSI EN 301 489-6 V1.4.1 (2015-05)



Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 6: Specific conditions for Digital Enhanced Cordless Telecommunications (DECT) equipment

Reference REN/ERM-EMC-328

Keywords

DECT, EMC, radio, regulation

#### ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

### (standards.iteh.ai)

SIST EN 301 489-6 V1.4.1:2015 https://standards.iteh.ai/catalog/standards/sist/f1bd58c0-be7c-4b78-ad94-13fc51913f IMPORTANT POLICE-v1-4-1-2015

The present document can be downloaded from: <u>http://www.etsi.org/standards-search</u>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <a href="http://portal.etsi.org/tb/status/status.asp">http://portal.etsi.org/tb/status/status.asp</a>

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

#### **Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI. The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015. All rights reserved.

DECT<sup>™</sup>, PLUGTESTS<sup>™</sup>, UMTS<sup>™</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP<sup>™</sup>** and LTE<sup>™</sup> are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM**® and the GSM logo are Trade Marks registered and owned by the GSM Association.

## Contents

| Intell     | ntellectual Property Rights  |    |
|------------|--|----|
| Forev      | vord   | 5  |
| Moda       | l verbs terminology  | 5  |
| 1          | Scope  | 6  |
| 2          | References   | 6  |
| 2.1        | Normative references   |    |
| 2.2        | Informative references   |    |
| 2          | Definitions and abbreviations  |    |
| 3<br>3.1   | Definitions and abbreviations  |    |
| 3.1<br>3.2 | Abbreviations  |    |
| 5.2        |  |    |
| 4          | Test conditions  |    |
| 4.1        | General  |    |
| 4.2        | Arrangements for test signals  |    |
| 4.2.1      | Arrangements for test signals at the input of transmitters                                   |    |
| 4.2.1.     | ~  |    |
| 4.2.1.2    | 2 Non-speech equipment<br>Arrangements for test signals at the output of transmitters        |    |
| 4.2.2      | Arrangements for test signals at the output of receivers                                     |    |
| 4.2.4      | Arrangements for test signals at the output of receivers                                     |    |
| 4.2.5      | Arrangements for testing transmitter and receiver together (as a system)                     |    |
| 4.3        | Exclusion bands.   | 9  |
| 4.4        | Narrow band responses on receivers or receivers which are part of transceivers               | 9  |
| 4.5        | Narrow band responses on receivers or receivers which are part of transceivers               | 9  |
| 5          |  |    |
| 5<br>5.1   | SIST EN 301 489-6 VI.4.1.2015  | 9  |
| 5.1<br>5.2 | Performance assessment <u>SIST EN 301 489-6 VI.4.1.2015</u><br>General                       | 9  |
| 5.2.1      | Altargements for the assessment of host dependant equipment and plug-in cards.               | 9  |
| 5.2.2      | Alternative B: use of a test jig and three hosts   | 10 |
| 5.3        | Assessment procedures  |    |
| 5.3.1      | Loss of user control functions or stored user defined data                                   | 10 |
| 5.3.2      | Audio breakthrough   |    |
| 5.4        | Ancillary equipment  |    |
| 5.5        | Equipment classification   | 12 |
| 6          | Performance criteria   | 12 |
| 6.1        | General  |    |
| 6.2        | Performance criteria for Continuous phenomena of Transceivers (CT)                           |    |
| 6.3        | Performance criteria for Transient phenomena applied to Transceivers (TT)                    |    |
| 6.4        | Performance criteria for Continuous phenomena applied to Receive-only equipment (CR)         |    |
| 6.5        | Performance criteria for Transient phenomena applied to Receive-only equipment (TR)          |    |
| 6.6        | Performance criteria for ancillary equipment tested on a stand alone basis                   |    |
| 7          | A multi sekiliter erremnierre  | 12 |
| 7<br>7.1   | Applicability overview<br>Emission   |    |
| 7.1.1      | General  |    |
| 7.1.1      | Special conditions   |    |
| 7.2        | Immunity   |    |
| 7.2.1      | General  |    |
| 7.2.2      | Special conditions   |    |
|            |  |    |
| Anne       | <b>x</b> A (normative): Definitions of cordless telecommunications equipment in the scope of |    |
|            | the present document   | 15 |
| A.1        | Digital Enhanced Cordless Telecommunications (DECT) equipment                                | 15 |
|            |  | -  |

#### ETSI EN 301 489-6 V1.4.1 (2015-05)

| Annex B (informative): | Void16         |
|------------------------|----------------|
| Annex C (informative): | Bibliography17 |
| History                |                |

## iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 489-6 V1.4.1:2015</u> https://standards.iteh.ai/catalog/standards/sist/f1bd58c0-be7c-4b78-ad94-13fc51913f2c/sist-en-301-489-6-v1-4-1-2015

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to mandate M/284 issued from the European Commission under Directive 98/34/EC [i.2] as amended by Directive 98/48/EC [i.3].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.1].

The present document is part 6 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

| iTeh STANDARD PREV<br>National transposition dates  | IEW              |
|---|------------------|
| Date of adoption of this EN: (standards.iteh.ai)  | 19 May 2015      |
| Date of latest announcement of this EN (do <u>a)ST EN 301 489-6 V1.4.1.2015</u>   | 31 August 2015   |
| https://standards.iteh.ai/catalog/standards/sist/flbd58c0-be7c<br>Date of latest publication of new National Standard<br>or endorsement of this EN (dop/e): | 29 February 2016 |
| Date of withdrawal of any conflicting National Standard (dow):  | 28 February 2017 |

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

5

## 1 Scope

The present document, together with ETSI EN 301 489-1 [1], covers the assessment of Digital Enhanced Cordless Telecommunications (DECT) equipment, and associated ancillary equipment, in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port and emissions from the enclosure port of the radio equipment are not included in the present document. Such technical specifications are found in the relevant product standards for the effective use of the radio spectrum.

The present document specifies the applicable test conditions, performance assessment and performance criteria for Digital Enhanced Cordless Telecommunications (DECT) equipment, and associated ancillary equipment.

Definitions of types of cordless telecommunications equipment covered by the present document are given in annex A.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and ETSI EN 301 489-1 [1], the provisions of the present document take precedence.

The environmental classification and the emission and immunity requirements used in the present document are as stated in ETSI EN 301 489-1 [1], except for any special conditions included in the present document.

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies. **Cost ten al** 

Referenced documents which are not found to be publicly available in the expected location might be found at <u>Mttp://docbox.etsi.org/Reference</u>. <u>SIST EN 301 489-6 V1.4.1:2015</u>

https://standards.iteh.ai/catalog/standards/sist/flbd58c0-be7c-4b78-ad94-NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

| [1] | ETSI EN 301 489-1 (V1.9.2) (09-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements". |
|-----|---|
| [2] | Recommendation ITU-T O.153 (10-1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".  |
| [3] | ETSI EN 300 175-2 (V2.5.1) (08-2013): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".   |
| [4] | ETSI EN 300 175-3 (V2.5.1) (08-2013): "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) Layer".  |
| [5] | ETSI EN 300 176-1 (V2.1.1) (07-2009): "Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 1: Radio".   |
| [6] | CENELEC EN 55024 (2010): "Information technology equipment - Immunity characteristics - Limits and methods of measurement".   |

#### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

| [i.1] | Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).           |
|-------|--|
| [i.2] | Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.                             |
| [i.3] | Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations. |

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 301 489-1 [1] and the following apply:

**bearer:** burst of the wanted RF signal used to establish and maintain the communications link for digital modulated and operated cordless telephone and similar radio communications equipment

**DECT equipment:** Digital Enhanced Cordless Telecommunications apparatus which includes one or more transceivers and/or receivers and/or parts thereof which conform to the requirements of ETSI EN 300 175-2 [3]

**host equipment:** any equipment which has a complete user functionality when not connected to the cordless telephone or similar radio communications equipment, and to which this radio equipment provides additional functionality, and to which connection is necessary for this radio equipment to offer functionality, and in which the transceiver part of the radio equipment is physically installed 3fc51913f2c/sist-en-301-489-6-v1-4-1-2015

**non-speech equipment:** cordless telephone or similar communications equipment intended for the provision and reception of digital data either originating from or destined to external digital speech processing circuitry or other external equipment

**speech equipment:** cordless telephone or similar communications equipment containing transducers such as microphones and/or loudspeakers intended for the provision and reception of acoustic audio signals

#### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| AC   | Alternative Current  |
|------|--|
| BER  | Bit Error Ratio  |
| BPF  | Band Pass Filter   |
| BT   | Bandwidth Time product   |
| BW   | BandWidth  |
| CF   | Carrier Frequency  |
| CFP  | Cordless Fixed Part  |
| CPP  | Cordless Portable Part   |
| CR   | Continuous phenomena applied to cordless telephone or communication Receive-only equipment |
| CT   | Continuous phenomena applied to cordless telephone or communication Transceivers           |
| DECT | Digital Enhanced Cordless Telecommunications   |
| EM   | ElectroMagnetic  |
| ERP  | Ear Reference Point  |
| EUT  | Equipment Under Test   |
| MRP  | Mouth Reference Point  |
| RF   | Radio Frequency  |

| SPL      | Sound Pressure Level   |
|----------|--|
| TR<br>TT | Transient phenomena applied to cordless telephone or communication Receive-only equipment<br>Transient phenomena applied to cordless telephone or communication Transceivers |
|          | runsient phenomena approve to contracts terephone of communication runseer ers   |

## 4 Test conditions

### 4.1 General

For the purposes of the present document, the test conditions of ETSI EN 301 489-1 [1], clause 4, shall apply as appropriate. Further product related test conditions for cordless telephone or communication equipment are specified in the present document, clauses 4.2 to 4.5.

## 4.2 Arrangements for test signals

The provisions of ETSI EN 301 489-1 [1], clause 4.2 shall apply.

#### 4.2.1 Arrangements for test signals at the input of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.1 shall apply with the following modification.

The transmitter part of the particular type of cordless telephone or communications equipment shall be modulated with normal test modulation as specified for that type of equipment (see clause 4.5).

#### 4.2.1.1 Speech equipment

Audio input signals may be provided to the EUT either by a non-metallic acoustic tube or, if provided, electrical connections. The equipment shall not be modified to provide any electrical connection ports for the purposes of EMC tests only. Suitable test arrangements for the acoustic tube are described in EN 55024 [6].

#### 4.2.1.2 Non-speech equipment

SIST EN 301 489-6 V1.4.1:2015

Digital (data) input signals shall be supplied to the EUT by electrical connection to the modulation input port via an appropriate connecting cable, test jig, or host equipment (see clauses 5.2.4 and 5.2.2).

#### 4.2.2 Arrangements for test signals at the output of transmitters

The provisions of ETSI EN 301 489-1 [1], clause 4.2.2 shall apply.

#### 4.2.3 Arrangements for test signals at the input of receivers

The provisions of ETSI EN 301 489-1 [1], clause 4.2.3 shall apply.

The receiver part or stand alone receiver of the particular type of cordless telephone or communications equipment shall be provided with the appropriate wanted RF signal modulated as specified for that type of equipment (see clause 4.5).

#### 4.2.4 Arrangements for test signals at the output of receivers

The provisions of ETSI EN 301 489-1 [1], clause 4.2.4 shall apply.

## 4.2.5 Arrangements for testing transmitter and receiver together (as a system)

The provisions of ETSI EN 301 489-1 [1], clause 4.2.5 shall apply.

The normal test modulation shall be transmitted by the test system and looped back in the radio equipment, as described in ETSI EN 300 175-3 [4] and ETSI EN 300 176-1 [5]. Further, the output of the radio equipment under test shall be monitored by the test system.

### 4.3 Exclusion bands

The provision of ETSI EN 301 489-1 [1], clause 4.3 shall apply with the following modifications.

The exclusion band for transmitters, receivers and receiver sections of transceivers is the band of frequencies over which no immunity tests with radiated RF are made.

The exclusion band shall be from 1 781,792 MHz to 1 997,344 MHz (+100 MHz to the upper side; -100 MHz to the lower side are added to the operation band).

# 4.4 Narrow band responses on receivers or receivers which are part of transceivers

The provision of ETSI EN 301 489-1 [1], clause 4.4 shall apply with the following modifications.

No immunity tests shall be carried out on frequencies of identified narrow band responses i.e. spurious responses, of the receiver parts of cordless telephone and similar communications equipment.

For DECT receivers, the identification criteria for narrow band responses are an increase of the speech output signal level for speech equipment, or an increase in the Bit Error Ratio (BER) of the looped back data from the EUT for non-speech equipment.

The nominal frequency offset to be used for the identification of narrowband responses shall be  $\pm 2$  MHz for the first part of the identification procedure, and  $\pm 2,5$  MHz for its second part.

## 4.5 Normal test modulation

The provision of ETSI EN 301 489-1 [1], clause 4.5 shall apply with the following modifications.

For all types of DECT equipment the wanted input signal shall be a Radio Frequency (RF) carrier set to the nominal centre frequency of one of the DECT RF channels, using Gaussian shaped frequency-shift keying (BT = 0,5) and modulated with a 1 152 kbit/s bit sequence. SIST EN 301 489-6 V1.4.1.2015

https://standards.iteh.ai/catalog/standards/sist/flbd58c0-be7c-4b78-ad94-The encoding of the bit sequence shall conformato the encoding specified in ETSI EN 300 175-2 [3] and ETSI EN 300 175-3 [4].

The parts of the data sequence that shall transmit a bit sequence conforming to the D-M2 pattern as specified in Recommendation ITU-T O.153 [2] are those which are looped back according to the loop back test message described in ETSI EN 300 175-3 [4].

The burst timings of this carrier shall conform to the limits specified in ETSI EN 300 175-2 [3].

## 5 Performance assessment

## 5.1 General

The provision of ETSI EN 301 489-1 [1], clause 5.1 shall apply.

# 5.2 Arrangements for the assessment of host dependant equipment and plug-in cards

For equipment parts for which integration with a host equipment is necessary in order to offer functionality, two alternative approaches defined in clauses 5.2.1 and 5.2.2 may be used. The manufacturer shall declare which alternative shall be used.