
Reference

DEN/SES-00376-1

Keywords

broadcasting, receiver, requirements, satellite

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Technical requirements specifications	9
4.1 Environmental profile.....	9
4.2 Equipment capabilities	9
4.3 Conformance requirements	9
4.3.1 Radiation from the ODU.....	9
4.3.2 Antenna gain pattern	10
4.3.3 Pointing accuracy capability	12
4.3.4 Antenna pointing and efficiency stability under severe environmental conditions.....	12
4.3.5 Linear polarization plane alignment capability	12
4.3.6 Image frequency rejection	13
4.3.7 Receiver blocking	13
5 Testing for compliance with technical requirements.....	13
5.1 Environmental conditions for testing	13
5.2 Interpretation of the measurement results	14
6 Test methods	14
6.1 Pointing accuracy capability.....	14
6.2 Receiver blocking.....	14
Annex A (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU.....	16
Annex B (informative): Interface between ODU and IDU	18
Annex C (normative): Generic LNBF specification	19
C.1 Introduction	19
C.2 Scope	19
C.3 Technical requirements specifications	19
C.3.1 Environmental profile.....	19
C.3.2 Equipment capabilities	19
C.3.3 Conformance requirements	20
C.3.3.1 Radiation from the LNBF	20
C.3.3.2 Cross-polar discrimination.....	20
C.3.3.3 Image frequency rejection	20
C.3.3.4 Clamp diameter.....	20
C.3.3.5 Location of phase centre	20
C.3.3.6 Taper.....	21
C.3.3.7 Receiver blocking	21
Annex D (informative): Applicability in conjunction with CENELEC EN 50585:2014.....	22

Annex E (informative): Applicability of parameters given in ETSI EG 203 336	23
Annex F (informative): Other ODU features and performance characteristics.....	24
History	25

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1324992-d9a4-4a14-84de-f0e216030154/etsi-en-303-372-1-v1.1.1-2016-08>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES), and is now submitted for the Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.11] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 1 of a multi-part deliverable covering satellite broadcast reception equipment, as identified below:

- Part 1:** "Outdoor unit receiving in the 10,7 GHz to 12,75 GHz frequency band";
Part 2: "Indoor unit".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Today, satellite communications is an important means for broadcast distribution of television and radio programs to homes. Satellites transmit signals that can be received directly by mass deployed consumer electronics equipment. The present document concerns the performance of this kind of equipment with regard to harmful interference. The avoidance of receiving or transmitting interfering signals is considered in the present document, whereas reception of the wanted signals is not considered. Satellite operators or broadcasters may create specifications for the latter purpose.

The present document is intended to cover the provisions of Radio Equipment Directive [i.1] article 3.2, which states that *"Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference"*. The directive requires that unwanted radio wave emissions of transmitters are limited in order to avoid harmful interference. It requires that receivers are resilient against harmful interference from radio waves in shared and adjacent frequency channels. In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Radio Equipment Directive [i.1] may apply to equipment within the scope of the present document.

The R&TTE Directive [i.5], which is the predecessor of the Radio Equipment Directive, contains no receiver requirements. Moreover, broadcast reception equipment is explicitly not covered. The present document becomes necessary with the adoption of the Radio Equipment Directive.

An overview of satellite broadcast reception equipment is given in the following. Typically, the equipment comprises an outdoor unit (ODU), and indoor unit (IDU), an inter-facility link (IFL) between these units, and optionally multi-switches for connecting multiple IDUs to an ODU. The ODU comprises an antenna and a low noise block converter (LNB). The frequency down-conversion by the LNB enables transmission on a coaxial cable to the IDU. A frequency range that contains several modulated carriers is down-converted as one block. The most popular kind of antenna is a parabolic reflector antenna with offset feed. In that case the feed horn is often integrated with the LNB into one unit called low noise block converter with feed (LNBF). The IDU demodulates one of the carriers, de-multiplexes the retrieved bit stream and decodes digital audio video and audio for display on a TV screen. Common terms for the IDU are set-top box or satellite receiver. IDUs may contain a hard disk for recording programs. An IDU may be capable of processing multiple carriers for direct viewing and recording. The IDU functionality may be integrated into a TV set. Typically, the satellite transmits two electromagnetic waves with orthogonal polarization at the same time. In case the satellite transmits a large frequency band, it is divided up for frequency conversion with different local oscillator frequencies. The IDU selects by control signals which polarization and frequency band the ODU provides on the IFL. An ODU may work with multiple IDUs or IDUs with multiple tuners via separate IFLs. Multi-switches connected to an ODU allow connecting a large number of IDUs.

Frequency bands are re-used by satellites on different orbital positions of the Geostationary Orbit arc. Discrimination between signals from wanted and adjacent orbital positions is provided by the directivity of the ODU antenna. The actually required discrimination depends on the specific scenario of satellite spacing and Equivalent Isotropically Radiated Power (EIRP), as well as on the robustness of the wanted signals. Moreover, a certain on-axis gain is required for receiving the wanted signals with the target availability. In general, a larger antenna provides better discrimination and gain, but on the other hand small antennas are better accepted by users and the public. Requirements on the antenna are often given by means of the minimum antenna diameter. The meaning of such a requirement is *"that the antenna gain pattern shall be compliant with a reference pattern or mask that includes the nominal antenna diameter as a parameter"*. The nominal diameter is a means for specifying and classifying antennas and in an easy way, but the actual antenna diameter may be different from it, or the antenna might not be circular. The concept of gain pattern definition with nominal antenna diameter is applied in the present document.

Besides the concept of ODU, IDU, IFL and optionally multi-switches, new concepts with different allocation of functionality exist. With channel stacking or SatCR, frequency channels are re-arranged by the ODU or an additional unit, so that all relevant channels can be carried on a single coaxial cable. IDUs or additional cables are connected by simple splitters. With Sat>IP, the ODU or an additional device performs demodulation and conversion to video over Internet Protocol. Common connected devices including tablet computers can be used to watch broadcast television inside a home network. Another concept applies optical fibre to carry signals between ODU and multi-switches. In conjunction with these and further concepts, the same requirements on the ODU characteristics exist.

The present document consists of multiple parts that apply to different kinds of equipment units, including ODUs for specific frequency bands and IDUs.

1 Scope

The present document applies to ODUs for satellite broadcast reception from geostationary satellites in the frequency band 10,7 GHz to 12,75 GHz. An ODU receives electromagnetic waves from a satellite. It amplifies the receive signal at low noise, converts it to a lower frequency band and makes it available to the IDU on an interface.

Part of the IDU functionality may be integrated with the ODU. In that case the present document applies only to the conventional ODU functionality.

The present document contains requirements to demonstrate that radio equipment both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI ETS 300 457 (Edition 1) (11-1995): "Satellite Earth Stations and Systems (SES); Test methods for Television Receive Only (TVRO) operating in the 11/12 GHz frequency bands".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI ETS 300 784: "Satellite Earth Stations and Systems (SES); Television Receive-Only (TVRO) satellite earth stations operating in the 11/12 GHz frequency bands".
- [i.3] CENELEC EN 50083-2 (1995): "Cabled distribution systems for television and sound signals; Part 2: Electromagnetic compatibility for equipment".
- [i.4] CISPR 16-1 (1993): "Specifications for radio interference measuring apparatus and measurements methods; Part 1: Radio disturbance and immunity measuring apparatus".
- [i.5] Directive 1999/05/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity.

- [i.6] ETSI EG 203 336 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".
- [i.7] CENELEC EN 50585:2014: "Communications protocol to transport satellite delivered signals over IP networks".
- [i.8] Recommendation ITU-R BO.1213: "Reference receiving Earth station antenna pattern for the broadcasting-satellite service in the 11.7-12.75 GHz band".
- [i.9] CENELEC EN 61319-1:1996: "Interconnections of satellite receiving equipment - Part 1: Europe".
- [i.10] CENELEC EN 50607:2015: "Satellite signal distribution over a single coaxial cable - second generation".
- [i.11] Commission Implementing Decision C(2015) 5376 final of 04.08.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53 of the European Parliament and of the Council
- [i.12] CENELEC EN 61319-1:1996/A11:1999: "Interconnections of satellite receiving equipment - Part 1: Europe".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

nominal antenna diameter: antenna diameter declared by the manufacturer that is a parameter in performance characteristics and that allows reference to a certain performance

NOTE: An antenna with circular aperture of diameter equal to the nominal diameter does typically have the performance specified.

off-axis angle: angle between the antenna boresight axis and the direction of interest

3.2 Symbols

For the purposes of the present document, the following symbols apply:

D	nominal antenna diameter
F	focal length of the antenna reflector
λ	wave length

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

EIRP	Equivalent Isotropically Radiated Power
IDU	InDoor Unit
IFL	InterFacility Link
LNB	Low Noise Block down-converter
LNBF	Low Noise Block down-converter with Feed
LO	Local Oscillator
ODU	OutDoor Unit
TV	TeleVision

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Equipment capabilities

The technical requirements of the present document apply under the capabilities of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared equipment capabilities.

Equipment capabilities comprise the following characteristics:

- Receive frequency band
- Polarization states
- Local oscillator frequency
- Nominal antenna diameter D
- Specific satellite network - if applicable

An ODU might be capable of receiving multiple frequency bands. The local oscillator frequency and the polarization states may be different in each frequency band. The declaration shall include all combinations of frequency band, polarization states and local oscillator frequency.

Polarization state can take the values horizontal linear, vertical linear, left hand circular and right hand circular. An ODU may receive multiple states in one frequency band.

If an ODU is designed for a specific satellite network, then certain requirements do not apply.

4.3 Conformance requirements

4.3.1 Radiation from the ODU

Specification 1: Unwanted radiation including Local Oscillator (LO) leakage radiated from the antenna

Purpose:

To limit the unwanted radiation level from the outdoor unit in order to protect adjacent satellites that use different frequency bands and are located near-by.

The EIRP of the unwanted radiation, including the LO frequency as well as its second harmonic, transmitted in the antenna axis (or boresight) direction, shall not exceed the following limits:

- $-60 + G_{0u}$ dBm in a 120 kHz bandwidth at the fundamental frequency of the LO
- $-50 + G_{0u}$ dBm in a 120 kHz bandwidth at the second harmonic of the LO
- $-60 + G_{0u}$ dBm in any other 120 kHz bandwidth

where $G_{0u} = 20 \log \frac{\pi D}{\lambda}$. D is the nominal antenna diameter, λ is the wave length.

This specification applies to the frequency range from 2,5 GHz to 25 GHz.

NOTE 1: These limits are derived from those in ETSI ETS 300 784 [i.2]. Here EIRP is used instead of power at the antenna flange, because an antenna flange may not be present. G_{ou} is the upper bound for the antenna on-axis gain, which corresponds to 100 % efficiency.

Verification:

The test method specified in clause 6.2 in ETSI ETS 300 457 [1] shall apply.

Specification 2: Radiation from the outdoor unit (EIRP)

Purpose:

To limit unwanted radiation level from the outdoor unit in order to protect other systems.

The EIRP of unwanted signals radiated by the outdoor unit within the band from 30 MHz to 25 GHz, shall not exceed the following values measured in any 120 kHz bandwidth (see CISPR No. 16-1 [i.4]):

- 20 dBpW in the range 30 MHz to 960 MHz;
- 43 dBpW in the range from 960 MHz to 2,5 GHz;
- 57 dBpW in the range from 2,5 GHz to 25 GHz.

The lower limits apply at the transition frequency.

This specification applies for all off-axis angles greater than 7°.

NOTE 2: EIRP limits are in accordance with CENELEC EN 50083-2 [i.3].

4.3.2 Antenna gain pattern

Purpose:

To protect the wanted signals from interference from terrestrial services and from other satellites.

Specification:

The relative co-polar and cross-polar off-axis antenna gain shall comply with the following masks.

Variables:

- φ : off-axis angle of the antenna relative to boresight (degrees)
- $g_{co}(\varphi)$: Co-polar antenna gain at off-axis angle φ relative to co-polar on-axis gain (decibel)
- $g_{cross}(\varphi)$: Cross-polar antenna gain at off-axis angle φ relative to co-polar on-axis gain (decibel)

Parameters:

- D : nominal antenna diameter
- λ : wavelength expressed in the same unit as the diameter

Co-polar mask:

$$g_{co}(\varphi) \leq -2,5 \times 10^{-3} \left(\frac{D}{\lambda} \varphi \right)^2 \text{ for } 0 \leq \varphi < \varphi_m$$

$$g_{co}(\varphi) \leq g_1 \text{ for } \varphi_m \leq \varphi < \varphi_r$$

$$g_{co}(\varphi) \leq 29 - 25 \log \varphi - G_0 \text{ for } \varphi_r \leq \varphi < \varphi_b$$

$$g_{co}(\varphi) \leq -5 - G_0 \text{ for } \varphi_b \leq \varphi < 70^\circ$$

$$g_{co}(\varphi) \leq -G_0 \text{ for } 70^\circ \leq \varphi < 180^\circ$$