



SLOVENSKI STANDARD SIST ETS 300 225 E2:2003

01-december-2003

FUX]g_UcdfYa U]b`g]ghYa]`f9GLĚHM b] bY`_UfU_hf]gh_Y]b`a Yf]bYa YlcXY`nU
dfYbcgbY`fUX]chY`YZ`bg_Y`UdUfUH`J<: `nUfYý]bY` c`bY

Radio Equipment and Systems (RES); Technical characteristics and methods of measurement for survival craft portable VHF radiotelephone apparatus

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **ETS 300 225 Edition 2**
<https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445c-b8da-a59eac8c9036/sist-ets-300-225-e2-2003>

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
47.020.70	Navigacijska in krmilna oprema	Navigation and control equipment

SIST ETS 300 225 E2:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 225 E2:2003

<https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8c9036/sist-ets-300-225-e2-2003>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 225

April 1997

Second Edition

Source: ETSI TC-RES

Reference: RE/RES-01024

ICS: 33.020

Key words: Maritime, radio, SAR, testing

**Radio Equipment and Systems (RES);
Technical characteristics and methods of
measurement for survival craft portable VHF
radiotelephone apparatus**

https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-
et300225e2003

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 225 E2:2003](https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8c9036/sist-ets-300-225-e2-2003)

<https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8c9036/sist-ets-300-225-e2-2003>

Contents

Foreword	7
1 Scope	9
2 Normative references	9
3 Abbreviations.....	9
4 General requirements	10
4.1 Construction.....	10
4.2 Frequencies and power	10
4.3 Controls.....	10
4.4 Switching time.....	11
4.5 Safety precautions	11
4.6 Class of emission and modulation characteristics.....	11
4.7 Battery.....	11
4.8 Labelling.....	12
5 Test conditions, power sources and ambient temperatures	12
5.1 Normal and extreme test conditions	12
5.2 Test power source	12
5.3 Normal test conditions	12
5.3.1 Normal temperature and humidity	12
5.3.2 Normal power source	13
5.4 Extreme test conditions	13
5.4.1 Extreme temperatures.....	13
5.4.1.1 Upper extreme temperature	13
5.4.1.2 Lower extreme temperature	13
5.4.2 Extreme test power supply values.....	13
5.4.2.1 Upper extreme test voltage	13
5.4.2.2 Lower extreme test voltage	13
5.5 Procedure for tests at extreme temperatures	13
6 General conditions of measurement	13
6.1 Test connections.....	13
6.2 Arrangements for test signals applied to the receiver input.....	14
6.3 Receiver mute or squelch facility	14
6.4 Normal test modulation.....	14
6.5 Artificial antenna	14
6.6 Test channels	14
6.7 Measurement uncertainty and interpretation of the measuring results.....	14
6.7.1 Measurement uncertainty.....	14
6.7.2 Interpretation of the measurement results	15
7 Environmental tests.....	15
7.1 Introduction	15
7.2 Procedure	15
7.3 Performance check.....	15
7.4 Drop test on hard surface	16
7.4.1 Definition	16
7.4.2 Method of measurement	16
7.4.3 Requirement.....	16
7.5 Vibration test.....	16
7.5.1 Method of measurement	16
7.5.2 Requirement.....	17
7.6 Temperature tests.....	17
7.6.1 General.....	17

7.6.2	Dry heat cycle	17
7.6.2.1	Method of measurement	17
7.6.2.2	Requirement	17
7.6.3	Damp heat cycle	17
7.6.3.1	Method of measurement	17
7.6.3.2	Requirement	18
7.6.4	Low temperature cycle	18
7.6.4.1	Method of measurement	18
7.6.4.2	Requirement	18
7.7	Corrosion test (sea water test)	18
7.7.1	General	18
7.7.2	Method of measurement	18
7.7.3	Requirements	19
7.8	Immersion test	19
7.8.1	Method of measurement	19
7.8.2	Requirements	19
7.9	Thermal shock	19
7.9.1	Method of measurement	19
7.9.2	Requirements	20
7.10	Solar radiation	20
7.10.1	Method of measurement	20
7.10.2	Requirements	20
7.11	Oil resistance test	20
7.11.1	Method of measurement	20
7.11.2	Requirement	20
8	Field measurement	20
8.1	Transmitter Effective Radiated Power (ERP)	21
8.1.1	Definition	21
8.1.2	Method of measurement	21
8.1.3	Limit	21
8.2	Spurious emissions from the transmitter	21
8.2.1	Definition	21
8.2.2	Method of measurement	22
8.2.3	Limit	22
8.3	Spurious emissions from the receiver	22
8.3.1	Definition	22
8.3.2	Method of measurement	22
8.3.3	Limit	22
9	Transmitter	22
9.1	Frequency error	22
9.1.1	Definition	22
9.1.2	Method of measurement	22
9.1.3	Limit	23
9.2	Carrier power referenced to ERP	23
9.2.1	Definition	23
9.2.2	Method of measurement	23
9.2.3	Limits	23
9.3	Frequency deviation	23
9.3.1	Definition	23
9.3.2	Maximum permissible frequency deviation	23
9.3.2.1	Method of measurement	23
9.3.2.2	Limit	23
9.3.3	Reduction of frequency deviation at modulation frequencies above 3 kHz ..	24
9.3.3.1	Method of measurement	24
9.3.3.2	Limits	24
9.4	Limitation characteristics of the modulator	24
9.4.1	Definition	24
9.4.2	Method of measurement	24
9.4.3	Limits	24
9.5	Sensitivity of the modulator, including microphone	25
9.5.1	Definition	25

	9.5.2	Method of measurement	25
	9.5.3	Limit	25
9.6		Audio frequency response	25
	9.6.1	Definition	25
	9.6.2	Method of measurement	25
	9.6.3	Limit	25
9.7		Audio frequency harmonic distortion of the emission	25
	9.7.1	Definition	25
	9.7.2	Method of measurement	25
		9.7.2.1 Normal test conditions	25
		9.7.2.2 Extreme test conditions	25
	9.7.3	Limit	26
9.8		Adjacent channel power	26
	9.8.1	Definition	26
	9.8.2	Method of measurement	26
	9.8.3	Limits	26
9.9		Residual modulation of the transmitter	26
	9.9.1	Definition	26
	9.9.2	Method of measurement	26
	9.9.3	Limit	27
9.10		Transient frequency behaviour of the transmitter	27
	9.10.1	Definitions	27
	9.10.2	Method of measurement	27
	9.10.3	Limits	28
10		Receiver	30
	10.1	Harmonic distortion and rated audio frequency output power	30
		10.1.1 Definition	30
		10.1.2 Methods of measurement	30
		10.1.3 Limits	30
	10.2	Audio frequency response	30
		10.2.1 Definition	30
		10.2.2 Method of measurement	30
		10.2.3 Limits	31
	10.3	Maximum usable sensitivity	31
		10.3.1 Definition	31
		10.3.2 Method of measurement	31
		10.3.3 Limits	31
	10.4	Co-channel rejection	31
		10.4.1 Definition	31
		10.4.2 Method of measurement	31
		10.4.3 Limit	32
	10.5	Adjacent channel selectivity	32
		10.5.1 Definition	32
		10.5.2 Method of measurement	32
		10.5.3 Limits	32
	10.6	Spurious response rejection	32
		10.6.1 Definition	32
		10.6.2 Method of measurement	32
		10.6.3 Limit	33
	10.7	Intermodulation response	33
		10.7.1 Definition	33
		10.7.2 Method of measurement	33
		10.7.3 Limit	33
	10.8	Blocking or desensitisation	33
		10.8.1 Definition	33
		10.8.2 Method of measurement	33
		10.8.3 Limit	34
	10.9	Amplitude response of the receiver limiter	34
		10.9.1 Definition	34
		10.9.2 Method of measurement	34
		10.9.3 Limit	34
	10.10	Receiver noise	34

	10.10.1	Definition.....	34
	10.10.2	Method of measurement.....	34
	10.10.3	Limit	34
11		Secondary battery charger.....	35
	11.1	General.....	35
	11.2	Environmental tests.....	35
	11.2.1	Introduction	35
	11.2.2	Vibration test.....	35
		11.2.2.1 Method of measurement.....	35
		11.2.2.2 Requirement	36
	11.2.3	Temperature tests	36
		11.2.3.1 General	36
		11.2.3.2 Dry heat cycle.....	36
		11.2.3.3 Damp heat cycle	36
		11.2.3.4 Low temperature cycle	36
	11.2.4	Corrosion test	37
		11.2.4.1 General	37
		11.2.4.2 Method of measurement.....	37
		11.2.4.3 Requirements.....	38
	11.3	Charging time.....	38
Annex A (normative):		Measuring receiver for adjacent channel power measurement.....	39
A.1		Power measuring receiver specification	39
	A.1.1	IF filter	39
	A.1.2	Attenuation indicator.....	40
	A.1.3	rms value indicator	40
	A.1.4	Oscillator and amplifier.....	40
Annex B (normative):		Solar radiation test source	41
B.1		Simulated solar radiation source	41
History			42

Full STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 225 E2:2003](https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8e9036/sist-ets-300-225-e2-2003)

<https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8e9036/sist-ets-300-225-e2-2003>

Foreword

This European Telecommunication Standard (ETS) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This ETS defines the minimum technical characteristics required for portable VHF radio telephones operating in survival craft, and optionally on board ships at sea, in certain frequency bands allocated to the Maritime Mobile Service (MMS). It also incorporates the requirements detailed in the Radio Regulations, International Convention for the Safety Of Life At Sea SOLAS 1974 (as amended in 1988) [3] and the relevant recommendations of the International Maritime Organization.

Every ETS prepared by ETSI is a voluntary standard. This ETS contains text concerning type approval of the equipment to which it relates. This text does not make this ETS mandatory in its status as a standard. However, this ETS can be referenced, wholly or in part, for mandatory application by decisions of regulatory bodies.

Transposition dates	
Date of adoption:	18 April 1997
Date of latest announcement of this ETS (doa):	31 July 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 January 1998
Date of withdrawal of any conflicting National Standard (dow):	31 January 1998

iteh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 225 E2:2003](https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8c9036/sist-ets-300-225-e2-2003)

<https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8c9036/sist-ets-300-225-e2-2003>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 225 E2:2003](https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8c9036/sist-ets-300-225-e2-2003)

<https://standards.iteh.ai/catalog/standards/sist/ac380430-c499-445e-b8da-a59eac8c9036/sist-ets-300-225-e2-2003>

1 Scope

This ETS states the minimum technical characteristics required for portable VHF radiotelephones operating in the bands between 156 MHz and 174 MHz allocated to the Maritime Mobile Services by the Radio Regulations (see Radio Regulations, Appendices 18 [1] and 19 [2]) and suitable for use in survival craft and, optionally, on board ships at sea. The requirements detailed in the Radio Regulations, International Convention for the Safety Of Life At Sea SOLAS 1974 [3], and the International Maritime Organization Resolutions A.694(17) [5] and A.762(18) [4] are incorporated in this ETS.

2 Normative references

This ETS incorporates by dated or undated reference provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent references to or revisions of any of these publication apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] Radio Regulations, Appendix 18: "Table of Transmitting Frequencies in the Band 156 - 174 MHz for Stations in the Maritime Mobile Service".
- [2] Radio Regulations, Appendix 19: "Technical Characteristics for Transmitters and Receivers used in the Maritime Mobile Service in the band 156 - 174 MHz".
- [3] International Convention for the Safety Of Life At Sea (SOLAS) 1974 as amended.
- [4] International Maritime Organization Resolution A.762(18): "Performance standards for survival craft two way VHF radiotelephone apparatus".
- [5] International Maritime Organization Resolution A.694(17): "General requirements for ship-borne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS)".
- [6] ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [7] CCITT Recommendation P.53 (1988): "Psophometric apparatus for the objective measurement of circuit noise".
- [8] ETS 300 019: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment".
- [9] ISO Recommendation 694: "Positioning of magnetic compasses in ships".

3 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

ad	amplitude difference
DSC	Digital Selective Calling
emf	electro-motive force
ERP	Effective Radiated Power
fd	frequency difference
IF	Intermediate Frequency
MMS	Maritime Mobile Service
RF	Radio Frequency
rms	root mean square
SINAD	(Signal + Noise + Distortion)/(Noise + Distortion) ratio
SOLAS	International Convention for the Safety Of Life At Sea

4 General requirements

4.1 Construction

The equipment shall be portable and capable of being used for on-scene communications between survival craft, between survival craft and ship and between survival craft and rescue unit. It may also be used for on-board communications when capable of operating on appropriate frequencies.

The equipment shall comprise at least:

- an integral transmitter/receiver including antenna and battery;
- an integral control unit including a press-to-transmit switch; and
- an internal microphone and loudspeaker.

The equipment shall be of either, highly visible yellow or orange colour, or marked with a surrounding highly visible yellow or orange marking strip, which shall be visible also during charging and storage, as applicable.

The mechanical and electrical construction and finish of the equipment shall conform in all respects to good engineering practice and the equipment shall be suitable for use on board ships and survival craft at sea.

All controls shall be of sufficient size to enable the usual control functions to be easily performed by a user wearing gloves for immersion suits, in accordance with SOLAS 1974 Chapter III, Regulation 33 [3]. The number of controls should be the minimum necessary for simple and satisfactory operation. With the possible exception of channel selection, it shall be possible to operate the equipment using only one hand.

Any parts of the equipment required to be checked during inspection or maintenance operations as laid down by the manufacturer, shall be readily accessible. Components shall be readily identifiable.

For the purpose of conformance testing in accordance with this ETS, adequate technical and operational documentation shall be supplied with the equipment.

The equipment shall not be unduly affected by sea water, oil, or exposure to sunlight.

The equipment shall be of small size and light weight (not more than 1,5 litres and 1,5 kg).

The manufacturer shall provide evidence on the method of attaching the equipment to the user's clothing, including the immersion suit specified in SOLAS 1974 Chapter III, Regulation 33 [3].

4.2 Frequencies and power

The equipment shall operate only on single-frequency channels for voice communications with manual control (simplex).

The equipment shall provide for transmission and reception of signals on channel 16 and at least one other single frequency channel from those specified in Appendix 18 of the Radio Regulations [1], (with the exception of the DSC calling channel 70), (see also subclause 6.6).

Independent selection of transmitting and receiving frequencies shall not be possible.

After switch on the equipment shall be operational within 5 seconds and meet the requirements of this ETS within 1 minute.

It shall not be possible to transmit during channel switching operations.

4.3 Controls

The equipment shall have a channel selector and shall indicate the designator of the channel at which the equipment is set, as given in Appendix 18 of the Radio Regulations [1].

It shall be possible to determine that channel 16 has been selected in all ambient light conditions.

The equipment shall have the following additional controls:

- on/off switch for the equipment with a visual indication that the equipment is switched on;
- a manual non-locking push to talk switch to operate the transmitter;
- a switch for reducing the power to not exceed 1 watt ERP; if the transmitter ERP is greater than 1 watt;
- an audio-frequency volume control;
- a squelch control;
- a carrier power detector giving a visual indication that the carrier is being produced.

The user shall not have access to any control which may impair the technical characteristics of the equipment if wrongly set.

4.4 Switching time

The channel switching arrangements shall be such that the time necessary to change over from using one of the channels to using any other channel does not exceed 5 seconds.

The time necessary to change over from transmission to reception and vice versa, shall not exceed 0,3 seconds.

4.5 Safety precautions

Means shall be incorporated to prevent damage to the equipment due to reversal of polarity of the battery power supply.

The equipment shall be designed to be free of sharp projections which could damage survival craft.

The manufacturer shall declare the survival craft compass safe distance according to ISO Recommendation 694 [9].

The equipment shall not be damaged by the effects of an open circuit or a short circuit of the antenna.

4.6 Class of emission and modulation characteristics

The equipment shall use phase modulation, G3E (frequency modulation with a pre-emphasis of 6 dB/octave) for speech.

The equipment shall be designed to operate satisfactorily to the requirements of this ETS with a channel separation of 25 kHz.

The frequency deviation corresponding to 100 % modulation shall approach ± 5 kHz as nearly as practicable.

4.7 Battery

The source of power, (i.e. battery) shall be integrated in the equipment; and in addition, provision may be made to operate the equipment using an external power source.

The capacity of the internal battery shall be sufficient to operate the equipment continuously for at least 8 hours at any temperature condition (see subclauses 5.3.1 and 5.4.1) with a 1:9 transmit to receive ratio at its highest rated transmitter power.