



SLOVENSKI STANDARD
SIST ETS 300 607-1 E3:2005
01-februar-2005

8 [[]HJb]`WV] b]`hY`Y_ca i b]_UW`g_]`g]ghYa `fZuU&L!`GdYVZ]_UW`Ug_`UXbcghj
a cV]`bY`dcgHUY`fA GL!`%`rXY.`GdYVZ]_UW`Ug_`UXbcghj`f] GA`%%`\$!`%&

Digital cellular telecommunications system (Phase 2) (GSM); Mobile Station (MS) conformance specification; Part 1: Conformance specification (GSM 11.10-1)

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **ETS 300 607-1 Edition 3**
<https://standards.iteh.ai/catalog/standards/sist/01e05121-7468-4cc3-b645-776054422b3/sist-ets-300-607-1-e3-2005>

ICS:

| | | |
|-----------|---|--|
| 33.070.50 | Globalni sistem za mobilno telekomunikacijo (GSM) | Global System for Mobile Communication (GSM) |
|-----------|---|--|

SIST ETS 300 607-1 E3:2005 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 607-1 E3:2005](https://standards.iteh.ai/catalog/standards/sist/61e05121-74b8-4cc5-b645-776054422bf3/sist-ets-300-607-1-e3-2005)

<https://standards.iteh.ai/catalog/standards/sist/61e05121-74b8-4cc5-b645-776054422bf3/sist-ets-300-607-1-e3-2005>



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 607-1

January 1997

Third edition

Source: ETSI TC-SMG

Reference: RE/SMG-07111OPR-1

ICS: 33.020

Key words: Digital cellular telecommunications system, Global System for Mobile Communication (GSM)



SIST ETS 300 607-1 E3:2005

<https://standards.iten.ai/catalog/standards/sist/61e05121-74b8-4cc5-b645-776054422619/sist-ets-300-607-1-e3-2005>

**Digital cellular telecommunication system (Phase 2);
Mobile Station (MS) conformance specification;
Part 1: Conformance specification
(GSM 11.10-1)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ETS 300 607-1 E3:2005](https://standards.iteh.ai/catalog/standards/sist/61e05121-74b8-4cc5-b645-776054422bf3/sist-ets-300-607-1-e3-2005)

<https://standards.iteh.ai/catalog/standards/sist/61e05121-74b8-4cc5-b645-776054422bf3/sist-ets-300-607-1-e3-2005>

Contents

| | |
|--|----|
| Foreword | 29 |
| 1 Scope | 30 |
| 2 Normative references | 30 |
| 3 Definitions, conventions, and applicability | 36 |
| 3.1 Mobile station definition and configurations | 36 |
| 3.2 Applicability | 37 |
| 3.2.1 Applicability of this specification | 37 |
| 3.2.2 Applicability of the individual tests | 37 |
| 3.2.3 Applicability to terminal equipment | 57 |
| 3.3 Definitions | 57 |
| 3.4 Conventions for mathematical notations | 58 |
| 3.4.1 Mathematical signs | 58 |
| 3.4.2 Powers to the base 10 | 58 |
| 3.5 Conventions on electrical terms | 58 |
| 3.5.1 Radio Frequency (RF) input signal level | 58 |
| 3.5.2 Reference sensitivity level | 59 |
| 3.5.3 Power level of fading signal | 59 |
| 3.6 Terms on test conditions | 59 |
| 3.6.1 Radio test conditions | 59 |
| 4 Test Equipment | 60 |
| 4.1 Terms used to describe test equipment in this ETS | 60 |
| 4.2 Functional requirements of test equipment | 60 |
| 5 Testing methodology in general (layers 1, 2, and 3) | 60 |
| 5.1 Testing of optional functions and procedures | 60 |
| 5.2 Test interfaces and facilities | 60 |
| 5.3 Different protocol layers | 61 |
| 5.4 Information to be provided by the apparatus supplier | 61 |
| 5.5 Definitions of transmit and receive times | 61 |
| 6 Reference test methods | 61 |
| 6.1 General | 61 |
| 6.2 Choice of frequencies in the frequency hopping mode | 62 |
| 6.3 "Ideal" radio conditions | 62 |
| 6.4 Standard test signals | 62 |
| 6.5 Power (control) levels | 62 |
| 7 Implicit testing | 62 |
| 8 Measurement uncertainty | 63 |
| 9 Format of tests | 63 |
| 10 Generic call set up procedures | 63 |
| 10.1 Generic call set-up procedure for mobile terminating speech calls | 63 |
| 10.1.1 Initial conditions | 63 |
| 10.1.2 Definition of system information messages | 64 |
| 10.1.3 Procedure | 66 |
| 10.1.4 Specific message contents | 67 |
| 10.2 Generic call set-up procedure for mobile originating speech calls | 68 |
| 10.2.1 Initial conditions | 68 |
| 10.2.2 Definition of system information messages | 68 |

| | | | |
|--------|--|--|-----|
| | 10.2.3 | Procedure | 69 |
| | 10.2.4 | Specific message contents..... | 69 |
| 10.3 | Generic call | set-up procedure for mobile terminating data calls | 71 |
| | 10.3.1 | Initial conditions | 71 |
| | 10.3.2 | Definition of system information messages | 71 |
| | 10.3.3 | Procedure | 72 |
| | 10.3.4 | Specific message contents..... | 72 |
| 10.4 | Generic call | set-up procedure for mobile originating data calls | 74 |
| | 10.4.1 | Initial conditions | 74 |
| | 10.4.2 | Definition of system information messages | 74 |
| | 10.4.3 | Procedure | 75 |
| | 10.4.4 | Specific message contents..... | 75 |
| 11 | General tests | | 78 |
| 11.1 | Verification of support and non-support of services (multiple numbering scheme or ISDN)..... | | 78 |
| | 11.1.1 | Mobile Terminated (MT) calls | 78 |
| | 11.1.2 | Mobile Originated (MO) calls | 79 |
| 11.2 | Verification of support of the single numbering scheme | | 80 |
| 11.3 | Verification of non-support of services (Advice of Charge Charging (AOCC)) | | 81 |
| 11.4 | Verification of non-support of services (call hold) | | 82 |
| 11.5 | Verification of non-support of services (multiparty)..... | | 83 |
| 11.6 | Verification of non-support of feature (Fixed Dialling Number (FDN)) | | 84 |
| 11.7 | IMEI Security | | 85 |
| 11.8 | Coding of the Bearer Capability information element..... | | 86 |
| | 11.8.1 | Network to MS Direction | 86 |
| | 11.8.1.1 | BS 21 to 26 - Asynchronous Service | 86 |
| | | 11.8.1.1.1 BS 21..... | 86 |
| | | 11.8.1.1.2 BS 22..... | 90 |
| | | 11.8.1.1.3 BS 23..... | 90 |
| | | 11.8.1.1.4 BS 24..... | 90 |
| | | 11.8.1.1.5 BS 25..... | 90 |
| | | 11.8.1.1.6 BS 26..... | 90 |
| | 11.8.1.2 | BS 31 to 34 - Synchronous Service | 91 |
| | | 11.8.1.2.1 BS 32..... | 91 |
| | | 11.8.1.2.2 BS 31..... | 95 |
| | | 11.8.1.2.3 BS 33..... | 96 |
| | | 11.8.1.2.4 BS 34..... | 96 |
| | 11.8.1.3 | BS 61 - Alternate Speech / Data | 96 |
| | | 11.8.1.3.1 Speech/Asynchronous Data, Transparent..... | 97 |
| | | 11.8.1.3.2 Speech/Asynchronous Data, Non Transparent..... | 99 |
| | | 11.8.1.3.3 Speech/Synchronous Data..... | 101 |
| | 11.8.1.4 | BS 81 - Speech followed by Data | 102 |
| | | 11.8.1.4.1 Speech followed by Asynchronous Data..... | 102 |
| | | 11.8.1.4.2 Speech followed by Synchronous Data..... | 102 |
| | 11.8.1.5 | TS 61 - Alternate Speech / Facsimile group 3 | 102 |
| | 11.8.1.6 | TS 62 - Automatic Facsimile group 3..... | 104 |
| 11.8.2 | MS to SS direction | | 104 |
| | 11.8.2.1 | BS 21 to 26 - Asynchronous Service | 104 |
| | | 11.8.2.1.1 BS 21..... | 105 |
| | | 11.8.2.1.2 BS 22..... | 109 |
| | | 11.8.2.1.3 BS 23..... | 109 |
| | | 11.8.2.1.4 BS 24..... | 109 |
| | | 11.8.2.1.5 BS 25..... | 109 |
| | | 11.8.2.1.6 BS 26..... | 109 |
| | 11.8.2.2 | BS 31 to 34 - Synchronous Service | 110 |
| | | 11.8.2.2.1 BS 32..... | 110 |
| | | 11.8.2.2.2 BS 31..... | 114 |
| | | 11.8.2.2.3 BS 33..... | 115 |

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ETS 300 607-1 E3:2005
<https://standards.iteh.ai/catalog/standards/sist/010121-7468-4cc5-b645-77605422015/sist-ets-300-607-1-e3-2005>

ETS 300 607-1 (GSM 11.10-1 version 4.16.1): January 1997

| | | | |
|----------|------------|---|-----|
| | 11.8.2.2.4 | BS 34 | 115 |
| 11.8.2.3 | | BS 41 to 46 - PAD Access Asynchronous | 116 |
| | 11.8.2.3.1 | ²⁾ BS 41 | 116 |
| | 11.8.2.3.2 | BS 42 | 117 |
| | 11.8.2.3.3 | BS 43 | 118 |
| | 11.8.2.3.4 | BS 44 | 118 |
| | 11.8.2.3.5 | BS 45 | 118 |
| | 11.8.2.3.6 | BS 46 | 118 |
| 11.8.2.4 | | BS 51 to 53 - Packet Service Synchronous | 119 |
| | 11.8.2.4.1 | ²⁾ BS 51 | 119 |
| | 11.8.2.4.2 | BS 52 | 119 |
| | 11.8.2.4.3 | BS 53 | 119 |
| 11.8.2.5 | | BS 61 - Alternate Speech / Data | 120 |
| | 11.8.2.5.1 | Speech/Asynchronous Data, Transparent | 120 |
| | 11.8.2.5.2 | Speech/Asynchronous Data, Non Transparent | 122 |
| | 11.8.2.5.3 | Speech/Synchronous Data | 124 |
| 11.8.2.6 | | BS 81 - Speech followed by Data | 125 |
| | 11.8.2.6.1 | Speech followed by Asynchronous Data | 125 |
| | 11.8.2.6.2 | Speech followed by Synchronous Data | 125 |
| 11.8.2.7 | | TS 61 - Alternate Speech / Facsimile group 3 | 125 |
| 11.8.2.8 | | TS 62 - Automatic Facsimile group 3 | 127 |
| 12 | | Transceiver | 128 |
| 12.1 | | Conducted spurious emissions | 128 |
| | 12.1.1 | MS allocated a channel | 128 |
| | 12.1.2 | MS in idle mode | 130 |
| 12.2 | | Radiated spurious emissions | 131 |
| | 12.2.1 | MS allocated a channel | 132 |
| | 12.2.2 | MS in idle mode | 134 |
| | | https://standards.iteh.ai/catalog/standards/sist/61e05121-74b8-4cc5-b645-776054422b3/sist-ets-300-607-1-e3-2005 | |
| 13 | | Transmitter | 136 |
| 13.1 | | Frequency error and phase error | 136 |
| 13.2 | | Frequency error under multipath and interference conditions | 139 |
| 13.3 | | Transmitter output power and burst timing | 141 |
| 13.4 | | Output RF spectrum | 148 |
| 13.5 | | Intermodulation attenuation | 154 |
| 14 | | Receiver | 156 |
| 14.1 | | Bad frame indication | 161 |
| | 14.1.1 | Bad frame indication - TCH/FS | 161 |
| | | 14.1.1.1 Bad frame indication - TCH/FS - Random RF input | 161 |
| | | 14.1.1.2 Bad frame indication - TCH/FS - Frequency hopping and downlink DTX | 162 |
| | 14.1.2 | Bad frame indication - TCH/HS | 164 |
| | | 14.1.2.1 Bad frame indication - TCH/HS - Random RF input | 164 |
| | | 14.1.2.2 Bad frame indication - TCH/HS - Frequency hopping and downlink DTX | 165 |
| | 14.1.3 | Bad frame indication - TCH/FS - Frequency hopping and downlink DTX - Phase 2 MS in a phase 1 network | 166 |
| | 14.1.4 | Bad frame indication - TCH/HS - Frequency hopping and downlink DTX - Phase 2 MS in a phase 1 network | 168 |
| 14.2 | | Reference sensitivity | 170 |
| | 14.2.1 | Reference sensitivity - TCH/FS | 170 |
| | 14.2.2 | Reference sensitivity - TCH/HS (Speech frames) | 172 |
| | 14.2.3 | Reference sensitivity - FACCH/F | 175 |
| | 14.2.4 | Reference sensitivity - FACCH/H | 176 |
| | 14.2.5 | Reference sensitivity - full rate data channels | 177 |
| | 14.2.6 | Reference sensitivity - half rate data channels | 178 |
| 14.3 | | Usable receiver input level range | 179 |

| | | |
|----------|--|-----|
| 14.4 | Co-channel rejection | 180 |
| 14.4.1 | Co-channel rejection - TCH/FS | 180 |
| 14.4.2 | Co-channel rejection - TCH/HS | 182 |
| 14.4.3 | Co-channel rejection - TCH/HS (SID frames) | 184 |
| 14.4.4 | Co-channel rejection - FACCH/F | 186 |
| 14.4.5 | Co-channel rejection - FACCH/H | 187 |
| 14.5 | Adjacent channel rejection | 188 |
| 14.5.1 | Adjacent channel rejection - speech channels | 188 |
| 14.5.2 | Adjacent channel rejection - control channels | 190 |
| 14.6 | Intermodulation rejection | 192 |
| 14.6.1 | Intermodulation rejection - speech channels | 192 |
| 14.6.2 | Intermodulation rejection - control channels | 194 |
| 14.7 | Blocking and spurious response | 196 |
| 14.7.1 | Blocking and spurious response - speech channels | 196 |
| 14.7.2 | Blocking and spurious response - control channels | 199 |
| 14.8 | AM suppression | 202 |
| 14.8.1 | AM suppression - speech channels | 202 |
| 14.8.2 | AM suppression - control channels | 203 |
| 15 | Timing advance and absolute delay | 206 |
| 16 | Reception time tracking speed | 208 |
| 17 | Access times during handover | 210 |
| 17.1 | Intra cell channel change | 210 |
| 17.2 | Inter cell handover | 212 |
| 18 | Temporary reception gaps | 215 |
| 19 | Channel release after unrecoverable errors | 217 |
| 19.1 | Channel release after unrecoverable errors - 1 | 217 |
| 19.2 | Channel release after unrecoverable errors - 2 | 218 |
| 19.3 | Channel release after unrecoverable errors - 3 | 219 |
| 20 | Cell selection and reselection | 221 |
| 20.1 | Cell selection | 222 |
| 20.2 | Cell selection with varying signal strength values | 224 |
| 20.3 | Basic cell reselection | 226 |
| 20.4 | Cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters | 228 |
| 20.5 | Cell reselection using parameters transmitted in the System Information type 2bis, type 7 and type 8 messages | 230 |
| 20.5.5 | Test Requirements | 231 |
| 20.6 | Cell reselection timings | 231 |
| 20.6.1 | Definition and applicability | 231 |
| 20.6.2 | Conformance requirement | 231 |
| 20.6.3 | Test purpose | 231 |
| 20.6.4 | Method of test | 232 |
| 20.6.4.1 | Initial conditions | 232 |
| 20.6.4.2 | Procedure | 232 |
| 20.6.5 | Test requirements | 232 |
| 20.7 | Priority of cells | 233 |
| 20.7.4.2 | Procedure | 234 |
| 20.7.5 | Test requirements | 234 |
| 20.8 | Cell reselection when C1 (serving cell) < 0 for 5 seconds | 234 |
| 20.8.1 | Definition and applicability | 234 |
| 20.8.2 | Conformance requirement | 234 |
| 20.8.3 | Test purpose | 234 |
| 20.8.4 | Method of test | 235 |
| 20.8.4.1 | Initial conditions | 235 |
| 20.8.4.2 | Procedure | 235 |
| 20.8.5 | Test requirements | 235 |
| 20.9 | Running average of the surrounding cell BCCH carrier signal levels | 235 |

ITeH STANDARD PREVIEW

(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/61e05121-74b8-4cc5-b645-776054422bf3/sist-ets-300-607-1-e3-2005>

ETS 300 607-1 (GSM 11.10-1 version 4.16.1): January 1997

| | | |
|---------|---|-----|
| 20.9.1 | Definition and applicability | 235 |
| 20.9.2 | Conformance requirement | 235 |
| 20.9.3 | Test purpose | 236 |
| 20.9.4 | Method of test..... | 236 |
| | 20.9.4.1 Initial conditions | 236 |
| | 20.9.4.2 Procedure | 236 |
| 20.9.5 | Test requirements | 236 |
| 20.10 | Running average of the serving cell BCCH carrier signal level | 237 |
| 20.10.1 | Definition and applicability | 237 |
| 20.10.2 | Conformance requirement | 237 |
| 20.10.3 | Test purpose | 237 |
| 20.10.4 | Method of test..... | 237 |
| | 20.10.4.1 Initial conditions | 237 |
| | 20.10.4.2 Procedure | 237 |
| 20.10.5 | Test requirement | 237 |
| 20.11 | Updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list..... | 238 |
| 20.11.1 | Definition and applicability | 238 |
| 20.11.2 | Conformance requirement | 238 |
| 20.11.3 | Test purpose | 238 |
| 20.11.4 | Method of test..... | 238 |
| | 20.11.4.1 Initial conditions | 238 |
| | 20.11.4.2 Procedure | 238 |
| 20.11.5 | Test requirements | 238 |
| 20.12 | Decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers | 239 |
| 20.12.1 | Definition and applicability | 239 |
| 20.12.2 | Conformance requirement | 239 |
| 20.12.3 | Test purpose | 239 |
| 20.12.4 | Method of test..... | 239 |
| | 20.12.4.1 Initial conditions | 239 |
| | 20.12.4.2 Procedure | 239 |
| 20.12.5 | Test requirements | 239 |
| 20.13 | Decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers | 240 |
| 20.13.1 | Definition and applicability | 240 |
| 20.13.2 | Conformance requirement | 240 |
| 20.13.3 | Test purpose | 240 |
| 20.13.4 | Method of test..... | 240 |
| | 20.13.4.1 Initial conditions | 240 |
| | 20.13.4.2 Procedure | 240 |
| 20.13.5 | Test requirements | 240 |
| 20.14 | Emergency calls..... | 241 |
| 20.14.1 | Definition and applicability | 241 |
| 20.14.2 | Conformance requirement | 241 |
| 20.14.3 | Test purpose | 241 |
| 20.14.4 | Method of test..... | 241 |
| | 20.14.4.1 Initial conditions | 241 |
| | 20.14.4.2 Procedure | 241 |
| 20.14.5 | Test requirements | 242 |
| 20.15 | Cell reselection due to MS rejection "LA not allowed" | 242 |
| 20.15.1 | Definition and applicability | 242 |
| 20.15.2 | Conformance requirement | 242 |
| 20.15.3 | Test purpose | 242 |
| 20.15.4 | Method of test..... | 243 |
| | 20.15.4.1 Initial conditions | 243 |
| | 20.15.4.2 Procedure | 243 |
| 20.15.5 | Test requirements | 243 |
| 20.16 | Downlink signalling failure..... | 244 |
| 20.16.1 | Definition and applicability | 244 |
| 20.16.2 | Conformance requirement | 244 |
| 20.16.3 | Test purpose | 244 |
| 20.17 | Cell selection if no suitable cell found in 10 s | 245 |

| | | |
|--------------|---|-----|
| 20.18 | Cell reselection due to MS rejection "Roaming not allowed in this LA" | 246 |
| 20.18.5 | Test requirements..... | 247 |
| 20.19 | Cell selection on release of SDCCH and TCH..... | 247 |
| 20.19.1 | Definition and applicability | 247 |
| 20.19.2 | Conformance requirement..... | 247 |
| 20.19.3 | Test purpose..... | 248 |
| 20.19.4 | Method of test | 248 |
| 20.19.4.1 | Initial conditions..... | 248 |
| 20.19.4.2 | Test procedure | 248 |
| 20.19.5 | Test requirements..... | 248 |
| 20.20 | Multiband cell selection and reselection..... | 249 |
| 20.20.1 | Multiband cell selection and reselection / Cell Selection | 249 |
| 20.20.2 | Multiband cell selection and reselection / Cell reselection..... | 251 |
| 21 | Received signal measurements | 253 |
| 21.1 | Signal strength | 253 |
| 21.2 | Signal strength selectivity..... | 256 |
| 21.3 | Signal quality under static conditions | 257 |
| 21.3.1 | Signal quality under static conditions - TCH/FS | 257 |
| 21.3.2 | Signal quality under static conditions - TCH/HS | 259 |
| 21.3.2.4.2 | Procedure..... | 260 |
| 21.4 | Signal quality under TU50 propagation conditions..... | 261 |
| 22 | Transmit power control timing and confirmation..... | 264 |
| 23 | Single frequency reference..... | 265 |
| 24 | Tests of the layer 1 signalling functions..... | 266 |
| 25 | Tests of the layer 2 signalling functions..... | 267 |
| 25.1 | Introduction, objective and scope..... | 267 |
| 25.1.1 | General | 267 |
| 25.1.2 | Test configurations..... | 267 |
| 25.1.3 | Pre-conditions..... | 267 |
| 25.1.4 | Layer 2 test frames..... | 268 |
| 25.1.5 | Establishment of the dedicated physical resource..... | 268 |
| 25.1.6 | Release of the dedicated physical resource | 269 |
| 25.2 | Test sequences..... | 269 |
| 25.2.1 | Initialization | 270 |
| 25.2.1.1 | Initialization when contention resolution required..... | 270 |
| 25.2.1.1.1 | Normal initialization | 270 |
| 25.2.1.1.2 | Initialization failure..... | 271 |
| 25.2.1.1.2.1 | Loss of UA frame | 271 |
| 25.2.1.1.2.2 | UA frame with different information field..... | 272 |
| 25.2.1.1.2.3 | Information frame and supervisory frames in response to an SABM frame..... | 273 |
| 25.2.1.1.3 | Initialization denial..... | 273 |
| 25.2.1.1.4 | Total initialization failure | 274 |
| 25.2.1.2 | Initialization, contention resolution not required | 275 |
| 25.2.1.2.1 | Normal initialization without contention resolution..... | 275 |
| 25.2.1.2.2 | Initialization failure..... | 276 |
| 25.2.1.2.3 | Initialization denial..... | 278 |
| 25.2.1.2.4 | Total initialization failure | 278 |
| 25.2.2 | Normal information transfer..... | 279 |
| 25.2.2.1 | Sequence counting and I frame acknowledgements | 279 |
| 25.2.2.2 | Receipt of an I frame in the timer recovery state | 282 |
| 25.2.2.3 | Segmentation and concatenation | 284 |
| 25.2.3 | Normal layer 2 disconnection | 287 |
| 25.2.4 | Test of link failure | 287 |
| 25.2.4.1 | I frame loss (MS to SS)..... | 287 |
| 25.2.4.2 | RR response frame loss (SS to MS)..... | 288 |

ETS 300 607-1 (GSM 11.10-1 version 4.16.1): January 1997

| | | | |
|--------|------------|---|-----|
| | 25.2.4.3 | RR response frame loss (MS to SS) | 289 |
| 25.2.5 | | Test of frame transmission with incorrect C/R values | 290 |
| | 25.2.5.1 | I frame with C bit set to zero | 290 |
| | 25.2.5.2 | SABM frame with C bit set to zero | 291 |
| 25.2.6 | | Test of errors in the control field | 292 |
| | 25.2.6.1 | N(S) sequence error | 292 |
| | 25.2.6.2 | N(R) sequence error | 294 |
| | 25.2.6.3 | Improper F bit | 294 |
| 25.2.7 | | Test on receipt of invalid frames | 295 |
| 26 | | Testing of layer 3 functions | 300 |
| 26.1 | | Default conditions and structured sequence of tests | 300 |
| | 26.1.1 | Default test conditions during layer 3 tests | 300 |
| | 26.1.2 | Structured sequence of the tests | 301 |
| | 26.1.3 | General rules for message parameters | 302 |
| | 26.1.4 | General rules for layer 3 testing | 302 |
| | 26.1.5 | Format of layer 3 test descriptions | 302 |
| 26.2 | | Initial tests | 304 |
| | 26.2.1 | Channel request | 304 |
| | 26.2.1.1 | Channel request / initial time | 304 |
| | 26.2.1.2 | Channel request / repetition time | 305 |
| | 26.2.1.3 | Channel request / random reference | 307 |
| | 26.2.2 | IMSI detach and IMSI attach | 308 |
| | 26.2.3 | Sequenced MM / CM message transfer | 312 |
| | 26.2.4 | Establishment cause | 313 |
| 26.3 | | Test of MS functions in idle mode | 321 |
| | 26.3.1 | Initial conditions | 321 |
| | 26.3.2 | MS indication of available PLMNs | 323 |
| | 26.3.3 | MS will send only if BSS is "on air" | 324 |
| | 26.3.4 | Manual mode of PLMN selection | 324 |
| 26.4 | | Lower layer failures in layer 3 testing | 326 |
| | 26.4.1 | Introduction | 326 |
| | 26.4.2 | Layer 1 reception failures | 326 |
| | 26.4.3 | Data link layer failures | 326 |
| | 26.4.4 | Lower layer failures, used for the tests in clause 25 | 326 |
| 26.5 | | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions | 327 |
| | 26.5.1 | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / unknown protocol discriminator | 327 |
| | 26.5.2 | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / TI and skip indicator | 328 |
| | 26.5.2.1 | TI and skip indicator / RR | 328 |
| | 26.5.2.1.1 | TI and skip indicator / RR / Idle Mode | 328 |
| | 26.5.2.1.2 | TI and skip indicator / RR / RR-Connection established | 329 |
| | 26.5.2.2 | TI and skip indicator / MM | 330 |
| | 26.5.2.3 | TI and skip indicator / CC | 332 |
| | 26.5.3 | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / undefined or unexpected message type | 334 |
| | 26.5.3.1 | Undefined or unexpected message type / undefined message type / CC | 334 |
| | 26.5.3.2 | Undefined or unexpected message type / undefined message type / MM | 335 |
| | 26.5.3.3 | Undefined or unexpected message type / undefined message type / RR | 337 |
| | 26.5.3.4 | Undefined or unexpected message type / unexpected message type / CC | 338 |
| | 26.5.4 | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / unforeseen information elements in the non-imperative message part | 339 |
| | 26.5.4.1 | Unforeseen information elements in the non-imperative message part / duplicated information elements | 339 |

| | | |
|--------------|---|-----|
| 26.5.5 | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / non-semantic mandatory IE errors | 341 |
| 26.5.5.1 | Non-semantic mandatory IE errors / RR | 341 |
| 26.5.5.1.1 | Non-semantic mandatory IE errors / RR / missing mandatory IE error..... | 341 |
| 26.5.5.1.1.1 | Non-semantic mandatory IE errors / RR / missing mandatory IE error / special case | 341 |
| 26.5.5.1.1.2 | Non-semantic mandatory IE errors / RR / missing mandatory IE error / general case..... | 342 |
| 26.5.5.1.2 | Non-semantic mandatory IE errors / RR / comprehension required | 343 |
| 26.5.5.2 | Non-semantic mandatory IE errors / MM | 344 |
| 26.5.5.2.1 | Non-semantic mandatory IE errors / MM / syntactically incorrect mandatory IE | 344 |
| 26.5.5.2.2 | Non-semantic mandatory IE errors / MM / syntactically incorrect mandatory IE | 345 |
| 26.5.5.2.3 | Non-semantic mandatory IE errors / MM / comprehension required | 347 |
| 26.5.5.3 | Non-semantic mandatory IE errors / CC | 349 |
| 26.5.5.3.1 | Non-semantic mandatory IE errors / CC / missing mandatory IE | 349 |
| 26.5.5.3.1.1 | Non-semantic mandatory IE errors / CC / missing mandatory IE / disconnect message | 349 |
| 26.5.5.3.1.2 | Non-semantic mandatory IE errors / CC / missing mandatory IE / general case..... | 350 |
| 26.5.5.3.2 | Non-semantic mandatory IE errors / CC / comprehension required | 351 |
| 26.5.6 | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / unknown IE, comprehension not required | 352 |
| 26.5.6.1 | Unknown information elements in the non-imperative message part / MM | 352 |
| 26.5.6.1.1 | Unknown IE, comprehension not required / MM / IE unknown in the protocol..... | 352 |
| 26.5.6.1.2 | Unknown IE, comprehension not required / MM / IE unknown in the message..... | 353 |
| 26.5.6.2 | Unknown information elements in the non-imperative message part / CC | 355 |
| 26.5.6.2.1 | Unknown information elements in the non-imperative message part / CC / Call establishment..... | 355 |
| 26.5.6.2.2 | Unknown information elements in the non-imperative message part / CC / disconnect | 356 |
| 26.5.6.2.3 | Unknown information elements in the non-imperative message part / CC / release..... | 357 |
| 26.5.6.2.4 | Unknown information elements in the non-imperative message part / CC / release complete..... | 358 |
| 26.5.6.3 | Unknown IE in the non-imperative message part, comprehension not required / RR | 359 |
| 26.5.7 | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions / spare bits | 361 |
| 26.5.7.1 | Spare bits / RR..... | 361 |
| 26.5.7.1.1 | Spare bits / RR / paging channel..... | 361 |

iTeh STANDARD PDF FILE
(standards.itih.ai)

SIST ETS 300 607-1 E3:2005

<https://standards.itih.ai/catalog/standards/sist/300-607-1/e3-2005>

7760574-2015/Sist:300-607-1/E3:2005

ETS 300 607-1 (GSM 11.10-1 version 4.16.1): January 1997

| | | | | |
|--------|------------|--|--|-----|
| | 26.5.7.1.2 | Spare bits / RR / BCCH | 362 | |
| | 26.5.7.1.3 | Spare bits / RR / AGCH | 364 | |
| | 26.5.7.1.4 | Spare bits / RR / Connected Mode | 366 | |
| | 26.5.7.2 | Spare bits / MM..... | 368 | |
| | 26.5.7.3 | Spare bits / CC | 369 | |
| 26.5.8 | | Default contents of messages..... | 371 | |
| 26.6 | | Test of the elementary procedures for radio resource management | 374 | |
| 26.6.1 | | Immediate assignment | 374 | |
| | 26.6.1.1 | Immediate assignment / SDCCH or TCH assignment | 374 | |
| | 26.6.1.2 | Immediate assignment / extended assignment..... | 375 | |
| | 26.6.1.3 | Immediate assignment / assignment rejection | 377 | |
| | 26.6.1.4 | Immediate assignment / ignore assignment..... | 379 | |
| | 26.6.1.5 | Immediate assignment after immediate assignment reject..... | 380 | |
| 26.6.2 | | Test of paging..... | 382 | |
| | 26.6.2.1 | Normal paging | 382 | |
| | | 26.6.2.1.1 | Paging / normal / type 1 | 382 |
| | | 26.6.2.1.2 | Paging / normal / type 2 | 384 |
| | | 26.6.2.1.3 | Paging / normal / type 3 | 386 |
| | 26.6.2.2 | Paging / extended..... | 388 | |
| | 26.6.2.3 | Paging / reorganization | 392 | |
| | | 26.6.2.3.1 | Paging / reorganization / procedure 1..... | 392 |
| | | 26.6.2.3.2 | Paging / reorganization / procedure 2..... | 395 |
| | 26.6.2.4 | Paging / same as before..... | 396 | |
| | 26.6.2.5 | Paging / multislot CCCH..... | 397 | |
| 26.6.3 | | Test of measurement report..... | 398 | |
| | 26.6.3.1 | Measurement / no neighbours..... | 398 | |
| | 26.6.3.2 | Measurement / all neighbours present | 402 | |
| | 26.6.3.3 | Measurement / barred cells and non-permitted NCCs | 406 | |
| | 26.6.3.4 | Measurement / DTX..... | 411 | |
| | 26.6.3.5 | Measurement / Frequency Formats | 415 | |
| | 26.6.3.6 | Measurement / multiband environment | 418 | |
| 26.6.4 | | Test of the channel assignment procedure | 423 | |
| | 26.6.4.1 | Dedicated assignment / successful case | 423 | |
| | 26.6.4.2 | Dedicated assignment / failure..... | 434 | |
| | | 26.6.4.2.1 | Dedicated assignment / failure / failure during active state..... | 434 |
| | | 26.6.4.2.2 | Dedicated assignment / failure / general case | 435 |
| 26.6.5 | | Test of handover | 437 | |
| | 26.6.5.1 | Handover / successful / active call / non-synchronized | 438 | |
| | 26.6.5.2 | Handover / successful / call under establishment / non-synchronized..... | 453 | |
| | 26.6.5.3 | Handover / successful / active call / finely synchronized | 471 | |
| | 26.6.5.4 | Handover / successful / call under establishment / finely synchronized..... | 476 | |
| | 26.6.5.5 | Pre-synchronized handovers | 486 | |
| | | 26.6.5.5.1 | Handover / successful / active call / pre-synchronized / Timing Advance IE not included..... | 486 |
| | | 26.6.5.5.2 | Handover / successful / call being established / pre-synchronized / timing advance IE is included / reporting of observed time difference requested. ... | 488 |
| | 26.6.5.6 | Handover / successful / active call / pseudo synchronized..... | 490 | |
| | 26.6.5.7 | Handover / successful / active call / non-synchronized / reporting of observed time difference requested | 492 | |
| | 26.6.5.8 | Handover / layer 3 failure..... | 493 | |
| | 26.6.5.9 | Handover / layer 1 failure..... | 495 | |
| 26.6.6 | | Test of frequency redefinition | 496 | |
| | 26.6.6.1 | Frequency redefinition | 496 | |
| 26.6.7 | | Test of the channel mode modify procedure..... | 501 | |
| | 26.6.7.1 | Test of the channel mode modify procedure / full rate | 502 | |
| | 26.6.7.2 | Test of the channel mode modify procedure / half rate | 504 | |

iTech STANDARDS PREVIEW
(standards.itich.ai)

<https://standards.itich.ai/catalog/standards/sist/300-607-1-e3-2005/ets-300-607-1-e3-2005-776054422bf3/sist-ets-300-607-1-e3-2005>

| | | |
|------------|--|-----|
| 26.6.8 | Test of ciphering mode setting | 506 |
| 26.6.8.1 | Ciphering mode / start ciphering | 506 |
| 26.6.8.2 | Ciphering mode / no ciphering | 507 |
| 26.6.8.3 | Ciphering mode / old cipher key | 509 |
| 26.6.8.4 | Ciphering mode / change of mode, algorithm and key | 510 |
| 26.6.8.5 | Ciphering mode / IMEISV request | 517 |
| 26.6.9 | Test of additional assignment | 519 |
| 26.6.10 | Test of partial release | 519 |
| 26.6.11 | Test of classmark | 519 |
| 26.6.11.1 | Classmark change | 519 |
| 26.6.11.2 | Classmark interrogation | 521 |
| 26.6.12 | Test of channel release | 523 |
| 26.6.12.1 | Channel release / SDCCH | 523 |
| 26.6.12.2 | Channel release / SDCCH - no L2 ACK | 524 |
| 26.6.12.3 | Channel release / TCH-F | 525 |
| 26.6.12.4 | Channel release / TCH-F - no L2 ACK | 527 |
| 26.6.13 | Test of starting time | 528 |
| 26.6.13.1 | Dedicated assignment with starting time / successful case / time not elapsed | 528 |
| 26.6.13.2 | Dedicated assignment with starting time / successful case / time elapsed | 530 |
| 26.6.13.3 | Dedicated assignment with starting time and frequency redefinition / failure case / time not elapsed | 532 |
| 26.6.13.4 | Dedicated assignment with starting time and frequency redefinition / failure case / time elapsed | 535 |
| 26.6.13.5 | Handover with starting time / successful case / time not elapsed | 537 |
| 26.6.13.6 | Handover with starting time / successful case / time elapsed | 539 |
| 26.6.13.7 | Handover with starting time and frequency redefinition / failure case / time not elapsed | 541 |
| 26.6.13.8 | Handover with starting time and frequency redefinition / failure case / time elapsed | 544 |
| 26.6.13.9 | Immediate assignment with starting time / successful case / time not elapsed | 546 |
| 26.6.13.10 | Immediate assignment with starting time / successful case / time elapsed | 548 |
| 26.6.14 | Default contents of GSM 900 layer 3 messages for RR tests | 550 |
| 26.6.15 | Default contents of DCS 1 800 layer 3 messages for RR tests | 561 |
| 26.7 | Elementary procedures of mobility management | 572 |
| 26.7.1 | TMSI reallocation | 572 |
| 26.7.2 | Authentication | 575 |
| 26.7.2.1 | Authentication accepted | 575 |
| 26.7.2.2 | Authentication rejected | 576 |
| 26.7.3 | Identification | 579 |
| 26.7.3.1 | General Identification | 579 |
| 26.7.3.2 | Handling of IMSI shorter than the maximum length | 581 |
| 26.7.4 | Location updating | 583 |
| 26.7.4.1 | Location updating / accepted | 584 |
| 26.7.4.2 | Location updating / rejected | 587 |
| 26.7.4.2.1 | Location updating / rejected / IMSI invalid | 587 |
| 26.7.4.2.2 | Location updating / rejected / PLMN not allowed | 590 |
| 26.7.4.2.3 | Location updating / rejected / location area not allowed | 594 |
| 26.7.4.2.4 | Location updating / rejected / roaming not allowed in this location area | 597 |
| 26.7.4.3 | Location updating / abnormal cases | 604 |
| 26.7.4.3.1 | Location updating / abnormal cases / random access fails | 604 |

ETS 300 607-1 (GSM 11.10-1 version 4.16.1): January 1997

| | | | |
|----------|--------------|--|-----|
| | 26.7.4.3.2 | Location updating / abnormal cases / attempt counter less or equal to 4, LAI different..... | 606 |
| | 26.7.4.3.3 | Location updating / abnormal cases / attempt counter equal to 4..... | 612 |
| | 26.7.4.3.4 | Location updating / abnormal cases / attempt counter less or equal to 4, stored LAI equal to broadcast LAI | 619 |
| 26.7.4.4 | | Location updating / release / expiry of T3240..... | 626 |
| 26.7.4.5 | | Location updating / periodic..... | 627 |
| | 26.7.4.5.1 | Location updating / periodic spread.... | 627 |
| | 26.7.4.5.2 | Location updating / periodic normal / test 1 | 629 |
| | 26.7.4.5.3 | Location updating / periodic normal / test 2 | 631 |
| | 26.7.4.5.4 | Location updating / periodic HPLMN search | 634 |
| | 26.7.4.5.4.1 | Location updating / periodic HPLMN search / MS waits time T | 634 |
| | 26.7.4.5.4.2 | Location updating / periodic HPLMN search / MS in manual mode..... | 635 |
| | 26.7.4.5.4.3 | Location updating / periodic HPLMN search / MS waits at least two minutes and at most T minutes | 636 |
| | 26.7.4.6 | Location updating / interworking of attach and periodic | 638 |
| 26.7.5 | | MM connection | 639 |
| | 26.7.5.1 | Introduction | 639 |
| | 26.7.5.2 | MM connection / establishment with cipher | 639 |
| | 26.7.5.3 | MM connection / establishment without cipher | 641 |
| | 26.7.5.4 | MM connection / establishment rejected | 642 |
| | 26.7.5.5 | MM connection / establishment rejected cause 4..... | 643 |
| | 26.7.5.6 | MM connection / expiry T3230..... | 644 |
| | 26.7.5.7 | MM connection / abortion by the network..... | 645 |
| | 26.7.5.7.1 | MM connection / abortion by the network / cause #6..... | 645 |
| | 26.7.5.7.2 | MM connection / abortion by the network / cause not equal to #6..... | 648 |
| | 26.7.5.8 | MM connection / follow-on request pending | 649 |
| | 26.7.5.8.1 | MM connection / follow-on request pending / test 1 | 649 |
| | 26.7.5.8.2 | MM connection / follow-on request pending / test 2 | 650 |
| | 26.7.5.8.3 | MM connection / follow-on request pending / test 3 | 651 |
| 26.7.6 | | Default contents of messages..... | 653 |
| 26.8 | | Tests related to circuit switched call control | 657 |
| 26.8.1 | | Circuit switched Call Control (CC) state machine verification | 657 |
| | 26.8.1.1 | General on CC state machine verification | 657 |
| | 26.8.1.1.1 | List of abbreviations..... | 658 |
| | 26.8.1.2 | Establishment of an outgoing call..... | 658 |
| | 26.8.1.2.1 | Outgoing call / U0 null state | 660 |
| | 26.8.1.2.1.1 | Outgoing call / U0 null state / MM connection requested | 660 |
| | 26.8.1.2.2 | Outgoing call / U0.1 MM connection pending | 661 |
| | 26.8.1.2.2.1 | Outgoing call / U0.1 MM connection pending / CM service rejected | 661 |
| | 26.8.1.2.2.2 | Outgoing call / U0.1 MM connection pending / CM service accepted | 662 |
| | 26.8.1.2.2.3 | Outgoing call / U0.1 MM connection pending / lower layer failure | 664 |
| | 26.8.1.2.3 | Outgoing call / U1 call initiated..... | 665 |