



**SLOVENSKI STANDARD**  
**SIST ETS 300 433/A1 E1:2000**  
**01-julij-2000**

---

**Radijska oprema in sistemi (RES) - Radijska oprema za CB (Citizens Band) z amplitudno modulacijo in dvobočnim oziroma enobočnim prenosom - Tehnične karakteristike in merilne metode**

Radio Equipment and Systems (RES); Double Side Band (DSB) and/or Single Side Band (SSB) amplitude modulated Citizens Band (CB) radio equipment; Technical characteristics and methods of measurement

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ETS 300 433/A1 E1:2000](https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000)

<https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000>

**Ta slovenski standard je istoveten z: ETS 300 433/A1 Edition 1**

---

**ICS:**

33.060.01	Radijske komunikacije na splošno	Radiocommunications in general
-----------	----------------------------------	--------------------------------

<b>SIST ETS 300 433/A1 E1:2000</b>	<b>en</b>
------------------------------------	-----------

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ETS 300 433/A1 E1:2000

<https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000>



# AMENDMENT

**ETS 300 433**

**A1**

December 1996

---

Source: ETSI TC-RES

Reference: RE/RES-00009

ICS: 33.020

**Key words:** CB, measurement, radio

**This amendment A1, will modify  
the European Telecommunication Standard ETS 300 433 (1995)**

**Radio Equipment and Systems (RES);  
Double Side Band (DSB) and/or Single Side Band (SSB)  
amplitude modulated Citizens' Band (CB) radio equipment;  
Technical characteristics and methods of measurement**

## ETSI

European Telecommunications Standards Institute

### ETSI Secretariat

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

---

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 433/A1 E1:2000](https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000)

<https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000>

## Foreword

This amendment to ETS 300 433 (1995) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI).

Transposition dates	
Date of adoption of this amendment:	6 December 1996
Date of latest announcement of this amendment (doa):	31 March 1997
Date of latest publication or endorsement of this amendment (dop/e):	30 September 1997
Date of withdrawal of any conflicting National Standard (dow):	30 September 1997

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 433/A1 E1:2000](https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000)

<https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000>

## Amendments

Replace table 1 on page 12 with the following table 1:

Table 1: Carrier frequency and channel number

Carrier frequencies (MHz)	Channel number	Carrier frequencies (MHz)	Channel number	Carrier frequencies (MHz)	Channel number
26,965	1	27,135	15	27,295	29
26,975	2	27,155	16	27,305	30
26,985	3	27,165	17	27,315	31
27,005	4	27,175	18	27,325	32
27,015	5	27,185	19	27,335	33
27,025	6	27,205	20	27,345	34
27,035	7	27,215	21	27,355	35
27,055	8	27,225	22	27,365	36
27,065	9	27,235	24	27,375	37
27,075	10	27,245	25	27,385	38
27,085	11	27,255	23	27,395	39
27,105	12	27,265	26	27,405	40
27,115	13	27,275	27		
27,125	14	27,285	28		

Replace subclause 9.3.2 Method of measurement (Inter-modulation response rejection) with the following:

Three input signals shall be connected to the receiver via a combining network, subclause 7.1.

The wanted test signal (A), at the nominal frequency of the receiver, with normal test modulation (DSB see subclause 7.5.1 b), SSB see subclause 7.5.2 c) at an emf of 12 dB $\mu$ V (DSB) or 6 dB $\mu$ V (SSB), i.e. the value of the limit for the maximum useable sensitivity, shall be applied to the receiver input connector via input of the combining network.

The unwanted test signal (B), at the frequency 20 kHz above the nominal frequency of the receiver, without modulation, shall be applied to the receiver input connector via the second input of the combining network.

The unwanted test signal (C), at a frequency of 40 kHz above the nominal frequency of the receiver, DSB amplitude modulated by 400 Hz to a modulation depth of 60 % shall be applied to the receiver input connector via the third input of the combining network.

The frequency of the unwanted test signals (B) and (C) may be slightly adjusted to search for maximum intermodulation.

The amplitude of the unwanted test signals (B) and (C) shall be maintained equal and adjusted until the SND/ND ratio, psophometrically weighted, at the output of the receiver is reduced to 14 dB.

The measure of the inter-modulation response rejection is the ratio in dB of the level of the unwanted test signals to the level of the wanted test signal at the receiver input for which the specified reduction in SND/ND ratio occurs. This ratio shall be recorded.

The two sets of measurements described above shall be repeated with the unwanted signals below the nominal frequency of the receiver by the specified amounts.

**Replace subclause 9.5.2 Method of measurement (Spurious response rejection) with the following:**

The two input signals shall be connected to the receiver via a combining network, see subclause 7.1.

The wanted test signal, at the nominal frequency of the receiver, with normal test modulation (DSB see subclause 7.5.1 b), SSB see subclause 7.5.2 c)) at an emf of 12 dB $\mu$ V (DSB) or 6 dB $\mu$ V (SSB), i.e. the value of the limit for the maximum useable sensitivity, shall be applied to the receiver input connector via one input of the combining network.

The unwanted test signal, DSB amplitude modulated by 400 Hz to a modulation depth of 60 % and at an emf of 92 dB $\mu$ V, shall be applied to the receiver input connector via the second input of the combining network. The unwanted test signal shall be tuned over the frequency range from 100 kHz to 1 GHz.

At each frequency at which a spurious response occurs, the input level shall be adjusted until the SND/ND ratio, psophometrically weighted, is reduced to 14 dB.

The value of spurious response rejection is the ratio in dB of the level of the unwanted test signal to the level of the wanted test signal at the receiver input for which the specified reduction in SND/ND ratio occurs.

The ratio shall be recorded as the spurious response rejection for each spurious response obtained.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 433/A1 E1:2000](https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000)

<https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000>

**History**

<b>Document history</b>	
November 1995	First Edition
December 1996	Amendment 1 to First Edition

## **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[SIST ETS 300 433/A1 E1:2000](https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000)

<https://standards.iteh.ai/catalog/standards/sist/218b97c7-2a79-4aa4-a610-7df3818e597c/sist-ets-300-433-a1-e1-2000>